



- A** 0.04 MAX. TO 0.034 MIN.
- B** SLOPE CONDITIONS SHOWN FOR HIGH SIDE SHOULDER ADJACENT TO SPEED CHANGE LANE PAVEMENT; FOR LOW SIDE OF SHOULDERS ADJACENT TO SPEED CHANGE LANE PAVEMENT, SHOULDER SLOPE SHALL BE 0.04.
- C** LONGITUDINAL JOINT PER BP-2.1

LEGEND

- ① ITEM 452 - 12" NON-REINFORCED CONCRETE PAVEMENT, CLASS QC IP
- ② ITEM 304 - 6" AGGREGATE BASE
- ③ ITEM 605 - 6" DEEP PIPE UNDERDRAINS
- ④ ITEM 606 - GUARDRAIL, TYPE 5
- ⑤ ITEM 659 - SEEDING AND MULCHING
- ⑥ ITEM 204 - SUBGRADE COMPACTION
- ⑦ ITEM 605 - 6" BASE PIPE UNDERDRAINS

TYPICAL SECTIONS - U.S. 86

MAD-86-10.64

MODEL: SP1304-6a PAPER SIZE: 34x22 (in.) DATE: 1/17/2025 TIME: 8:00:00 AM
pvc:\ohiodot-pw-bentley.com\ohiodot-pw-02\Documents\03 Standards\Sample Plans\02-Working\SP1304-6a.dgn

DESIGN AGENCY	
XYZ	
Planning • Engineering • Surveying	
DESIGNER	
MNN	
REVIEWER	
PMH 01/17/25	
PROJECT ID	
130406	
SHEET	TOTAL
P.9	306