



**TYPICAL SECTION  
OF ADJOINING PAVEMENT  
STA. 2+25, S.R. 28**

**LEGEND**

- (L) Standard Longitudinal Joint As Per BP-2.1
- (S) Standard Longitudinal Joint As Per BP-2.1 Without Tie Bars
- (C) Contraction Joint As Per BP-2.2
- (Y) Butt Joint Between Existing Pavement and Proposed Pavement, A Dowelled Type Y Joint As Per BP-2.5 Shall Be Provided. Grouting and Drilling Requirements Shall Be Per Specification 255 and BP-2.5 Except The Requirement That The Drilling Device Shall Be Capable Of Drilling Three Holes At One Time Shall Be Waived.
- (A) 10" Reinforced Concrete Pavement
- (B) 10" Non-Reinforced Concrete Pavement
- (C) 10" Granular Subbase
- (D) Tied Longitudinal Joint

LOR-28-0.00

MODEL: SP1311-7a PAPER SIZE: 34x22 (in.) DATE: 1/17/2025 TIME: 8:00:00 AM  
pw:\ohiodot-pw\entire\com\ohiodot-pw-02\Documents\03\_Standards\Sample Plans\SP1311-7a.dgn

PAVEMENT JOINT DETAIL  
S.R. 28

DESIGN AGENCY



DESIGNER  
AAM

REVIEWER  
DEM 01/17/25

PROJECT ID  
131107

SHEET TOTAL  
P.48 | 96