

PID: 119890	SFN: N/A	PROJECT: FUL-20A-19.20	STATION / OFFSET: 1017+72, 10' LT.			START: 7/16/24	END: 7/17/24	PG 2 OF 3	B-004-0-24												
MATERIAL DESCRIPTION AND NOTES		ELEV. 697.8	DEPTHS		SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG					ODOT CLASS (GI)	HOLE SEALED
STIFF, GRAY, SILTY CLAY , "AND" SAND, SLIGHTLY ORGANIC (LOI = 3.3%), MOIST (continued)			27	3	3	9	100	SS-17	0.50	-	-	-	-	-	-	-	-	27	A-6b (V)		
					4	6	20	100	SS-18A	-	-	-	-	-	-	-	-	-	-		A-6b (V)
VERY STIFF TO HARD, GRAY, SILTY CLAY , LITTLE SAND, TRACE GRAVEL, DAMP @30': VERY STIFF		695.8	28	8				SS-18B	>4.5	-	-	-	-	-	-	-	-	16	A-6b (V)		
					3	5	22	100	SS-19	3.75	-	-	-	-	-	-	-	-	16		A-6b (V)
					5	9	32	100	SS-20	>4.5	-	-	-	-	-	-	-	-	16		A-6b (V)
					7	11	26	0	SS-21	-	-	-	-	-	-	-	-	-	-		A-6b (V)
					5	7	25	0	SS-22	-	-	-	-	-	-	-	-	-	-		A-6b (V)
					5	7	23	100	SS-23	3.75	-	-	-	-	-	-	-	-	16		A-6b (V)
					5	6	25	100	SS-24	3.50	-	-	-	-	-	-	-	-	15		A-6b (V)
					5	7	23	100	SS-25	3.25	-	-	-	-	-	-	-	-	29		A-7-6 (V)
					2	5	17	100	SS-26	3.25	1	2	6	23	68	47	25	22	29	A-7-6 (14)	
					5	7	20	100	SS-27	2.50	-	-	-	-	-	-	-	-	28	A-7-6 (V)	
@42': STIFF TO VERY STIFF		686.3	37	11	3	4	13	100	SS-28	2.50	-	-	-	-	-	-	-	28	A-7-6 (V)		
					3	4	13	100	SS-29	2.25	-	-	-	-	-	-	-	28	A-7-6 (V)		
					3	5	16	100	SS-30	2.50	-	-	-	-	-	-	-	24	A-7-6 (V)		
					3	5	16	100	SS-31	2.00	-	-	-	-	-	-	-	20	A-6a (V)		
VERY STIFF, GRAY, SILT AND CLAY , TRACE SAND, TRACE GRAVEL, MOIST		673.8	48	6	3	5	17	100	SS-32	2.50	1	2	5	24	68	31	20	11	26	A-6a (8)	
					1	4	17	100	SS-33A	-	-	-	-	-	-	-	-	-	-	A-6a (V)	
VERY STIFF, GRAY, SILTY CLAY , LITTLE SAND, TRACE GRAVEL, MOIST		671.8	51	8				SS-33B	4.00	-	-	-	-	-	-	-	-	14	A-6b (V)		
					5	11	23	50	100	SS-34A	-	-	-	-	-	-	-	-	-	A-6b (V)	
HARD, GRAY, SANDY SILT , SOME CLAY, TRACE GRAVEL, DAMP		670.8	52	23				SS-34B	-	-	-	-	-	-	-	-	-	8	A-4a (V)		
								SS-35A	-	-	-	-	-	-	-	-	-	-	A-4a (V)		
					8	10	35	100	SS-35B	>4.5	-	-	-	-	-	-	-	-	14	A-6b (V)	