

PID: 119890	SFN: N/A	PROJECT: FUL-20A-19.20	STATION / OFFSET: 1017+72, 10' LT.					START: 7/16/24	END: 7/17/24	PG 3 OF 3			B-004-0-24																					
MATERIAL DESCRIPTION AND NOTES			ELEV. 669.9	DEPTHS		SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)				ATTERBERG				ODOT CLASS (GI)	HOLE SEALED														
HARD, GRAY, SILTY CLAY , LITTLE SAND, TRACE GRAVEL, DAMP (continued)					4	14	34	83	SS-36	>4.5	-	-	-	-	-	-	-	13	A-6b (V)															
					7	16																												
@55.5': SOME SAND					16	24	73	100	SS-37	>4.5	-	-	-	-	-	-	-	14	A-6b (V)															
					26																													
HARD, GRAY, SILTY CLAY , SOME SAND, TRACE GRAVEL, DAMP QU = 9.97 TSF, DD = 123.9 PCF					6	10	36	100	SS-38	>4.5	-	-	-	-	-	-	-	13	A-6a (V)															
					15																													
					5	10															38	100	SS-39	>4.5	-	-	-	-	-	-	-	15	A-6a (V)	
					16																													
					6	11															39	100	SS-40	>4.5	4	4	18	25	49	30	18	12	15	A-6a (9)
					16																													
					6	12														42	100	SS-41	>4.5	-	-	-	-	-	-	-	-	15	A-6a (V)	
					17																													
6	9	31	100	SS-42	>4.5	-	-	-	-	-	-	-	-	-	16	A-6a (V)																		
12	14																																	
			658.8	EOB	65																													
NOTES: NONE																																		
ABANDONMENT METHODS, MATERIALS, QUANTITIES: PLACED 0.5 BAG ASPHALT PATCH; PUMPED 18 CF CEMENT-BENTONITE GROUT																																		