

PID: 119890	SFN: N/A	PROJECT: FUL-20A-19.20	STATION / OFFSET: 1013+36, 9' LT.		START: 7/22/24	END: 7/23/24	PG 3 OF 3			B-001-0-24											
MATERIAL DESCRIPTION AND NOTES		ELEV.	DEPTHS		SPT/ RQD	N <sub>60</sub>	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG				ODOT CLASS (GI)	HOLE SEALED	
		677.5								GR	CS	FS	SI	CL	LL	PL	PI	WC			
VERY STIFF, GRAY, <b>SANDY SILT</b> , SOME CLAY, TRACE GRAVEL, MOIST (continued)		675.3	W 675.5	55	6	23	100	SS-34	3.25	-	-	-	-	-	-	-	-	14	A-4a (V)		
					2	10															
					4	16	100	SS-35	2.50	-	-	-	-	-	-	-	-	-	16		A-4a (V)
VERY STIFF, GRAY, <b>SILT AND CLAY</b> , LITTLE SAND, TRACE GRAVEL, MOIST QU = 2.10 TSF, DD = 122.9 PCF		670.8		56	3	17	100	SS-36	3.75	4	5	14	15	62	24	13	11	14	A-6a (8)		
@57.5': VERY STIFF TO HARD				57	5	17	100	SS-36	3.75	4	5	14	15	62	24	13	11	14	A-6a (8)		
				58	3	25	100	SS-37	>4.5	-	-	-	-	-	-	-	-	-	13		A-6a (V)
				59	8	25	100	SS-37	>4.5	-	-	-	-	-	-	-	-	-	13		A-6a (V)
@59': STIFF				60	3	19	100	SS-38	>4.5	-	-	-	-	-	-	-	-	-	-		15
HARD, GRAY, <b>SILTY CLAY</b> , LITTLE SAND, TRACE GRAVEL, MOIST		666.3	EOB	61	10	54	100	SS-39	>4.5	-	-	-	-	-	-	-	-	15	A-6b (V)		
				62	16	54	100	SS-39	>4.5	-	-	-	-	-	-	-	-	-	15		A-6b (V)
				63	5	31	100	SS-40	>4.5	-	-	-	-	-	-	-	-	-	14	A-6b (V)	
				64	8	31	100	SS-40	>4.5	-	-	-	-	-	-	-	-	-	14	A-6b (V)	
				65	7	41	100	SS-41	4.25	-	-	-	-	-	-	-	-	-	-	15	A-6b (V)
NOTES: NONE																					
ABANDONMENT METHODS, MATERIALS, QUANTITIES: PLACED 0.5 BAG ASPHALT PATCH: PUMPED 18 CF CEMENT-BENTONITE GROUT																					