



B-003-0-23



Run #	Depth (ft)		Recovery		RQD	
NQ2-1	30.5	34.8	52 in. / 52 in.	100%	39 in. / 52 in.	75%
NQ2-2	34.8	44.8	120 in. / 120 in.	100%	90 in. / 120 in.	75%

ATH-690-4.21 PID 114592



B-003-0-23



Run #	Depth (ft)		Recovery		RQD	
NQ2-2	34.8	44.8	120 in. / 120 in.	100%	90 in. / 120 in.	75%
NQ2-3	44.8	50.0	62 in. / 62 in.	100%	62 in. / 62 in.	100%

ATH-690-4.21 PID 114592



B-002-0-23



Run #	Depth (ft)		Recovery		RQD	
NQ2-1	26.0	29.8	45 in. / 45 in.	100%	12 in. / 45 in.	27%
NQ2-2	29.8	34.8	60 in. / 60 in.	100%	26 in. / 60 in.	43%
NQ2-3	34.8	44.8	116 in. / 120 in.	97%	74 in. / 120 in.	62%

ATH-690-4.21 PID 114592



B-002-0-23



Run #	Depth (ft)		Recovery		RQD	
NQ2-3	34.8	44.8	116 in. / 120 in.	97%	74 in. / 120 in.	62%

ATH-690-4.21 PID 114592



B-001-0-23



Run #	Depth (ft)		Recovery		RQD	
NQ2-1	29.5	33.5	37 in. / 48 in.	77%	23 in. / 48 in.	48%
NQ2-2	33.5	37.5	48 in. / 48 in.	100%	44 in. / 48 in.	92%
NQ2-3	37.5	44.5	84 in. / 84 in.	100%	79 in. / 84 in.	94%

ATH-690-4.21 PID 114592



B-001-0-23



Run #	Depth (ft)		Recovery		RQD	
NQ2-3	37.5	44.5	84 in. / 84 in.	100%	79 in. / 84 in.	94%
NQ2-4	44.5	49.5	60 in. / 60 in.	100%	58 in. / 60 in.	97%

ATH-690-4.21 PID 114592