BASED ON THE BORINGS COMPLETED FOR THIS EXPLORATION, THE SUBSURFACE PROFILE ENCOUNTERED UNDERLYING THE SURFACE AND FILL MATERIALS CAN BE GENERALLY CHARACTERIZED BY FIVE STRATA OF COHESIVE SOILS WITH VARYING STRENGTH AND MOISTURE CHARACTERISTICS

STRATUM I CONSISTED OF PREDOMINANTLY SOFT TO MEDIUM STIFF COHESIVE SOILS ENCOUNTERED UNDERLYING THE FILL IN BORINGS B-001 AND B-002-1 TO DEPTHS OF 11 FEET AND 8½ FEET, RESPECTIVELY (ELEVS, 708±AND 710±, RESPECTIVELY). THE STRATUM I SOILS CONSISTED OF SILTY CLAY (ODOT A-6B) WITH LITTLE SAND AND TRACE GR AVE

STRATUM II CONSISTED OF PREDOMINANTLY STIFF TO VERY STIFF COHESIVE SOILS ENCOUNTERED UNDERLYING THE FILL IN BORING B-004 AND STRATUM I IN BORING B-002-1. STRATUM II EXTENDED TO DEPTHS OF 11 FEET (ELEV. 708±) IN BORING B-002-1 AND 6 FEET (ELEV. 713±) IN BORING B-004. THESE COHESIVE SOILS CONSISTED OF SILT AND CLAY (A-6A) AS WELL AS SILTY CLAY (A-6B) WITH VARYING AMOUNTS OF SAND AND GRAVEI

**PEET REDOMINANTLY VERY STIFF TO HARD Add space between 1/2 and F ED UNDERLYING STRATUM I IN BORING B UVI, AS WELL AS STRATUM I'N BORINGS B-002-1 AND B-004. STRATUM III EXTENDED TO BORING TERMINATION AT A DEPTH OF 20 FEET IN BORING B-004, AS WELL AS TO DEPTHS OF 49% FEET (ELEV. 680±) IN BORING B-001 AND 38% FEAT (ELEV. 680±) IN BORING B-002-1. THESE COHESIVE SOILS CONSISTED OF SANDY SILT (A-4A), SILT AND CLAY (A-6A), AS WELL AS SILTY CLAY (A-6B).

STRATUM IV CONSISTED OF PREDOMINANTLY HARD COHESIVE SOILS ENCOUNTERED UNDERLYING STRATUM II IN BORINGS B-001 AND B-002-1 TO DEPTHS OF 73 FEET AND 737/FEET, RESPECTIVELY (ELEVS. 646± AND 645±, RESPECTIVELY). THESE COHESIVE SOILS CONSISTED OF SILT AND CLAY (A-6A) AS WELL AS SILTY CLAY (A-6B).

STRATUM V CONSISTED OF PREDOMINANTLY "VERY HARD" CHESIVE SOILS ENCOUNTERED UNDERLYING STRATUM IV IN BORINGS B-001 AND B-002-1 TO TERMINATION AT A DEPTH OF 80 FEET (ELEV. 639±). THESE COHESIVE SOILS CONSISTED OF SANDY SILT (A-4A).

GROUNDWATER WAS INITIALLY ENCOUNTERED DURING DRILLING AND GROUNDWATER WAS INITIALLY ENCOUNTERED DURING DRILLING AND OBSERVED UPON COMPLETION OF DRILLING OPERATIONS IN ONLY BORING B-001 AT A DEPTH OF 79.5 FEET (ELEV. 639.5). IT SHOULD BE NOTED THAT EACH BORING WAS GENERALLY DRILLED AND BACKFILLED OR SEALED WITHIN THE SAME DAY. THEREFORE, STABILIZED AMBIENT WATER LEVELS WERE NOT OBSERVED OVER THIS LIMITED TIME PERIOD. INSTRUMENTATION WAS NOT INSTALLED FOR LONG TERM GROUNDWATER PEADINGS LONG-TERM GROUNDWATER READINGS.

THIS GEOTECHNICAL EXPLORATION WAS PERFORMED IN ACCORDANCE WITH THE STATE OF OHIO, DEPARTMENT OF TRANSPORTATION, OFFICE OF GEOTECHNICAL ENGINEERING, SPECIFICATIONS FOR GEOTECHNICAL EXPLORATIONS (SGE), DATED JULY 2020.

AVAILABLE INFORMATION

THE SOIL, BEDROCK, AND GROUNDWATER INFORMATION COLLECTED FOR THIS SUBSURFACE EXPLORATION THAT CAN BE CONVENIENTLY DISPLAYED ON THE SOIL PROFILE SHEETS HAS BEEN PRESENTED. GEOTECHNICAL REPORTS, IF PREPARED, ARE AVAILABLE FOR REVIEW ON THE OFFICE OF CONTRACT SALES WEBSITE.

RECON CPI 10/01/20 DRILLING TB 10/07/20 THROUGH 10/09/20 DRAWN TRR 01/22 REVIEWED CPI 01/22

B-001 keep as a whole

B-004

keep as a whole

B-001

keep as a whole

STARTUM III keep as a whole

STATE OF THE STATE OF THE STATE OF ERLYING STRA [GS B-002-] AND ANI AT A DEDTU

keep as a whole

the "1" is oddly faint

HARD" COH Add space between " and C

> B-002-1 keep as a whole

SOIL PROFILR - ROADWAY EXPLORATION NOTES - (CONTINUED).

CPI 01/22 CPI 01/18/22

101140

2 43

FUL-120-14.08