

SHEET NUM.													PART.	ITEM	ITEM	GRAND	UNIT	DESCRIPTION	SEE SHEET NO.
P.0	Office Calcs	P.3	P.4	P.5	P.6	P.17	P.18	P.27	P.32				01/IMS	EXT	TOTAL				
		LS											LS	201	11000	LS	CLEARING AND GRUBBING		
	1,887												1,887	202	23000	1,887	SY	PAVEMENT REMOVED	
							1,396						1,396	202	30000	1,396	SF	WALK REMOVED	
							45						45	202	30001	45	SF	WALK REMOVED, AS PER PLAN	P.4
							606						606	202	32000	606	FT	CURB REMOVED	
							114						114	202	35100	114	FT	PIPE REMOVED, 24" AND UNDER	
							5						5	202	58100	5	EACH	CATCH BASIN REMOVED	
							80						80	SPECIAL	20270000	80	FT	FILL AND PLUG EXISTING CONDUIT	P.4
							159						159	202	75000	159	FT	FENCE REMOVED	
22													22	203	10000	22	CY	EXCAVATION	
2													2	203	20000	2	CY	EMBANKMENT	
	497						278						775	204	10000	775	SY	SUBGRADE COMPACTION	
							25						25	606	15050	25	FT	GUARDRAIL, TYPE MGS	
							1						1	606	26150	1	EACH	ANCHOR ASSEMBLY, MGS TYPE E	
							1						1	606	26550	1	EACH	ANCHOR ASSEMBLY, MGS TYPE T	
							1						1	606	60022	1	EACH	IMPACT ATTENUATOR, TYPE 2 (UNIDIRECTIONAL) (PERMANENT)	
							254						254	607	23000	254	FT	FENCE, TYPE CLT	
							832						832	608	52000	832	SF	CURB RAMP	
							90						90	622	24000	90	FT	CONCRETE BARRIER, TYPE D	
							226						226	622	24001	226	FT	CONCRETE BARRIER, TYPE D, AS PER PLAN	P.3
		1											1	622	90000	1	FT	BARRIER, MISC.: TRANSITION CONCRETE BARRIER, TYPE D TO CITY OF TOLEDO INTEGRAL CONCRETE CURB-TYPE A	P.3
																		EROSION CONTROL	
				15	5								20	616	10000	20	MGAL	WATER	
		2											2	659	00100	2	EACH	SOIL ANALYSIS TEST	
		1,329											1,329	659	10000	1,329	SY	SEEDING AND MULCHING	
		66											66	659	14000	66	SY	REPAIR SEEDING AND MULCHING	
		66											66	659	15000	66	SY	INTER-SEEDING	
		0.18											0.18	659	20000	0.18	TON	COMMERCIAL FERTILIZER	
		0.27											0.27	659	31000	0.27	ACRE	LIME	
		3.75											3.75	659	35000	3.75	MGAL	WATER	
		5,000											5,000	832	30000	5,000	EACH	EROSION CONTROL	
																		DRAINAGE	
							2						2	601	21050	2	SY	TIED CONCRETE BLOCK MAT WITH TYPE 1 UNDERLAYMENT	
							25						25	605	13300	25	FT	6" UNCLASSIFIED PIPE UNDERDRAINS	
							265						265	605	14000	265	FT	6" BASE PIPE UNDERDRAINS	
							44						44	611	00510	44	FT	6" CONDUIT, TYPE F FOR UNDERDRAIN OUTLETS	
							107						107	611	04400	107	FT	12" CONDUIT, TYPE B	
							1						1	611	98150	1	EACH	CATCH BASIN, NO. 3	
							2						2	611	98180	2	EACH	CATCH BASIN, NO. 3A	
							1						1	611	98720	1	EACH	INLET, NO. 2-8	
							1						1	611	99710	1	EACH	PRECAST REINFORCED CONCRETE OUTLET	
																		PAVEMENT	
	83												83	301	56000	83	CY	ASPHALT CONCRETE BASE, PG64-22, (449)	
			6										6	301	56001	6	CY	ASPHALT CONCRETE BASE, (449), AS PER PLAN	P.4
	83												83	304	20000	83	CY	AGGREGATE BASE	
	58												58	407	20000	58	GAL	NON-TRACKING TACK COAT	
	20												20	441	70300	20	CY	ASPHALT CONCRETE INTERMEDIATE COURSE, TYPE 2, (449)	
	17												17	441	70000	17	CY	ASPHALT CONCRETE SURFACE COURSE, TYPE 1, (449), PG64-22	
							278						278	452	10050	278	SY	6" NON-REINFORCED CONCRETE PAVEMENT, CLASS QC MS	
							32						32	609	30000	32	FT	CURB, TYPE 8	
							163						163	609	98000	163	FT	CURB, MISC.: CITY OF TOLEDO CONCRETE CURB, TYPE A	P.3
																		LIGHTING	
								6					6	625	00450	6	EACH	CONNECTION, FUSED PULL APART	
								4					4	625	00460	4	EACH	CONNECTION, UNFUSED PULL APART	
								9					9	625	00480	9	EACH	CONNECTION, UNFUSED PERMANENT	
								1					1	625	02501	1	EACH	TRANSFORMER BASE, TYPE AT-A, AS PER PLAN	P.31
								1					1	625	10505	1	EACH	ERECTING REUSABLE DOWNED LIGHT POLE, AS PER PLAN	P.31
								1					1	625	14101	1	EACH	LIGHT POLE FOUNDATION, 24" X 8' DEEP, AS PER PLAN	P.31
								1					1	625	14500	1	EACH	LIGHT POLE FOUNDATION	
								115					115	625	23400	115	FT	NO. 10 AWG POLE AND BRACKET CABLE	
								142					142	625	24324	142	FT	1-1/2" DUCT CABLE WITH THREE NO. 6 AWG 2400 VOLT CABLES	
								233					233	625	25400	233	FT	CONDUIT, 2", 725.04	
								285					285	625	25500	285	FT	CONDUIT, 3", 725.04	
								79					79	625	25902	79	FT	CONDUIT, JACKED OR DRILLED, 725.04, 3"	
								20					20	625	25920	20	FT	CONDUIT, MISC.: EXTEND CONDUIT	P.31
								1					1	625	26253	1	EACH	LUMINAIRE, CONVENTIONAL, SOLID STATE (LED), AS PER PLAN, 250W HPS EQUIVALENT, TYPE III, 480 VOLT	P.31
								2					2	625	27520	2	EACH	REMOVAL OF LUMINAIRE AND REERECTION	
								2					2	625	28000	2	EACH	GLARE SHIELD	

GENERAL SUMMARY

DESIGN AGENCY

 DESIGNER
 AIM
 REVIEWER
 JRE 01/28/26
 PROJECT ID
 124242
 SHEET TOTAL
 P.14 | P.47