
**DRAFT REPORT
ROADWAY EXPLORATION REPORT
SUM-76-6.15
SUMMIT COUNTY, OHIO
PID#: 100713**

Prepared For:

GPD GROUP
520 South Main Street, Suite 2531
Akron, Ohio 44311

Prepared by:

NATIONAL ENGINEERING AND ARCHITECTURAL SERVICES INC.
2800 Corporate Exchange Drive, Suite 240
Columbus, Ohio 43231

NEAS PROJECT 19-0002

July 31, 2019



EXECUTIVE SUMMARY

The Ohio Department of Transportation (ODOT) has proposed an interstate improvement project (SUM-76-6.15, PID 100713) along portions of Interstate Route 76 (IR-76), IR-77, and IR-277 part of the Akron Beltway in Akron, Summit County, Ohio. This portion of the Akron Beltway planned for improvement is designated as the Kenmore Leg and includes the IR-77 and IR-76 Interchange (NW Interchange), the IR-76 and IR-277 Interchange (SW Interchange), as well as portions of connecting mainline interstates and associated ramps. The overall project limits extend west to east along IR-76/IR-277 from approximately 30th Street (St) SW to Maryland Avenue (Ave) and south to north along IR-76/IR-77 from approximately IR-277 to Lawton St. It is our understanding that the proposed project improvements consist of: 1) the reconstruction/widening of IR-76 Eastbound (EB), IR-76 Northbound (NB) and IR-77 NB in the vicinity of the NW Interchange; 2) the reconstruction/widening of IR-277 EB and IR-76 Westbound (WB) in the vicinity of the SW Interchange; 3) the realignment and reconstruction of 3 connecting ramps (Ramp T, Ramp V, and Ramp W); 4) the widening/reconstruction of 7 connecting ramps/roadways (Ramp N, Ramp M, Ramp U, Ramp J, Ramp L, Ramp A2 and Ramp B); and, 5) the construction of approximately 13 noise barriers along the referenced interstates within the project limits.

National Engineering & Architectural Services, Inc. (NEAS) has been contracted to perform geotechnical engineering services for the project. The purpose of the geotechnical engineering services was to perform geotechnical explorations within the project limits to obtain information concerning the subsurface soil and groundwater conditions relevant to the design and construction of the project. Between January 14, 2019 and May 10, 2019, NEAS performed the site reconnaissance and exploration program for the project. The subsequent document presents the results of the roadway exploration for IR-76, IR-77 and IR-277 mainline freeway segments and the associated connecting ramps noted above. As part of the interchange improvement project, NEAS advanced a total of 86 borings which were utilized for roadway and subgrade characterization purposes.

The existing pavement sections encountered varied throughout the project limits, and consisted of asphalt pavement, concrete pavement or a combination of the two, overlying granular base material. Project asphalt pavement only thickness ranged from 5 to 15.5 inches while concrete pavement only thicknesses ranged from 9 to 16 inches. In general, the overall thickness of the project pavements ranged from 5 to 18 inches. Below the existing pavement section, the subgrade conditions in the project area are relatively consistent and are generally comprised of either fill soils (i.e., embankment fill, historical/urban fill, etc.) or natural soils consisting of non-cohesive sand, silt and gravel combinations or low to moderately plastic sandy silt, silt, and silt/clay combinations. About fifty percent of the subgrade soils encountered at the site were classified as either Coarse and Fine Sand (A-3a) or cohesive/non-cohesive Sandy Silt (A-4a). The remainder of the subgrade soils were generally classified as A-1-a, A-1-b, A-2-4, A-3, A-4b or A-6a. The exception to this is the southeast portion of the project where natural organic silts (A-8a) were encountered. With respect to sulfate within the subgrade soil, based on the project laboratory testing program, each subgrade soil sample tested was determined to have a sulfate content of less than 5,000 parts per million (i.e., lower than the level which ODOT considers high and may prevent the use of chemical stabilization).

Based on our evaluation of the subsurface conditions and our geotechnical engineering analyses of the proposed improvement project, it is our opinion that subgrade conditions are generally satisfactory and pavement can be designed without the need for extreme levels of remediation. In general, it is recommended that the subgrade soil of project interstates and connecting ramps be globally (chemically) stabilized to a depth of 14 inches utilizing cement as the stabilization chemical. In addition to subgrade stabilization, bedrock was encountered at various locations within two feet of the bottom of the proposed asphalt or concrete pavement and therefore is recommended for remediation. Estimated limits of rock removal are presented within Section 5.4.2. of this report. NEAS's opinion that the subgrade soils will provide adequate pavement support assuming it is designed and constructed in accordance with the recommendations provided within this report, as well as all applicable ODOT standards and specifications.

TABLE OF CONTENTS

1. INTRODUCTION.....	4
1.1. GENERAL.....	4
2. GEOLOGY AND OBSERVATIONS OF THE PROJECT	4
2.1. GEOLOGY AND PHYSIOGRAPHY	4
2.2. HYDROLOGY/HYDROGEOLOGY.....	5
2.3. MINING AND OIL/GAS PRODUCTION.....	6
2.4. HISTORICAL RECORDS AND PREVIOUS PHASES OF PROJECT EXPLORATION.....	6
2.5. FIELD RECONNAISSANCE	6
2.5.1. <i>Land Use and Cover</i>	7
2.5.2. <i>Interstate Routes</i>	7
2.5.3. <i>Connecting Ramps</i>	7
3. GEOTECHNICAL EXPLORATION.....	9
3.1. ROADWAY EXPLORATION PROGRAM.....	9
3.2. LABORATORY TESTING PROGRAM.....	10
3.2.1. <i>Classification Testing</i>	10
3.2.2. <i>Standard Penetration Test Results</i>	10
3.2.3. <i>Sulfate Testing</i>	10
3.2.4. <i>Direct Shear Testing</i>	11
3.2.5. <i>Loss on Ignition Testing</i>	11
3.2.6. <i>Unconfined Compressive Strength of Cohesive Soil Testing</i>	11
4. FINDINGS.....	11
4.1. EXISTING PAVEMENT	12
4.1.1. <i>Pavement Thickness/Buildup Measurements</i>	12
4.2. SUBSURFACE CONDITIONS	12
4.2.1. <i>IR-77/IR-76</i>	13
4.2.2. <i>IR-277/IR-76</i>	13
4.2.3. <i>Ramp B & A2</i>	13
4.2.4. <i>Ramp J</i>	14
4.2.5. <i>Ramp L</i>	14
4.2.6. <i>Ramps N & M</i>	14
4.2.7. <i>Ramp P</i>	15
4.2.8. <i>Ramp T</i>	15
4.2.9. <i>Ramp U</i>	15
4.2.10. <i>Ramp V</i>	16
4.2.11. <i>Ramp W</i>	16
4.2.12. <i>Groundwater</i>	16
5. ANALYSES AND RECOMMENDATIONS.....	17
5.1. SUBGRADE ANALYSIS	17
5.1.1. <i>Pavement Design Recommendations</i>	17
5.1.2. <i>Unsuitable Subgrade</i>	18
5.1.2.1. <i>Rock</i>	18
5.1.2.2. <i>Prohibited Soils</i>	19
5.1.2.3. <i>Weak Soils</i>	19
5.1.2.4. <i>High Moisture Content Soils</i>	20
5.2. EMBANKMENT STABILITY ANALYSIS.....	21
5.3. EMBANKMENT CONSTRUCTION RECOMMENDATIONS.....	23
5.4. STABILIZATION RECOMMENDATIONS.....	24
5.4.1. <i>Subgrade Stabilization</i>	24
5.4.2. <i>Shallow Bedrock</i>	24
6. QUALIFICATIONS	26

LIST OF TABLES

TABLE 1:	DIRECT SHEAR TESTING SUMMARY	11
TABLE 2:	UNCONFINED COMPRESSIVE STRENGTH TESTING SUMMARY	11
TABLE 3:	MEASURED PAVEMENT THICKNESS AT BORING LOCATIONS	12
TABLE 4:	PAVEMENT DESIGN VALUES	18
TABLE 5:	SHALLOW ROCK LOCATION SUMMARY	18
TABLE 6:	PROHIBITED SOILS LOCATION SUMMARY	19
TABLE 7:	WEAK SOIL LOCATIONS SUMMARY	20
TABLE 8:	HIGH MOISTURE CONTENT SOILS LOCATION SUMMARY	20
TABLE 9:	SOIL PROFILE AND ESTIMATED ENGINEERING PROPERTIES – IR-76 EB - STA. 98+00	21
TABLE 10:	SOIL PROFILE AND ESTIMATED ENGINEERING PROPERTIES – IR-77 SB/IR-76 EB – STA. 242+00	22
TABLE 11:	SOIL PROFILE AND ESTIMATED ENGINEERING PROPERTIES – IR-76 WB – STA. 50+00	22
TABLE 12:	SOIL PROFILE AND ESTIMATED ENGINEERING PROPERTIES – IR-76 WB – STA. 50+00	22
TABLE 13:	SOIL PROFILE AND ESTIMATED ENGINEERING PROPERTIES – RAMP A2 – STA. 15+00	22
TABLE 14:	SOIL PROFILE AND ESTIMATED ENGINEERING PROPERTIES – RAMP A2 – STA. 17+00	22
TABLE 15:	ESTIMATED LIMITS OF REQUIRED ROCK EXCAVATION	25

LIST OF APPENDICES

APPENDIX A:	SOIL PROFILE SHEETS
APPENDIX B:	BORING LOGS AND LABORATORY TESTING RESULTS
APPENDIX C:	SULFATE CONTENT DATA
APPENDIX D:	GEOTECHNICAL BULLETIN 1 (GB1) ANALYSIS SPREADSHEETS
APPENDIX E:	EMBANKMENT STABILITY OUTPUTS
APPENDIX F:	ODNR OIL WELL REPORTS

1. INTRODUCTION

1.1. General

National Engineering & Architectural Services, Inc. (NEAS) presents our Roadway Exploration Report for the Ohio Department of Transportation (ODOT) project SUM-76-6.15 (PID 100713) along portions of Interstate Route 76 (IR-76), IR-77, and IR-277 part of the Akron Beltway in Akron, Summit County, Ohio. The project portion of the Akron Beltway planned for improvement is designated as the Kenmore Leg and includes the IR-77 and IR-76 Interchange (NW Interchange), the IR-76 and IR-277 Interchange (SW Interchange), as well as portions of connecting mainline interstates and associated ramps. This report presents a summary of the project encountered surficial and subsurface conditions and our recommendations for subgrade stabilization, embankment construction and pavement design parameters for: 1) the reconstruction/widening of IR-76 Eastbound (EB), IR-76 Northbound (NB) and IR-77 NB in the vicinity of the NW Interchange; 2) the reconstruction/widening of IR-277 EB and IR-76 Westbound (WB) in the vicinity of the SW Interchange; 3) the realignment and reconstruction of ramps (Ramp T, Ramp V, and Ramp W); and, 4) the widening/reconstruction of 7 connecting ramps/roadways (Ramp N, Ramp M, Ramp U, Ramp J, Ramp L, Ramp A2 and Ramp B). The analysis performed as part of this report has been performed in accordance with ODOT's *Geotechnical Bulletin 1* (GB1) (ODOT [1], 2019) and *Pavement Design Manual* (PDM) (ODOT PDM, 2019).

The exploration was conducted in general accordance with NEAS's proposal to GPD Group (GPD), dated May 22, 2018 and with the provisions of ODOT's *Specifications for Geotechnical Explorations* (SGE) (ODOT SGE, 2019).

The scope of work performed by NEAS as part of the referenced project included: a review of published geotechnical information; performing 86 total test borings as part of the roadway exploration; laboratory testing of soil samples in accordance with the SGE; performing geotechnical engineering analysis to assess subgrade stabilization requirements, embankment and pavement design parameters; and development of this summary report.

2. GEOLOGY AND OBSERVATIONS OF THE PROJECT

2.1. Geology and Physiography

The topography at the project site is relatively flat in the northern and southern portions of the site with sloping grades present in the central portion. In the northern portion of the site the topography gradually slopes upwards from west to east with the peak elevation within this part of the site at an approximate elevation of 1076 ft above mean sea level (amsl) near Ramp J. The central portion of the project site between the NW and SW interchanges generally slopes upward from west to east with a peak elevation of 1033 ft amsl near the East Ave/IR-76 overpass. The south end of the project site slopes very gradually upward from west to east with the peak elevation being approximately 1000 ft amsl at the eastern end of IR-277.

The project site is located within the Akron-Canton Interlobate Plateau physiographic region, part of the Glaciated Allegheny Plateaus (ODGS, 1998). This is a moderate relief, hummocky area between two converging glacial lobes dominated by kames, kame terraces, eskers, kettles, kettle lakes, and bogs/fens. Soils in this region are characteristically Wisconsinan-age sand and older drift over Devonian to Pennsylvanian age sandstones, conglomerates and shales.

Roadway Exploration Report - DRAFT
SUM-76-6.15 – Kenmore Leg
Summit County, Ohio
PID: 100713

The northern portion of the project site (IR-77, IR-76) is mapped as 30 ft of Wisconsinan-age sand and gravel, underlain by 150 feet of complexly interbedded deposits of clay, silt, sand, gravel and till. The area which includes the NW Interchange as well as the eastern portions of IR-76 is mapped as 160 ft of Wisconsinan-age till above bedrock. The portion of the project between the NW and SW Interchanges is mapped as 80 ft of Wisconsinan-age till near the SW interchange thinning out to 20 ft towards the NW interchange. The southern portion of the of project site (IR-277 and IR-76, SW interchange) is mapped as 160 ft of Wisconsinan-age Ice-contact deposits, underlain by 90 feet of Wisconsinan-age sand and gravel. Small areas of organic deposits were noted on the surficial geology maps southeast of the SW Interchange (ODGS, 2005).

Based on the Bedrock Geologic Units Map of Ohio (USGS & ODGS, 2006), bedrock within the project area consists of shale and siltstone of the Allegheny and Pottsville Groups, Undivided. This unit is comprised of Pennsylvanian-age shale and siltstone locally containing marine fossils, with minor lithologic constituents of limestone and sandstone. The shale in this formation is described as black, gray and olive in color, clayey to silty, and calcareous in part, while the siltstone is described as gray, greenish and olive in color, clayey to sandy, and thin to medium bedded. Bedrock is anticipated to be sloping upward from west to east at the project site. Based on the ODNR bedrock topography map of Ohio, bedrock elevations at the project site can be expected to be between elevations of 1050 and 800 ft amsl (ODGS, 2003), putting bedrock at a depth ranging from about 225 ft below ground surface (bgs) to outcropping (above the ground surface) in locations. Bedrock was observed to be relatively shallow in the northeast portion of the site as outcropped rock was observed on the eastern side of IR-76 near the East Ave/IR-76 crossing as well as along the northern portion of Ramp V.

The soils at the project site are generally mapped (Web Soil Survey) by the Natural Resources Conservation Service (USDA, 2015) as Udorthents. These soils can be described as soils that have been disturbed by cutting and filling. These soils are not classified according to the AASHTO method of soil classification, but it can be expected that these soils will largely consist of fill soils and often vary in composition. A significant portion of the soils surrounding the project site have been mapped as Canfield-Urban land complex, Chili-Urban land complex, Bogart loam and Carlisle Muck. Soils in the Canfield series are characterized as very deep, moderately well drained soils formed in Wisconsinan age till on plains. Soils in the Chili series are characterized as very deep, well drained soils on outwash plains, terraces, kames, and beach ridges while Bogart series soils are characterized a very deep, moderately well drained soils that formed in stratified outwash deposits on terraces, beach ridges, and outwash plains. Soil mapped as Carlisle Muck were encountered near the SW Interchange as well as southeast of the interchange. The Carlisle Muck series are characterized as very deep, very poorly drained soils formed in woody and herbaceous organic materials in depressions within lake plains, outwash plains, till plains, flood plains, and moraines. Based on the Web Soil Survey these surrounding soils are comprised of a mix of both coarse-grained and fine-grained soils, classifying as A-4, A-2, A-6 or A-2-6 type soils according to the AASHTO method of soil classification. The soils mapped as Carlisle Muck and are classified primarily as A-8 according to the AASHTO method of soil classification.

2.2. Hydrology/Hydrogeology

Groundwater at the project site can be expected at an elevation consistent with that of the Tuscarawas River (or tributaries to the Tuscarawas River) as it is the most dominant hydraulic influence in the vicinity of the project's boundaries. The water level of the Tuscarawas River may be generally representative of the local groundwater table. However, as there are relatively thin overburden soils at the site and the topography of the site gradually slopes downward to the river's elevation, it is not anticipated that a static groundwater table will be present within the overburden soil. Rather it is anticipated that if encountered, groundwater is

likely to be present at the bedrock surface or within the upper few feet of bedrock where the stratum is highly weathered. Furthermore, it should be noted that perched groundwater systems may be existent in areas due to the presence of fine-grained soils making it difficult for groundwater to permeate to the bedrock surface. According to historic boring logs and associated groundwater observations, groundwater elevations range from approximately 953 to 997 ft amsl across the project site.

The project site is not located within a special flood hazard area based on available mapping by the Federal Emergency Management Agency's (FEMA) National Flood Hazard mapping program (FEMA, 2019).

2.3. Mining and Oil/Gas Production

No abandoned mines are noted on ODNR's Abandoned Underground Mine Locator in the vicinity of the bridge site (ODNR [1], 2016).

Four (4) active oil or gas wells were mapped on ODNR's Ohio Oil & Gas Locator in the vicinity of the project site (ODNR [2], 2016). Three are located near the NW Interchange while one is located at the southeast end of the project near IR-277. One active well was located 230 ft east of S Hawkins Ave and 330 ft north of Morse St. while a second active well was located 522 ft east of S Hawkins Ave and 615 ft north of Jason St. The third active well was located 490 ft west of Anfield St. and 315 ft north of Morse St. and the fourth active well was located 730 ft east of Gaugler Ave. and 400 ft north of W Waterloo Rd. Each of the identified wells were drilled to depths greater than 3900 ft bgs and are currently producing. More information on the identified wells can be found on the ODNR Oil Well reports included in Appendix F.

2.4. Historical Records and Previous Phases of Project Exploration

The following report/plans were available for review and evaluation for this report:

- Soil Profile Sheets as part of ODOT project SUM-18-6.88, Sheets 1-17, prepared by the State Highway Testing and Research Laboratory dated Nov. 10, 1960;
- Soil Profile Sheets as part of ODOT project SUM-5-10.62, Sheets 1-9, prepared by the State Highway Testing and Research Laboratory dated Sept. 25, 1961;
- Soil Profile Sheets as part of ODOT project SUM-224-5.85 Sheets 1-12, prepared by the State Highway Testing and Research Laboratory dated May 9, 1960;
- Soil Profile Sheets as part of ODOT project SUM-5-9.33 Sheets 1-27, prepared by the State Highway Testing and Research Laboratory dated Oct. 30, 1963; and,
- Soil Profile Sheets as part of ODOT project SUM-18-9.23 Sheets 1-16, prepared by the State Highway Testing and Research Laboratory dated Jan. 6, 1961.

Historical soil borings associated with the above plans were reviewed, however, were not utilized for our analysis, and therefore, are not referenced or presented within this report.

2.5. Field Reconnaissance

Field reconnaissance visits for the overall project area were conducted between January 14, 2019 and January 17, 2019, along IR-76, IR-77, IR-277 and connecting ramps. Site conditions, including the existing pavement conditions, were noted and photographed during the visit. A summary of the land use and pavement conditions by roadway segment including photographs of notable pavement distress are provided and is provided below.

Roadway Exploration Report - DRAFT
SUM-76-6.15 – Kenmore Leg
Summit County, Ohio
PID: 100713

2.5.1. Land Use and Cover

The land use of most of the project area along IR-76 and IR-77 consists of residential property generally comprised of family homes and apartment buildings. Near the SW Interchange and along the project portion of IR-277 the land use is generally open property and wetlands. More minor land uses within the area surrounding the project include: 1) educational/institutional facilities (i.e., high school, middle school, churches, public works, etc.); 2) commercial property including various small shops and restaurants; and 3) industrial structures.

2.5.2. Interstate Routes

In general, the pavement condition along IR-76 and IR-277 was observed to be fair to good with marginal signs of weathering and surface wear. Low to moderate severity longitudinal and transverse cracking was common along these sections, as well as a few low severity potholes and low severity crack sealing deficiencies (Photograph 1).

The condition of the pavement along IR-77 can be divided into two sections. The pavement condition of the asphalt portion of IR-77 located at the northern end of the project was observed to be fair with minor signs of weathering and surface wear. Low severity longitudinal and lateral joint spalling and patching was observed in this section (Photograph 2). The pavement condition of the concrete portion of IR-77 located just north of the NW interchange was observed to be poor with various signs of distress and surface wear. Low severity settlement as well as high severity longitudinal and transverse cracking as well as spalling was common in this section. Extensive high severity faulting was also apparent (Photograph 3).

The project portion of each interstate appeared to be well drained to storm drains, drainage swales, and/or grassy/vegetated embankment slopes. Ponding water or obvious drainage deficiencies were not observed.

2.5.3. Connecting Ramps

The pavement condition for the connecting ramps was generally observed to be good with few low severity transverse cracks along the ramps. The exceptions to this was Ramp J and Ramp L which were observed to be in fair condition with moderate severity longitudinal and transverse cracking as well as moderate severity rutting and edge cracking (Photograph 4). The concrete portion of Ramp P was also observed to be in poor condition with extensive medium to high severity longitudinal and transverse cracks (Photograph 5).

Photograph 1: IR-76 and IR-277 Pavement Wear



Roadway Exploration Report - DRAFT
SUM-76-6.15 – Kenmore Leg
Summit County, Ohio
PID: 100713

Photograph 2: IR-77 Pavement (Asphalt)



Photograph 3: IR-77 Pavement (Concrete)



Photograph 4: Ramp L Pavement



Photograph 5: Ramp P Concrete Pavement



3. GEOTECHNICAL EXPLORATION

3.1. Roadway Exploration Program

The subsurface exploration was conducted by NEAS between February 25, 2019 and May 10, 2019 and included 86 borings drilled to depths between 2.8 and 42.6 ft below ground surface (bgs). The boring locations were selected by NEAS in general accordance with the guidelines contained in the SGE with the intent to evaluate subsurface soil and groundwater conditions. Borings were typically located within the planned roadway/subgrade improvement areas that were not restricted by underground utilities or dictated by terrain (i.e. steep embankment slopes). Target boring locations were located in the field by NEAS prior to drilling utilizing handheld GPS equipment. Each as-drilled project boring location and corresponding ground surface elevation was surveyed in the field by Northwest Consultants, Inc. (project surveyor) following drilling. Each individual project boring log (included within Appendix B) includes the recorded boring latitude and longitude location (based on the surveyed Ohio State Plane North, NAD83, location) and the corresponding ground surface elevation. The boring locations are depicted in the Soil Profile Sheets provided in Appendix A.

Borings were drilled using either a CME 45B, CME 55T or CME 55X, truck-mounted or track-mounted drilling rigs utilizing 3.25-inch (inner diameter) hollow stem augers. Soil samples for subgrade borings were typically recovered continuously to a depth of 7.5 ft bgs, while samples for embankment/roadway borings were typically recovered at 2.5-ft intervals to varying termination depths, each using an 18-inch split spoon sampler (AASHTO T-206 “Standard Method for Penetration Test and Split Barrel Sampling of Soils.”). It should be noted that some embankment/roadway borings are planned to be utilized as noise wall borings for future phases of the project. The soil samples obtained from the exploration program were visually observed in the field by the NEAS field representative and preserved for review by a Geologist for possible laboratory testing. Standard penetration tests (SPT) were conducted using CME auto hammers that have been calibrated to be between 78.0% and 85.0% efficient (depending on the specific rig used and the calibration date of the hammer) as indicated on the boring logs (Appendix B).

Field boring logs were prepared by drilling personnel and included pavement description (where present), lithological description, SPT results recorded as blows per 6-inch increment of penetration, and estimated unconfined shear strength values on specimens exhibiting cohesion (using a hand-penetrometer). After completing the borings, the boreholes were backfilled with either auger cuttings, bentonite chips, or a

combination of these materials and patched accordingly with the cold patch asphalt and/or cement when drilling through the roadway.

3.2. Laboratory Testing Program

The laboratory testing program consisted of classification testing, moisture content determinations, sulfate content testing, direct shear testing and loss on ignition testing. The individual laboratory data sheets and results are included in Appendix B while a summary of the sulfate content testing results can be found in Appendix C. Additionally, data from the laboratory testing program was incorporated onto the final borings logs (when possible). Soil samples are retained at the laboratory for 60 days following report submittal, after which time they will be discarded.

3.2.1. Classification Testing

Representative soil samples were selected for index property (Atterberg Limits) and gradation testing for classification purposes on approximately 42% of the samples. At each boring location, the upper two samples obtained below the proposed top of subgrade elevation were generally tested while additional samples were selected for testing with the intent of properly classifying the subsurface soil and groundwater conditions within the planned project limits. Soils not selected for testing were compared to laboratory tested samples/strata and classified visually. Moisture content testing was conducted on all samples. The laboratory testing was performed in general accordance with applicable AASHTO specifications and ODOT Supplements.

Final classification of soil strata in accordance with AASHTO M-145 “Classification of Soils and Soil-Aggregate Mixtures for Highway Construction Purposes,” as modified by ODOT “Classification of Soils” was made once laboratory test results became available. The results of the soil classification are presented on the boring logs in Appendix B.

3.2.2. Standard Penetration Test Results

Standard Penetration Tests (SPT) and split-barrel (commonly known as split-spoon) sampling of soils were performed at varying intervals (i.e., continuous, 2.5, or 5.0-ft intervals) in the project borings performed. To account for the high efficiency (automatic) hammers used during SPT sampling, field SPT N-values were converted based on the calibrated efficiency (energy ratio) of the specific drill rig's hammer. Field N-values were converted to an equivalent rod energy of 60% (N_{60}) for use in analysis or for correlation purposes. The resulting N_{60} values are shown on the boring logs provided in Appendix B.

3.2.3. Sulfate Testing

Sulfate testing was generally performed on one sample for each roadway boring performed for pavement/subgrade design purposes for the subgrade analyses. The selected samples were tested in accordance with ODOT Supplement 1122, “Determining Sulfate Content in Soils” dated July 17, 2015. In general, the upper most sample (within 3 ft of the proposed subgrade elevation) from each boring was tested. Based on the testing results, each subgrade soil sample tested was determined to have a sulfate content of less than 5,000 parts per million (i.e., lower than the level which ODOT considers high and may prevent the use of chemical stabilization). Testing results are summarized in Appendix C.

Roadway Exploration Report - DRAFT
SUM-76-6.15 – Kenmore Leg
Summit County, Ohio
PID: 100713

3.2.4. *Direct Shear Testing*

Direct Shear testing was conducted in accordance with ASTM D 3080, “Direct Shear Test of Soils Under Consolidated Drained Conditions” on one Shelby Tube sample (ST-1) obtained from boring B-017-0-18. The soil tested was classified as hard, brown mottled with orangish brown and gray, Sandy Silt. The results of the Direct Shear test are summarized in Table 1 below and in Appendix B.

Table 1: Direct Shear Testing Summary

Boring Number	Depth of Sample (ft)	Classification	Average Wet Density ⁽¹⁾ (pcf)	Average Void Ratio ⁽¹⁾	Cohesion - Effective (psf)	Angle of Friction - Effective (°)
B-017-0-18	2.0 - 4.0	Sandy Silt (A-4a)	129.0	0.521	173	29.5
Notes:						
1. Indicated average values were collected prior to Direct Shear testing (i.e., initial readings).						

3.2.5. *Loss on Ignition Testing*

Loss on Ignition testing (LOI) was performed on one Shelby tube sample (ST-2) from boring B-034-0-18 which was performed for embankment/roadway design purposes. The selected sample was tested in accordance with AASHTO T267 “Standard Method of Test for Determination of Organic Content in Soils by Loss on Ignition”. The sample was found to have an organic content of 28.4%. Per the SGE, an organic content greater than 10% is considered highly organic. The lab test report of the LOI test is presented in Appendix B.

3.2.6. *Unconfined Compressive Strength of Cohesive Soil Testing*

An Unconfined Compressive Strength of Cohesive Soils Test was conducted in accordance with ASTM D 2166 “Standard Test Method for Unconfined Compressive Strength of Cohesive Soil” on ST-2 from boring B-034-0-18. In general, the soil was classified as very soft, black with brown, organic silt, highly organic. The Unconfined Compressive Strength of Cohesive Soil Test results are summarized in Table 2 below and provided in Appendix B.

Table 2: Unconfined Compressive Strength Testing Summary

Boring Number	Depth of Sample (ft)	Classification	Wet Density (pcf)	Moisture Content (%)	Unconfined Compressive Strength (psf)	Strain (%)
B-034-0-18	5.0 - 5.5	Organic Silt (A-8a)	73.7	26.2	257	10.0

4. FINDINGS

The subsurface conditions encountered during NEAS’s explorations are described in the following subsections and/or on each boring log presented in Appendix B. The boring logs represent NEAS’s interpretation of the subsurface conditions encountered at each boring location based on our site observations, field logs, visual review of the soil samples by NEAS’s geologist, and laboratory test results. The lines designating the interfaces between various soil strata on the boring logs represent the approximate interface location; the actual transition between strata may be gradual and indistinct. The subsurface soil and groundwater characterizations included herein, including summary test data, are based on the subsurface findings from the geotechnical explorations performed by NEAS as part of the referenced project. At the time of the composition of this report, pavement grade information has been assumed to be

Roadway Exploration Report - DRAFT
SUM-76-6.15 – Kenmore Leg
Summit County, Ohio
PID: 100713

consistent with project Plan and Profile sheets provided by GPD dated June 25, 2019 and labeled as Option 4. It should be noted that for the purposes of this report and our analysis the term 'subgrade' has been assumed to represent soils and/or soil conditions from 1.5 ft below proposed final pavement grades to a depth of 7.5 ft below the proposed pavement grades

4.1. Existing Pavement

4.1.1. Pavement Thickness/Buildup Measurements

The pavement section thicknesses in terms of asphalt and/or concrete were measured at subgrade borings where existing pavement was present. Pavement section thicknesses were measured during the subsurface exploration and are recorded on the test boring logs provided in Appendix B. A summary of these measurements are provided in Table 3 below.

Table 3: Measured Pavement Thickness at Boring Locations

Boring ID	Existing Alignment	Depth (ft)	Asphalt thickness (in)	Concrete thickness (in)	Total Thickness (in)
B-001-0-18	IR-77/IR-76	7.5	-	16.0	16.0
B-002-0-18	IR-77/IR-76	7.5	-	11.0	11.0
B-003-0-18	IR-77/IR-76	7.5	-	14.0	14.0
B-004-0-18	IR-77/IR-76	7.5	-	13.0	13.0
B-005-0-18	IR-77/IR-76	7.5	-	13.0	13.0
B-006-0-18	IR-77/IR-76	7.5	-	14.0	14.0
B-020-0-18	IR-277	36.5	3.0	10.0	13.0
B-023-0-18	IR-277	11.5	4.0	9.0	13.0
B-025-0-18	IR-277	7.5	10.0	7.0	17.0
B-026-0-18	IR-277	7.5	13.0	-	13.0
B-039-0-18	IR-77/IR-76	7.5	-	9.0	9.0
B-040-0-18	IR-77/IR-76	7.5	-	13.0	13.0
B-041-0-18	IR-77/IR-76	6.1	14.0	-	14.0
B-042-0-18	IR-77/IR-76	6.5	5.0	-	5.0
B-043-0-18	IR-77/IR-76/Ramp V	7.5	5.0	13.0	18.0
B-044-0-18	IR-77/IR-76	7.5	13.0	-	13.0
B-045-0-18	IR-77/IR-76	11.5	10.0	-	10.0
B-045-1-18	Ramp J	6.7	2.0	13.0	15.0
B-046-0-18	IR-77/IR-76	7.5	5.0	-	5.0
B-047-0-18	IR-77/IR-76/Ramp L	10.4	6.0	-	6.0
B-049-0-18	IR-77/IR-76	7.5	14.0	-	14.0
B-050-0-18	IR-77/IR-76	20.1	6.0	-	6.0
B-051-0-18	Ramp T	7.5	8.0	-	8.0
B-053-0-18	Ramp T	7.5	3.0	10.0	13.0
B-054-0-18	Ramp V	7.5	14.0	-	14.0
B-056-0-18	Ramp W	7.5	15.5	-	-
B-061-0-18	IR-77/IR-76	7.5	14.0	-	14.0
B-066-0-18	Ramp B	26.5	15.5	-	15.5
B-067-0-18	Ramp U	36.5	4.0	8.0	12.0
B-072-0-18	Ramp V	42.6	11.0	-	11.0
B-073-0-18	Ramp V	6.9	13.0	-	13.0
B-074-0-18	Ramp V	10.1	2.5	10.5	13.0
B-077-0-18	Ramp L	7.5	12.0	-	12.0
B-077-1-18	Ramp J	7.5	12.0	-	12.0
B-077-2-18	Ramp J	7.5	2.0	10.0	12.0
B-077-3-18	Ramp J	7.5	13.0	-	13.0
B-077-4-18	Ramp J	7.5	12.0	-	12.0

4.2. Subsurface Conditions

The subsurface conditions in the project area are relatively consistent and are generally comprised of either fill soils (i.e., embankment fill, historical/urban fill, etc.) or natural soils consisting of non-cohesive sand, silt and gravel combinations or low to moderately plastic sandy silt, silt, and silt/clay combinations. About fifty percent of the subgrade soils encountered at the site were classified as either Coarse and Fine Sand (A-3a) or cohesive/non-cohesive Sandy Silt (A-4a). The remainder of the subgrade soils were generally classified as A-1-a, A-1-b, A-2-4, A-3, A-4b or A-6a. The exception to this is the southeast portion of the project where natural organic silts (A-8a) were encountered. With respect to sulfate within the subgrade soil, based on the project laboratory testing program, each subgrade soil sample tested was determined to have a sulfate content of less than 5,000 parts per million (i.e., lower than the level which ODOT considers high and may prevent the use of chemical stabilization).

The following subsections present a brief summary of the subsurface conditions by ramp/roadway segment with problem areas highlighted where present.

Roadway Exploration Report - DRAFT
SUM-76-6.15 – Kenmore Leg
Summit County, Ohio
PID: 100713

4.2.1. IR-77/IR-76

The project portions of IR-76 EB and IR-77 NB near the NW Interchange are planned to be widened to the east and to the north, respectively.

Along IR-76 EB and IR-77 NB, thirty-eight percent (38%) of the samples taken along the interstate were classified as coarse-grained, non-cohesive soils and were comprised of: 1) Coarse and Fine Sand (A-3a, 12% of samples), 2) Gravel with Sand and Silt (A-2-4, 12% of samples); 3) Gravel with Sand (A-1-b, 8% of samples); 4) Gravel and/or Stone Fragments (A-1-a, 5% of samples); and, 5) Sandy Silt (A-4a, 1% of samples). With respect to the relative density of the coarse-grained soils, the descriptions varied from loose to very dense correlating to converted SPT-N values (N_{60}) values between 6 and 105 blows per foot (bpf). Natural moisture contents ranged from 4 to 21 percent.

Fifty-two (52%) of the soil samples were identified as fine-grained soils and were comprised of: 1) cohesive Sandy Silt (A-4a, 42% of samples); 2) Silt (A-4b, 1% of samples); and, 3) Silt and Clay (A-6a, 9% of samples). With respect to the consistency of the fine-grained soils, the descriptions varied from medium stiff to hard correlating to N_{60} values between 7 and 95 bpf. Natural moisture contents ranged from 8 to 18 percent.

The remaining ten percent (10%) of the samples were identified as Rock generally classified as shale.

4.2.2. IR-277/IR-76

The project portions of IR-277 EB and IR-76 WB near the SW Interchange are planned to be widened to the east and west, respectively.

Sixty-eight percent (68%) of the samples taken along the interstate(s) were classified as coarse-grained, non-cohesive soils and were comprised of: 1) Coarse and Fine Sand (A-3a, 34% of samples); 2) Fine Sand (A-3, 23% of samples); 3) Gravel with Sand (A-1-b, 8% of samples); and, Sandy Silt (A-4a, 3% of samples). With respect to the relative density of the coarse-grained soils, the descriptions varied from very loose to dense correlating to N_{60} values between 0 (weight of hammer) and 31 bpf. Natural moisture contents ranged from 5 to 35 percent.

Thirty-two percent (32%) of the soil samples were identified as fine-grained soils and were comprised of 1) Cohesive Sandy Silt (A-4a, 18% of samples); 2) Silt (A-4b, 11% of samples); and 3) Silt and Clay (A-6a, 3% of samples) With respect to the consistency of the fine-grained soils, the descriptions varied from medium stiff to hard correlating to N_{60} values between 6 and 35 bpf. Natural moisture contents ranged from 12 to 24 percent.

It should also be noted that within the project portion of IR-277 EB (near the SW Interchange and extending east), Organic Silt (A-8a) as well as very loose Sandy Silts (A-4a) and Coarse and Fine Sands (A-3a) were encountered. Organic Silt was encountered in boring B-034-0-18 which was located south of the existing IR-277 EB pavement. The Organic Silt encountered at the site had an organic content of 28.4% (highly organic) and was encountered from 0 to 8 ft bgs. The referenced portion of IR-277 EB also encountered very loose soil (A-3a and A-4a) in five of the borings performed in the area. The very loose and 0 bpf material was encountered below the subgrade at depths between 5 and 27 ft bgs.

4.2.3. Ramp B & A2

Ramps B and A2 are the IR-76 SB ramp to IR-277 EB. These ramps are planned for full depth pavement replacement and widening.

Roadway Exploration Report - DRAFT
SUM-76-6.15 – Kenmore Leg
Summit County, Ohio
PID: 100713

Ninety-five percent (95%) of the samples taken along the ramps were classified as coarse-grained, non-cohesive soils and were comprised of: 1) Coarse and Fine Sand (A-3a, 39% of samples); 2) Fine Sand (A-3, 48% of samples); 3) Sandy Silt (A-4a, 4% of samples); and, 4) Gravel with Sand (A-1-b, 4% of samples). With respect to the relative density of the coarse-grained soils, the descriptions varied from very loose to medium dense correlating to N_{60} values between 0 and 27 bpf. Natural moisture contents ranged from 6 to 35 percent.

Five percent (5%) of the samples taken along the proposed ramps was classified as fine-grained soils and were comprised of Silt (A-4b, 5% of samples). With respect to the relative density of the fine-grained soils, the description loose correlating to an N_{60} value of 7 bpf. Natural moisture content of the soil was 30 percent.

4.2.4. *Ramp J*

Ramp J is the IR-77 NB/IR-76 WB ramp to Superior Ave and East Ave. which is planned for full depth pavement replacement.

Twenty percent (20%) of the samples taken along Ramp J were classified as coarse-grained, non-cohesive soils and were comprised of: 1) Coarse and Fine Sand (A-3a, 10% of samples); 2) Gravel with Sand and Silt (A-2-4, 5% of samples); and 3) Gravel with Sand (A-1-b, 5% of samples). With respect to the relative density of the coarse-grained soils, the descriptions varied from loose to very dense correlating to N_{60} values between 9 and 51 bpf. Natural moisture contents ranged from 6 to 10 percent.

Sixty percent (60%) of the samples taken along the ramp were classified as fine-grained soils and were comprised of cohesive Sandy Silt (A-4a, 25% of samples) and Silt (A-4b, 35% of samples). With respect to the consistency of the fine-grained soils, the descriptions varied from medium stiff to hard correlating to N_{60} values between 10 and 22 bpf. Natural moisture contents ranged from 16 to 27 percent.

The remaining twenty percent (20%) of the samples were identified as Rock generally classified as gray, severely weathered and weak to very weak shale.

4.2.5. *Ramp L*

Ramp L is the East Ave. on ramp to IR-77 NB/IR-76 EB which is planned for full depth pavement replacement and widening.

Ten percent (10%) of the samples taken along Ramp L were classified as coarse-grained, non-cohesive soils and were comprised of Gravel with Sand (A-1-b, 1 sample). With respect to the relative density of the coarse-grained soils, the descriptions varied from loose to dense correlating to N_{60} values between 10 and 39 bpf. Natural moisture content of the sample was 5 percent.

Forty-five percent (45%) of the samples taken along the ramp were classified as fine-grained soils and were comprised of cohesive Sandy Silt (A-4a, 5 samples). With respect to the consistency of the fine-grained soils, the descriptions varied from stiff to very stiff correlating to N_{60} values between 10 and 22 bpf. Natural moisture contents ranged from 9 to 16 percent.

The remaining forty-five percent (45%) of the samples were identified as Rock classified as gray, highly weathered, very weak shale.

4.2.6. *Ramps N & M*

Ramp N and Ramp M are the IR-77 NB on and off ramps to/from Frederick Blvd/Diagonal Rd. It is planned for full depth replacement.

Roadway Exploration Report - DRAFT
SUM-76-6.15 – Kenmore Leg
Summit County, Ohio
PID: 100713

Fifty-four percent (54%) of the samples taken along the ramps were classified as coarse-grained, non-cohesive soils and were comprised of Coarse and Fine Sand (A-3a, 7 samples). With respect to the relative density of the coarse-grained soils, the descriptions varied from loose to dense correlating to N_{60} values between 6 and 44 bpf. Natural moisture contents ranged from 5 to 26 percent.

Forty-six percent (46%) of the soil samples were identified as fine-grained soils, comprised of cohesive Sandy Silt (A-4a, 31% of samples) and Silty Clay (A-6b, 15% of samples). With respect to the consistency of the fine-grained soils, the descriptions varied from stiff to very stiff correlating to N_{60} values between 10 and 24 bpf. Natural moisture contents ranged from 11 to 21 percent.

4.2.7. Ramp P

Ramp P is the Vernon Odom Blvd. on ramp to IR-77 SB/IR-76 EB in which a portion is planned for full depth pavement replacement.

Fifty percent (50%) of the samples taken along the ramp were classified as coarse-grained, non-cohesive soils and were comprised of Gravel and/or Stone Fragments (A-1-a, 6 samples). The relative density of the coarse grained soils encountered was medium dense correlating to N_{60} values between 15 and 29 bpf. Natural moisture contents ranged from 7 to 11 percent.

Fifty percent (50%) of the soil samples were identified as fine-grained soils that were comprised of cohesive Sandy Silt (A-4a, 25% of samples) and Silt and Clay (A-6a, 25% of samples). With respect to the consistency of the fine-grained soils, the descriptions varied from stiff to hard correlating to N_{60} values between 15 and 36 bpf. Natural moisture contents ranged from 14 to 21 percent.

4.2.8. Ramp T

Ramp T is the IR-77 SB ramp to IR-76 WB which is planned for full depth pavement replacement and realignment. Minimal cut and fill is anticipated at this ramp.

Thirty-six percent (36%) of the samples taken along the ramp were classified as coarse-grained, non-cohesive soils that were comprised of Gravel with Sand and Silt (A-2-4, 27% of samples) and 2) Gravel with Sand (A-1-b, 9% of samples). With respect to the relative density of the coarse-grained soils, the descriptions varied from dense to very dense correlating to N_{60} values between 36 and 85 bpf. Natural moisture contents ranged from 6 to 7 percent.

Sixty-four percent (64%) of the soil samples were identified as fine-grained soils that were comprised of cohesive Sandy Silt (A-4a, 7 samples). With respect to the consistency of the fine-grained soils, the descriptions varied from stiff to very stiff correlating to N_{60} values between 11 and 21 bpf. Natural moisture contents ranged from 10 to 16 percent.

4.2.9. Ramp U

Ramp U is the IR-76 EB ramp to IR-77/IR-76 EB which is planned for full depth pavement replacement.

Thirty-five percent (35%) of the samples taken along the ramp were classified as coarse-grained, non-cohesive soils and were comprised of Gravel with Sand and Silt (A-2-4, 14% of samples) and Gravel with Sand (A-1-b, 21% of samples). With respect to the relative density of the coarse-grained soils, the descriptions varied from medium dense to very dense correlating to N_{60} values between 29 and 77 bpf. Natural moisture contents ranged from 5 to 17 percent.

Roadway Exploration Report - DRAFT
SUM-76-6.15 – Kenmore Leg
Summit County, Ohio
PID: 100713

Thirty-six percent (36%) of the soil samples were identified as fine-grained soils that were comprised of cohesive Sandy Silt (A-4a, 29% of samples) and Clay (A-7-6, 7% of samples). With respect to the consistency of the fine-grained soils, the descriptions varied from stiff to hard correlating to N_{60} values between 12 and 40 bpf. Natural moisture contents ranged from 6 to 16 percent.

The remaining twenty-nine percent (29%) of the samples were identified as Rock classified as light tan, highly weathered, slightly strong sandstone.

4.2.10. Ramp V

Ramp V is the IR-77 NB/IR-76 WB ramp to IR-76 WB which is planned for full depth pavement replacement and realignment. Minimal cut and fill is anticipated at this ramp.

Thirty-seven percent (37%) of the samples taken along the ramp were classified as coarse-grained, non-cohesive soils and were comprised of: 1) Gravel with Sand (A-1-b, 16% of samples); 2) Gravel with Sand and Silt (A-2-4, 13% of samples); and, 3) Coarse and Fine Sand (A-3a, 9% of samples). With respect to the relative density of the coarse-grained soils, the descriptions varied from loose to very dense correlating to N_{60} values between 6 and 60 bpf. Natural moisture contents ranged from 2 to 11 percent.

Forty-four percent (44%) of the soil samples were identified as fine-grained soils and were comprised of: 1) Cohesive Sandy Silt (A-4a, 38% of samples); 2) Silt (A-4b, 3% of samples); and, 3) Silt and Clay (A-6a, 3% of samples). With respect to the consistency of the fine-grained soils, the descriptions varied from soft to hard correlating to N_{60} values between 4 and 95 bpf. Natural moisture contents ranged from 5 to 16 percent.

The remaining Nineteen percent (19%) of the samples were identified as Rock classified as light brown, highly weathered, slightly strong sandstone.

4.2.11. Ramp W

Ramp W is the IR-76 EB ramp to IR-77 NB which is planned for full depth pavement replacement and realignment. Cut and fills are anticipated to be needed over the length of the proposed new alignment.

Forty-seven percent (47%) of the samples taken along Ramp W were classified as coarse-grained, non-cohesive soils and were comprised of: 1) Coarse and Fine Sand (A-3a, 20% of samples); 2) Gravel with Sand and Silt (A-2-4, 10% of samples); 3) Gravel with Sand (A-1-b, 10% of samples); and, 4) Sandy Silt (A-4a, 7% of samples). With respect to the relative density of the coarse-grained soils, the descriptions varied from loose to very dense correlating to N_{60} values between 6 and 105 bpf. Natural moisture contents ranged from 2 to 11 percent.

Thirty-nine percent (39%) of the soil samples were identified as fine-grained soils that were comprised of cohesive Sandy Silt (A-4a, 36% of samples) and Silt and Clay (A-6a, 3% of samples). With respect to the relative density of the fine-grained soils, the descriptions varied from soft to hard correlating to N_{60} values between 4 and 48 bpf. Natural moisture contents ranged from 9 to 16 percent.

The remaining thirteen percent (13%) of the samples were identified as Rock classified as light gray, severely weathered, weak to moderately strong sandstone.

4.2.12. Groundwater

Groundwater measurements were taken during the boring drilling procedures and/or immediately following the completion of each borehole. Groundwater was encountered in 14 of the 86 project borings. Across the

project site groundwater was encountered at depths ranging from 0 to 28 ft bgs or from elevations ranging from 964.8 to 1011.8 ft amsl. Groundwater was encountered within 7.5 ft (within subgrade portion) of the ground surface in 10 borings.

It should be noted that groundwater is affected by many hydrologic characteristics in the area and may vary.

5. ANALYSES AND RECOMMENDATIONS

We understand that the reconstruction/widening of the Akron Beltway portions of IR-76, IR-77 and IR-277 known as the Kenmore Leg is planned as part of ODOT project SUM-76-6.15 (PID 100713). In addition to the mainline interstates, reconstruction and realignment of various connecting ramps/roadways are also planned. Ramp T, Ramp W, and Ramp V are planned for realignment and reconstruction while full or partial full depth pavement replacement is planned for Ramp B, Ramp A2, Ramp J, Ramp L, Ramp N, Ramp M, Ramp P, and Ramp U. For this purpose, a roadway exploration and subsequent analysis was completed for the referenced project. The subgrade analysis was performed in accordance with ODOT's GB1 criteria utilizing the ODOT provided *GB1: Subgrade Analysis Spreadsheet* (GB1_SubgradeAnalysis.xls, Version 14.5 dated July 19, 2019). Input information for the spreadsheet was based on the soil characteristics gathered during NEAS's exploration (i.e., SPT results, laboratory test results, etc.). A GB1 analysis was performed for each of the referenced mainline and ramp segments. Embankment Stability analysis was performed in accordance Load and Resistance Factor Design (LRFD) method as set forth in AASHTO's Publication *LRFD Bridge Design Specifications, 8th Edition* (BDS) (AASHTO, 2017), *ODOT's 2019 LRFD Bridge Design Manual* (BDM) (ODOT, 2019), and ODOT's *Geotechnical Bulletin 2* (GB2) (ODOT [2], 2017).

Based on our evaluation of the subsurface conditions and our geotechnical engineering analyses of the proposed improvement project, it is our opinion that the subgrade conditions encountered are generally satisfactory and pavement can be designed without the need for extreme levels of remediation, especially with the use of global stabilization on interstate projects per the GB1. In general, the subgrade soils throughout the project will be stabilized by global (chemical) stabilization. The following sections provide further detail about the analysis performed and the recommended remediation.

5.1. Subgrade Analysis

A GB1 analysis was performed to identify the method, location, and dimensions (including depth) of required subgrade stabilization for the project. In addition to identifying stabilization recommendations, pavement design parameters are also determined to aid in pavement section design. The subsections below present the results of our GB1 analysis including pavement design parameters and unsuitable subgrade conditions identified within the project limits. GB1 analysis spreadsheets are provided in Appendix D.

Again, it should be noted that for the purposes of this report and our analysis, the term 'proposed subgrade' has been assumed to represent soils and/or soil conditions from 1.5 ft below proposed final pavement grades to a depth of 7.5 ft below the proposed pavement grades.

5.1.1. Pavement Design Recommendations

It is our understanding that pavement analysis and design is to be performed to determine the proposed pavement sections for the segments within the project limits to undergo full depth replacement. A GB1 analysis was performed using the subgrade soil data obtained during our field exploration program to evaluate the soil characteristics to develop pavement parameters for use in pavement design. The subgrade

Roadway Exploration Report - DRAFT
SUM-76-6.15 – Kenmore Leg
Summit County, Ohio
PID: 100713

analysis parameters recommended for use in pavement design are presented in Table 4 below. Provided in the table are ranges of maximum, minimum and average N_{60L} values for the indicated segments as well as the design CBR value recommended for use in pavement design.

Table 4: Pavement Design Values

Segment	Maximum N_{60L}	Minimum N_{60L}	Average N_{60L}	Average PI Values	Design CBR
IR-76/IR-77 (NW Interchange)	30	6	18	8	9
IR-277/IR-76 (SW Interchange)	27	0	7	8	9
Ramp B & A2	9	0	5	NP	13
Ramp J	30	9	17	7	8
Ramp L	30	17	26	8	9
Ramp N & M	23	6	14	10	9
Ramp P	25	15	18	9	10
Ramp T	30	11	18	8	8
Ramp U	30	0	17	12	9
Ramp V	30	4	21	7	9
Ramp W	30	0	17	6	10
Entire Project	30	0	16	8	9

5.1.2. *Unsuitable Subgrade*

Per ODOT's GB1, the presence of select subgrade conditions are prohibited within the subgrade zone for new pavement construction. These prohibited subgrade conditions generally include the presence of rock, specific soil types, weak soil conditions, and overly moist soil conditions. With respect to the referenced interstate improvement project these subgrade conditions are further discussed in the following subsections.

5.1.2.1. *Rock*

Rock was encountered within the subgrade in twelve (12) borings performed within the project roadway limits. In these borings, bedrock was encountered at depths ranging from 0 ft to 6.5 ft below the top of the assumed subgrade elevation. Per ODOT's GB1, if rock is encountered within 24 inches of the bottom of the proposed asphalt or concrete pavement it is to be removed in accordance with 204.05 of the ODOT CMS and replaced with Item 204 Embankment. Of the twelve borings in which rock was encountered, remediation is required in seven borings (B-041-0-18, B-045-0-18, B-045-1-18, B-048-0-18, B-057-0-18, B-058-0-18, and B-070-0-18). A summary of the boring locations where rock was encountered within the proposed subgrade are shown in Table 5 below, per the roadway segment for which they were encountered.

Table 5: Shallow Rock Location Summary

Boring ID	Roadway Segment	Depth Below Proposed Subgrade (ft)	Top of Rock Elevation (ft)
B-041-0-18	IR-77/IR-76	1.5	1019.7
B-045-0-18	IR-77/IR-76	1.0	1064.4
B-045-1-18	Ramp J	0.0	1065.6
B-047-0-18	IR-77/IR-76, Ramp L	5.5	1056.6
B-048-0-18	IR-77/IR-76, Ramp L	1.0	1048.1
B-057-0-18	Ramp W	1.0	1009.4
B-058-0-18	Ramp W	1.4	1005.1
B-059-0-18	Ramp W	2.5	1000.8
B-070-0-18	Ramp U	0.5	1034.8
B-073-0-18	Ramp V	3.0	1011.8
B-074-0-18	Ramp V	2.5	1011.2
B-076-0-18	Ramp V	4.2	1030.5

Roadway Exploration Report - DRAFT
SUM-76-6.15 – Kenmore Leg
Summit County, Ohio
PID: 100713

5.1.2.2. *Prohibited Soils*

Prohibited soil types per the GB1, which include A-4b, A-2-5, A-5, A-7-5, A-8a, A-8b, and soils with liquid limits greater than 65, were encountered within the subgrade of the referenced project roadway segments. Soil Type A-4b (Silt) was encountered: 1) at depths ranging from 0 to 5.5 ft below subgrade along IR-277 EB in borings B-035-0-18, B-036-0-18 and B-037-0-18; 2) at depths ranging from 0 to 6 ft below subgrade along portions of Ramp J in borings B-077-3-18 and B-077-4-18; and, 3) between depths of 0 to 3 ft below subgrade in boring B-075-0-18 performed along Ramp V. A summary of the boring locations where prohibited soils were encountered and the associated GB1 recommended remediation depths are shown in Tables 6 below, per the roadway segment for which they were encountered.

Table 6: Prohibited Soils Location Summary

Boring ID	Prohibited Soil Type	Depth Below Subgrade (ft)	Remediation Depth (inches)		
			Excavate and Replace (Item 204 w/ Geotextile)	Excavate and Replace (Item 204 w/ Geogrid - SS 861)	Chemical Stabilization (Item 206)
Roadway Segment: IR-277 EB					
B-035-0-18	A-4b	0.0 - 3.0	36	-	14
B-036-0-18	A-4b	0.0 - 5.5	36	-	14
B-037-0-18	A-4b	0.0 - 3.0	36	-	14
Roadway segment: Ramp V					
B-075-0-18	A-4b	0.0 - 3.0	36	-	14
Roadway segment: Ramp J					
B-077-3-18	A-4b	2.0 - 6.0	12	-	14
B-077-4-18	A-4b	0.0 - 6.0	36	-	14

5.1.2.3. *Weak Soils*

The GB1 recommends subgrade stabilization for soils in which the N_{60} value of a particular soil sample (SS) at a referenced boring location is less than 12 bpf and in some cases less than 15 bpf (i.e., where moisture content is greater than optimum plus 3 percent). Based on the specific N_{60} value at the subject boring, *Figure B - Subgrade Stabilization* within the GB1 recommends a depth of subgrade stabilization for ODOT standard stabilization methods. For the purposes of this report the term 'weak soils' has been assumed to represent subgrade soils of these conditions. It should be noted that although a soil sample's N_{60} value may meet the criteria to be considered a weak soil, the depth in which the weak soil is encountered in relation to the proposed subgrade is considered when each individual subgrade boring is analyzed. For example, if the GB1 recommends an excavate and replace of 12 inches within a weak soil underlying 18 inches of stable material, it would be unreasonable to recommend the removal of both the stable and unstable material for a total of 30 inches of excavate and replace.

Based on N_{60} values encountered within the project borings, our GB1 analysis suggests the need for 12 to 14 inches of either chemical treatment or excavate and replace at select locations. A summary of the boring locations where weak soils were encountered and determined to have a potential impact on subgrade performance are shown in Table 7 below, per the roadway segment for which they were encountered. Also included is the associated GB1 recommended remediation depth at that location.

Roadway Exploration Report - DRAFT
SUM-76-6.15 – Kenmore Leg
Summit County, Ohio
PID: 100713

Table 7: Weak Soil Locations Summary

Boring ID	Sample ID	N ₆₀	Moisture Above Optimum (%)	Depth Below Subgrade (ft)	Remediation Depth (inches)		
					Excavate and Replace (Item 204 w/ Geotextile)	Excavate and Replace (Item 204 w/ Geogrid - SS 861)	Chemical Stabilization (Item 206)
Roadway Segment: IR-77/IR-76							
B-002-0-18	SS-1	7	3	0.0 - 1.5	18	-	14
B-053-0-18	SS-1	11	1	0.0 - 1.5	12	-	12
Roadway Segment: IR-277							
B-020-0-18	SS-1	8	3	0.5 - 6.5	12	-	14
B-027-0-18	SS-1A	13	19	0.0 - 1.3	12	-	12
B-035-0-18	SS-1	11	13	0.0 - 3.0	To be remediated due to prohibited soil (A-4b)		
B-036-0-18	SS-1	14	18	0.0 - 5.5	To be remediated due to prohibited soil (A-4b)		
B-037-0-18	SS-1	10	4	0.0 - 0.4	To be remediated due to prohibited soil (A-4b)		
Roadway Segment: Ramp T							
B-053-0-18	SS-1	11	1	0.0 - 3.0	12	-	12

It should be noted that *Figure B - Subgrade Stabilization* does not apply to soil types A-1-a, A-1-b, A-3, or A-3a, nor to soils with N_{60L} values of 15 or more. Per GB1 guidance, *these soils should be reworked to stabilize the subgrade.*

5.1.2.4. High Moisture Content Soils

High moisture content soils are defined by the GB1 as soils that exceed the estimated optimum moisture content (per *Figure A - Optimum Moisture Content* within the GB1) for a given classification by 3 percent or more. Per the GB1, soils determined to be above the identified moisture content levels are a likely indication of the presence of an unstable subgrade and may require some form of subgrade stabilization. Similar to our analysis of weak soils, although a soil sample’s moisture content may meet the criteria to be considered high, the depth in which the high moisture soil is encountered in relation to the proposed subgrade is considered when each individual subgrade boring is analyzed for stabilization recommendations. Summaries of the boring locations where high moisture content conditions were encountered within the limits of each alignment are shown in Table 8 below.

Table 8: High Moisture Content Soils Location Summary

Boring ID	Moisture Content (%)	Optimum Moisture Content (%)	Moisture Above Optimum (%)	Depth Below Subgrade (ft)	Boring ID	Moisture Content (%)	Optimum Moisture Content (%)	Moisture Above Optimum (%)	Depth Below Subgrade (ft)
Roadway Segment: IR-77/IR-76					Ramp Segment: Ramp J				
B-002-0-18	17	14	3	0.0 - 1.5	B-077-2-18	17	13	4	1.5 - 3.0
B-010-0-18	15	11	4	1.0 - 2.5	B-077-3-18	18	10	8	2.0 - 3.0
B-015-0-18	13	10	3	1.0 - 2.5	B-077-4-18	22	10	12	2.0 - 3.0
B-053-0-18	16	10	6	1.5 - 3.0	Roadway Segment: Ramp L				
Roadway Segment: IR-277					B-070-0-18	16	10	6	1.5 - 3.0
B-020-0-18	17	14	3	1.0 - 2.5	Ramp Segment: Ramp N & M				
B-027-0-18	29	10	19	0.0 - 1.3	B-081-0-18	21	16	5	1.5 - 3.0
B-028-0-18	16	11	5	1.0 - 2.5	Roadway Segment: Ramp T				
B-035-0-18	24	11	13	1.0 - 2.5	B-053-0-18	16	10	6	2.0-2.3
B-036-0-18	29	11	18	1.0 - 2.5	Roadway Segment: Ramp U				
B-037-0-18	19	11	8	1.0 - 2.5	B-069-0-18	17	10	7	1.0 - 2.5
Roadway Segment: Ramp B & A2									
B-028-0-18	16	11	5	1.0 - 2.5					

5.2. Embankment Stability Analysis

For purposes of evaluating stability of the planned roadway embankments and embankment widening proposed as part of the project, NEAS reviewed cross-sections along the length of the project roadway segments to identify sections that were interpreted to represent conditions that posed the greatest potential for slope instability as a result of the planned construction. In general, cross-sections along each of the proposed roadway alignments were reviewed to identify planned alterations that may present a combination of existing subsurface conditions and planned site grading (i.e., cutting and/or filling) that would potentially be critical to the stability of the existing and/or proposed slopes at the site. Based on our review of the available information along the referenced alignments and the associated soil properties, five cross-sections estimated to be most "critical" along the proposed roadways and were analyzed for global stability. The five cross-sections selected to be evaluated include: 1) the cross-section along IR-76 EB at approximate STA. 98+00; 2) the cross-section along IR-77 SB/IR-76 EB at approximate STA. 242+00; 3) the cross-section along IR-76 WB at STA. 50+00; and, 4) the cross-sections along Ramp A2 at STA. 15+00 and STA. 17+00.

For these cross-sections, NEAS developed a representative cross-sectional model to use as the basis for global stability analyses. The model was developed from NEAS’s interpretation of the available information which included: 1) the referenced project’s proposed Option 4 roadway plans dated June 25, 2019 provided by GPD Group; 2) a live load surcharge of 240 pounds per square foot (psf), accounting for traffic induced loads; and, 3) test borings and laboratory data developed as part of this report.

For analysis purposes, borings performed along or nearby the indicated embankment sections were reviewed and a generalized material profile was developed for analysis to represent worse case conditions at each cross-section location. Utilizing the generalized soil profile, engineering properties for each soil strata were estimated based on the field (i.e., SPT N_{60} Values, hand penetrometer values, etc.) and laboratory (i.e., Atterberg Limits, grain size, etc.) test results using correlations provided in published engineering manuals, research reports and guidance documents. The developed soil profile and estimated engineering soil properties for use in analysis (with sited correlation/reference material) is summarized within Tables 9 through 14 below. Each table presents the effective and total stress analysis soil parameters for each of the referenced cross-sections as well as the project borings utilized to estimate the indicated parameters.

Table 9: Soil Profile and Estimated Engineering Properties – IR-76 EB - STA. 98+00

Embankment Stability Analysis, B-055-0-18, B-056-0-18 & B-072-0-18				
Soil Description	Unit Weight⁽¹⁾ (pcf)	Undrained Shear Strength⁽²⁾ (psf)	Effective Cohesion⁽³⁾ (psf)	Effective Friction Angle⁽³⁾ (degrees)
Coarse and Fine Sand Elevation (1079.6 ft - 1010.8 ft)	125	-	-	34
Coarse and Fine Sand Elevation (1010.8 ft - 1007.8 ft)	120	-	-	34
Silty Clay Elevation (1007.8 ft - 1003.1 ft)	112	500	50	20
Silty Clay Elevation (1003.1 ft - 987.3 ft)	122	2400	200	25
Notes:				
1. Values interpreted from Geotechnical Bulletin 7 Table 1.				
2. Values calculated from Terzaghi and Peck (1967) if $N_{60} < 52$, else Stroud and Butler (1975) was used.				
3. Values interpreted from Geotechnical Bulletin 7 Table 2.				

Roadway Exploration Report - DRAFT
SUM-76-6.15 – Kenmore Leg
Summit County, Ohio
PID: 100713

Table 10: Soil Profile and Estimated Engineering Properties – IR-77 SB/IR-76 EB – STA. 242+00

Embankment Stability Analysis, B-044-0-18				
Soil Description	Unit Weight⁽¹⁾ (pcf)	Undrained Shear Strength⁽²⁾ (psf)	Effective Cohesion⁽³⁾ (psf)	Effective Friction Angle⁽³⁾ (degrees)
Silt and Clay Elevation (1079.6 ft - 1052.4 ft)	115	2700	250	26
Notes: 1. Values interpreted from Geotechnical Bulletin 7 Table 1. 2. Values calculated from Terzaghi and Peck (1967) if $N_{60} < 52$, else Stroud and Butler (1975) was used. 3. Values interpreted from Geotechnical Bulletin 7 Table 2.				

Table 11: Soil Profile and Estimated Engineering Properties – IR-76 WB – STA. 50+00

Embankment Stability Analysis, B-022-0-18 & B-023-0-18				
Soil Description	Unit Weight⁽¹⁾ (pcf)	Undrained Shear Strength⁽²⁾ (psf)	Effective Cohesion⁽³⁾ (psf)	Effective Friction Angle⁽³⁾ (degrees)
Fine Sand Elevation (1079.6 ft - 977 ft)	122	-	-	36
Fine Sand Elevation (977 ft - 965.8 ft)	110	-	-	30
Notes: 1. Values interpreted from Geotechnical Bulletin 7 Table 1. 2. Values calculated from Terzaghi and Peck (1967) if $N_{60} < 52$, else Stroud and Butler (1975) was used. 3. Values interpreted from Geotechnical Bulletin 7 Table 2.				

Table 12: Soil Profile and Estimated Engineering Properties – IR-76 WB – STA. 50+00

Embankment Stability Analysis, B-024-0-18				
Soil Description	Unit Weight⁽¹⁾ (pcf)	Undrained Shear Strength⁽²⁾ (psf)	Effective Cohesion⁽³⁾ (psf)	Effective Friction Angle⁽³⁾ (degrees)
Fine Sand Elevation (1079.6 ft - 991.3 ft)	122	-	-	36
Fine Sand Elevation (991.3 ft - 971.8 ft)	120	-	-	31
Notes: 1. Values interpreted from Geotechnical Bulletin 7 Table 1. 2. Values calculated from Terzaghi and Peck (1967) if $N_{60} < 52$, else Stroud and Butler (1975) was used. 3. Values interpreted from Geotechnical Bulletin 7 Table 2.				

Table 13: Soil Profile and Estimated Engineering Properties – Ramp A2 – STA. 15+00

Embankment Stability Analysis, B-064-0-18 & B-066-0-18				
Soil Description	Unit Weight⁽¹⁾ (pcf)	Undrained Shear Strength⁽²⁾ (psf)	Effective Cohesion⁽³⁾ (psf)	Effective Friction Angle⁽³⁾ (degrees)
Fine Sand Elevation (1079.6 ft - 984.4 ft)	120	-	-	33
Fine Sand Elevation (984.4 ft - 963.8 ft)	110	-	-	30
Silt Elevation (963.8 ft - 961.8 ft)	120	-	-	28
Notes: 1. Values interpreted from Geotechnical Bulletin 7 Table 1. 2. Values calculated from Terzaghi and Peck (1967) if $N_{60} < 52$, else Stroud and Butler (1975) was used. 3. Values interpreted from Geotechnical Bulletin 7 Table 2.				

Table 14: Soil Profile and Estimated Engineering Properties – Ramp A2 – STA. 17+00

Embankment Stability Analysis, B-065-0-18 & B-066-0-18				
Soil Description	Unit Weight⁽¹⁾ (pcf)	Undrained Shear Strength⁽²⁾ (psf)	Effective Cohesion⁽³⁾ (psf)	Effective Friction Angle⁽³⁾ (degrees)
Fine Sand Elevation (1079.6 ft - 984.4 ft)	120	-	-	33
Fine Sand Elevation (984.4 ft - 963.8 ft)	110	-	-	30
Notes: 1. Values interpreted from Geotechnical Bulletin 7 Table 1. 2. Values calculated from Terzaghi and Peck (1967) if $N_{60} < 52$, else Stroud and Butler (1975) was used. 3. Values interpreted from Geotechnical Bulletin 7 Table 2.				

The above referenced slope stability models were analyzed for long-term (Effective Stress) and short-term (Total Stress) slope stability utilizing the software entitled *Slide 7.0* by Rocscience, Inc. Specifically, the Modified Bishop and Spencer analysis methods were used to calculate a factor of safety (FOS) for circular and block type slope failures, respectively. The FOS is the ratio of the resisting forces and the driving forces, with the desired safety factor being more than about 1.33 which equates to an AASHTO resistance factor less than 0.75 (per AASHTO's LRFD BDS the specified resistance factors are essentially the inverse of the FOS that should be targeted in slope stability programs). For this analysis, a resistance factor of 0.75 or lower is targeted as the slope does not contain or support a structural element.

Based on our slope stability analyses for the above referenced roadway embankment sections, the minimum slope stability safety factor is about 1.34 (0.75 resistance factor) for the section analyzed along IR-76 WB at STA. 50+00. The graphical output of the slope stability program (cross-sectional model, calculated safety factor, and critical failure plane) for each analyzed section is presented in Appendix E. It should be noted, for the above referenced analysis which yielded the minimum slope stability safety factor (section STA. 50+00 along IR-76 WB), a cohesion value of 20 psf was assigned to the non-cohesive soil layer along the slope in order to prevent impractical failure plane generation e.g. the generation of small surficial failure planes.

5.3. Embankment Construction Recommendations

As indicated above, each of the embankment cross-sections analyzed for slope stability were determined to be stable (i.e., FOS greater than about 1.33) as proposed in the SUM-76-6.15 project's Option 4 roadway plans dated June 25, 2019 provided by GPD Group. Therefore, the proposed embankment slopes can be constructed in accordance with Item 203 "Roadway Excavation and Embankment" of the ODOT CMS.

In areas where additional embankment material is proposed along existing slopes that are steeper than 8 Horizontal to 1 Vertical (8H:1V) but flatter than 4H:1V, it is recommended that the proposed embankment be benched into the existing slopes in accordance with Item 203.05 "Embankment Construction Methods" of the ODOT CMS. For areas where additional embankment material is proposed along existing slopes that are steeper than 4H:1V, it is recommended that the proposed embankment be designed and constructed in accordance with GB2. For sidehill fills planned on existing slopes steeper than 4H:1V, ODOT's GB2 recommends that *the embankment slopes be constructed utilizing special benching in order to blend the new embankment with the existing slope to prevent the development of a weak shear plane at the interface between the proposed fill and existing slope material* (ODOT [2], 2017). As the project embankment fill slopes were determined to be stable as-proposed based on our embankment stability analysis, a special benching scheme similar to that shown in Figure 1 of the ODOT GB2 can be used in areas where special benching is recommended. The height and width dimensions of the special benching scheme shown in Figure 1 should be arranged to minimize the required cut and fill quantities, though the height of a single bench shall not exceed 20 ft without a stability analysis and design per OSHA requirements. Additionally, it may be appropriate to adjust the bench slope shown from a 1H:1V to a 1.75H:1V slope if the existing slope is made up of primarily granular materials. The benched material should be replaced with compacted engineered fill per Item 203 of the ODOT CMS, while proper lift thicknesses and material density should be maintained in the proposed fill per Item 203.06 of the ODOT CMS. In situations where it is not practical to extend the final bench through the existing roadway due to maintenance of traffic concerns, a benching scheme similar to that shown in Figure 1a of the ODOT GB2 can be used in order to avoid impacting the existing roadway, guardrail or shoulder. This scheme results in the placement of a temporary over-steepened fill that can later be "shaved-off" to bring the slope to the final proposed grade.

Due to the organic silt and very loose granular material encountered along the project portion of IR-277 EB (near the SW Interchange and extending east), it is recommended that an additional geotechnical exploration be performed to determine if special considerations will be required for widened embankment construction. The organic silt was encountered from 0 to 8 ft bgs while the very loose soil (A-3a and A-4a) was encountered at depths between 5 and 27 ft bgs. These materials may impact design and construction of the proposed improvements and therefore, are recommend to be further delineated to aid in the evaluation of the proposed design.

5.4. Stabilization Recommendations

5.4.1. Subgrade Stabilization

Guidance from ODOT's GB1 states that *"For all Interstates and other divided highways with four or more lanes more than 1-mile in project length, the subgrade of the entire project shall be chemically stabilized (global stabilization), except where it is determined that soil is present where a majority of sulfate content values are found to be greater than 3,000 parts per million (ppm), or individual soil samples with sulfate contents greater than 5,000 ppm are present"* and therefore global chemical stabilization is recommended for the proposed improvement project except where otherwise indicated in this report.

The global chemical stabilization of the referenced mainline and ramp subgrade soils included within this project, should be performed to a minimum depth of 14 inches utilizing cement as the stabilizing chemical. The stabilization efforts should extend a minimum of 18-inches beyond the edge of the paved roadway, shoulder or median. The mix design should be conducted in accordance with ODOT's CMS Supplement 1120 (Mixture Design for Chemically Stabilized Soils). For design purposes it may be assumed that the cement addition will be 5% using the following formula.

$$\text{Cement: } C = 0.75 \times T \times 115 \times 0.05$$

Where:

C = amount of chemical in pounds / square yard and

T = thickness of the treatment zone in inches

A dry density of 115-pounds per cubic foot (pcf) is assumed.

The unsuitable subgrade conditions encountered along the proposed mainline and roadway/ramp segments include areas of identified "prohibited soils" and "weak soils". It is NEAS's opinion based on: 1) samples obtained from borings performed; 2) the depth and composition of the "prohibited soils" and "weak soils" encountered; and, 3) the relative density (compactness) of overlying soils, that the recommended 14 inches of global chemical stabilization would be sufficient in stabilizing the subgrade at each location.

It should be noted that per ODOT's GB1, *typical chemical stabilization equipment cannot stabilize areas less than 8 ft in width*. If it is anticipated that the project will require multiple maintenance of traffic phases, it is recommended that the roadway work is coordinated with the maintenance of traffic schemes in such a way that an 8-ft minimum width for chemical stabilization exists. If areas of less than 8 ft in width are anticipated, subgrade soils may be excavated out, mixed with stabilization chemical, and compacted in place, though this method is not practical for large areas

5.4.2. Shallow Bedrock

Guidance from ODOT's GB1 states that, *if rock is encountered within 24 inches of the bottom of the asphalt or concrete pavement it is to be removed*. Based on the borings performed, at the locations where bedrock

Roadway Exploration Report - DRAFT
SUM-76-6.15 – Kenmore Leg
Summit County, Ohio
PID: 100713

is encountered within two feet of the bottom of the proposed asphalt or concrete pavement, it is recommended that the rock encountered be excavated in accordance with Item 204.05 "Rock, Shale, or Coal Subgrade" of ODOT's CMS and replaced with Item 204 Embankment. The estimated limits of required rock excavation can be found in Table 15 below.

Table 15: Estimated Limits of Required Rock Excavation

Start Station	End Station	Excavate and Replace (inches)	Unsuitable Subgrade Conditions	Borings Considered
IR-77/IR-76				
222+00	258+00	24	Bedrock	B-059-0-18, B-041-0-18, B-070-0-18, B-045-0-18, B-045-1-18, B-048-0-18
IR-76 EB				
99+50	104+18	24	Bedrock	B-057-0-18
Ramp J				
0+00 ⁽¹⁾	6+00 ⁽¹⁾	24	Bedrock	B-045-1-18
Ramp L				
5+00 (Begin Work)	12+30 (End Work)	24	Bedrock	B-047-0-18, B-048-0-18
Ramp V				
0+00 (Begin Work)	20+28 (End Work)	24	Bedrock	B-045-1-18, B-074-0-18, B-057-0-18,
Ramp W				
104+18 (Begin Work)	112+40 (End Work)	24	Bedrock	B-057-0-18, B-058-0-18, B-059-0-18
<i>Notes:</i>				
1. Stationing for Ramp J not available at time of the report. Initial 600 ft of Ramp J is estimated to require 24 inches of Excavate and Replace.				

6. QUALIFICATIONS

This investigation was performed in accordance with accepted geotechnical engineering practice for the purpose of characterizing the subgrade conditions along the referenced portions of roadways. This report has been prepared for GPD Group, ODOT and their design consultants to be used solely in evaluating the roadway subgrade soils within the project limits and presenting geotechnical engineering recommendations specific to this project. The assessment of general site environmental conditions or the presence of pollutants in the soil, rock and groundwater of the site was beyond the scope of this geotechnical exploration. Our recommendations are based on the results of our field explorations, laboratory tests results from representative soil samples, and geotechnical engineering analyses. The results of the field explorations and laboratory tests, which form the basis of our recommendations, are presented in the appendices as noted. This report does not reflect any variations that may occur between the borings or elsewhere on the site, or variations whose nature and extent may not become evident until a later stage of construction. In the event that any changes occur in the nature, design or location of the proposed pavement rehabilitation work, the conclusions and recommendations contained in this report should not be considered valid until they are reviewed and have been modified or verified in writing by a geotechnical engineer.

It has been a pleasure to be of service to GPD Group in performing this geotechnical exploration for the SUM-76-6.15 project. Please call if there are any questions, or if we can be of further service.

Respectfully Submitted,

Brendan P. Andrews, P.E.
Geotechnical Engineer

Erich R.G. Beyer, E.I.
Staff Engineer

REFERENCES

- AASHTO. (2017). *LRFD Bridge Design Specifications*. Washington, D.C.: American Association of State Highway and Transportation Officials.
- FEMA. (2019). *National Flood Hazard Layer kmz v3.2*. Federal Emergency Management Agency.
- ODGS. (2003). Bedrock-topography data for Ohio: Ohio Department of Natural Resources, Division of Geological Survey Map BG-3, 1 CD-ROM, GIS file formats. Revised January 9, 2004.
- ODGS. (2005). Surficial geology of the western portion of the Lancaster 30 x 60-minute quadrangle: Ohio Division of Geological Survey Map SG-2 Lancaster. scale 1:100,000.
- ODNR [1]. (2016). Ohio Abandoned Mine Locator Interactive Map. *Mines of Ohio*. Ohio Department of Natural Resources, Division of Geological Survey & Division of Mineral Resources. Retrieved from <https://gis.ohiodnr.gov/MapView/?config=OhioMines>
- ODNR [2]. (2016). Ohio Oil & Gas Locator Interactive Map. *Ohio Oil & Gas Wells*. Ohio Department of Natural Resources, Division of Oil and Gas. Retrieved from <https://gis.ohiodnr.gov/MapView/?config=oilgaswells>
- ODOT [1]. (2019). *Geotechnical Bulletin 1*. Columbus, Ohio: Ohio Department of Transportation: Office of Geotechnical Engineering. Retrieved from https://www.dot.state.oh.us/Divisions/Engineering/Geotechnical/Geotechnical_Documents/GB1_Plan_Subgrades.pdf
- ODOT [2]. (2017). *Geotechnical Bulletin 2: Special Benching and Sidehill Embankment Fills*. Columbus, Ohio: Ohio Department of Transportation: Office of Geotechnical Engineering. Retrieved from <http://www.dot.state.oh.us/Divisions/Engineering/Geotechnical/Pages/Manuals.aspx>
- ODOT. (2019). *2019 Bridge Design Manual*. Columbus, OH: Ohio Department of Transportation: Office of Structural Engineering.
- ODOT PDM. (2019). *Pavement Design Manual*. Columbus, Ohio: Ohio Department of Transportation: Office of Pavement Engineering. Retrieved from http://www.dot.state.oh.us/Divisions/Engineering/Pavement/Pavement%20Design%20%20Rehabilitation%20Manual/Complete_PDM_2015-07-17_version.pdf
- ODOT SGE. (2019). *Specifications for Geotechnical Explorations*. Ohio Department of Transportation: Office of Geotechnical Engineering.
- USDA. (2015, September). Web Soil Survey. Retrieved from <http://websoilsurvey.nrcs.usda.gov>
- USGS & ODGS. (2006, June). Geologic Units of Ohio. *ohgeol.kmz*. United States Geologic Survey.

APPENDIX A
SOIL PROFILE SHEETS

TO BE PROVIDED

APPENDIX B
BORING LOGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:10 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6.15-2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / ASHBAUGH</u>	DRILL RIG: <u>CME 45B</u>	STATION / OFFSET: <u>210+67, 52' LT.</u>	EXPLORATION ID <u>B-001-0-18</u>
TYPE: <u>SUBGRADE</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>IR-77 & IR-76</u>	
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>995.6 (MSL)</u> EOB: <u>7.5 ft.</u>	PAGE 1 OF 1
START: <u>4/9/19</u> END: <u>4/9/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>84</u>	LAT / LONG: <u>41.061777, -81.570129</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL
								GR	CS	FS	SI	CL	LL	PL	PI			
16" CONCRETE (DRILLERS DESCRIPTION)	995.6																	X
	994.3	1																X
MEDIUM DENSE, BROWN, COARSE AND FINE SAND , SOME GRAVEL, LITTLE SILT, TRACE CLAY, DAMP (FILL)		2	11															>>>
		3	8	24	0	SS-1	-	24	21	38	11	6	NP	NP	NP	10	A-3a (0)	>>>
		4	5															>>>
	991.1	4	4	11	6	SS-2	-	-	-	-	-	-	-	-	-	10	A-3a (V)	>>>
VERY STIFF TO HARD, BROWN MOTTLED WITH GRAY, SANDY SILT , SOME CLAY, LITTLE GRAVEL, CONTAINS BRICK FRAGMENTS, DAMP (FILL)		5	2															>>>
		6	4	14	56	SS-3	2.25	19	7	13	38	23	28	18	10	15	A-4a (5)	>>>
		7	3															>>>
	988.1	7	6	21	50	SS-4	4.25	-	-	-	-	-	-	-	-	17	A-4a (V)	>>>
		EOB																>>>

NOTES: GROUNDWATER ENCOUNTERED AT 4.5' DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: PLACED 0.5 BAG ASPHALT PATCH; SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:10 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6.15 2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / ASHBAUGH</u>	DRILL RIG: <u>CME 45B</u>	STATION / OFFSET: <u>207+22, 51' RT.</u>	EXPLORATION ID <u>B-002-0-18</u>
TYPE: <u>SUBGRADE</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>IR-77 & IR-76</u>	PAGE 1 OF 1
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>1002.1 (MSL)</u> EOB: <u>7.5 ft.</u>	
START: <u>4/10/19</u> END: <u>4/10/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>84</u>	LAT / LONG: <u>41.062207, -81.571304</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL	
								GR	CS	FS	SI	CL	LL	PL	PI				
11.0" CONCRETE (DRILLERS DESCRIPTION)	1001.2	1																X	
MEDIUM STIFF, BROWN MOTTLED ORANGISH BROWN, SILT AND CLAY, SOME SAND, TRACE GRAVEL, CONTAINS IRON STAINING, DAMP	999.1	2	3	2	7	17	SS-1	0.75	-	-	-	-	-	-	-	-	17	A-6a (V)	<>
DENSE, LIGHT BROWN MOTTLED WITH ORANGISH BROWN, GRAVEL WITH SAND AND SILT, LITTLE CLAY, CONTAINS IRON STAINING, DAMP	994.6	3	4	10	34	89	SS-2	-	27	9	38	14	12	NP	NP	NP	6	A-2-4 (0)	<>
		4	7	10	14	35	78	SS-3	-	24	9	36	17	14	19	13	6	8	A-2-4 (0)
	994.6	6	3	11	49	89	SS-4	-	-	-	-	-	-	-	-	-	5	A-2-4 (V)	<>
		7	11	24														<>	

EOB

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: PLACED 0.5 BAG ASPHALT PATCH; SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:10 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6.15-2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / ASHBAUGH</u>	DRILL RIG: <u>CME 45B</u>	STATION / OFFSET: <u>204+23, 50' LT.</u>	EXPLORATION ID <u>B-003-0-18</u>
TYPE: <u>SUBGRADE</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>IR-77 & IR-76</u>	PAGE 1 OF 1
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>999.8 (MSL)</u> EOB: <u>7.5 ft.</u>	
START: <u>4/10/19</u> END: <u>4/10/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>84</u>	LAT / LONG: <u>41.063006, -81.571741</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL	
								GR	CS	FS	SI	CL	LL	PL	PI				
14.0" CONCRETE (DRILLERS DESCRIPTION)	999.8																	X	
	998.6	1																<>	
MEDIUM DENSE TO DENSE, BROWN AND ORANGISH BROWN, GRAVEL AND/OR STONE FRAGMENTS WITH SAND AND SILT , TRACE TO LITTLE CLAY, CONTAINS IRON STAINING, DAMP TO DRY		2	8	38	100	SS-1	-	30	11	28	18	13	17	13	4	7	A-2-4 (0)	<>	
		3	5	13	39	100	SS-2	-	35	11	31	13	10	NP	NP	NP	5	A-2-4 (0)	<>
		4	13	15														<>	
@4.5' TO 7.5'; BECOMES LIGHT BROWN AND ORANGISH BROWN		5	8	12	34	100	SS-3	-	-	-	-	-	-	-	-	5	A-2-4 (V)	<>	
		6	12	12														<>	
	992.3	7	12	9	27	100	SS-4	-	-	-	-	-	-	-	-	4	A-2-4 (V)	<>	
		EOB																<>	

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: PLACED 0.5 BAG ASPHALT PATCH; SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:10 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6-15-2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / ASHBAUGH</u>	DRILL RIG: <u>CME 45B</u>	STATION / OFFSET: <u>200+64, 8' LT.</u>	EXPLORATION ID <u>B-004-0-18</u>
TYPE: <u>SUBGRADE</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>IR-77 & IR-76</u>	PAGE 1 OF 1
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>1000.8 (MSL)</u> EOB: <u>7.5 ft.</u>	
START: <u>4/11/19</u> END: <u>4/11/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>84</u>	LAT / LONG: <u>41.063742, -81.572600</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL	
								GR	CS	FS	SI	CL	LL	PL	PI				
13.0" CONCRETE (DRILLERS DESCRIPTION)	1000.8																	<V> <V> <V>	
	999.7	1																<V> <V> <V>	
STIFF, BROWN, SANDY SILT , "AND" GRAVEL, LITTLE CLAY, CONTAINS NO INTACT SOIL FOR HP READINGS, DAMP		2	6	5	15	78	SS-1	-	37	8	16	24	15	29	19	10	14	A-4a (1)	<V> <V> <V>
	997.8	3	12	6														<V> <V> <V>	
VERY STIFF, BROWN, SILT AND CLAY , SOME SAND, TRACE TO LITTLE GRAVEL, CONTAINS NO INTACT SOIL FOR HP READINGS, DAMP		4	12	12	36	67	SS-2	-	-	-	-	-	-	-	-	-	16	A-6a (V)	<V> <V> <V>
		5	9	11	34	78	SS-3	-	11	7	18	38	26	29	18	11	16	A-6a (6)	<V> <V> <V>
		6	7	13														<V> <V> <V>	
	993.3	7	9	10	27	78	SS-4	-	-	-	-	-	-	-	-	-	16	A-6a (V)	<V> <V> <V>
		EOB																<V> <V> <V>	

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:10 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6.15 KENMORE\GINT FILES\SUM-76-6.15 2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / ASHBAUGH</u>	DRILL RIG: <u>CME 45B</u>	STATION / OFFSET: <u>193+62, 13' LT.</u>	EXPLORATION ID <u>B-006-0-18</u>
TYPE: <u>SUBGRADE</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>IR-77 & IR-76</u>	PAGE 1 OF 1
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>987.9 (MSL)</u> EOB: <u>7.5 ft.</u>	
START: <u>4/11/19</u> END: <u>4/11/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>84</u>	LAT / LONG: <u>41.065496, -81.573614</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL
								GR	CS	FS	SI	CL	LL	PL	PI			
14.0" CONCRETE AND 4.0" BASE (DRILLERS DESCRIPTION)	987.9																	
	986.4	1																
MEDIUM DENSE, BROWN AND GRAY, GRAVEL , SOME SAND, TRACE SILT, TRACE CLAY, DAMP		2	10															
		3	7	21	100	SS-1	-	62	18	13	5	2	NP	NP	NP	11	A-1-a (0)	
		4	7	8														
		5	9	28	100	SS-2	-	-	-	-	-	-	-	-	-	8	A-1-a (V)	
		6	11															
	981.9	7	6	5	15	100	SS-3	-	-	-	-	-	-	-	-	8	A-1-a (V)	
STIFF, BROWN, SANDY SILT , SOME GRAVEL, LITTLE CLAY, CONTAINS NO INTACT SOIL FOR HP READINGS, MOIST		6	5	6														
	980.4	7	8	8	22	100	SS-4	-	22	17	20	21	20	24	17	7	21	A-4a (1)
		EOB																

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: PLACED 0.5 BAG ASPHALT PATCH; SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:10 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6-15 KENMORE\GINT FILES\SUM-76-6-15 2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / J. HODGES</u>	DRILL RIG: <u>CME 55X</u>	STATION / OFFSET: <u>189+75, 74' LT.</u>	EXPLORATION ID <u>B-007-0-18</u>
TYPE: <u>ROADWAY</u>	SAMPLING FIRM / LOGGER: <u>NEAS / J.HODGES</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>IR-77 & IR-76</u>	
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>976.4 (MSL)</u> EOB: <u>10.5 ft.</u>	PAGE 1 OF 1
START: <u>4/30/19</u> END: <u>4/30/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>85</u>	LAT / LONG: <u>41.066552, -81.573713</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL	
								GR	CS	FS	SI	CL	LL	PL	PI				
LOOSE, BROWN, COARSE AND FINE SAND , LITTLE SILT, LITTLE CLAY, TRACE GRAVEL, SS-1 CONTAINS TRACE IRON STAINING, WET	976.4																		
		1																<V>	
		2																<V>	
		3	2	3	9	56	SS-1	-	-	-	-	-	-	-	-	14	A-3a (V)	<V>	
		4																<V>	
		5	1	2	7	100	SS-2	-	8	31	33	17	11	NP	NP	NP	16	A-3a (0)	<V>
		6																<V>	
		7																<V>	
		8	2	3	10	56	SS-3	-	-	-	-	-	-	-	-	17	A-3a (V)	<V>	
		9																<V>	
LOOSE, GRAY, SILT , SOME SAND, TRACE CLAY, TRACE GRAVEL, WET	965.9																	<V>	
		10	4	10	56	SS-4	-	3	4	24	61	8	NP	NP	NP	21	A-4b (7)	<V>	
																		<V>	

EOB

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:10 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6-15 KENMORE\GINT FILES\SUM-76-6-15 2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / ASHBAUGH</u>	DRILL RIG: <u>CME 55T</u>	STATION / OFFSET: <u>181+94, 76' LT.</u>	EXPLORATION ID <u>B-008-0-18</u>
TYPE: <u>ROADWAY</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>IR-77 & IR-76</u>	
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>983.4 (MSL)</u> EOB: <u>11.5 ft.</u>	PAGE 1 OF 1
START: <u>2/26/19</u> END: <u>2/26/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>78</u>	LAT / LONG: <u>41.068655, -81.573829</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	983.4	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG				ODOT CLASS (GI)	BACK FILL	
									GR	CS	FS	SI	CL	LL	PL	PI	WC			
MEDIUM DENSE, DARK BROWN, GRAVEL AND STONE FRAGMENTS WITH SAND AND SILT , TRACE TO LITTLE CLAY, CONTAINS TRACE ROOTS, ASPHALT, AND STONE FRAGMENTS >1", DAMP	981.4		1	4 6 8	18	100	SS-1	-	-	-	-	-	-	-	-	-	-	9	A-2-4 (V)	<V> >V<
VERY STIFF, BROWN MOTTLED WITH GRAY, SILT AND CLAY , "AND" SAND, TRACE GRAVEL, CONTAINS TRACE IRON STAINING, DAMP	978.9		3	4 6	13	100	SS-2	2.25	7	10	44	22	17	25	14	11	13	A-6a (1)	<V> >V<	
HARD, GRAY MOTTLED WITH BROWN AND ORANGISH BROWN, SANDY SILT , LITTLE CLAY, TRACE GRAVEL, CONTAINS TRACE IRON STAINING, DAMP TO MOIST	973.9		5	2 4 12	21	100	SS-3	4.5+	-	-	-	-	-	-	-	-	11	A-4a (V)	<V> >V<	
			6																	<V> >V<
			7																	<V> >V<
			8	3 3 6	12	100	SS-4	4.50	3	19	38	24	16	23	15	8	16	A-4a (1)	<V> >V<	
			9																	<V> >V<
MEDIUM DENSE, GRAYISH BROWN, COARSE AND FINE SAND , LITTLE SILT, TRACE CLAY, TRACE GRAVEL, MOIST	971.9		10	2 5 8	17	100	SS-5	-	-	-	-	-	-	-	-	-	13	A-3a (V)	<V> >V<	
			11																	<V> >V<

EOB

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:10 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6-15 KENMORE\GINT FILES\SUM-76-6-15 2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / ASHBAUGH</u>	DRILL RIG: <u>CME 55T</u>	STATION / OFFSET: <u>177+99, 66' LT.</u>	EXPLORATION ID <u>B-009-0-18</u>
TYPE: <u>ROADWAY</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>IR-77 & IR-76</u>	
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>984.9 (MSL)</u> EOB: <u>11.5 ft.</u>	PAGE 1 OF 1
START: <u>2/26/19</u> END: <u>2/26/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>78</u>	LAT / LONG: <u>41.069741, -81.573854</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG				ODOT CLASS (GI)	BACK FILL		
								GR	CS	FS	SI	CL	LL	PL	PI	WC				
VERY DENSE, DARK BROWN, GRAVEL AND STONE FRAGMENTS WITH SAND AND SILT , TRACE CLAY, CONTAINS PLASTIC FRAGMENTS, DAMP (FILL)	984.9	1	50/3"	-	100	SS-1	-	-	-	-	-	-	-	-	-	-	-	7	A-2-4 (V)	< > < >
	982.9	2																		< > < >
MEDIUM DENSE, LIGHT BROWN AND GRAY, COARSE AND FINE SAND , SOME GRAVEL AND STONE FRAGMENTS, LITTLE SILT, LITTLE CLAY, DAMP	980.4	3	5	16	100	SS-2	-	21	11	38	18	12	20	17	3	12		A-3a (0)	< > < >	
		4	7																	< > < >
VERY STIFF TO HARD, BROWN AND GRAY, SANDY SILT , LITTLE CLAY, TRACE GRAVEL, DAMP TO MOIST @5.0' TO 6.5'; SS-3 CONTAINS LIGHT BROWN AND ORANGISH BROWN MOTTLES, TRACE IRON STAINING	980.4	5	4	17	100	SS-3	4.50	6	16	30	29	19	21	14	7	13		A-4a (3)	< > < >	
		6	7																	< > < >
		8	3	14	100	SS-4	2.75	-	-	-	-	-	-	-	-	-	15	A-4a (V)	< > < >	
	973.4	9	5																	< > < >
		10	6	14	100	SS-5	4.5+	-	-	-	-	-	-	-	-	12	A-4a (V)	< > < >		
		11	5																	< > < >

EOB

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:10 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6-15 KENMORE\GINT FILES\SUM-76-6-15 2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / ASHBAUGH</u>	DRILL RIG: <u>CME 55T</u>	STATION / OFFSET: <u>173+98, 60' LT.</u>	EXPLORATION ID <u>B-010-0-18</u>
TYPE: <u>ROADWAY</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>IR-77 & IR-76</u>	
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>985.0 (MSL)</u> EOB: <u>11.5 ft.</u>	PAGE 1 OF 1
START: <u>2/26/19</u> END: <u>2/26/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>78</u>	LAT / LONG: <u>41.070840, -81.573860</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG				WC	ODOT CLASS (GI)	BACK FILL	
								GR	CS	FS	SI	CL	LL	PL	PI					
DENSE, BROWN, GRAVEL WITH SAND AND SILT , TRACE CLAY, CONTAINS TRACE IRON STAINING, DAMP	985.0	1	7	11	31	100	SS-1	-	-	-	-	-	-	-	-	-	-	12	A-2-4 (V)	<V>
	983.0	2	13																	<V>
STIFF TO VERY STIFF, BROWN MOTTLED WITH ORANGISH BROWN AND GRAY, SANDY SILT , LITTLE CLAY, LITTLE GRAVEL, CONTAINS TRACE IRON STAINING, DAMP	980.5	3	5	7	18	100	SS-2	2.00	11	17	29	26	17	23	16	7	15	A-4a (2)	<V>	
		4	7																	<V>
MEDIUM DENSE, BROWN, GRAVEL AND STONE FRAGMENTS WITH SAND AND SILT , LITTLE CLAY, DAMP	978.0	5	5	6	18	100	SS-3	-	23	17	28	21	11	22	17	5	14	A-2-4 (0)	<V>	
		6	8																	<V>
STIFF TO VERY STIFF, GRAY MOTTLED WITH ORANGISH BROWN, SANDY SILT , LITTLE CLAY, TRACE GRAVEL, CONTAINS TRACE IRON STAINING, DAMP	973.5	7	4	5	16	100	SS-4	3.00	-	-	-	-	-	-	-	-	16	A-4a (V)	<V>	
		8	5	7																<V>
		9																		<V>
		10	5																	<V>
		11	5	6	14	100	SS-5	2.00	-	-	-	-	-	-	-	-	15	A-4a (V)	<V>	
		EOB	6																	<V>

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT. - 7/29/19 09:10 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6.15-2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / ASHBAUGH</u>	DRILL RIG: <u>CME 55T</u>	STATION / OFFSET: <u>165+85, 59' LT.</u>	EXPLORATION ID <u>B-012-0-18</u>
TYPE: <u>ROADWAY</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>IR-77 & IR-76</u>	
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>982.9 (MSL)</u> EOB: <u>11.5 ft.</u>	PAGE 1 OF 1
START: <u>2/26/19</u> END: <u>2/26/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>78</u>	LAT / LONG: <u>41.073072, -81.573836</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL		
								GR	CS	FS	SI	CL	LL	PL	PI					
HARD, DARK BROWN AND LIGHT BROWN, SANDY SILT , SOME GRAVEL, LITTLE CLAY, CONTAINS TRACE IRON STAINING, DAMP	982.9	1	8															< > < > < >		
		2	11	30	100	SS-1	4.25	-	-	-	-	-	-	-	-	-	11	A-4a (V)	< > < > < >	
		3	6																< > < > < >	
STIFF TO VERY STIFF, BROWN MOTTLED WITH ORANGISH BROWN AND GRAY, SANDY SILT , LITTLE CLAY, TRACE GRAVEL, CONTAINS TRACE IRON STAINING, DAMP	978.4	4	9	23	100	SS-2	4.25	24	9	29	23	15	21	14	7	10	A-4a (1)	< > < > < >		
		5	5																< > < > < >	
		6	6	7	17	100	SS-3	1.25	8	23	28	27	14	26	20	6	18	A-4a (1)	< > < > < >	
		7																	< > < > < >	
		8	5																< > < > < >	
		9	6	6	16	100	SS-4	2.00	-	-	-	-	-	-	-	-	-	17	A-4a (V)	< > < > < >
		10																	< > < > < >	
		11	6	7	17	100	SS-5	1.50	-	-	-	-	-	-	-	-	-	17	A-4a (V)	< > < > < >
	971.4	EOB																< > < > < >		

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT. - 7/29/19 09:10 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6-15 KENMORE\GINT FILES\SUM-76-6-15 2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / ASHBAUGH</u>	DRILL RIG: <u>CME 55T</u>	STATION / OFFSET: <u>161+79, 60' LT.</u>	EXPLORATION ID <u>B-013-0-18</u>
TYPE: <u>ROADWAY</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>IR-77 & IR-76</u>	
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>981.8 (MSL)</u> EOB: <u>11.5 ft.</u>	PAGE 1 OF 1
START: <u>2/26/19</u> END: <u>2/26/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>78</u>	LAT / LONG: <u>41.074185, -81.573819</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL			
								GR	CS	FS	SI	CL	LL	PL	PI						
MEDIUM DENSE TO DENSE, DARK BROWN BECOMING LIGHT TAN AND ORANGISH BROWN, GRAVEL AND STONE FRAGMENTS WITH SAND AND SILT , TRACE CLAY, SS-1 CONTAINS TRACE ROOTS, SS-3 CONTAINS IRON STAINING, MOIST TO DAMP	981.8	1	13															< >			
		2	10	25	100	SS-1	-	-	-	-	-	-	-	-	-	-	-	< >			
		3	7	9	23	89	SS-2	-	38	11	37	9	5	NP	NP	NP	7	A-2-4 (0)	< >		
		4																		< >	
		5	6																	< >	
LOOSE, BROWN AND ORANGISH BROWN, COARSE AND FINE SAND , TRACE SILT, TRACE CLAY, TRACE GRAVEL, SS-5 CONTAINS IRON STAINING, WET	974.8	6	12	36	89	SS-3	-	-	-	-	-	-	-	-	-	-	-	8	A-2-4 (V)	< >	
		7																		< >	
		8	4	3	9	100	SS-4	-	0	21	65	8	6	NP	NP	NP	17	A-3a (0)	< >		
		9																		< >	
		10	2	3	10	100	SS-5	-	-	-	-	-	-	-	-	-	-	-	27	A-3a (V)	< >
		11	3	5																	< >
	970.3	EOB																		< >	

NOTES: GROUNDWATER ENCOUNTERED AT 9.0' DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:10 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6-15 KENMORE\GINT FILES\SUM-76-6-15 2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / ASHBAUGH</u>	DRILL RIG: <u>CME 55T</u>	STATION / OFFSET: <u>157+96, 60' LT.</u>	EXPLORATION ID <u>B-014-0-18</u>
TYPE: <u>ROADWAY</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>IR-77 & IR-76</u>	
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>982.7 (MSL)</u> EOB: <u>11.5 ft.</u>	PAGE 1 OF 1
START: <u>2/26/19</u> END: <u>2/26/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>78</u>	LAT / LONG: <u>41.075237, -81.573806</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG				ODOT CLASS (GI)	BACK FILL	
								GR	CS	FS	SI	CL	LL	PL	PI	WC			
STIFF, BROWN, SANDY SILT , LITTLE CLAY, TRACE GRAVEL, MOIST	982.7	1	5	16	100	SS-1	1.25	4	19	28	30	19	25	15	10	16	A-4a (3)	<V> >V<	
	980.7	2	7															<V> >V<	
LOOSE TO MEDIUM DENSE, BROWN, COARSE AND FINE SAND , LITTLE SILT, LITTLE CLAY, TRACE GRAVEL, SS-3 CONTAINS TRACE ROOT HAIRS, MOIST TO WET	973.7	3	3	10	100	SS-2	-	-	-	-	-	-	-	-	-	12	A-3a (V)	<V> >V<	
		4	4															<V> >V<	
		5	3															<V> >V<	
		6	4	12	100	SS-3	-	7	39	25	18	11	23	18	5	15	A-3a (0)	<V> >V<	
		7	5																<V> >V<
		8	4																<V> >V<
		9	4	12	100	SS-4	-	-	-	-	-	-	-	-	-	18	A-3a (V)	<V> >V<	
		10	5																<V> >V<
		11	3	10	100	SS-5	-	-	-	-	-	-	-	-	-	29	A-3a (V)	<V> >V<	
	971.2	EOB	4															<V> >V<	

NOTES: GROUNDWATER ENCOUNTERED AT 9.0' DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:10 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6-15 KENMORE\GINT FILES\SUM-76-6-15 2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / J. HODGES</u>	DRILL RIG: <u>CME 55X</u>	STATION / OFFSET: <u>154+04, 73' LT.</u>	EXPLORATION ID <u>B-015-0-18</u>
TYPE: <u>ROADWAY</u>	SAMPLING FIRM / LOGGER: <u>NEAS / CHIPUKAIZER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>IR-77 & IR-76</u>	
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>984.3 (MSL)</u> EOB: <u>10.5 ft.</u>	PAGE 1 OF 1
START: <u>5/1/19</u> END: <u>5/1/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>85</u>	LAT / LONG: <u>41.076317, -81.573749</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG				ODOT CLASS (GI)	BACK FILL		
								GR	CS	FS	SI	CL	LL	PL	PI	WC				
VERY STIFF, BROWN, SANDY SILT , LITTLE CLAY, LITTLE GRAVEL, CONTAINS IRON STAINING, DAMP (FILL)	984.3	1																< > < >		
		2																< > < >		
		3	4	6	23	100	SS-1	3.00	17	16	27	24	16	25	15	10	13	A-4a (1)	< > < >	
		4																	< > < >	
LOOSE, BROWN, COARSE AND FINE SAND , SOME SILT, TRACE CLAY, TRACE GRAVEL, CONTAINS IRON STAINING, SS-4 CONTAINS TRACE PLASTIC DEBRIS, WET (FILL)	977.3	5	2															< > < >		
		6	2	3	7	56	SS-2	2.50	11	17	26	28	18	27	17	10	15	A-4a (2)	< > < >	
		7																	< > < >	
		8	2	2	6	56	SS-3	-	-	-	-	-	-	-	-	-	-	21	A-3a (V)	< > < >
		9	2	2	7	56	SS-4	-	-	-	-	-	-	-	-	-	-	20	A-3a (V)	< > < >
		10	2	3															< > < >	
	973.8	EOB																< > < >		

NOTES: GROUNDWATER ENCOUNTERED AT 7.5' DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: SHOVELED SOIL CUTTINGS

Direct Shear Test


D3080

Project: SUM-76-6.15

Project Number: 100713

Location: B-017-0-18

Client Name:



C (psi): 1.2

Phi (°): 29.5

Residual C (psi): NA

Residual Phi (°): NA

	Specimen Number								
	Initial	1	2	3	4	5	6	7	8
Moisture (%):		20.2	17.3	15.6					
Dry Density (pcf):		106.9	110.3	111.6					
Void Ratio:		0.560	0.511	0.493					
Saturation (%):		96.3	90.5	84.5					
Diameter (in):		2.4973	2.4973	2.4973					
Height (in):		1.0033	0.9998	1.0000					
	Final	1	2	3	4	5	6	7	8
Moisture (%):		21.9	20.0	17.6					
Dry Density (pcf):		108.9	111.0	113.6					
Void Ratio:		0.531	0.502	0.467					
Saturation (%):		110.2	106.3	100.7					
Height (in):		1.0003	0.9998	0.9901					
Normal Stress (psi):		2.5	5.0	10.0					
Peak Shear Stress (psi):		2.6	4.0	6.8					
Residual Stress (psi):		NA	NA	NA					
Horizontal Deformation (%):		3.3	3.7	4.1					
Rate (in/min):		0.003535	0.003707	0.005000					

Direct Shear Test

D3080

Project: SUM-76-6.15

Project Number: 100713

Sampling Date: 6/19/2019

Sample Number: ST-1

Sample Depth: 2.0-4.0 ft

Location: B-017-0-18

Client Name:

Remarks:

Information Parameters	Specimen Number							
	1	2	3	4	5	6	7	8
Liquid Limit:	24	24	24					
Plastic Limit:	17	17	17					
Specific Gravity:	2.67	2.67	2.67					
Specific Gravity Method:	ASSUMED	ASSUMED	ASSUMED					
Initial Parameters	1	2	3	4	5	6	7	8
Test Temperature (°C):	21.1	21.1	21.1					
Sample Shape:	ROUND	ROUND	ROUND					
Height (in):	1.0033	0.9998	1.0000					
Diameter (in):	2.4973	2.4973	2.4973					
Area (in ²):	4.898	4.898	4.898					
Volume (in ³):	4.9146	4.8975	4.8983					
Moisture (%):	20.2	17.3	15.6					
Dry Density (pcf):	106.9	110.3	111.6					
Wet Density (pcf):	128.4	129.4	129.1					
Saturation (%):	96.3	90.5	84.5					
Void Ratio:	0.560	0.511	0.493					
Porosity (%):	35.9	33.8	33.0					
Consolidation Parameters	1	2	3	4	5	6	7	8
Initial Reference Height (in):	1.0033	0.9998	1.0000					
Final Reference Height (in):	1.0003	0.9998	0.9901					
Height (in):	1.0003	0.9998	0.9901					
Final Parameters	1	2	3	4	5	6	7	8
Moisture Content (%)	21.9	20.0	17.6					
Dry Density (pcf):	108.9	111.0	113.6					
Wet Density (pcf):	132.7	133.2	133.6					
Saturation (%):	110.2	106.3	100.7					
Void Ratio:	0.531	0.502	0.467					
Porosity (%):	34.7	33.4	31.8					

Direct Shear Test

D3080

Project: SUM-76-6.15
Project Number: 100713
Sampling Date: 6/19/2019
Sample Number: ST-1
Sample Depth: 2.0-4.0 ft
Location: B-017-0-18
Client Name:
Remarks:

Specific Gravity: 2.67

Plastic Limit: 17

Liquid Limit: 24

Type: ST

Soil Classification: A-4a

Specimen Description: Hard, brown mottled with orangish brown and gray, SANDY SILT, some clay, trace gravel, damp.

Specimen 1
Failure Sketch

Specimen 2
Failure Sketch

Specimen 3
Failure Sketch


Specimen 4
Failure Sketch

Specimen 5
Failure Sketch

Specimen 6
Failure Sketch

Specimen 7
Failure Sketch

Specimen 8
Failure Sketch



Direct Shear Test

D3080

Specimen 3

Test Description: D3080

Other Associated Tests:

Device Details: HM-5760

Test Specification:

Test Time: 6/21/2019

Technician: L. Rosenbeck

Sampling Method: ST

Specimen Code: 3.8' - 3.9'

Specimen Lab #: 3

Specimen Description: Hard, brown mottled with orangish brown and gray, SANDY SILT, some clay, trace gravel, damp.

Specific Gravity: 2.67


Plastic Limit: 17

Liquid Limit: 24

Test Remarks:

Direct Shear Test - Shear Stress Vs. Normal Stress


D3080



Tangent Results		C (psi)	Phi (°)
Peak Tangent:		1.2	29.5
Residual Tangent:		NA	NA


Graph - Stress Deformation

D3080



Graph - Delta H

D3080



Direct Shear Test - Specimen 1 - Consolidation Summary

D3080

Sample Description: Hard, brown mottled with orangish brown and gray, SANDY SILT, some clay, trace gravel, damp.

Project Number: 100713

Depth:

Remarks

Sample Number: ST-1

Boring Number: B-017-0-18

Project: SUM-76-6.15

Client:

Location: B-017-0-18

Index	Loading Sequence (psi)	Cummulative Change in Height (ft)	Specimen Height (ft)	Height of Voids (ft)	Vertical Strain (%)	Void Ratio	T90 Fitting Time (Hr)	T50 Fitting Time (Hr)	T90 Cv (in ² /Min)	T50 Cv (in ² /Min)
0	0.0	0.000	0.084	0.000	0.0	0.56	0.000	0.000	0.00000	0.00000
1	2.5	0.000	0.083	0.030	0.3	0.55	0.034	1.430	0.10442	0.00058

Consol Test - Specimen 1 - Sequence 1 - 2.5 (psi)


D3080

LIMS Code: [TO COME FROM LIMS] LIMS Specimen Code: [TO COME FROM LIMS]

Index	Elapsed Time (hh:mm:ss)	Load (Lbf)	Load (Lbf)	Settlement (in)	Axial Strain (%)	Void Ratio
0	00:00:00	11.6	-0.0114	0.0000	0.0	0.56
1	00:00:06	11.9	-0.0117	0.0003	0.0	0.56
2	00:00:15	12.2	-0.0120	0.0005	0.1	0.56
3	00:00:30	12.2	-0.0122	0.0007	0.1	0.56
4	00:01:00	12.3	-0.0125	0.0010	0.1	0.56
5	00:02:00	12.2	-0.0127	0.0013	0.1	0.56
6	00:04:00	12.2	-0.0130	0.0016	0.2	0.55
7	00:08:00	12.3	-0.0134	0.0020	0.2	0.55
8	00:15:00	12.2	-0.0137	0.0023	0.2	0.55
9	00:30:00	12.3	-0.0140	0.0025	0.3	0.55
10	01:00:00	12.2	-0.0142	0.0027	0.3	0.55
11	02:00:00	12.2	-0.0143	0.0028	0.3	0.55
12	04:00:00	12.2	-0.0144	0.0029	0.3	0.55
13	08:00:00	12.2	-0.0144	0.0030	0.3	0.55
14	12:00:00	12.3	-0.0144	0.0030	0.3	0.55
15	16:00:00	12.2	-0.0145	0.0030	0.3	0.55
16	20:00:00	12.2	-0.0145	0.0030	0.3	0.55
17	21:21:57	12.2	-0.0145	0.0030	0.3	0.55

Square Root Time - Specimen 1 - Sequence 1 - 2.5 (psi)

D3080



Tangent Construction Results


T90 (Min):	2.044
T50 (Min):	1.135
Cv (in ² /Min):	0.104

Logarithmic Time - Specimen 1 - Sequence 1 - 2.5 (psi)

D3080

LIMS Code: [TO COME FROM LIMS]

LIMS Specimen Code: [TO COME FROM LIMS]



Tangent Construction Results

T90 (Min):	NA
T50 (Min):	NA
Cv (in ² /Min):	NA

Direct Shear Test - Specimen 2 - Consolidation Summary

D3080

Sample Description: Hard, brown mottled with orangish brown and gray, SANDY SILT, some clay, trace gravel, damp.

Project Number: 100713

Depth:

Remarks

Sample Number: ST-1

Boring Number: B-017-0-18

Project: SUM-76-6.15

Client:

Location: B-017-0-18

Index	Loading Sequence (psi)	Cummulative Change in Height (ft)	Specimen Height (ft)	Height of Voids (ft)	Vertical Strain (%)	Void Ratio	T90 Fitting Time (Hr)	T50 Fitting Time (Hr)	T90 Cv (in ² /Min)	T50 Cv (in ² /Min)
0	0.0	0.000	0.083	0.000	0.0	0.51	0.000	0.000	0.00000	0.00000
1	5.0	0.001	0.083	0.027	0.7	0.50	0.032	1.394	0.10913	0.00059

Consol Test - Specimen 2 - Sequence 1 - 5.0 (psi)


D3080

LIMS Code: [TO COME FROM LIMS] LIMS Specimen Code: [TO COME FROM LIMS]

Index	Elapsed Time (hh:mm:ss)	Load (Lbf)	Load (Lbf)	Settlement (in)	Axial Strain (%)	Void Ratio
0	00:00:00	23.3	-0.0168	0.0000	0.0	0.51
1	00:00:06	23.9	-0.0175	0.0007	0.1	0.51
2	00:00:15	24.5	-0.0182	0.0014	0.1	0.51
3	00:00:30	24.5	-0.0189	0.0021	0.2	0.50
4	00:01:00	24.5	-0.0195	0.0027	0.3	0.50
5	00:02:00	24.6	-0.0202	0.0034	0.3	0.50
6	00:04:00	24.5	-0.0209	0.0041	0.4	0.50
7	00:08:00	24.4	-0.0217	0.0049	0.5	0.50
8	00:15:00	24.4	-0.0223	0.0055	0.6	0.50
9	00:30:00	24.5	-0.0228	0.0060	0.6	0.50
10	01:00:00	24.4	-0.0230	0.0063	0.6	0.50
11	02:00:00	24.3	-0.0232	0.0064	0.6	0.50
12	04:00:00	24.5	-0.0237	0.0070	0.7	0.50
13	04:35:07	24.5	-0.0238	0.0070	0.7	0.50

Square Root Time - Specimen 2 - Sequence 1 - 5.0 (psi)

D3080



Tangent Construction Results


T90 (Min):	1.942
T50 (Min):	1.079
Cv (in ² /Min):	0.109

Logarithmic Time - Specimen 2 - Sequence 1 - 5.0 (psi)

D3080

LIMS Code: [TO COME FROM LIMS]

LIMS Specimen Code: [TO COME FROM LIMS]



Tangent Construction Results

T90 (Min):	NA
T50 (Min):	NA
Cv (in ² /Min):	NA

Direct Shear Test - Specimen 3 - Consolidation Summary

D3080

Sample Description: Hard, brown mottled with orangish brown and gray, SANDY SILT, some clay, trace gravel, damp.

Project Number: 100713

Depth:

Remarks

Sample Number: ST-1

Boring Number: B-017-0-18

Project: SUM-76-6.15

Client:

Location: B-017-0-18

Index	Loading Sequence (psi)	Cummulative Change in Height (ft)	Specimen Height (ft)	Height of Voids (ft)	Vertical Strain (%)	Void Ratio	T90 Fitting Time (Hr)	T50 Fitting Time (Hr)	T90 Cv (in ² /Min)	T50 Cv (in ² /Min)
0	0.0	0.000	0.083	0.000	0.0	0.49	0.000	0.000	0.00000	0.00000
1	10.0	0.001	0.083	0.027	1.0	0.48	0.024	1.200	0.14722	0.00068

Consol Test - Specimen 3 - Sequence 1 - 10.0 (psi)


D3080

LIMS Code: [TO COME FROM LIMS] LIMS Specimen Code: [TO COME FROM LIMS]

Index	Elapsed Time (hh:mm:ss)	Load (Lbf)	Load (Lbf)	Settlement (in)	Axial Strain (%)	Void Ratio
0	00:00:00	46.7	-0.0379	0.0000	0.0	0.49
1	00:00:06	48.4	-0.0397	0.0018	0.2	0.49
2	00:00:15	48.8	-0.0408	0.0030	0.3	0.49
3	00:00:30	49.1	-0.0418	0.0040	0.4	0.48
4	00:01:00	49.3	-0.0428	0.0050	0.5	0.48
5	00:02:00	49.1	-0.0438	0.0060	0.6	0.48
6	00:04:00	48.9	-0.0449	0.0071	0.7	0.48
7	00:08:00	49.0	-0.0461	0.0082	0.8	0.48
8	00:15:00	49.1	-0.0467	0.0089	0.9	0.48
9	00:30:00	48.9	-0.0472	0.0093	0.9	0.48
10	01:00:00	49.0	-0.0474	0.0095	1.0	0.48
11	02:00:00	49.0	-0.0476	0.0097	1.0	0.48
12	04:00:00	48.9	-0.0477	0.0099	1.0	0.48
13	05:42:57	49.0	-0.0478	0.0099	1.0	0.48

Square Root Time - Specimen 3 - Sequence 1 - 10.0 (psi)

D3080



Tangent Construction Results


T90 (Min): 1.440
 T50 (Min): 0.800
 Cv (in²/Min): 0.144

Logarithmic Time - Specimen 3 - Sequence 1 - 10.0 (psi)

D3080

LIMS Code: [TO COME FROM LIMS]

LIMS Specimen Code: [TO COME FROM LIMS]



Tangent Construction Results

T90 (Min):	NA
T50 (Min):	NA
Cv (in ² /Min):	NA

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:10 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6-15 KENMORE\GINT FILES\SUM-76-6-15 2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / ASHBAUGH</u>	DRILL RIG: <u>CME 55T</u>	STATION / OFFSET: <u>146+83, 59' LT.</u>	EXPLORATION ID <u>B-018-0-18</u>
TYPE: <u>ROADWAY</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>IR-77 & IR-76</u>	
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>987.9 (MSL)</u> EOB: <u>11.5 ft.</u>	PAGE 1 OF 1
START: <u>2/28/19</u> END: <u>2/28/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>78</u>	LAT / LONG: <u>41.078313, -81.574111</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG				ODOT CLASS (GI)	BACK FILL	
								GR	CS	FS	SI	CL	LL	PL	PI	WC			
MEDIUM DENSE, BROWN, GRAVEL WITH SAND AND SILT , LITTLE CLAY, DAMP	987.9	1	12 8	22	100	SS-1	-	22	17	31	18	12	20	17	3	9	A-2-4 (0)	<V> >V<	
VERY STIFF, BROWN AND DARK BROWN, SANDY SILT , SOME CLAY, LITTLE GRAVEL, SS-2 CONTAINS IRON STAINING, DAMP	985.9	2																<V> >V<	
		3	5 7	25	100	SS-2	2.50	-	-	-	-	-	-	-	-	12	A-4a (V)	<V> >V<	
		4																	<V> >V<
		5	6 8	23	100	SS-3	3.50	-	-	-	-	-	-	-	-	-	13	A-4a (V)	<V> >V<
DENSE, LIGHT BROWN AND ORANGISH BROWN, STONE FRAGMENTS WITH SAND AND SILT , LITTLE CLAY, STONE FRAGMENTS ARE SANDSTONE, CONTAINS IRON STAINING, DAMP	980.9	6	8 10	23	100	SS-3	3.50	-	-	-	-	-	-	-	-			<V> >V<	
		7																	<V> >V<
DENSE, LIGHT BROWN AND ORANGISH BROWN, STONE FRAGMENTS WITH SAND AND SILT , LITTLE CLAY, STONE FRAGMENTS ARE SANDSTONE, CONTAINS IRON STAINING, DAMP	978.4	8	9 14	38	100	SS-4	-	-	-	-	-	-	-	-	-	9	A-2-4 (V)	<V> >V<	
		9	15																<V> >V<
MEDIUM DENSE, BROWN, COARSE AND FINE SAND , LITTLE SILT, TRACE CLAY, TRACE GRAVEL, DAMP	976.4	10	9	13	100	SS-5	-	-	-	-	-	-	-	-	-	12	A-3a (V)	<V> >V<	
	976.4	11	5	5														<V> >V<	

EOB

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:10 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6-15 2.GPJ

PID: 100713		SFN: _____		PROJECT: SUM-76-06.15		STATION / OFFSET: 43+79, 49' LT.		START: 4/16/19		END: 4/16/19		PG 2 OF 2		B-020-0-18						
MATERIAL DESCRIPTION AND NOTES			ELEV. 972.4	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL
										GR	CS	FS	SI	CL	LL	PL	PI			
HARD, GRAYISH BROWN AND DARK GRAY, SANDY SILT, LITTLE GRAVEL, LITTLE CLAY, DAMP (continued)			970.4	31	8	24	50	SS-12	4.25	-	-	-	-	-	-	-	-	14	A-4a (V)	<>L> <>L> <>L> <>L>
				32	9															
MEDIUM DENSE, BROWN, COARSE AND FINE SAND, TRACE TO LITTLE SILT, TRACE CLAY, TRACE GRAVEL, DAMP			965.9	33	4	14	100	SS-13	-	-	-	-	-	-	-	-	-	9	A-3a (V)	<>L> <>L> <>L> <>L>
				34	5															
				35	6															<>L> <>L> <>L> <>L>
				36	7	20	100	SS-14	-	-	-	-	-	-	-	-	-	-	10	A-3a (V)
				EOB																
NOTES: GROUNDWATER ENCOUNTERED AT 28.0' DURING DRILLING. HOLE DID NOT CAVE.																				
ABANDONMENT METHODS, MATERIALS, QUANTITIES: PLACED 0.5 BAG ASPHALT PATCH; SHOVELED SOIL CUTTINGS																				

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:10 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6-15 KENMORE\GINT FILES\SUM-76-6-15 2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / J. HODGES</u>	DRILL RIG: <u>CME 55X</u>	STATION / OFFSET: <u>45+68, 110' LT.</u>	EXPLORATION ID <u>B-021-0-18</u>
TYPE: <u>EMBANKMENT</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>IR-277</u>	
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>976.5 (MSL)</u> EOB: <u>11.5 ft.</u>	PAGE 1 OF 1
START: <u>3/19/19</u> END: <u>3/19/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>85</u>	LAT / LONG: <u>41.035855, -81.573662</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG				ODOT CLASS (GI)	BACK FILL
								GR	CS	FS	SI	CL	LL	PL	PI	WC		
MEDIUM STIFF, BROWN, SILT AND CLAY , "AND" SAND, TRACE GRAVEL, MOIST	976.5	1																<< < > >>
		2																<< < > >>
		3	1	3	33	SS-1	0.75	5	16	27	28	24	29	17	12	19	A-6a (4)	<< < > >>
	972.0	4																<< < > >>
LOOSE, BROWN, COARSE AND FINE SAND , SOME SILT, TRACE GRAVEL, TRACE CLAY, DAMP		5	2															<< < > >>
		6	3	9	100	SS-2	-	-	-	-	-	-	-	-	-	11	A-3a (V)	<< < > >>
	969.5	7																<< < > >>
MEDIUM DENSE, BROWN AND GRAY, GRAVEL WITH SAND AND SILT , LITTLE CLAY, CONTAINS IRON STAINING, MOIST		8	3															<< < > >>
		9	4	13	100	SS-3	-	6	23	39	17	15	24	15	9	17	A-2-4 (0)	<< < > >>
	967.0	10	5															<< < > >>
MEDIUM DENSE, BROWN, GRAVEL WITH SAND , TRACE SILT, TRACE CLAY, CONTAINS IRON STAINING, DAMP		11	4	9	23	89	SS-4	-	-	-	-	-	-	-	-	11	A-1-b (V)	<< < > >>
	965.0	EOB	7															<< < > >>

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:10 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6.15 KENMORE\GINT FILES\SUM-76-6.15 2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / J. HODGES</u>	DRILL RIG: <u>CME 55X</u>	STATION / OFFSET: <u>51+87, 138' LT.</u>	EXPLORATION ID <u>B-024-0-18</u>
TYPE: <u>SIDEHILL CUT SECTION</u>	SAMPLING FIRM / LOGGER: <u>NEAS / CHIPUKAIZER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>IR-277</u>	
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>998.3 (MSL)</u> EOB: <u>26.5 ft.</u>	PAGE 1 OF 1
START: <u>3/26/19</u> END: <u>3/26/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>85</u>	LAT / LONG: <u>41.035902, -81.571418</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTH	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL	
								GR	CS	FS	SI	CL	LL	PL	PI				
VERY DENSE, BROWN, COARSE AND FINE SAND , LITTLE SILT, LITTLE GRAVEL, TRACE CLAY, DAMP	998.3	1																	
		2																	
		3	6	18	64	100	SS-1	-	11	30	31	20	8	NP	NP	NP	7	A-3a (0)	
DENSE, BROWN AND DARK BROWN, GRAVEL AND STONE FRAGMENTS WITH SAND AND SILT , TRACE CLAY, CONTAINS STONE FRAGMENTS >1.0", CONTAINS IRON STAINING, DAMP	993.8	4																	
		5	4	14	43	100	SS-2	-	-	-	-	-	-	-	-	-	8	A-2-4 (V)	
VERY STIFF, BROWN, SANDY SILT , LITTLE CLAY, LITTLE GRAVEL, DAMP	991.3	6																	
LOOSE TO MEDIUM DENSE, BROWN AND LIGHT BROWN, COARSE AND FINE SAND , TRACE TO LITTLE SILT, TRACE GRAVEL, TRACE CLAY, SS-7 CONTAINS IRON STAINING, DAMP	990.1	7																	
		8	3	3	11	56	SS-3A	3.00	-	-	-	-	-	-	-	-	12	A-4a (V)	
LOOSE TO MEDIUM DENSE, BROWN AND LIGHT BROWN, COARSE AND FINE SAND , TRACE TO LITTLE SILT, TRACE GRAVEL, TRACE CLAY, SS-7 CONTAINS IRON STAINING, DAMP	983.3	9																	
		10																	
		11																	
		12	3	4	11	56	SS-5	-	-	-	-	-	-	-	-	-	5	A-3a (V)	
		13	4	5	14	78	SS-6	-	-	-	-	-	-	-	-	-	7	A-3a (V)	
		14																	
		15	4	7	17	100	SS-7	-	-	-	-	-	-	-	-	-	11	A-3a (V)	
		16																	
		17																	
		18	2	2	9	100	SS-8	-	-	-	-	-	-	-	-	-	6	A-3a (V)	
MEDIUM DENSE, BROWN, GRAVEL AND STONE FRAGMENTS WITH SAND , TRACE SILT, TRACE CLAY, DAMP	978.8	19																	
MEDIUM DENSE, BROWN, GRAVEL AND STONE FRAGMENTS WITH SAND , TRACE SILT, TRACE CLAY, DAMP	973.8	20	2	3	11	39	SS-9	-	-	-	-	-	-	-	-	5	A-1-b (V)		
		21																	
LOOSE, BROWN, COARSE AND FINE SAND , TRACE SILT, TRACE GRAVEL, TRACE CLAY, DAMP	971.8	22																	
		23	3	4	11	56	SS-10	-	13	51	26	8	2	NP	NP	NP	5	A-1-b (0)	
		24																	
		25	2	3	9	61	SS-11	-	-	-	-	-	-	-	-	4	A-3a (V)		
		26																	

EOB

NOTES: GROUNDWATER ENCOUNTERED AT 15.0' DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:10 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6-15 KENMORE\GINT FILES\SUM-76-6-15 2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / ASHBAUGH</u>	DRILL RIG: <u>CME 45B</u>	STATION / OFFSET: <u>55+67, 60' LT.</u>	EXPLORATION ID <u>B-025-0-18</u>
TYPE: <u>SUBGRADE</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>IR-277</u>	PAGE 1 OF 1
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>973.1 (MSL)</u> EOB: <u>7.5 ft.</u>	
START: <u>4/16/19</u> END: <u>4/16/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>84</u>	LAT / LONG: <u>41.035672, -81.570045</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL	
								GR	CS	FS	SI	CL	LL	PL	PI				
10" ASPHALT AND 7" CONCRETE	973.1																	X	
	971.7	1																X	
MEDIUM DENSE TO DENSE, BROWN, COARSE AND FINE SAND , LITTLE GRAVEL, LITTLE SILT, TRACE CLAY, SS-2 CONTAINS CONCRETE FRAGMENTS, DRY (FILL)		2	13 10 12	31	0	SS-1	-	-	-	-	-	-	-	-	-	-	-	A-3a (V)	<V>
		3	11 8 11	27	89	SS-2	-	15	26	42	13	4	NP	NP	NP	5	A-3a (0)	<V>	
	968.6	4	4 9 12	29	100	SS-3	-	1	1	1	89	8	NP	NP	NP	22	A-4b (8)	<V>	
MEDIUM DENSE, GRAY, SILT , TRACE CLAY, TRACE SAND, TRACE GRAVEL, CONTAINS TRACE IRON STAINING, WET		5	3 8 11	27	89	SS-4	-	-	-	-	-	-	-	-	-	22	A-4b (V)	<V>	
	965.6	6																<V>	
		7																<V>	
		EOB																<V>	

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: PLACED 0.5 BAG ASPHALT PATCH; SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:10 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6.15 2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / ASHBAUGH</u>	DRILL RIG: <u>CME 45B</u>	STATION / OFFSET: <u>58+92, 72' LT.</u>	EXPLORATION ID <u>B-026-0-18</u>
TYPE: <u>SUBGRADE</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>IR-277</u>	
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>971.4 (MSL)</u> EOB: <u>7.5 ft.</u>	PAGE 1 OF 1
START: <u>4/16/19</u> END: <u>4/16/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>84</u>	LAT / LONG: <u>41.035690, -81.568868</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTH	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL		
								GR	CS	FS	SI	CL	LL	PL	PI					
13.0" ASPHALT AND 5.0" BASE (DRILLERS DESCRIPTION)	971.4																	X		
	969.9	1																<>		
MEDIUM DENSE, BROWN AND GRAY, COARSE AND FINE SAND , LITTLE GRAVEL, LITTLE SILT, TRACE CLAY, MOIST TO WET		2	5	7	18	0	SS-1	-	-	-	-	-	-	-	-	-	-	A-3a (V)	<>	
		3	3	4	6	11	67	SS-2	-	14	22	43	14	7	NP	NP	NP	14	A-3a (0)	<>
		4	3	4	4	11	67	SS-2	-	14	22	43	14	7	NP	NP	NP	14	A-3a (0)	<>
		5	3	5	7	17	89	SS-3	-	17	27	38	12	6	NP	NP	NP	13	A-3a (0)	<>
		6	3	4	5	13	89	SS-4	-	-	-	-	-	-	-	-	-	15	A-3a (V)	<>
	963.9	7	4	5	13	89	SS-4	-	-	-	-	-	-	-	-	-	15	A-3a (V)	<>	
		EOB																		

NOTES: GROUNDWATER ENCOUNTERED AT 5.0' DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: PLACED 0.5 BAG ASPHALT PATCH; SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:10 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6.15 KENMORE\REIGNIT FILES\SUM-76-6.15 2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / J. HODGES</u>	DRILL RIG: <u>CME 55X</u>	STATION / OFFSET: <u>63+44, 55' LT.</u>	EXPLORATION ID <u>B-027-0-18</u>
TYPE: <u>ROADWAY</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>IR-277</u>	
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>969.8 (MSL)</u> EOB: <u>11.5 ft.</u>	PAGE 1 OF 1
START: <u>3/19/19</u> END: <u>3/19/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>85</u>	LAT / LONG: <u>41.035623, -81.567231</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTH	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL		
								GR	CS	FS	SI	CL	LL	PL	PI					
STIFF, BROWN WITH ORANGISH BROWN MOTTLES, SILT AND CLAY , SOME SAND, TRACE GRAVEL, CONTAINS ROOTS, MOIST	969.8																	<< < > >>		
	967.0	▼ 966.8	4	5	13	89	SS-1A	-	-	-	-	-	-	-	-	-	29	A-4a (V)	<< < > >>	
LOOSE TO MEDIUM DENSE, GRAY, COARSE AND FINE SAND , TRACE TO SOME GRAVEL, LITTLE SILT, TRACE CLAY, WET	962.8	W 964.8		3	3	9	67	SS-2	-	26	18	37	13	6	NP	NP	NP	16	A-3a (0)	<< < > >>
			3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3
VERY LOOSE TO MEDIUM DENSE, BROWN, GRAVEL AND STONE FRAGMENTS WITH SAND , TRACE TO LITTLE SILT, TRACE CLAY, CONTAINS TRACE ROOTS, STONE FRAGMENTS >1.0", WET	958.3		1	1	3	44	SS-3	-	-	-	-	-	-	-	-	-	-	18	A-1-b (V)	<< < > >>
			5	5	11	100	SS-4	-	-	-	-	-	-	-	-	-	-	18	A-1-b (V)	<< < > >>
EOB																				<< < > >>

NOTES: GROUNDWATER ENCOUNTERED AT 5.0' DURING DRILLING, 3.0' AFTER COMPLETION. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:10 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6-15 KENMORE\IGINT FILES\SUM-76-6-15 2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / J. HODGES</u>	DRILL RIG: <u>CME 55X</u>	STATION / OFFSET: <u>65+78, 65' RT.</u>	EXPLORATION ID <u>B-028-0-18</u>
TYPE: <u>ROADWAY</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>IR-277</u>	
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>972.9 (MSL)</u> EOB: <u>16.5 ft.</u>	PAGE 1 OF 1
START: <u>3/19/19</u> END: <u>3/19/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>85</u>	LAT / LONG: <u>41.035283, -81.566391</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTH	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL
								GR	CS	FS	SI	CL	LL	PL	PI			
MEDIUM DENSE, BROWN WITH ORANGISH BROWN MOTTLES, SANDY SILT , TRACE CLAY, TRACE GRAVEL, CONTAINS IRON STAINING, MOIST	972.9	1															<< < <	
		2															<< < <	
		3	3	10	27	100	SS-1	-	2	3	53	35	7	NP	NP	NP	16	A-4a (1)
	968.4	4																<< < <
VERY LOOSE TO LOOSE, BROWN, FINE SAND , TRACE SILT, TRACE COARSE SAND, TRACE CLAY, TRACE GRAVEL, CONTAINS IRON STAINING, WET		5	5	3	9	100	SS-2	-	-	-	-	-	-	-	-	-	26	A-3 (V)
		6																<< < <
		7																<< < <
		8	3	1	3	78	SS-3	-	1	4	86	6	3	NP	NP	NP	27	A-3 (0)
		9																<< < <
		10	1	1	4	78	SS-4	-	-	-	-	-	-	-	-	-	29	A-3 (V)
		11																<< < <
		12																<< < <
		13	1	1	3	100	SS-5	-	-	-	-	-	-	-	-	-	23	A-3 (V)
		14																<< < <
		15	1	2	6	100	SS-6	-	-	-	-	-	-	-	-	-	23	A-3 (V)
	956.4	16		2	2													<< < <
		EOB																<< < <

NOTES: GROUNDWATER ENCOUNTERED AT 6.0' DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:10 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6-15 KENMORE\GINT FILES\SUM-76-6-15 2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / ASHBAUGH</u>	DRILL RIG: <u>CME 55T</u>	STATION / OFFSET: <u>75+72, 61' RT.</u>	EXPLORATION ID <u>B-031-0-18</u>
TYPE: <u>EMBANKMENT</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>IR-277</u>	
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>976.1 (MSL)</u> EOB: <u>16.5 ft.</u>	PAGE 1 OF 1
START: <u>2/26/19</u> END: <u>2/26/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>78</u>	LAT / LONG: <u>41.035247, -81.562786</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTH	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL	
								GR	CS	FS	SI	CL	LL	PL	PI				
VERY STIFF, BROWN MOTTLED WITH ORANGISH BROWN AND GRAY, SILT , SOME SAND, LITTLE CLAY, TRACE GRAVEL, CONTAINS TRACE ROOTS AND IRON STAINING, DAMP (FILL)	976.1	1	3	4	10	100	SS-1	3.75	0	2	29	57	12	22	19	3	18	A-4b (7)	<<V>>
LOOSE, BROWN, COARSE AND FINE SAND , TRACE SILT, TRACE CLAY, TRACE GRAVEL, CONTAINS TRACE IRON STAINING, WET (FILL)	974.1	2	4	3	8	100	SS-2	-	5	7	76	7	5	NP	NP	NP	19	A-3a (0)	<<V>>
VERY LOOSE, ORANGISH BROWN, FINE SAND , TRACE TO LITTLE SILT, TRACE COARSE SAND, TRACE CLAY, TRACE GRAVEL, CONTAINS TRACE IRON STAINING, WET (FILL)	971.6	3	1	1	3	100	SS-3	-	-	-	-	-	-	-	-	-	24	A-3 (V)	<<V>>
		4	WOH	WOH	0	100	SS-4	-	3	5	82	7	3	NP	NP	NP	26	A-3 (0)	<<V>>
		5	WOH	WOH	0	67	SS-5	-	-	-	-	-	-	-	-	-	27	A-3 (V)	<<V>>
		6	WOH	WOH	0	100	SS-6	-	-	-	-	-	-	-	-	-	25	A-3 (V)	<<V>>
		7	WOH	WOH	0	100	SS-7	-	-	-	-	-	-	-	-	-	30	A-3 (V)	<<V>>
	959.6	16	WOH	WOH	0	100	SS-7	-	-	-	-	-	-	-	-	-	30	A-3 (V)	<<V>>

EOB


NOTES: GROUNDWATER ENCOUNTERED AT 6.0' DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:10 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6.15 2.GPJ


PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / ASHBAUGH</u>	DRILL RIG: <u>CME 55T</u>	STATION / OFFSET: <u>77+74, 58' RT.</u>	EXPLORATION ID <u>B-032-0-18</u>
TYPE: <u>ROADWAY</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>IR-277</u>	
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>976.8 (MSL)</u> EOB: <u>31.5 ft.</u>	PAGE 1 OF 2
START: <u>2/27/19</u> END: <u>2/27/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>78</u>	LAT / LONG: <u>41.035245, -81.562054</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTH	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL	
								GR	CS	FS	SI	CL	LL	PL	PI				
VERY LOOSE TO LOOSE, DARK BROWN AND BROWN CHANGING TO BROWN, COARSE AND FINE SAND , TRACE TO LITTLE GRAVEL, TRACE TO LITTLE SILT, TRACE CLAY, SS-1 CONTAINS ROOT HAIRS, DAMP TO WET @12.5' TO 14.0'; CONTAINS TRACE ROOT HAIRS @22.5' TO 27.0'; CHANGES TO BROWNISH GRAY	976.8		2					16	17	53	10	4	NP	NP	NP	10	A-3a (0)	<><><>	
		1	3	9	100	SS-1	-												<><><>
		2																	<><><>
		3	2	3	8	100	SS-2	-	-	-	-	-	-	-	-	-	15	A-3a (V)	<><><>
		4																	<><><>
		5	2	2	5	100	SS-3	-	-	-	-	-	-	-	-	-	17	A-3a (V)	<><><>
		6																	<><><>
		7																	<><><>
		8	1	WOH	0	67	SS-4	-	-	-	-	-	-	-	-	-	19	A-3a (V)	<><><>
		9		WOH															<><><>
		10		WOH															<><><>
		11		WOH	0	100	SS-5	-	9	17	59	9	6	NP	NP	NP	21	A-3a (0)	<><><>
	12																	<><><>	
	13		WOR	0	33	SS-6	-	-	-	-	-	-	-	-	-	19	A-3a (V)	<><><>	
	14		WOR															<><><>	
	15		WOR															<><><>	
	16		WOH	1	3	100	SS-7	-	-	-	-	-	-	-	-	20	A-3a (V)	<><><>	
	17																	<><><>	
	18		1	WOH	0	100	SS-8	-	-	-	-	-	-	-	-	19	A-3a (V)	<><><>	
	19			WOH														<><><>	
	20			WOR														<><><>	
	21		WOR	0	100	SS-9	-	-	-	-	-	-	-	-	-	17	A-3a (V)	<><><>	
	22			WOR														<><><>	
	23		WOH	0	100	SS-10	-	-	-	-	-	-	-	-	-	20	A-3a (V)	<><><>	
	24			WOH														<><><>	
	25			WOR														<><><>	
	26		WOR	0	100	SS-11	-	-	-	-	-	-	-	-	-	20	A-3a (V)	<><><>	
	27	949.8																<><><>	
VERY SOFT TO SOFT, GRAY, SILT , SOME CLAY, TRACE SAND, TRACE GRAVEL, SLIGHTLY ORGANIC, WET	947.3																	<><><>	
			WOH	2	5	100	SS-12	0.25	0	0	10	59	31	27	19	8	26	A-4b (8)	<><><>
																		<><><>	
																		<><><>	

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:10 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6.15 2.GPJ

PID: 100713	SFN: _____	PROJECT: SUM-76-06.15	STATION / OFFSET: 77+74, 58' RT.	START: 2/27/19	END: 2/27/19	PG 2 OF 2	B-032-0-18													
MATERIAL DESCRIPTION AND NOTES		ELEV.	DEPTHS		SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL
VERY LOOSE, GRAY, COARSE AND FINE SAND , TRACE SILT, TRACE CLAY, TRACE GRAVEL, WET (<i>continued</i>) 		946.8								GR	CS	FS	SI	CL	LL	PL	PI			
		945.3	31	1	3	100	SS-13	-	-	-	-	-	-	-	-	-	-	25	A-3a (V)	<L> >L> <V> >V>

EOB



NOTES: GROUNDWATER ENCOUNTERED AT 7.0' DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:10 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6-15 2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / J. HODGES</u>	DRILL RIG: <u>CME 55X</u>	STATION / OFFSET: <u>81+72, 68' RT.</u>	EXPLORATION ID <u>B-033-0-18</u>
TYPE: <u>ROADWAY</u>	SAMPLING FIRM / LOGGER: <u>NEAS / J.HODGES</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>IR-277</u>	
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>976.8 (MSL)</u> EOB: <u>16.5 ft.</u>	PAGE 1 OF 1
START: <u>3/12/19</u> END: <u>3/12/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>85</u>	LAT / LONG: <u>41.035201, -81.560613</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTH	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL
								GR	CS	FS	SI	CL	LL	PL	PI			
LOOSE, BROWN, COARSE AND FINE SAND , SOME SILT, LITTLE GRAVEL, TRACE CLAY, CONTAINS TRACE ROOTS, MOIST	976.8	1																<< < <
		2																<< < <
		3	2	9	56	SS-1	-	-	-	-	-	-	-	-	19	A-3a (V)	<< < <	
VERY SOFT TO SOFT, DARK BROWN, SANDY SILT , TRACE CLAY, TRACE GRAVEL, MODERATELY ORGANIC, CONTAINS ROOTS, WET	972.3	4	2	4														<< < <
		5	1	4	67	SS-2	0.50	3	8	45	35	9	NP	NP	NP	40	A-4a (2)	<< < <
		6	2	1														<< < <
		7																<< < <
		8	WOH	0	22	SS-3	0.00	-	-	-	-	-	-	-	-	40	A-4a (V)	<< < <
VERY LOOSE, BROWN, COARSE AND FINE SAND , TRACE SILT, TRACE CLAY, TRACE GRAVEL, WET	967.3	9	WOH															<< < <
		10	WOH	0	50	SS-4	-	3	17	65	9	6	NP	NP	NP	18	A-3a (0)	<< < <
		11	WOH															<< < <
		12	WOH															<< < <
	960.3	13	WOH	0	3	SS-5	-	-	-	-	-	-	-	-	14	A-3a (V)	<< < <	
		14	WOH															<< < <
		15	WOH															<< < <
		16	WOH	0	11	SS-6	-	-	-	-	-	-	-	-	19	A-3a (V)	<< < <	

EOB

NOTES: GROUNDWATER ENCOUNTERED AT 10.0' DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:11 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6.15 KENMORE\GINT FILES\SUM-76-6.15 2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / J. HODGES</u>	DRILL RIG: <u>CME 55X</u>	STATION / OFFSET: <u>83+65, 98' RT.</u>	EXPLORATION ID <u>B-034-0-18</u>
TYPE: <u>EMBANKMENT</u>	SAMPLING FIRM / LOGGER: <u>NEAS / J.HODGES</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>IR-277</u>	PAGE 1 OF 1
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>972.3 (MSL)</u> EOB: <u>11.5 ft.</u>	
START: <u>3/12/19</u> END: <u>3/12/19</u>	SAMPLING METHOD: <u>SPT / ST</u>	ENERGY RATIO (%): <u>85</u>	LAT / LONG: <u>41.035109, -81.559916</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL	
								GR	CS	FS	SI	CL	LL	PL	PI				
VERY SOFT, BLACK WITH BROWN, ORGANIC SILT , SOME TO "AND" SAND, LITTLE CLAY, TRACE GRAVEL, HIGHLY ORGANIC, CONTAINS ROOTS, WET @5.0' TO 5.5'; 28.4% ORGANIC CONTENT @5.0' TO 5.5'; Qu = 257 PSF	972.3	0																<V>	
		1																	<V>
		2																	<V>
		3	1	1	3	33	SS-1	0.00	2	5	38	41	14	NP	NP	NP	41	A-8a (4)	<V>
		4																	<V>
		5																	<V>
		6				40	ST-2	0.25	1	4	26	53	16	NP	NP	NP	26	A-8a (7)	<V>
	7																	<V>	
MEDIUM DENSE, GRAY, COARSE AND FINE SAND , LITTLE SILT, TRACE CLAY, TRACE GRAVEL, PETROLIFEROUS ODOR, WET	964.3	8	WOH	4	16	50	SS-3A	0.00	-	-	-	-	-	-	-	-	28	A-8a (V)	<V>
		9		7			SS-3B	-	-	-	-	-	-	-	-	-	34	A-3a (V)	<V>
		10																	<V>
		11	2	5	11	100	SS-4	-	2	6	77	11	4	NP	NP	NP	30	A-3a (0)	<V>
	960.8	EOB		3														<V>	

NOTES: GROUNDWATER ENCOUNTERED AT SURFACE. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: SHOVELED SOIL CUTTINGS

Organic Content in Soils by Loss on Ignition (AASHTO T267)

Date of Test: 4/9/2019 Technician: L. Rosenbeck

Project Name: SUM-76-6.15 Kenmore

Boring Number:	B-034-0-18				
Sample Number:	ST-2				
Depth:	5.0-7.0'				
Initial -#10 sample weight:	104.5g				

Moisture Content (if assigned):

Container ID:	HP-9				
Container Empty:	117.48				
Container with Wet Soil:	221.98				
Container with Dry Soil:	200.28				
MC%:	26				

or

MC from Hydro sheet:					
----------------------	--	--	--	--	--

Organic Content 455+-10°C:

Crucible ID:	A				
Crucible Wt:	62.30				
Crucible and Soil before:	92.23				
Crucible and Soil After:	83.73				
% Organic Content:	28.4%				

Unconfined Compressive Strength of Cohesive Soil (ASTM D2166)

(Project: SUM-76-6.15 Kenmore, Boring Location: B-034-0-18, ST-2, Depth: 5.0 - 5.5ft)

Tested Date: 4/8/2019

Specimen Properties


Average Dia., D_{avg} (in):	2.89
Average Height, H_{avg} (in):	5.74
Area, A (in ²):	6.55
Volume, V (in ³):	37.58
Wet Mass of Specimen (lb):	1.6
Moisture Content (%):	26.2
Dry Mass of Specimen (lb):	1.3
Wet Unit Weight, γ (lb/ft ³):	73.7
Dry Unit Weight, γ_d (lb/ft ³):	58.4

Final Specimen Figure



Results

Unconfined Compressive Strength (psf):	257
Strain (%):	10.0



Notes: Very soft, black with brown, ORGANIC SILT, some sand, little clay, trace gravel, wet. Contains 28.4% organic content.

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:11 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6.15-2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / J. HODGES</u>	DRILL RIG: <u>CME 55X</u>	STATION / OFFSET: <u>85+67, 68' RT.</u>	EXPLORATION ID <u>B-035-0-18</u>
TYPE: <u>ROADWAY</u>	SAMPLING FIRM / LOGGER: <u>NEAS / J.HODGES</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>IR-277</u>	PAGE 1 OF 1
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>978.6 (MSL)</u> EOB: <u>11.5 ft.</u>	
START: <u>3/11/19</u> END: <u>3/11/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>85</u>	LAT / LONG: <u>41.035183, -81.559182</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL	
								GR	CS	FS	SI	CL	LL	PL	PI				
MEDIUM DENSE, GRAY MOTTLED WITH ORANGISH BROWN, SILT , LITTLE SAND, LITTLE CLAY, TRACE GRAVEL, CONTAINS TRACE ROOT HAIRS, WET	978.6	1															<V>		
		2															<V>		
		3	3	4	11	100	SS-1	-	1	3	14	71	11	NP	NP	NP	24	A-4b (8)	<V>
STIFF TO VERY STIFF, GRAY MOTTLED WITH DARK BROWN AND ORANGISH BROWN, SANDY SILT , LITTLE CLAY, TRACE GRAVEL, CONTAINS TRACE ROOT HAIRS, DAMP TO WET	974.1	4															<V>		
		5	2	2	6	44	SS-2	2.00	3	5	36	44	12	25	21	4	20	A-4a (4)	<V>
		6																<V>	
MEDIUM DENSE, GRAY, COARSE AND FINE SAND , LITTLE SILT, TRACE CLAY, WET	969.1	7															<V>		
		8	1	2	4	56	SS-3	1.25	-	-	-	-	-	-	-	-	24	A-4a (V)	<V>
		9																<V>	
MEDIUM DENSE, GRAY, COARSE AND FINE SAND , LITTLE SILT, TRACE CLAY, WET	967.1	10	2	5	17	100	SS-4	-	0	0	75	15	10	NP	NP	NP	16	A-3a (0)	<V>
		11																<V>	

EOB

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:11 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6.15-2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / J. HODGES</u>	DRILL RIG: <u>CME 55X</u>	STATION / OFFSET: <u>89+69, 67' RT.</u>	EXPLORATION ID <u>B-036-0-18</u>
TYPE: <u>ROADWAY</u>	SAMPLING FIRM / LOGGER: <u>NEAS / J.HODGES</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>IR-277</u>	PAGE 1 OF 1
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>981.5 (MSL)</u> EOB: <u>11.5 ft.</u>	
START: <u>3/11/19</u> END: <u>3/11/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>85</u>	LAT / LONG: <u>41.035165, -81.557726</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			ODOT CLASS (GI)	BACK FILL		
								GR	CS	FS	SI	CL	LL	PL	PI			WC	
LOOSE TO MEDIUM DENSE, LIGHT BROWN BECOMING ORANGISH BROWN MOTTLED WITH GRAY, SILT , LITTLE CLAY, TRACE SAND, TRACE GRAVEL, CONTAINS TRACE IRON STAINING, WET	981.5	1															<V>		
		2																<V>	
		3	2	5	14	67	SS-1	-	1	0	5	81	13	NP	NP	NP	29	A-4b (8)	<V>
		4																	<V>
		5	1	2	9	100	SS-2	-	0	1	8	79	12	NP	NP	NP	27	A-4b (8)	<V>
MEDIUM DENSE, BROWN, COARSE AND FINE SAND , TRACE TO LITTLE SILT, TRACE CLAY, TRACE GRAVEL, DAMP	974.5	6																<V>	
		7																<V>	
		8	1	5	14	100	SS-3	-	-	-	-	-	-	-	-	-	11	A-3a (V)	<V>
		9																	<V>
VERY STIFF, BROWN MOTTLED WITH ORANGISH BROWN, SANDY SILT , SOME CLAY, TRACE GRAVEL, MOIST	970.3 970.0	10	1	4	14	100	SS-4A	-	-	-	-	-	-	-	-	-	7	A-3a (V)	<V>
		11		6			SS-4B	3.00	-	-	-	-	-	-	-	-	21	A-4a (V)	<V>

EOB

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:11 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6.15-2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / J. HODGES</u>	DRILL RIG: <u>CME 55X</u>	STATION / OFFSET: <u>93+64, 62' RT.</u>	EXPLORATION ID <u>B-037-0-18</u>
TYPE: <u>ROADWAY</u>	SAMPLING FIRM / LOGGER: <u>NEAS / J.HODGES</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>IR-277</u>	PAGE 1 OF 1
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>983.3 (MSL)</u> EOB: <u>11.5 ft.</u>	
START: <u>3/12/19</u> END: <u>3/12/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>85</u>	LAT / LONG: <u>41.035162, -81.556293</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTH	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL
								GR	CS	FS	SI	CL	LL	PL	PI			
DENSE, GRAY, SILT , LITTLE CLAY, TRACE SAND, TRACE GRAVEL, CONTAINS TRACE IRON STAINING, WET	983.3	1															<V>	
		2															<V>	
		3	6	12	35	100	SS-1	-	0	0	4	79	17	NP	NP	NP	19	A-4b (8)
MEDIUM DENSE, BROWN, COARSE AND FINE SAND , LITTLE GRAVEL, LITTLE SILT, TRACE CLAY, CONTAINS TRACE IRON STAINING, DAMP	978.8	4															<V>	
	977.3	5	3	5	14	100	SS-2A	-	-	-	-	-	-	-	-	-	8	A-3a (V)
MEDIUM DENSE, BROWN, SANDY SILT , TRACE CLAY, TRACE GRAVEL, CONTAINS TRACE IRON STAINING, MOIST		6					SS-2B	-	-	-	-	-	-	-	-	-	20	A-4a (V)
		7																<V>
		8	4	6	20	100	SS-3	-	4	6	31	49	10	NP	NP	NP	17	A-4a (5)
		9																<V>
		10	3	8	30	100	SS-4	-	-	-	-	-	-	-	-	-	18	A-4a (V)
	971.8	11	3	8	13												<V>	

EOB

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:11 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6.15-2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / ASHBAUGH</u>	DRILL RIG: <u>CME 55T</u>	STATION / OFFSET: <u>219+40, 45' RT.</u>	EXPLORATION ID <u>B-039-0-18</u>
TYPE: <u>SUBGRADE</u>	SAMPLING FIRM / LOGGER: <u>NEAS / ASHBAUGH</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>IR-77 & IR-76</u>	
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>997.5 (MSL)</u> EOB: <u>7.5 ft.</u>	PAGE 1 OF 1
START: <u>2/21/19</u> END: <u>2/21/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>78</u>	LAT / LONG: <u>41.060352, -81.567580</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			ODOT CLASS (GI)	BACK FILL			
								GR	CS	FS	SI	CL	LL	PL	PI			WC		
9.0" CONCRETE (DRILLERS DESCRIPTION)	997.5																			
VERY STIFF TO HARD, BROWN, SANDY SILT , LITTLE TO SOME CLAY, TRACE TO SOME GRAVEL, CONTAINS TRACE IRON STAINING, DAMP	996.7	1															X			
		2	4	7	22	67	SS-1	4.5+	26	12	25	21	16	23	15	8	9	A-4a (0)	<><><>	
		3	5	7	10														<><><>	
		4	7	8	20	56	SS-2	4.5+	-	-	-	-	-	-	-	-	11	A-4a (V)	<><><>	
		5	4	7	9	21	67	SS-3	4.00	7	12	25	32	24	27	17	10	14	A-4a (4)	<><><>
		6	3	4	9															<><><>
		990.0	7	4	9	17	89	SS-4	3.50	-	-	-	-	-	-	-	-	13	A-4a (V)	<><><>
		EOB																		

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: PLACED 0.5 BAG ASPHALT PATCH; SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:11 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6.15-2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / ASHBAUGH</u>	DRILL RIG: <u>CME 45B</u>	STATION / OFFSET: <u>223+88, 37' LT.</u>	EXPLORATION ID <u>B-040-0-18</u>
TYPE: <u>SUBGRADE</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>IR-77 & IR-76</u>	PAGE 1 OF 1
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>1007.9 (MSL)</u> EOB: <u>7.5 ft.</u>	
START: <u>4/9/19</u> END: <u>4/9/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>84</u>	LAT / LONG: <u>41.060208, -81.565940</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTH	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL	
								GR	CS	FS	SI	CL	LL	PL	PI				
13.0" CONCRETE (DRILLERS DESCRIPTION)	1007.9																		
13.0" CONCRETE (DRILLERS DESCRIPTION)	1006.8																X		
MEDIUM DENSE, LIGHT BROWN AND BROWN, SANDY SILT , LITTLE CLAY, TRACE GRAVEL, DAMP	1004.9	1	10													9	A-4a (V)	< >	
DENSE TO VERY DENSE, LIGHT BROWN, COARSE AND FINE SAND , LITTLE SILT, LITTLE CLAY, TRACE GRAVEL, CONTAINS TRACE IRON STAINING, DAMP	1001.9	2	9	28	6	SS-1	-	-	-	-	-	-	-	-	-	11		< >	
	1000.4	3	9	42	100	SS-2	-	5	4	58	19	14	NP	NP	NP	16	8	A-3a (0)	< >
	1000.4	4	11	105	100	SS-3	-	-	-	-	-	-	-	-	-	44	8	A-3a (V)	< >
VERY DENSE, GRAY, SANDY SILT , LITTLE CLAY, TRACE GRAVEL, DAMP	1000.4	5	13	98	100	SS-4	-	4	4	48	26	18	NP	NP	NP	29	7	A-4a (2)	< >
	1000.4	6	13	98	100	SS-4	-	4	4	48	26	18	NP	NP	NP	41	7	A-4a (2)	< >
	1000.4	7	13	98	100	SS-4	-	4	4	48	26	18	NP	NP	NP	41	7	A-4a (2)	< >

EOB

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: PLACED 0.5 BAG ASPHALT PATCH; SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:11 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6-15 KENMORE\GINT FILES\SUM-76-6-15 2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / ASHBAUGH</u>	DRILL RIG: <u>CME 45B</u>	STATION / OFFSET: <u>227+78, 10' LT.</u>	EXPLORATION ID <u>B-041-0-18</u>
TYPE: <u>SUBGRADE</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>IR-77 & IR-76</u>	PAGE 1 OF 1
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>1022.7 (MSL)</u> EOB: <u>6.1 ft.</u>	
START: <u>4/11/19</u> END: <u>4/11/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>84</u>	LAT / LONG: <u>41.059975, -81.564569</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG				ODOT CLASS (GI)	BACK FILL
								GR	CS	FS	SI	CL	LL	PL	PI	WC		
14.0" ASPHALT AND 4.0" BASE (DRILLERS DESCRIPTION)	1022.7																	
MEDIUM DENSE, BROWN AND GRAY, STONE FRAGMENTS WITH SAND , TRACE SILT, TRACE CLAY, DAMP	1021.2	1																
SANDSTONE, BROWN AND GRAY, HIGHLY WEATHERED, STRONG, FRIABLE.	1019.7	2	8	29	22	SS-1	-	-	-	-	-	-	-	-	-	5	A-1-b (V)	
		3	11	-	100	SS-2	-	-	-	-	-	-	-	-	-	-	Rock (V)	
		4	50/1"	-	100	SS-3	-	-	-	-	-	-	-	-	-	-	Rock (V)	
		5	50/1"	-	100	SS-3	-	-	-	-	-	-	-	-	-	-	Rock (V)	
@6.0' TO 6.1'; SS-4 NO RECOVERY	1016.6	6	50/1"	-	0	SS-4	-	-	-	-	-	-	-	-	-	-	Rock (V)	
		EOB																

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: PLACED 0.5 BAG ASPHALT PATCH; SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:11 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6.15-2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / ASHBAUGH</u>	DRILL RIG: <u>CME 45B</u>	STATION / OFFSET: <u>231+81, 41' LT.</u>	EXPLORATION ID <u>B-042-0-18</u>
TYPE: <u>SUBGRADE</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>IR-77 & IR-76</u>	
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>1036.4 (MSL)</u> EOB: <u>6.5 ft.</u>	PAGE 1 OF 1
START: <u>4/9/19</u> END: <u>4/9/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>84</u>	LAT / LONG: <u>41.060028, -81.563111</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTH	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			ODOT CLASS (GI)	BACK FILL
								GR	CS	FS	SI	CL	LL	PL	PI		
5.0" ASPHALT AND 13.0" BASE (DRILLERS DESCRIPTION)	1036.4																
HARD, BROWN MOTTLED WITH GRAY, SANDY SILT , SOME GRAVEL AND STONE FRAGMENTS, LITTLE CLAY, DAMP	1034.9	1															
VERY DENSE, LIGHT TAN, STONE FRAGMENTS WITH SAND , TRACE SILT, TRACE CLAY, DAMP	1033.4	2	25 30 31	85	89	SS-1	4.5+	28	18	15	23	16	23	16	7	9	A-4a (1)
HARD, GRAY, SANDY SILT , SOME CLAY, LITTLE GRAVEL AND STONE FRAGMENTS, DAMP	1031.9	3	5 44 19	88	33	SS-2	-	-	-	-	-	-	-	-	-	4	A-1-b (V)
		4	20 18 19	52	100	SS-3	4.5+	13	9	17	36	25	23	15	8	10	A-4a (5)
	1029.9	5	50	-	100	SS-4	4.5+	-	-	-	-	-	-	-	-	7	A-4a (V)
		6															

EOB

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: PLACED 0.5 BAG ASPHALT PATCH; SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:11 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6.15 2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / ASHBAUGH</u>	DRILL RIG: <u>CME 45B</u>	STATION / OFFSET: <u>234+79, 43' LT.</u>	EXPLORATION ID <u>B-043-0-18</u>
TYPE: <u>SUBGRADE</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>IR-77 & IR-76</u>	PAGE 1 OF 1
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>1047.6 (MSL)</u> EOB: <u>7.5 ft.</u>	
START: <u>4/9/19</u> END: <u>4/9/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>84</u>	LAT / LONG: <u>41.060030, -81.562031</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTH	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL	
								GR	CS	FS	SI	CL	LL	PL	PI				
5.0" ASPHALT AND 13.0" CONCRETE (DRILLERS DESCRIPTION)	1047.6																	X	
VERY DENSE, BROWN, GRAVEL WITH SAND AND SILT , LITTLE CLAY, CONTAINS TRACE IRON STAINING, DAMP	1046.1	1																<V>	
HARD, BROWN MOTTLED WITH ORANGISH BROWN BECOMING GRAY, SANDY SILT , SOME CLAY, LITTLE GRAVEL, CONTAINS TRACE IRON STAINING, DAMP	1044.6	2	31	95	67	SS-1	-	40	16	15	17	12	23	17	6	10	A-2-4 (0)	<V>	
		3	2	22	100	SS-2	4.5+	14	14	19	31	22	25	18	7	11	A-4a (4)	<V>	
			4	18	95	100	SS-3	4.5+	-	-	-	-	-	-	-	-	12	A-4a (V)	<V>
			5	29	95	100	SS-3	4.5+	-	-	-	-	-	-	-	-	12	A-4a (V)	<V>
			6	13	60	100	SS-4	4.5+	-	-	-	-	-	-	-	-	11	A-4a (V)	<V>
	1040.1	7	20	60	100	SS-4	4.5+	-	-	-	-	-	-	-	-	11	A-4a (V)	<V>	
		EOB	23															<V>	

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: PLACED 0.5 BAG ASPHALT PATCH; SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT. - 7/29/19 09:11 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6.15-2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / ASHBAUGH</u>	DRILL RIG: <u>CME 55T</u>	STATION / OFFSET: <u>244+88, 54' LT.</u>	EXPLORATION ID <u>B-045-1-18</u>
TYPE: <u>ROADWAY</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>IR-77 & IR-76</u>	
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>1067.1 (MSL)</u> EOB: <u>6.7 ft.</u>	PAGE 1 OF 1
START: <u>4/17/19</u> END: <u>4/17/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>78</u>	LAT / LONG: <u>41.060049, -81.558373</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			ODOT CLASS (GI)	BACK FILL		
								GR	CS	FS	SI	CL	LL	PL	PI			WC	
2.0" ASPHALT AND 13.0" CONCRETE AND 3.0" BASE (DRILLERS DESCRIPTION)	1067.1																		
SHALE, DARK GRAY, SEVERELY WEATHERED, VERY WEAK TO WEAK, SILTY, FISSILE.	1065.6	TR	1																
			2	10	40	100	SS-1	-	-	-	-	-	-	-	-	-	-	Rock (V)	
			3	5	22	60	89	SS-2	-	-	-	-	-	-	-	-	-	Rock (V)	
			4	5	24														
			5	5	50	-	100	SS-3	-	-	-	-	-	-	-	-	-	-	Rock (V)
	1060.4	EOB	6	15	-	100	SS-4	-	-	-	-	-	-	-	-	-	-	Rock (V)	

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: PLACED 0.5 BAG ASPHALT PATCH; SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:11 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6-15 KENMORE\GINT FILES\SUM-76-6-15 2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / ASHBAUGH</u>	DRILL RIG: <u>CME 55T</u>	STATION / OFFSET: <u>251+65, 53' RT.</u>	EXPLORATION ID <u>B-047-0-18</u>
TYPE: <u>ROADWAY</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>IR-77 & IR-76</u>	
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>1063.6 (MSL)</u> EOB: <u>10.4 ft.</u>	PAGE 1 OF 1
START: <u>4/8/19</u> END: <u>4/8/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>78</u>	LAT / LONG: <u>41.059884, -81.555900</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG				ODOT CLASS (GI)	BACK FILL	
								GR	CS	FS	SI	CL	LL	PL	PI	WC			
6.0" ASPHALT AND 12.0" BASE (DRILLERS DESCRIPTION)	1063.6																		
HARD, GRAY, SANDY SILT , LITTLE TO SOME CLAY, LITTLE GRAVEL AND STONE FRAGMENTS, CONTAINS TRACE IRON STAINING, DAMP	1062.1	1																	<>
		2																	<>
		3	12	39	100	SS-1	4.5+	11	11	23	33	22	21	15	6	9	A-4a (4)		<>
		4	15	15															<>
VERY DENSE, LIGHT GRAY, STONE FRAGMENTS WITH SAND , TRACE SILT, TRACE CLAY, DAMP	1058.2	5	8	57	100	SS-2A	4.5+	18	11	23	28	20	20	15	5	8	A-4a (3)		<>
	1056.6	6	27	17		SS-2B	-	-	-	-	-	-	-	-	-	5	A-1-b (V)		<>
SHALE , GRAY, HIGHLY WEATHERED, VERY WEAK TO WEAK.	1053.2	7																	<>
		8	13	-	100	SS-3	-	-	-	-	-	-	-	-	-	-	Rock (V)		<>
		9	50/3"																<>
	10	EOB	50/5"	-	100	SS-4	-	-	-	-	-	-	-	-	-	-	Rock (V)		<>

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:11 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6-15 KENMORE\GINT FILES\SUM-76-6-15 2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / ASHBAUGH</u>	DRILL RIG: <u>CME 55T</u>	STATION / OFFSET: <u>256+17, 70' RT.</u>	EXPLORATION ID <u>B-048-0-18</u>
TYPE: <u>ROADWAY</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>IR-77 & IR-76</u>	
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>1050.6 (MSL)</u> EOB: <u>10.8 ft.</u>	PAGE 1 OF 1
START: <u>4/8/19</u> END: <u>4/8/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>78</u>	LAT / LONG: <u>41.060077, -81.554258</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG				ODOT CLASS (GI)	BACK FILL
								GR	CS	FS	SI	CL	LL	PL	PI	WC		
HARD, BROWN, SANDY SILT , LITTLE CLAY, LITTLE GRAVEL AND STONE FRAGMENTS, DAMP	1050.6		2															
			4	10	67	SS-1	4.5+	14	21	17	31	17	23	17	6	11	A-4a (3)	< > < > < >
SHALE, GRAY, HIGHLY WEATHERED, VERY WEAK, FISSILE.	1048.1	TR	12															
			36	109	100	SS-2	-	-	-	-	-	-	-	-	-	-	Rock (V)	< > < > < >
			48															
			22															
			50/4"	-	100	SS-3	-	-	-	-	-	-	-	-	-	-	Rock (V)	< > < > < >
			22	73	100	SS-4	-	-	-	-	-	-	-	-	-	-	Rock (V)	< > < > < >
			25															
			31															
	1039.8	EOB	29															
			50/4"	-	100	SS-5	-	-	-	-	-	-	-	-	-	-	Rock (V)	< > < > < >

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:11 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6.15 2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / ASHBAUGH</u>	DRILL RIG: <u>CME 45B</u>	STATION / OFFSET: <u>260+50, 10' RT.</u>	EXPLORATION ID <u>B-049-0-18</u>
TYPE: <u>SUBGRADE</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>IR-77 & IR-76</u>	PAGE 1 OF 1
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>1035.1 (MSL)</u> EOB: <u>7.5 ft.</u>	
START: <u>4/11/19</u> END: <u>4/11/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>84</u>	LAT / LONG: <u>41.060544, -81.552909</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL															
								GR	CS	FS	SI	CL	LL	PL	PI																		
14.0" ASPHALT AND 4.0" BASE (DRILLERS DESCRIPTION)	1035.1																1		X														
VERY STIFF TO HARD, GRAY, SANDY SILT , LITTLE TO SOME CLAY, LITTLE GRAVEL, DAMP	1033.6		4														2	7	21	67	SS-1	4.5+	18	11	15	35	21	23	16	7	10	A-4a (4)	<><><>
			3	4													3	8			SS-2	4.5+	19	10	13	38	20	24	17	7	10	A-4a (5)	<><><>
			4	12	25	100	SS-2	4.5+	19	10	13	38	20	24	17	7	10	A-4a (5)	<><><>														
			5	3	5	15	89	SS-3	4.00	-	-	-	-	-	-	-	-	15	A-4a (V)	<><><>													
			6	5	6												6	6			SS-3	4.00	-	-	-	-	-	-	-	-	15	A-4a (V)	<><><>
			7	3	6	14	100	SS-4	3.75	-	-	-	-	-	-	-	-	13	A-4a (V)	<><><>													
		1027.6	EOB	6	4												7	4			SS-4	3.75	-	-	-	-	-	-	-	-	13	A-4a (V)	<><><>

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: PLACED 0.5 BAG ASPHALT PATCH; SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:11 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6-15 KENMORE\GINT FILES\SUM-76-6-15 2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / ASHBAUGH</u>	DRILL RIG: <u>CME 55T</u>	STATION / OFFSET: <u>263+62, 63' RT.</u>	EXPLORATION ID <u>B-050-0-18</u>
TYPE: <u>NOISE WALL</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>IR-77 & IR-76</u>	
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>1022.1 (MSL)</u> EOB: <u>20.1 ft.</u>	PAGE 1 OF 1
START: <u>4/8/19</u> END: <u>4/8/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>78</u>	LAT / LONG: <u>41.060686, -81.551665</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTH	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG				ODOT CLASS (GI)	BACK FILL	
								GR	CS	FS	SI	CL	LL	PL	PI	WC			
6.0" ASPHALT AND 18.0" BASE (DRILLERS DESCRIPTION)	1022.1	1																	
HARD, BROWN AND GRAY, SANDY SILT , LITTLE TO SOME CLAY, TRACE TO SOME GRAVEL, SS-1 CONTAINS TRACE PLASTIC FRAGMENTS, DAMP (FILL)	1020.1	2																	
		3	7	10	26	100	SS-1	4.5+	21	12	15	35	17	22	15	7	8	A-4a (3)	
		4																	
		5	5	6	7	17	100	SS-2	4.5+	6	11	15	44	24	27	18	9	14	A-4a (7)
		6																	
@7.5' TO 9.0'; SS-3 CONTAINS NO RECOVERY		7																	
		8	14	13	15	36	0	SS-3	-	-	-	-	-	-	-	-	-		
		9																	
@10.0' TO 11.5'; SS-4 CONTAINS BRICK FRAGMENTS, NO INTACT SOIL FOR HP READINGS		10																	
		11	14	16	16	42	39	SS-4	-	-	-	-	-	-	-	-	9	A-4a (V)	
	1010.1	12																	
VERY STIFF TO HARD, BROWN MOTTLED WITH ORANGISH BROWN, SANDY SILT , SOME CLAY, LITTLE TO SOME GRAVEL, CONTAINS IRON STAINING, DAMP		13	12	14	16	39	100	SS-5	4.25	-	-	-	-	-	-	-	15	A-4a (V)	
		14																	
		15	5	6	6	16	89	SS-6	2.75	-	-	-	-	-	-	-	15	A-4a (V)	
	1004.6	16																	
SANDSTONE , ORANGISH BROWN BECOMING GRAY, HIGHLY WEATHERED, WEAK.		17																	
		18	50/5"			20		SS-7	-	-	-	-	-	-	-	-	-	Rock (V)	
	1002.0	19																	
		20	50/1"			100		SS-8	-	-	-	-	-	-	-	-	-	Rock (V)	
	EOB																		

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT. - 7/29/19 09:11 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6-15 KENMORE\REIGNIT FILES\SUM-76-6-15 2.GPJ


PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / ASHBAUGH</u>	DRILL RIG: <u>CME 45B</u>	STATION / OFFSET: <u>10+73, 15' RT.</u>	EXPLORATION ID <u>B-051-0-18</u>
TYPE: <u>SUBGRADE</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>RAMP T</u>	PAGE 1 OF 1
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>1017.6 (MSL)</u> EOB: <u>7.5 ft.</u>	
START: <u>4/10/19</u> END: <u>4/10/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>84</u>	LAT / LONG: <u>41.059555, -81.568264</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			ODOT CLASS (GI)	BACK FILL	
								GR	CS	FS	SI	CL	LL	PL	PI			WC
8.0" ASPHALT AND 7.0" BASE (DRILLERS DESCRIPTION)	1017.6																	
MEDIUM STIFF TO HARD, BROWN MOTTLED WITH GRAY AND TRACE ORANGISH BROWN, SANDY SILT , LITTLE TO SOME CLAY, TRACE TO LITTLE GRAVEL, CONTAINS TRACE IRON STAINING, DAMP	1016.3	1																
		2	5	14	89	SS-1	4.5+	18	11	12	36	23	26	18	8	13	A-4a (5)	
		3	5	21	78	SS-2	4.5+	8	13	29	30	20	21	14	7	10	A-4a (3)	
		4	8	7														
		5	3	5	14	89	SS-3	3.75	-	-	-	-	-	-	-	-	11	A-4a (V)
		6	2	5	5													
		7	5	21	89	SS-4	1.00	-	-	-	-	-	-	-	-	-	14	A-4a (V)
	1010.1	EOB																

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: PLACED 0.5 BAG ASPHALT PATCH; SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:11 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6-15-2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / J. HODGES</u>	DRILL RIG: <u>CME 55X</u>	STATION / OFFSET: <u>8+07, 32' LT.</u>	EXPLORATION ID <u>B-052-0-18</u>
TYPE: <u>ROADWAY</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>RAMP T</u>	PAGE 1 OF 1
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>1003.7 (MSL)</u> EOB: <u>6.9 ft.</u>	
START: <u>3/25/19</u> END: <u>3/25/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>85</u>	LAT / LONG: <u>41.060278, -81.568502</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL
								GR	CS	FS	SI	CL	LL	PL	PI			
VERY DENSE, BROWN AND GRAY, GRAVEL AND STONE FRAGMENTS , SOME SAND, TRACE SILT, TRACE CLAY, CONTAINS CONCRETE FRAGMENTS, DAMP (FILL) 	1003.7																	
		1																<<V>>
		2																<<V>>
		3		7	24	62	100	SS-1	-	-	-	-	-	-	-	7	A-1-a (V)	<<V>>
		4			20													<<V>>
		5		4	37	85	56	SS-2	-	57	20	13	7	3	NP	NP	NP	7
@6.5' TO 6.9'; SS-3 STONE FRAGMENTS ARE CONCRETE	996.8	EOB	50/5"	-	-	100	SS-3	-	-	-	-	-	-	-	7	A-1-a (V)	<<V>>	

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:11 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6.15 KENMORE\GINT FILES\SUM-76-6.15 2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / ASHBAUGH</u>	DRILL RIG: <u>CME 45B</u>	STATION / OFFSET: <u>4+17, 30' LT.</u>	EXPLORATION ID <u>B-053-0-18</u>
TYPE: <u>SUBGRADE</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>RAMP T</u>	PAGE 1 OF 1
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>997.3 (MSL)</u> EOB: <u>7.5 ft.</u>	
START: <u>4/10/19</u> END: <u>4/10/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>84</u>	LAT / LONG: <u>41.061084, -81.569477</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			ODOT CLASS (GI)	BACK FILL		
								GR	CS	FS	SI	CL	LL	PL	PI			WC	
3" ASPHALT AND 10" CONCRETE (DRILLERS DESCRIPTION)	997.3																	X	
HARD, LIGHT BROWN BECOMING GRAYISH BROWN, SANDY SILT, SOME CLAY, LITTLE GRAVEL, DAMP	996.2	1																>>>	
		2	4	11	78	SS-1	4.5+	12	7	16	41	24	23	17	6	13	A-4a (6)	>>>	
		3	4	6	17	89	SS-2	4.5+	-	-	-	-	-	-	-	16	A-4a (V)	>>>	
		4	6	4	15	78	SS-3	4.5+	11	5	9	43	32	28	19	9	15	A-4a (8)	>>>
DENSE, LIGHT TAN AND BROWN, GRAVEL AND/OR STONE FRAGMENTS WITH SAND AND SILT, TRACE CLAY, DAMP	991.3	5	4	7	15	78	SS-3	4.5+	11	5	9	43	32	28	19	9	15	A-4a (8)	>>>
	989.8	6	4	15	36	78	SS-4	-	-	-	-	-	-	-	-	6	A-2-4 (V)	>>>	
		7	15	11														>>>	
		EOB																	

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: PLACED 0.5 BAG ASPHALT PATCH; SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:11 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6.15 KENMORE\GINT FILES\SUM-76-6.15 2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / ASHBAUGH</u>	DRILL RIG: <u>CME 45B</u>	STATION / OFFSET: <u>94+72, 25' RT.</u>	EXPLORATION ID <u>B-054-0-18</u>
TYPE: <u>SUBGRADE</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>IR - 76</u>	PAGE 1 OF 1
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>1016.2 (MSL)</u> EOB: <u>7.5 ft.</u>	
START: <u>4/10/19</u> END: <u>4/10/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>84</u>	LAT / LONG: <u>41.060211, -81.568035</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG				ODOT CLASS (GI)	BACK FILL
								GR	CS	FS	SI	CL	LL	PL	PI	WC		
14.0" ASPHALT (DRILLERS DESCRIPTION)	1016.2																	
HARD, BROWN MOTTLED WITH GRAY AND ORANGISH BROWN, SANDY SILT , SOME GRAVEL, LITTLE CLAY, CONTAINS IRON STAINING, DAMP	1015.0	1																
DENSE, LIGHT BROWN, GRAVEL AND STONE FRAGMENTS WITH SAND AND SILT , LITTLE CLAY, DAMP	1013.2	2	24	28	89	SS-1	4.5+	32	11	11	29	17	25	18	7	9	A-4a (2)	
MEDIUM DENSE, LIGHT BROWN, GRAVEL AND STONE FRAGMENTS WITH SAND , TRACE SILT, TRACE CLAY, DAMP	1011.7	3	12	38	78	SS-2	-	39	18	12	19	12	23	17	6	7	A-2-4 (0)	
HARD, BROWN AND GRAY, SANDY SILT , SOME CLAY, LITTLE GRAVEL AND STONE FRAGMENTS, CONTAINS TRACE WOOD FRAGMENTS AND IRON STAINING, DAMP	1009.3	4	13															
@4.5' TO 6.0'; SS-3 NO RECOVERY	1008.7	5	5	22	0	SS-3	-	-	-	-	-	-	-	-	-	-		
		6	7	9														
		7	5	16	48	78	SS-4A	-	-	-	-	-	-	-	-	-	2	A-1-b (V)
			18				SS-4B	4.5+	-	-	-	-	-	-	-	-	12	A-4a (V)

EOB

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: PLACED 0.5 BAG ASPHALT PATCH; SHOVELED SOIL CUTTINGS

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / J. HODGES</u>	DRILL RIG: <u>CME 55X</u>	STATION / OFFSET: <u>98+03, 78' RT.</u>	EXPLORATION ID <u>B-055-0-18</u>
TYPE: <u>EMBANKMENT</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>IR - 76</u>	
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>993.8 (MSL)</u> EOB: <u>6.6 ft.</u>	PAGE 1 OF 1
START: <u>3/22/19</u> END: <u>3/22/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>85</u>	LAT / LONG: <u>41.060960, -81.567593</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			ODOT CLASS (GI)	BACK FILL
								GR	CS	FS	SI	CL	LL	PL	PI		
MEDIUM STIFF TO VERY STIFF, BROWN, SILT AND CLAY, LITTLE SAND, LITTLE GRAVEL, CONTAINS IRON STAINING, MOIST	993.8	1															<V> >L>
		2															<V> >L>
		3	5														<V> >L>
		4	5	14	78	SS-1	1.00										<V> >L>
		5	3														<V> >L>
	987.3	6	6	21	100	SS-2	3.50										<V> >L>
SANDSTONE, GRAY, SLIGHTLY WEATHERED, VERY STRONG.	987.2	TR ₃	50/1"	-	100	SS-3	-										<V> >L>

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT. - 7/29/19 09:11 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6-15 KENMORE\GINT FILES\SUM-76-6-15 2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / ASHBAUGH</u>	DRILL RIG: <u>CME 45B</u>	STATION / OFFSET: <u>97+76, 30' RT.</u>	EXPLORATION ID <u>B-056-0-18</u>
TYPE: <u>SUBGRADE</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>IR - 76</u>	PAGE 1 OF 1
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>1013.8 (MSL)</u> EOB: <u>7.5 ft.</u>	
START: <u>4/10/19</u> END: <u>4/10/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>84</u>	LAT / LONG: <u>41.060971, -81.567787</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL
								GR	CS	FS	SI	CL	LL	PL	PI			
15.5" ASPHALT (DRILLERS DESCRIPTION)	1013.8																	
	1012.5	1																
LOOSE TO MEDIUM DENSE, BROWN MOTTLED WITH ORANGISH BROWN AND GRAY, COARSE AND FINE SAND , LITTLE SILT, LITTLE GRAVEL, LITTLE CLAY, CONTAINS IRON STAINING, DAMP		2	15															
		3	9	20	33	SS-1	-	-	-	-	-	-	-	-	-	8	A-3a (V)	
		4	4	11	56	SS-2	-	12	17	39	18	14	17	12	5	11	A-3a (0)	
		5	4	4														
	1007.8	6	1	6	78	SS-3	-	16	15	38	17	14	18	12	6	10	A-3a (0)	
STIFF, BROWN MOTTLED WITH ORANGISH BROWN, SILT AND CLAY , LITTLE SAND, TRACE GRAVEL, CONTAINS IRON STAINING, DAMP		7	1	4	78	SS-4	1.75	-	-	-	-	-	-	-	-	16	A-6a (V)	
	1006.3	EOB	2															

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: PLACED 0.5 BAG ASPHALT PATCH; SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT. - 7/29/19 09:11 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6.15-2.GPJ



PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / J. HODGES</u>	DRILL RIG: <u>CME 55X</u>	STATION / OFFSET: <u>102+30, 28' RT.</u>	EXPLORATION ID <u>B-057-0-18</u>
TYPE: <u>ROADWAY</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>IR - 76</u>	PAGE 1 OF 1
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>1011.9 (MSL)</u> EOB: <u>2.8 ft.</u>	
START: <u>3/22/19</u> END: <u>3/22/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>85</u>	LAT / LONG: <u>41.061635, -81.566566</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL
								GR	CS	FS	SI	CL	LL	PL	PI			
VERY DENSE, DARK BROWN, COARSE AND FINE SAND , SOME STONE FRAGMENTS, LITTLE SILT, TRACE CLAY, CONTAINS ROOTS AND TRACE IRON STAINING, DAMP	1011.9	1															<V> <L> <V> <L>	
SANDSTONE , GRAY, SLIGHTLY WEATHERED, MODERATELY STRONG.	1009.4 1009.1	2	4		44	SS-1A SS-1B	3.75 -	22 -	19 -	38 -	13 -	8 -	NP -	NP -	NP -	9 -	A-3a (0) Rock (V)	<V> <L> <V> <L>

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:11 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6-15 2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / J. HODGES</u>	DRILL RIG: <u>CME 55X</u>	STATION / OFFSET: <u>106+50, 1' RT.</u>	EXPLORATION ID <u>B-058-0-18</u>
TYPE: <u>ROADWAY</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>RAMP W</u>	PAGE 1 OF 1
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>1008.0 (MSL)</u> EOB: <u>4.2 ft.</u>	
START: <u>3/21/19</u> END: <u>3/21/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>85</u>	LAT / LONG: <u>41.061258, -81.565290</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL
								GR	CS	FS	SI	CL	LL	PL	PI			
 VERY DENSE, BROWN, GRAVEL AND STONE FRAGMENTS WITH SAND , TRACE SILT, TRACE CLAY, STONE FRAGMENTS ARE SANDSTONE, DAMP	1008.0																	<L> >L> <L> >L> <L> >L>
	1005.1	TR																<L> >L> <L> >L> <L> >L>
 SANDSTONE , LIGHT TAN, SEVERELY WEATHERED, VERY WEAK, FRIABLE.	1003.8	EOB																<L> >L> <L> >L> <L> >L>
																		<L> >L> <L> >L> <L> >L>



NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:11 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6.15 KENMORE\GINT FILES\SUM-76-6.15 2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / J. HODGES</u>	DRILL RIG: <u>CME 55X</u>	STATION / OFFSET: <u>110+72, 15' RT.</u>	EXPLORATION ID <u>B-059-0-18</u>
TYPE: <u>ROADWAY</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>RAMP W</u>	
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>1004.8 (MSL)</u> EOB: <u>6.6 ft.</u>	PAGE 1 OF 1
START: <u>3/21/19</u> END: <u>3/21/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>85</u>	LAT / LONG: <u>41.060386, -81.565883</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTH	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL
								GR	CS	FS	SI	CL	LL	PL	PI			
VERY DENSE, BROWN, SANDY SILT , LITTLE CLAY, TRACE STONE FRAGMENTS, DAMP	1004.8	1															<V>	
		2															<V>	
		3	3														<V>	
	1000.8	4	10 50	85	100	SS-1	-	0	1	62	23	14	NP	NP	NP	11	A-4a (0)	<V>
SANDSTONE , LIGHT GRAY, SEVERELY WEATHERED, WEAK TO MODERATELY STRONG, FRIABLE, CONTAINS SILT AND CLAY LENSES.		5															<V>	
	998.2	6	4														<V>	
		EOB	50/1"		-	100	SS-3	-	-	-	-	-	-	-	-	8	Rock (V)	<V>

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:11 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6-15 KENMORE\GINT FILES\SUM-76-6-15 2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / J. HODGES</u>	DRILL RIG: <u>CME 55X</u>	STATION / OFFSET: <u>219+30, 76' LT.</u>	EXPLORATION ID <u>B-060-0-18</u>
TYPE: <u>ROADWAY</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>IR-77 & IR-76</u>	PAGE 1 OF 1
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>992.3 (MSL)</u> EOB: <u>11.5 ft.</u>	
START: <u>3/22/19</u> END: <u>3/22/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>85</u>	LAT / LONG: <u>41.060669, -81.567456</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	992.3	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG				ODOT CLASS (GI)	BACK FILL		
									GR	CS	FS	SI	CL	LL	PL	PI	WC				
VERY STIFF, BROWN, GRAVEL WITH SAND AND SILT , LITTLE CLAY, CONTAINS IRON STAINING, DAMP	987.8		1																<< < > >>		
			2																<< < > >>		
			3	3	11	30	100	SS-1	2.50	32	11	27	18	12	23	17	6	11	A-2-4 (0)	<< < > >>	
VERY STIFF TO HARD, GRAY, SANDY SILT , LITTLE CLAY, TRACE TO LITTLE GRAVEL, CONTAINS IRON STAINING, DAMP	980.8		4																<< < > >>		
			5	3	6	17	100	SS-2	2.50	-	-	-	-	-	-	-	-	11	A-4a (V)	<< < > >>	
			6	6	6															<< < > >>	
			7																		<< < > >>
			8	3	3	13	78	SS-3	2.50	15	12	25	29	19	22	15	7	12	A-4a (3)	<< < > >>	
			9																<< < > >>		
			10	5	8	26	100	SS-4	4.5+	-	-	-	-	-	-	-	9	A-4a (V)	<< < > >>		
			11	10															<< < > >>		

EOB

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:11 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6.15-2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / ASHBAUGH</u>	DRILL RIG: <u>CME 45B</u>	STATION / OFFSET: <u>215+87, 54' LT.</u>	EXPLORATION ID <u>B-061-0-18</u>
TYPE: <u>SUBGRADE</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>IR-77 & IR-76</u>	
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>992.3 (MSL)</u> EOB: <u>7.5 ft.</u>	PAGE 1 OF 1
START: <u>4/9/19</u> END: <u>4/9/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>84</u>	LAT / LONG: <u>41.060996, -81.568596</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL
								GR	CS	FS	SI	CL	LL	PL	PI			
14.0" CONCRETE (DRILLERS DESCRIPTION)	992.3																	
	991.1	1																
DENSE, LIGHT TAN AND DARK GRAY, GRAVEL AND/OR STONE FRAGMENTS WITH SAND AND SILT , LITTLE CLAY, DAMP	989.3	2	18	49	100	SS-1	-	27	12	33	16	12	NP	NP	NP	6	A-2-4 (0)	
		3	8	32	100	SS-2	4.5+	12	14	37	22	15	21	15	6	8	A-4a (0)	
HARD, BROWN AND LIGHT BROWN MOTTLED WITH GRAY, SANDY SILT , LITTLE CLAY, LITTLE GRAVEL, DAMP		4	11	35	100	SS-3	4.5+	-	-	-	-	-	-	-	-	9	A-4a (V)	
		5	5	12	13													
		6	8	7	8													
	984.8	7	7	21	100	SS-4	4.5+	-	-	-	-	-	-	-	-	13	A-4a (V)	
		EOB																

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: PLACED 0.5 BAG ASPHALT PATCH; SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:12 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6.15.2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / J. HODGES</u>	DRILL RIG: <u>CME 55X</u>	STATION / OFFSET: <u>2+43, 28' LT.</u>	EXPLORATION ID <u>B-062-0-18</u>
TYPE: <u>ROADWAY</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>RAMP B</u>	
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>973.0 (MSL)</u> EOB: <u>16.5 ft.</u>	PAGE 1 OF 1
START: <u>3/20/19</u> END: <u>3/20/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>85</u>	LAT / LONG: <u>41.034690, -81.567609</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTH	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL		
								GR	CS	FS	SI	CL	LL	PL	PI					
LOOSE TO MEDIUM DENSE, BROWN, COARSE AND FINE SAND , LITTLE TO SOME SILT, TRACE TO LITTLE GRAVEL, TRACE CLAY, MOIST TO WET @7.5' TO 16.5'; BECOMES VERY LOOSE	973.0																	<< < > >>		
			1																<< < > >>	
			2																<< < > >>	
			3	3	2	7	100	SS-1	-	14	17	43	18	8	NP	NP	NP	13	A-3a (0)	<< < > >>
			4																<< < > >>	
			5	5	4	14	78	SS-2	-	-	-	-	-	-	-	-	-	12	A-3a (V)	<< < > >>
			6																<< < > >>	
			7																<< < > >>	
			8	WOH WOH WOH	0	33	SS-3	-	-	-	-	-	-	-	-	-	-	14	A-3a (V)	<< < > >>
			9																<< < > >>	
			10	WOH WOH WOH	0	100	SS-4	-	10	20	35	25	10	NP	NP	NP	14	A-3a (0)	<< < > >>	
			11																<< < > >>	
			12																<< < > >>	
			13	WOH WOH WOH	0	100	SS-5	-	-	-	-	-	-	-	-	-	-	15	A-3a (V)	<< < > >>
			14																<< < > >>	
			15																<< < > >>	
	956.5	16	WOH WOH WOH	0	100	SS-6	-	-	-	-	-	-	-	-	-	-	16	A-3a (V)	<< < > >>	

EOB

NOTES: GROOUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:12 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6-15 2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / J. HODGES</u>	DRILL RIG: <u>CME 55X</u>	STATION / OFFSET: <u>10+02, 57' LT.</u>	EXPLORATION ID <u>B-063-0-18</u>
TYPE: <u>ROADWAY</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>RAMP B</u>	
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>970.7 (MSL)</u> EOB: <u>16.5 ft.</u>	PAGE 1 OF 1
START: <u>3/20/19</u> END: <u>3/20/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>85</u>	LAT / LONG: <u>41.034019, -81.566973</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTH	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL		
								GR	CS	FS	SI	CL	LL	PL	PI					
<p>MEDIUM DENSE, BROWN, COARSE AND FINE SAND, LITTLE TO SOME SILT, LITTLE GRAVEL, TRACE CLAY, CONTAINS STONE FRAGMENTS >1.0", MOIST TO WET</p> <p>@5.0' TO 16.5'; BECOMES VERY LOOSE</p>	970.7																			
			1																<<V>>	
			2																<<V>>	
			3	3	5	14	56	SS-1	-	20	21	33	17	9	NP	NP	NP	13	A-3a (0)	<<V>>
			4																<<V>>	
			5	1															<<V>>	
			6	1	2	4	17	SS-2	-	-	-	-	-	-	-	-	-	13	A-3a (V)	<<V>>
			7																<<V>>	
			8	WOH															<<V>>	
			9	WOH															<<V>>	
			10	WOH															<<V>>	
			11	WOH	1		28	SS-4	-	13	17	36	24	10	NP	NP	NP	15	A-3a (0)	<<V>>
			12																<<V>>	
			13	WOH	1		78	SS-5	-	-	-	-	-	-	-	-	-	14	A-3a (V)	<<V>>
			14																<<V>>	
			15	WOH															<<V>>	
	954.2	16	WOH	1		78	SS-6	-	-	-	-	-	-	-	-	-	16	A-3a (V)	<<V>>	

NOTES: GROUNDWATER ENCOUNTERED AT 8.0' DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT. - 7/29/19 09:12 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6.15 KENMORE\REIGNIT FILES\SUM-76-6.15 2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / J. HODGES</u>	DRILL RIG: <u>CME 55X</u>	STATION / OFFSET: <u>14+79, 63' LT.</u>	EXPLORATION ID <u>B-064-0-18</u>
TYPE: <u>ROADWAY</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>RAMP A2</u>	
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>973.3 (MSL)</u> EOB: <u>11.5 ft.</u>	PAGE 1 OF 1
START: <u>3/20/19</u> END: <u>3/20/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>85</u>	LAT / LONG: <u>41.034416, -81.565886</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	973.3	DEPTH	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL	
									GR	CS	FS	SI	CL	LL	PL	PI				
LOOSE TO MEDIUM DENSE, BROWN, FINE SAND , SOME COARSE SAND, TRACE SILT, TRACE CLAY, TRACE GRAVEL, DAMP @5.0' TO 9.0'; BECOMES TRACE COARSE SAND, WET			1																<V>	
			2																<V>	
			3	6	5	14	100	SS-1	-	1	26	64	7	2	NP	NP	NP	9	A-3 (0)	<V>
			4																	<V>
			5	4	3	9	100	SS-2	-	-	-	-	-	-	-	-	-	24	A-3 (V)	<V>
		6																		<V>
		7																		<V>
		8	4	4	13	100	SS-3	-	1	1	89	6	3	NP	NP	NP	26	A-3 (0)	<V>	
	963.8		9																	<V>
		10																		<V>
LOOSE, BROWN, SILT , SOME SAND, TRACE CLAY, TRACE GRAVEL, WET		961.8	11	2	3	7	100	SS-4	-	1	1	28	65	5	NP	NP	NP	30	A-4b (7)	<V>
			EOB																	<V>

NOTES: GROUNDWATER ENCOUNTERED AT 5.0' DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:12 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6-15-2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / J. HODGES</u>	DRILL RIG: <u>CME 55X</u>	STATION / OFFSET: <u>17+36, 77' LT.</u>	EXPLORATION ID <u>B-065-0-18</u>
TYPE: <u>EMBANKMENT</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>RAMP A2</u>	
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>973.9 (MSL)</u> EOB: <u>11.5 ft.</u>	PAGE 1 OF 1
START: <u>3/20/19</u> END: <u>3/20/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>85</u>	LAT / LONG: <u>41.035059, -81.565818</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTH	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL		
								GR	CS	FS	SI	CL	LL	PL	PI					
VERY LOOSE TO MEDIUM DENSE, BROWN, FINE SAND , LITTLE COARSE SAND, TRACE SILT, TRACE GRAVEL, TRACE CLAY, SS-4 CONTAINS TRACE IRON STAINING, DAMP @5.0' TO 11.5'; BECOMES WET	973.9																			
			1															<V>		
			2															<V>		
			3	5	4	14	100	SS-1	-	5	12	74	6	3	NP	NP	NP	9	A-3 (0)	<V>
			4		6														<V>	
			5	2	3	9	100	SS-2	-	-	-	-	-	-	-	-	-	26	A-3 (V)	<V>
			6		3														<V>	
			7																<V>	
			8	1	1	3	100	SS-3	-	3	11	79	5	2	NP	NP	NP	22	A-3 (0)	<V>
			9																<V>	
			10	3	6	18	100	SS-4	-	-	-	-	-	-	-	-	-	27	A-3 (V)	<V>
	962.4	11		7														<V>		
		EOB																		

NOTES: GROUNDWATER ENCOUNTERED AT 5.0' DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:12 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6.15 KENMORE\GINT FILES\SUM-76-6.15 2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / ASHBAUGH</u>	DRILL RIG: <u>CME 45B</u>	STATION / OFFSET: <u>17+39, 30' LT.</u>	EXPLORATION ID <u>B-066-0-18</u>
TYPE: <u>EMBANKMENT</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>RAMP A2</u>	
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>991.4 (MSL)</u> EOB: <u>26.5 ft.</u>	PAGE 1 OF 1
START: <u>4/17/19</u> END: <u>4/17/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>84</u>	LAT / LONG: <u>41.035062, -81.565647</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTH	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL	
								GR	CS	FS	SI	CL	LL	PL	PI				
15.5" ASPHALT AND 14.5" BASE (DRILLERS DESCRIPTION)	991.4																ASPHALT		
	988.9	2															ASPHALT		
MEDIUM DENSE, BROWN, GRAVEL WITH SAND , TRACE SILT, TRACE CLAY, DAMP	986.9	3	7 5	14	67	SS-1	-	29	37	23	7	4	NP	NP	NP	9	A-1-b (0)	GRAVEL	
		4	5														GRAVEL		
VERY LOOSE TO MEDIUM DENSE, BROWN, FINE SAND , LITTLE TO SOME COARSE SAND, TRACE SILT, TRACE CLAY, TRACE GRAVEL, CONTAINS IRON STAINING, WET TO DAMP		5	3	4	13	100	SS-2	-	1	13	78	4	4	NP	NP	NP	14	A-3 (0)	FINE SAND
		6	4	5													FINE SAND		
		7															FINE SAND		
		8	2	3	8	100	SS-3	-	-	-	-	-	-	-	-	6	A-3 (V)	FINE SAND	
		9	3														FINE SAND		
		10	2	3	10	100	SS-4	-	-	-	-	-	-	-	-	12	A-3 (V)	FINE SAND	
		11	3	4													FINE SAND		
		12															FINE SAND		
@12.5' TO 14.0'; BECOMES BROWN AND ORANGISH BROWN, CONTAINS IRON STAINING		13	3	2	6	100	SS-5	-	-	-	-	-	-	-	-	6	A-3 (V)	FINE SAND	
		14	2	2													FINE SAND		
		15	1														FINE SAND		
		16	2	1	4	100	SS-6	-	-	-	-	-	-	-	-	6	A-3 (V)	FINE SAND	
		17															FINE SAND		
		18	2	1	4	100	SS-7	-	1	24	70	3	2	NP	NP	NP	5	A-3 (0)	FINE SAND
		19		2													FINE SAND		
		20	2	2	7	100	SS-8	-	-	-	-	-	-	-	-	8	A-3 (V)	FINE SAND	
		21	2	3													FINE SAND		
		22															FINE SAND		
@22.5' TO 26.5'; BECOMES WET		23	3	2	6	100	SS-9	-	-	-	-	-	-	-	-	23	A-3 (V)	FINE SAND	
		24	2	2													FINE SAND		
		25	2	3	7	89	SS-10	-	-	-	-	-	-	-	-	21	A-3 (V)	FINE SAND	
	964.9	26	2	2													FINE SAND		

NOTES: GROUNDWATER ENCOUNTERED AT 22.5' DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: PLACED 0.5 BAG ASPHALT PATCH; SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:12 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6.15.2.GPJ

PID: 100713	SFN: _____	PROJECT: SUM-76-06.15	STATION / OFFSET: 8+40, 5' RT.	START: 2/19/19	END: 2/19/19	PG 2 OF 2	B-067-0-18													
MATERIAL DESCRIPTION AND NOTES	ELEV. 989.4	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL		
								GR	CS	FS	SI	CL	LL	PL	PI					
MEDIUM DENSE TO DENSE, LIGHT BROWN, GRAVEL AND STONE FRAGMENTS WITH SAND, TRACE TO LITTLE SILT, TRACE CLAY, CONTAINS IRON STAINING, WET (continued)		31	3	5	49	67	SS-12	-	-	-	-	-	-	-	-	-	15	A-1-b (V)	<>L> <>L> <>L> <>L>	
		32																	<>L> <>L> <>L>	
		33	33	5	7	25	67	SS-13	-	-	-	-	-	-	-	-	14	A-1-b (V)	<>L> <>L> <>L> <>L>	
		34																	<>L> <>L> <>L>	
		35		8	9	29	78	SS-14	-	-	-	-	-	-	-	-	13	A-1-b (V)	<>L> <>L> <>L> <>L>	
		36																		<>L> <>L> <>L>
		982.9	EOB																	<>L> <>L> <>L>

NOTES: GROUNDWATER ENCOUNTERED AT 25.0' DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: PLACED 0.5 BAG ASPHALT PATCH; SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:12 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6.15 KENMORE\GINT FILES\SUM-76-6.15 2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / ASHBAUGH</u>	DRILL RIG: <u>CME 55T</u>	STATION / OFFSET: <u>12+37, 19' RT.</u>	EXPLORATION ID <u>B-068-0-18</u>
TYPE: <u>ROADWAY</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>RAMP U</u>	
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>1012.1 (MSL)</u> EOB: <u>11.5 ft.</u>	PAGE 1 OF 1
START: <u>2/19/19</u> END: <u>2/19/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>78</u>	LAT / LONG: <u>41.059630, -81.566188</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTH	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL	
								GR	CS	FS	SI	CL	LL	PL	PI				
HARD, BROWN AND DARK BROWN BECOMING GRAY, SANDY SILT , SOME GRAVEL, LITTLE CLAY, CONTAINS IRON STAINING, DAMP	1012.1	1	8 10 11	27	89	SS-1	4.5+	24	16	24	23	13	23	16	7	10	A-4a (0)	X	
	1009.3	2																>>>	
DENSE TO VERY DENSE, GRAY, GRAVEL AND STONE FRAGMENTS WITH SAND , LITTLE SILT, TRACE CLAY, CONTAINS IRON STAINING, DAMP	1008.6	3	5 15 18	43	78	SS-2A	4.5+	-	-	-	-	-	-	-	-	2	A-4a (V)	>>>	
		4					SS-2B	-	-	-	-	-	-	-	-	5	A-1-b (V)	>>>	
		5																	>>>
		6	13 30 29	77	89	SS-3	-	-	-	-	-	-	-	-	-	7	A-1-b (V)	>>>	
VERY DENSE, BROWN AND ORANGISH BROWN, GRAVEL WITH SAND AND SILT , TRACE CLAY, CONTAINS IRON STAINING, DAMP	1002.6	7																>>>	
		8	23 17 22	51	33	SS-4	-	-	-	-	-	-	-	-	7	A-1-b (V)	>>>		
		9																>>>	
	1000.6	10	13 21 44	85	67	SS-5	-	-	-	-	-	-	-	-	11	A-2-4 (V)	>>>		
		11																>>>	

NOTES: GROUNDWATER ENCOUNTERED AT 10.0' DURING DRILLING, 3.5' AFTER COMPLETION. HOLE CAVED AT 6.0'.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: PLACED 0.5 BAG ASPHALT PATCH; SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT. - 7/29/19 09:12 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6-15 KENMORE\GINT FILES\SUM-76-6-15 2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / ASHBAUGH</u>	DRILL RIG: <u>CME 55T</u>	STATION / OFFSET: <u>16+94, 19' RT.</u>	EXPLORATION ID <u>B-069-0-18</u>
TYPE: <u>NOISE WALL</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>RAMP U</u>	
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>1024.3 (MSL)</u> EOB: <u>15.3 ft.</u>	PAGE 1 OF 1
START: <u>2/19/19</u> END: <u>2/19/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>78</u>	LAT / LONG: <u>41.059717, -81.564576</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTH	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL
								GR	CS	FS	SI	CL	LL	PL	PI			
DENSE, LIGHT BROWN AND ORANGISH BROWN, GRAVEL AND STONE FRAGMENTS WITH SAND AND SILT , LITTLE CLAY, CONTAINS STONE FRAGMENTS >1.0", TRACE IRON STAINING, MOIST	1024.3	1																
		2																
		3	5	6	40	100	SS-1	-	-	-	-	-	-	-	-	-	17	A-2-4 (V)
VERY STIFF TO HARD, BROWN MOTTLED WITH ORANGISH BROWN AND GRAY, CLAY , SOME SAND, TRACE SILT, TRACE GRAVEL, CONTAINS IRON STAINING, DAMP	1019.8	4																
		5	8	13	40	100	SS-2	4.25	5	8	14	7	66	49	22	27	16	A-7-6 (16)
		6																
SANDSTONE , LIGHT BROWN AND WHITE, HIGHLY WEATHERED, STRONG, FRIABLE.	1016.3	7																
		8	5	50/1"	-	86	SS-3A SS-3B	2.50	-	-	-	-	-	-	-	-	20	A-7-6 (V) Rock (V)
		9																
		10	46	50/2"	-	100	SS-4	-	-	-	-	-	-	-	-	-	7	Rock (V)
		11																
		12																
		13																
		14																
		15																
	1009.0	EOB																

NOTES: GROUNDWATER ENCOUNTERED AT 12.5' DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: PLACED 0.5 BAG ASPHALT PATCH; SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:12 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6-15 KENMORE\GINT FILES\SUM-76-6-15 2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / ASHBAUGH</u>	DRILL RIG: <u>CME 55T</u>	STATION / OFFSET: <u>231+79, 79' RT.</u>	EXPLORATION ID <u>B-070-0-18</u>
TYPE: <u>ROADWAY</u>	SAMPLING FIRM / LOGGER: <u>NEAS / ASHBAUGH</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>IR-77 & IR-76</u>	PAGE 1 OF 1
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>1036.8 (MSL)</u> EOB: <u>5.3 ft.</u>	
START: <u>2/21/19</u> END: <u>2/21/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>78</u>	LAT / LONG: <u>41.059700, -81.563121</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL	
								GR	CS	FS	SI	CL	LL	PL	PI				
5.0" TOPSOIL (DRILLERS DESCRIPTION) MEDIUM DENSE, DARK BROWN, COARSE AND FINE SAND , SOME SILT, LITTLE GRAVEL, TRACE CLAY, CONTAINS ROOTS, WET	1036.8																		
	1036.4	1	4	8	29	56	SS-1	-	20	16	34	22	8	NP	NP	NP	17	A-3a (0)	
	1034.8	2																	
SANDSTONE , LIGHT TAN, HIGHLY WEATHERED, SLIGHTLY STRONG, FRIABLE.		3																	
		4																	
	1031.5	5	50/4"			50	SS-2	-	-	-	-	-	-	-	-	-	12	Rock (V)	
		EOB	50/3"			67	SS-3	-	-	-	-	-	-	-	-	-	8	Rock (V)	

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: PLACED 0.5 BAG ASPHALT PATCH; SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:12 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6.15 KENMORE\GINT FILES\SUM-76-6.15 2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / ASHBAUGH</u>	DRILL RIG: <u>CME 55T</u>	STATION / OFFSET: <u>235+80, 74' RT.</u>	EXPLORATION ID <u>B-071-0-18</u>
TYPE: <u>ROADWAY</u>	SAMPLING FIRM / LOGGER: <u>NEAS / ASHBAUGH</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>IR-77 & IR-76</u>	
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>1048.8 (MSL)</u> EOB: <u>11.5 ft.</u>	PAGE 1 OF 1
START: <u>2/21/19</u> END: <u>2/21/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>78</u>	LAT / LONG: <u>41.059709, -81.561666</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL
								GR	CS	FS	SI	CL	LL	PL	PI			
6.0" TOPSOIL (DRILLERS DESCRIPTION) VERY STIFF TO HARD, BROWN AND ORANGISH BROWN, SANDY SILT , SOME CLAY, TRACE TO LITTLE GRAVEL, CONTAINS IRON STAINING, DAMP	1048.8	1	1															
	1048.3	2	4	12	67	SS-1	2.75	-	-	-	-	-	-	-	-	11	A-4a (V)	
		3	10															
		4	10 16	34	100	SS-2	4.5+	10	9	18	39	24	25	17	8	11	A-4a (6)	
DENSE TO VERY DENSE, BROWN AND ORANGISH BROWN BECOMING GRAY AND BROWN, GRAVEL WITH SAND AND SILT , TRACE CLAY, DAMP	1044.3	5	6															
		6	19 24	56	89	SS-3	-	38	14	19	20	9	21	17	4	10	A-2-4 (0)	
		7																
		8	8 14 18	42	100	SS-4	-	-	-	-	-	-	-	-	-	8	A-2-4 (V)	
SANDSTONE , LIGHT BROWN, HIGHLY WEATHERED, SLIGHTLY STRONG, FINE TO COARSE GRAINED, FRIABLE.	1039.3	9																
		10	10															
	1037.3	11	10 14 22	47	67	SS-5	-	-	-	-	-	-	-	-	2	Rock (V)		
		TR																
		EOB																

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: PLACED 0.5 BAG ASPHALT PATCH; SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:12 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6.15 KENMORE\GINT FILES\SUM-76-6.15 2.GPJ

PID: 100713 SFN: _____ PROJECT: SUM-76-06.15 STATION / OFFSET: 99+85, 38' LT. START: 5/1/19 END: 5/1/19 PG 2 OF 2 B-072-0-18

MATERIAL DESCRIPTION AND NOTES	ELEV. 987.6	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL		
								GR	CS	FS	SI	CL	LL	PL	PI					
VERY STIFF TO HARD, GRAY, SILT AND CLAY, LITTLE TO SOME SAND, TRACE TO LITTLE GRAVEL, DAMP (continued)	987.6	31	12 11 8	25	56	SS-12	4.5+	-	-	-	-	-	-	-	-	-	14	A-6a (V)	<V>	
		32																		<V>
		33	8 5 6	14	89	SS-13	4.25	-	-	-	-	-	-	-	-	-	14	A-6a (V)	<V>	
		34																		<V>
		35	18 24 10	44	100	SS-14	3.25	-	-	-	-	-	-	-	-	-	14	A-6a (V)	<V>	
SANDSTONE, GRAY, MODERATELY WEATHERED, MODERATELY STRONG, FINE GRAINED, MODERATELY ARGILLACEOUS.	980.6	37																		<V>
		38	18 50/3"	-	11	SS-15	-	-	-	-	-	-	-	-	-	7	Rock (V)	<V>		
		39																		<V>
		40	50/2"	-	50	SS-16	-	-	-	-	-	-	-	-	-	7	Rock (V)	<V>		
	975.0	41																	<V>	
		42																		<V>
@42.5' TO 42.6'; SS-17 CONTAINS NO RECOVERY		EOB	50/1"	-	0	SS-17	-	-	-	-	-	-	-	-	-					<V>

NOTES: GROUNDWATER ENCOUNTERED AT 28.0' DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: PLACED 0.5 BAG ASPHALT PATCH; SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT. - 7/29/19 09:12 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6-15 KENMORE\REIGNIT FILES\SUM-76-6-15 2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / ASHBAUGH</u>	DRILL RIG: <u>CME 55T</u>	STATION / OFFSET: <u>103+14, 39' LT.</u>	EXPLORATION ID <u>B-073-0-18</u>
TYPE: <u>SUBGRADE</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>IR - 76</u>	
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>1016.3 (MSL)</u> EOB: <u>6.9 ft.</u>	PAGE 1 OF 1
START: <u>5/1/19</u> END: <u>5/1/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>78</u>	LAT / LONG: <u>41.061843, -81.566284</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL
								GR	CS	FS	SI	CL	LL	PL	PI			
13.0" ASPHALT (DRILLERS DESCRIPTION)	1016.3																	<L> >L>
MEDIUM DENSE TO DENSE, BROWN AND LIGHT BROWN, GRAVEL AND STONE FRAGMENTS WITH SAND , TRACE TO LITTLE SILT, TRACE CLAY, SS-1 CONTAINS 1.25" STONE FRAGMENTS, DAMP	1015.2	1																<L> >L>
		2	14															<L> >L>
		3	15	34	78	SS-1	-	49	14	25	7	5	NP	NP	NP	6	A-1-b (0)	<L> >L>
		4	4															<L> >L>
	1011.8	TR	10	26	56	SS-2	-	40	21	21	11	7	NP	NP	NP	5	A-1-b (0)	<L> >L>
		5	6															<L> >L>
SANDSTONE , LIGHT TAN, SEVERELY WEATHERED, MODERATELY STRONG, FINE TO COARSE GRAINED, CONGLOMERITIC.			7	52	78	SS-3	-	-	-	-	-	-	-	-	-	5	Rock (V)	<L> >L>
@6.0' TO 6.9'; SS-4 CONTAINS A 1.75" SILT AND CLAY SEAM	1009.4	EOB	7															<L> >L>
			50/5"		91	SS-4	-	-	-	-	-	-	-	-	-	12	Rock (V)	<L> >L>

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: PLACED BAG ASPHALT PATCH; SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:12 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6.15 KENMORE\GINT FILES\SUM-76-6.15 2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / ASHBAUGH</u>	DRILL RIG: <u>CME 45B</u>	STATION / OFFSET: <u>18+11, 7' RT.</u>	EXPLORATION ID <u>B-074-0-18</u>
TYPE: <u>ROADWAY</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>RAMP V</u>	
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>1015.2 (MSL)</u> EOB: <u>10.1 ft.</u>	PAGE 1 OF 1
START: <u>5/1/19</u> END: <u>5/1/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>84</u>	LAT / LONG: <u>41.061545, -81.565017</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL
								GR	CS	FS	SI	CL	LL	PL	PI			
2.5" ASPHALT AND 10.5" CONCRETE (DRILLERS DESCRIPTION) VERY DENSE, LIGHT BROWN, STONE FRAGMENTS WITH SAND , TRACE SILT, TRACE CLAY, CONTAINS 1.5" STONE FRAGMENTS, DAMP	1015.2																	
	1014.1	1																<><><>
SANDSTONE , LIGHT BROWN, HIGHLY WEATHERED, MODERATELY STRONG, FINE TO COARSE GRAINED, CONGLOMERITIC.	1011.2	TR																<><><>
		3	10 17 26	60	56	SS-1	-	48	20	24	5	3	NP	NP	NP	6	A-1-b (0)	<><><>
@7.5' TO 9.0'; SS-3 CONTAINS NO RECOVERY		4																<><><>
		5	50/5"	-	40	SS-2	-	-	-	-	-	-	-	-	-	7	Rock (V)	<><><>
@10.0' TO 10.1'; SS-4 CONTAINS NO RECOVERY		7																<><><>
		8	50/2"	-	0	SS-3	-	-	-	-	-	-	-	-	-			<><><>
	1005.1	EOB																<><><>
		10	50/1"	-	0	SS-4	-	-	-	-	-	-	-	-	-			<><><>

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: PLACED 0.5 BAG ASPHALT PATCH; SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:12 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6.15 2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / J. HODGES</u>	DRILL RIG: <u>CME 55X</u>	STATION / OFFSET: <u>14+42, 77' LT.</u>	EXPLORATION ID <u>B-075-0-18</u>
TYPE: <u>ROADWAY</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>RAMP V</u>	
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>1021.2 (MSL)</u> EOB: <u>5.9 ft.</u>	PAGE 1 OF 1
START: <u>3/21/19</u> END: <u>3/21/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>85</u>	LAT / LONG: <u>41.060670, -81.564256</u>	


MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTH	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG				ODOT CLASS (GI)	BACK FILL	
								GR	CS	FS	SI	CL	LL	PL	PI	WC			
STIFF TO VERY STIFF, GRAY, SILT , SOME CLAY, LITTLE SAND, TRACE GRAVEL, NO INTACT SOIL FOR HP READINGS, DRY	1021.2																		<L> >L>
		1																	<L> >L>
		2																	<L> >L>
		3	5	7	23	100	SS-1	-	1	1	15	57	26	25	16	9	5	A-4b (8)	<L> >L>
		4																	<L> >L>
HARD, LIGHT TAN, SANDY SILT , SOME CLAY, TRACE GRAVEL AND STONE FRAGMENTS, CONTAINS A 1.25" QUARTZITE PEBBLE, NO INTACT SOIL FOR HP READINGS, DRY	1016.7																		<L> >L>
	1015.3	EOB	4	50/5"	-	73	SS-2	-	10	9	21	37	23	24	15	9	5	A-4a (5)	<L> >L>

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT. - 7/29/19 09:12 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6-15 KENMORE\IGINT FILES\SUM-76-6-15 2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / J. HODGES</u>	DRILL RIG: <u>CME 55X</u>	STATION / OFFSET: <u>10+85, 59' LT.</u>	EXPLORATION ID <u>B-076-0-18</u>
TYPE: <u>ROADWAY</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>RAMP V</u>	
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>1036.2 (MSL)</u> EOB: <u>6.0 ft.</u>	PAGE 1 OF 1
START: <u>3/21/19</u> END: <u>3/21/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>85</u>	LAT / LONG: <u>41.060150, -81.563065</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTH	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL
								GR	CS	FS	SI	CL	LL	PL	PI			
VERY DENSE, LIGHT TAN WITH ORANGISH BROWN AND BROWN MOTTLES, GRAVEL AND STONE FRAGMENTS WITH SAND AND SILT , TRACE CLAY, CONTAINS STONE FRAGMENTS >1.0", DAMP	1036.2	1																<L> >L>
		2																<L> >L>
		3		11														
VERY DENSE, BROWN WITH TRACE ORANGISH BROWN MOTTLES, SANDY SILT , LITTLE CLAY, LITTLE GRAVEL, DAMP	1031.7	4	15	51	78	SS-1	-	20	12	37	21	10	NP	NP	NP	7	A-2-4 (0)	<L> >L>
	1030.5	5	5															<L> >L>
SANDSTONE , LIGHT GRAY AND REDDISH BROWN, HIGHLY WEATHERED, SLIGHTLY STRONG.	1030.2	6	50	-	100	SS-2A SS-2B	-	13	14	35	24	14	19	15	4	9	A-4a (1) Rock (V)	<L> >L>



NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:12 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6-15-2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / ASHBAUGH</u>	DRILL RIG: <u>CME 55T</u>	STATION / OFFSET: <u>4+70, 22' LT.</u>	EXPLORATION ID <u>B-077-0-18</u>
TYPE: <u>SUBGRADE</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>RAMP L</u>	
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>1079.5 (MSL)</u> EOB: <u>7.5 ft.</u>	PAGE 1 OF 1
START: <u>4/17/19</u> END: <u>4/17/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>78</u>	LAT / LONG: <u>41.059466, -81.557415</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL
								GR	CS	FS	SI	CL	LL	PL	PI			
12.0" ASPHALT AND 3.0" BASE (DRILLERS DESCRIPTION) VERY STIFF TO HARD, BROWN BECOMING BROWN MOTTLED WITH ORANGISH BROWN AND GRAY, SANDY SILT , SOME CLAY, LITTLE TO SOME GRAVEL, CONTAINS IRON STAINING, DAMP	1079.5																	
	1078.3	1																
		2	7	12	25	100	SS-1	4.25	23	10	13	33	21	25	17	8	13	A-4a (4)
		3	11	9	27	100	SS-2	4.25	-	-	-	-	-	-	-	-	16	A-4a (V)
		4	12															
		5	5	11	30	100	SS-3	4.5+	18	12	13	35	22	27	18	9	13	A-4a (4)
		6	7	6	17	100	SS-4	3.25	-	-	-	-	-	-	-	-	16	A-4a (V)
	1072.0	7																

EOB

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: PLACED 0.5 BAG ASPHALT PATCH; SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:12 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6-15-2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / ASHBAUGH</u>	DRILL RIG: <u>CME 55T</u>	STATION / OFFSET: _____	EXPLORATION ID <u>B-077-1-18</u>
TYPE: <u>SUBGRADE</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>RAMP J</u>	
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>1071.4 (MSL)</u> EOB: <u>7.5 ft.</u>	PAGE 1 OF 1
START: <u>4/17/19</u> END: <u>4/17/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>78</u>	LAT / LONG: <u>41.060756, -81.558959</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL
								GR	CS	FS	SI	CL	LL	PL	PI			
12.0" ASPHALT (DRILLERS DESCRIPTION)	1071.4																	
MEDIUM DENSE, BROWN MOTTLED WITH ORANGISH BROWN, GRAVEL WITH SAND AND SILT , LITTLE CLAY, CONTAINS IRON STAINING, DAMP	1070.4	1	8															
		2	6	21	78	SS-1	-	26	20	20	23	11	19	15	4	9	A-2-4 (0)	
DENSE TO VERY DENSE, BROWN MOTTLED WITH ORANGISH BROWN AND GRAY, COARSE AND FINE SAND , SOME SILT, SOME GRAVEL, TRACE CLAY, CONTAINS IRON STAINING, DAMP	1068.4	3	4	20	51	SS-2	-	21	32	17	21	9	NP	NP	NP	7	A-3a (0)	
		4	19															
		5	3	14	34	SS-3	-	-	-	-	-	-	-	-	-	6	A-3a (V)	
	1065.4	6	4	13	44	SS-4	4.5+	-	-	-	-	-	-	-	-	10	A-4a (V)	
	1063.9	7	21															

EOB

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: PLACED 0.5 BAG ASPHALT PATCH; SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:12 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6.15 2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / ASHBAUGH</u>	DRILL RIG: <u>CME 55T</u>	STATION / OFFSET: _____	EXPLORATION ID <u>B-077-2-18</u>
TYPE: <u>SUBGRADE</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>RAMP J</u>	PAGE 1 OF 1
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>1082.8 (MSL)</u> EOB: <u>7.5 ft.</u>	
START: <u>4/17/19</u> END: <u>4/17/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>78</u>	LAT / LONG: <u>41.061393, -81.558576</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL	
								GR	CS	FS	SI	CL	LL	PL	PI				
2.0" ASPHALT AND 10.0" CONCRETE (DRILLERS DESCRIPTION) VERY STIFF TO HARD, GRAY MOTTLED WITH ORANGISH BROWN BECOMING BROWN, SANDY SILT , SOME CLAY, TRACE TO SOME GRAVEL, CONTAINS IRON STAINING, DAMP	1082.8																		
	1081.8	1																	
		2	7	5	14	100	SS-1	4.25	9	4	11	47	29	27	17	10	14	A-4a (8)	
		3	3	6															
		4	7	7	18	89	SS-2	4.25	29	4	8	38	21	26	18	8	17	A-4a (5)	
		5	4	6	16	100	SS-3	4.25	-	-	-	-	-	-	-	-	16	A-4a (V)	
		6	2	6															
	1075.3	7	5	13	100	SS-4	4.00	-	-	-	-	-	-	-	-	17	A-4a (V)		
		EOB																	

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: PLACED 0.5 BAG ASPHALT PATCH; SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:12 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6.15-2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / ASHBAUGH</u>	DRILL RIG: <u>CME 55T</u>	STATION / OFFSET: _____	EXPLORATION ID <u>B-077-3-18</u>
TYPE: <u>SUBGRADE</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>RAMP J</u>	PAGE 1 OF 1
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>1080.4 (MSL)</u> EOB: <u>7.5 ft.</u>	
START: <u>4/17/19</u> END: <u>4/17/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>78</u>	LAT / LONG: <u>41.061127, -81.558151</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL
								GR	CS	FS	SI	CL	LL	PL	PI			
13" ASPHALT (DRILLERS DESCRIPTION)	1080.4																	X
	1079.3	1																< >
LOOSE, BROWN, GRAVEL WITH SAND , TRACE SILT, TRACE CLAY, DAMP		2	3	9	89	SS-1	-	10	55	27	4	4	NP	NP	NP	6	A-1-b (0)	< >
	1076.9	3	2	4	10	SS-2A	-	-	-	-	-	-	-	-	-	7	A-1-b (V)	< >
VERY STIFF TO HARD, BROWN, SILT , SOME SAND, LITTLE CLAY, TRACE GRAVEL, CONTAINS IRON STAINING, DAMP TO MOIST		4	4	10	78	SS-2B	4.25	-	-	-	-	-	-	-	-	18	A-4b (V)	< >
		5	3	5	13	SS-3	4.25	6	4	17	58	15	22	18	4	19	A-4b (8)	< >
		6	2	5	5													< >
	1072.9	7	5	12	22	SS-4	3.25	-	-	-	-	-	-	-	-	19	A-4b (V)	< >
		EOB																< >

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: PLACED 0.5 BAG ASPHALT PATCH; SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:12 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6.15 KENMORE\REIGNIT FILES\SUM-76-6.15 2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / ASHBAUGH</u>	DRILL RIG: <u>CME 55T</u>	STATION / OFFSET: _____	EXPLORATION ID <u>B-077-4-18</u>
TYPE: <u>SUBGRADE</u>	SAMPLING FIRM / LOGGER: <u>NEAS / E. ROLLER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>RAMP J</u>	
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>1087.2 (MSL)</u> EOB: <u>7.5 ft.</u>	PAGE 1 OF 1
START: <u>4/17/19</u> END: <u>4/17/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>78</u>	LAT / LONG: <u>41.060741, -81.557344</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL	
								GR	CS	FS	SI	CL	LL	PL	PI				
12.0" ASPHALT (DRILLERS DESCRIPTION)	1087.2																1086.2		X
VERY STIFF TO HARD, BROWN MOTTLED WITH GRAY, SILT , SOME CLAY, TRACE TO LITTLE SAND, TRACE GRAVEL, CONTAINS TRACE IRON STAINING, DAMP TO MOIST		1																	< >
		2	3	5	14	100	SS-1	4.25	2	3	9	53	33	29	19	10	16	A-4b (8)	< >
		3	5	7	21	100	SS-2	4.25	-	-	-	-	-	-	-	-	22	A-4b (V)	< >
		4	3	4	13	100	SS-3	4.00	0	1	2	69	28	30	23	7	22	A-4b (8)	< >
		5	4	6	13	100	SS-4	3.75	-	-	-	-	-	-	-	-	27	A-4b (V)	< >
		6	4	6	13	100	SS-4	3.75	-	-	-	-	-	-	-	-	27	A-4b (V)	< >
		7	4	6	13	100	SS-4	3.75	-	-	-	-	-	-	-	-	27	A-4b (V)	< >
	1079.7	EOB																< >	

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: PLACED 0.5 BAG ASPHALT PATCH; SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:12 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6-15 KENMORE\IGINT FILES\SUM-76-6-15 2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / J. HODGES</u>	DRILL RIG: <u>CME 55X</u>	STATION / OFFSET: <u>4+35, 23' LT.</u>	EXPLORATION ID <u>B-078-0-18</u>
TYPE: <u>ROADWAY</u>	SAMPLING FIRM / LOGGER: <u>NEAS / CHIPUKAIZER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>RAMP N</u>	
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>985.6 (MSL)</u> EOB: <u>10.5 ft.</u>	PAGE 1 OF 1
START: <u>4/30/19</u> END: <u>4/30/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>85</u>	LAT / LONG: <u>41.065507, -81.573407</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	985.6	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG				ODOT CLASS (GI)	BACK FILL	
									GR	CS	FS	SI	CL	LL	PL	PI	WC			
VERY STIFF TO HARD, BROWN BECOMING BROWN MOTTLED WITH REDDISH BROWN AND GRAY, SANDY SILT , LITTLE CLAY, LITTLE GRAVEL, DAMP			1																<< < > >>	
			2																<< < > >>	
			3	5	5	16	56	SS-1	4.5+	12	12	25	32	19	23	16	7	12	A-4a (3)	<< < > >>
			4		6															<< < > >>
			5																	<< < > >>
			6	2	6	21	78	SS-2	4.5+	12	14	25	31	18	23	15	8	12	A-4a (3)	<< < > >>
			7																	<< < > >>
			8	4	10	24	100	SS-3	4.5+	-	-	-	-	-	-	-	-	11	A-4a (V)	<< < > >>
			9		3															<< < > >>
		975.1		10	2	9	100	SS-4	2.00	-	-	-	-	-	-	-	-	15	A-4a (V)	<< < > >>

EOB

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:12 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6-15-2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / J. HODGES</u>	DRILL RIG: <u>CME 55X</u>	STATION / OFFSET: <u>7+31, 36' LT.</u>	EXPLORATION ID <u>B-079-0-18</u>
TYPE: <u>ROADWAY</u>	SAMPLING FIRM / LOGGER: <u>NEAS / CHIPUKAIZER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>RAMP N</u>	
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>976.9 (MSL)</u> EOB: <u>10.5 ft.</u>	PAGE 1 OF 1
START: <u>4/30/19</u> END: <u>4/30/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>85</u>	LAT / LONG: <u>41.066348, -81.573379</u>	


MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL	
								GR	CS	FS	SI	CL	LL	PL	PI				
LOOSE, GRAYISH BROWN BECOMING BROWN, COARSE AND FINE SAND , LITTLE TO SOME SILT, TRACE TO LITTLE GRAVEL, TRACE CLAY, WET	976.9																	<< < > >>	
		1																<< < > >>	
		2																<< < > >>	
		3	1	2	7	56	SS-1	-	-	-	-	-	-	-	-	20	A-3a (V)	<< < > >>	
		4																<< < > >>	
		5	2	2	7	100	SS-2	-	11	25	37	17	10	NP	NP	NP	17	A-3a (0)	<< < > >>
		6																<< < > >>	
		7																<< < > >>	
		8	1	2	6	50	SS-3	-	8	23	34	25	10	22	18	4	21	A-3a (0)	<< < > >>
		9																	<< < > >>
	966.4	10	2	6	100	SS-4	-	-	-	-	-	-	-	-	26	A-3a (V)	<< < > >>		
		EOB																<< < > >>	

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:12 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6-15 KENMORE\REIGNIT FILES\SUM-76-6-15 2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / J. HODGES</u>	DRILL RIG: <u>CME 55X</u>	STATION / OFFSET: <u>9+06, 27' LT.</u>	EXPLORATION ID <u>B-080-0-18</u>
TYPE: <u>SUBGRADE</u>	SAMPLING FIRM / LOGGER: <u>NEAS / CHIPUKAIZER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>RAMP N</u>	
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>979.3 (MSL)</u> EOB: <u>7.5 ft.</u>	PAGE 1 OF 1
START: <u>5/1/16</u> END: <u>5/1/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>85</u>	LAT / LONG: <u>41.066752, -81.572913</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL	
								GR	CS	FS	SI	CL	LL	PL	PI				
MEDIUM DENSE, DARK GRAY AND BROWN, GRAVEL AND STONE FRAGMENTS WITH SAND , LITTLE SILT, TRACE CLAY, DAMP	979.3		3																
	977.8	1	8	28	56	SS-1	-	26	27	26	13	8	NP	NP	NP	9	A-1-b (0)	< > < > < >	
		2	5	14	44	100	SS-2	-	10	26	34	18	12	NP	NP	NP	9	A-3a (0)	< > < > < >
MEDIUM DENSE TO DENSE, BROWN, COARSE AND FINE SAND , LITTLE SILT, LITTLE CLAY, TRACE GRAVEL, DAMP		3	14																
		4	3	9	33	67	SS-3	-	-	-	-	-	-	-	-	9	A-3a (V)	< > < > < >	
		5	5	7	23	100	SS-4	-	-	-	-	-	-	-	-	11	A-3a (V)	< > < > < >	
		6	3	9															
	971.8	7	5	13	100	SS-5	-	-	-	-	-	-	-	-	-	13	A-3a (V)	< > < > < >	
		EOB	4																



NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: SHOVELED SOIL CUTTINGS

STANDARD ODOT SOIL BORING LOG (8.5 X 11) - OH DOT.GDT - 7/29/19 09:12 - X:\ACTIVE PROJECTS\ACTIVE SOIL PROJECTS\SUM-76-6.15-2.GPJ

PROJECT: <u>SUM-76-06.15</u>	DRILLING FIRM / OPERATOR: <u>NEAS / J. HODGES</u>	DRILL RIG: <u>CME 55X</u>	STATION / OFFSET: <u>5+43, 7' RT.</u>	EXPLORATION ID <u>B-081-0-18</u>
TYPE: <u>SUBGRADE</u>	SAMPLING FIRM / LOGGER: <u>NEAS / CHIPUKAIZER</u>	HAMMER: <u>CME AUTOMATIC</u>	ALIGNMENT: <u>RAMP M</u>	PAGE 1 OF 1
PID: <u>100713</u> SFN: _____	DRILLING METHOD: <u>3.25" HSA</u>	CALIBRATION DATE: <u>11/21/17</u>	ELEVATION: <u>979.6 (MSL)</u> EOB: <u>7.5 ft.</u>	
START: <u>5/1/19</u> END: <u>5/1/19</u>	SAMPLING METHOD: <u>SPT</u>	ENERGY RATIO (%): <u>85</u>	LAT / LONG: <u>41.067521, -81.573746</u>	

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL	
								GR	CS	FS	SI	CL	LL	PL	PI				
MEDIUM DENSE, BROWN, COARSE AND FINE SAND , SOME GRAVEL AND STONE FRAGMENTS, TRACE CLAY, DAMP	979.6																		
	978.8	1	5			SS-1A	-	-	-	-	-	-	-	-	5	A-3a (V)	< > < >		
978.1	4		5	13	50	SS-1B	4.5+	15	17	28	21	19	28	16	12	A-6a (2)	< > < >		
HARD, DARK GRAY AND BROWN, SILT AND CLAY , "AND" SAND, LITTLE GRAVEL, DAMP		2	4	5	14	56	SS-2	3.25	4	14	22	30	30	36	17	19	18	A-6b (9)	< > < >
		3	3	5	10	100	SS-3	2.75	-	-	-	-	-	-	-	-	21	A-6b (V)	< > < >
STIFF TO VERY STIFF, BROWN MOTTLED WITH ORANGISH BROWN AND GRAY, SILTY CLAY , SOME TO "AND" SAND, TRACE GRAVEL, CONTAINS IRON STAINING, MOIST		4	4	4	7	100	SS-4	1.75	-	-	-	-	-	-	-	-	20	A-6b (V)	< > < >
	973.6	5	2	3	7	100	SS-4	1.75	-	-	-	-	-	-	-	-	20	A-6b (V)	< > < >
MEDIUM DENSE, BROWN, COARSE AND FINE SAND , LITTLE SILT, TRACE GRAVEL, TRACE CLAY, WET		6	3	3															
	972.1	7	3	5	11	56	SS-5	-	-	-	-	-	-	-	-	-	19	A-3a (V)	< > < >

EOB

NOTES: GROUNDWATER NOT ENCOUNTERED DURING DRILLING. HOLE DID NOT CAVE.
 ABANDONMENT METHODS, MATERIALS, QUANTITIES: SHOVELED SOIL CUTTINGS

APPENDIX C
SULFATE CONTENT DATA



OHIO DEPARTMENT OF TRANSPORTATION
DETERMINING SULFATE CONTENT IN SOILS
SUPPLEMENT 1122

Project C-R-S:	SUM-76-6.15
PID No:	100713
Report Date:	7/15/2019
Consultant:	NEAS Inc.
Technician:	L. Rosenbeck

Boring ID & Sample #	Station	Offset	Latitude & Longitude or State Plane Coordinates		Elevation	Soaking Time (hr)	Replicate Sample Readings						Sulfate Content (ppm)
							1		2		3		
							Dilution	Reading	Dilution	Reading	Dilution	Reading	
B-001-0-18 SS-1	210+67	52 L	41.061777	-81.570129	995.6	18.20	20	25	20	28	20	25	520
B-002-0-18 SS-1	207+22	50 R	41.062207	-81.571304	1002.1	19.80	20	20	20	19	20	19	387
B-003-0-18 SS-1	204+23	50 L	41.063006	-81.571741	999.8	18.22	20	7	20	7	20	7	140
B-004-0-18 SS-1	200+64	8 L	41.063742	-81.572600	1000.8	21.35	20	9	20	7	20	9	167
B-005-0-18 SS-1	196+37	7 L	41.064784	-81.573297	994.7	21.35	40	29	40	30	40	36	1267
B-006-0-18 SS-1	196+62	13 L	41.065496	-81.573614	987.9	21.37	40	71	40	65	40	63	2653
B-007-0-18 SS-1	189+75	74 L	41.066552	-81.573713	976.4	19.83	20	1	20	0	20	0	7
B-008-0-18 SS-1	181+94	76 L	41.068655	-81.573829	983.4	19.18	20	12	20	12	20	11	233
B-010-0-18 SS-1	173+98	60 L	41.070840	-81.573860	985.0	19.10	20	5	20	4	20	5	93
B-011-0-18 SS-1	170+00	60 L	41.071934	-81.573846	984.0	19.05	20	8	20	11	20	8	180
B-012-0-18 SS-1	165+85	59 L	41.073072	-81.573836	982.9	19.05	20	1	20	1	20	2	27
B-013-0-18 SS-1	161+79	60 L	41.074185	-81.573819	981.8	19.03	20	5	20	4	20	8	113
B-014-0-18 SS-2	157+96	60 L	41.075237	-81.573806	982.7	19.08	20	4	20	2	20	3	60
B-015-0-18 SS-1	154+04	73 L	41.076317	-81.573749	984.3	18.20	20	4	20	4	20	4	80
B-016-0-18 SS-1	150+15	60 L	41.077400	-81.573883	987.4	23.80	20	1	20	2	20	2	33
B-017-0-18 ST-1	149+98	94 L	41.077460	-81.573770	980.2	20.95	20	1	20	1	20	1	20
B-018-0-18 SS-2	146+83	59 L	41.078313	-81.574111	987.9	23.80	20	64	20	70	20	64	1320
B-019-0-18 SS-2	143+71	60 L	41.079148	-81.574449	988.2	19.17	20	0	20	0	20	0	0

B-020-0-18 SS-1	43+79	49 L	41.035695	-81.574353	1002.4	21.02	20	25	20	25	20	25	500
B-022-0-18 SS-1	47+81	68 L	41.035730	-81.572893	987.7	21.43	20	1	20	2	20	0	20
B-023-0-18 SS-1	51+80	49 L	41.035659	-81.571451	977.3	18.82	20	3	20	3	20	3	60
B-025-0-18 SS-2	55+67	60 L	41.035672	-81.570045	973.1	18.88	20	9	20	9	20	9	180
B-026-0-18 SS-2	58+92	72 L	41.035690	-81.568868	971.4	18.78	20	4	20	4	20	4	80
B-027-018 SS-1B	63+44	55 L	41.035623	-81.567231	969.8	21.38	20	3	20	0	20	1	27
B-028-0-18 SS-2	65+78	65 R	41.035283	-81.566391	972.9	19.20	20	0	20	0	20	0	0
B-029-0-18 SS-2	67+70	66 R	41.035262	-81.564969	973.9	18.90	20	0	20	0	20	1	7
B-030-0-18 SS-2	73+70	61 R	41.035256	-81.563520	975.7	18.83	20	0	20	0	20	0	0
B-032-0-18 SS-2	77+74	58 R	41.035245	-81.562054	976.8	18.97	20	1	20	1	20	0	13
B-033-0-18 SS-1	81+72	68 R	41.035201	-81.560613	976.8	23.82	20	0	20	0	20	0	0
B-035-0-18 SS-2	85+67	68 R	41.035183	-81.559182	978.6	17.92	40	28	40	31	40	28	1160
B-037-0-18 SS-2B	93+64	62 R	41.035162	-81.556293	983.3	19.17	20	1	20	1	20	1	20
B-038-0-18 SS-2	96+70	66 R	41.035125	-81.555196	985.1	18.00	20	17	20	14	20	18	327
B-039-0-18 SS-2	219+40	45 R	41.060352	-81.567580	997.5	23.78	20	15	20	13	20	14	280
B-040-0-18 SS-2	223+88	37 L	41.060208	-81.565940	1007.9	17.87	20	4	20	4	20	4	80
B-041-0-18 SS-1	227+78	10 L	41.059975	-81.564569	1022.7	21.35	20	14	20	19	20	17	333
B-042-0-18 SS-1	231+81	41 L	41.060028	-81.563111	1036.4	17.87	20	44	20	43	20	48	900
B-043-0-18 SS-2	234+79	43 L	41.060030	-81.562031	1047.6	17.87	20	22	20	18	20	20	400
B-044-0-18 SS-2			41.059881	-81.560305	1061.9	21.20	20	6	20	7	20	7	133
B-046-0-18 SS-1	247+75	52 R	41.059780	-81.557323	1068.9	17.87	20	57	20	60	20	59	1173
B-047-0-18 SS-1	251+65	53 R	41.059884	-81.555900	1063.6	17.87	20	66	20	70	20	73	1393
B-048-0-18 SS-1	256+17	70 R	41.060077	-81.554258	1050.6	21.35	20	2	20	3	20	1	40
B-049-0-18 SS-2	260+50	10 R	41.060544	-81.552909	1035.1	21.45	40	41	40	35	40	43	1587
B-050-0-18 SS-1	263+62	63 R	41.060686	-81.551665	1022.1	18.80	40	41	40	38	40	35	1520
B-051-0-18 SS-1	10+73	15 R	41.059555	-81.568264	1017.6	18.24	20	51	20	51	20	46	987
B-053-0-18 SS-1	4+17	30 L	41.061084	-81.569477	997.3	19.82	20	14	20	15	20	12	273
B-054-0-18 SS-1	94+72	25 R	41.060211	-81.568035	1016.2	17.87	20	21	20	20	20	18	393
B-056-0-18 SS-3	97+76	30 R	41.060971	-81.567787	1013.8	21.30	20	12	20	15	20	14	273
B-058-0-18 SS-1	106+50	1 R	41.061258	-81.565290	1008.0	18.93	20	1	20	2	20	2	33
B-059-0-18 SS-1	110+72	15 R	41.060386	-81.565883	1004.8	18.90	20	2	20	3	20	3	53
B-061-0-18 SS-1	215+87	54 L	41.060996	-81.568596	992.3	19.82	20	5	20	3	20	7	100
B-062-0-18 SS-1	2+43	28 L	41.034690	-81.567609	973.0	21.45	20	2	20	0	20	1	20

B-063-0-18 SS-1	10+02	57 L	41.034019	-81.566973	970.7	21.57	20	4	20	1	20	3	53
B-064-0-18 SS-1	14+79	63 L	41.034416	-81.565886	973.3	21.48	20	0	20	0	20	0	0
B-066-0-18 SS-2	17+39	30 L	41.035062	-81.565647	991.4	20.97	20	2	20	2	20	2	40
B-067-0-18 SS-2	8+40	5 R	41.058936	-81.567209	1019.4	17.42	20	26	20	22	20	23	473
B-068-0-18 SS-2B	12+37	19 R	41.059630	-81.566188	1012.1	17.95	40	39	40	39	40	35	1507
B-069-0-18 SS-1	16+94	19 R	41.059717	-81.564576	1024.3	17.95	20	0	20	2	20	0	13
B-071-0-18 SS-2	235+80	74 R	41.059709	-81.561666	1048.8	21.38	20	17	20	16	20	18	340
B-072-0-18 SS-1	99+85	38 L	41.061524	-81.567471	1017.6	21.00	20	4	20	3	20	4	73
B-073-0-18 SS-1	103+14	39 L	41.061843	-81.566284	1016.3	17.62	20	0	20	1	20	1	13
B-074-0-18 SS-1	18+11	7 R	41.061545	-81.565017	1015.2	17.32	20	0	20	1	20	1	13
B-075-0-18 SS-1	14+42	77 L	41.060670	-81.564256	1021.2	21.53	20	1	20	1	20	1	20
B-076-0-18 SS-1	10+85	59 L	41.060150	-81.563065	1036.2	21.52	20	56	20	61	20	53	1133
B-077-0-18 SS-1	4+70	22 L	41.059466	-81.557415	1079.5	18.80	20	11	20	11	20	11	220
B-077-1-18 SS-1			41.060756	-81.558959	1071.4	18.75	20	5	20	5	20	5	100
B-077-2-18 SS-1			41.061393	-81.558576	1082.8	18.72	20	11	20	12	20	12	233
B-077-3-18 SS-1			41.061127	-81.558151	1080.4	18.75	20	1	20	0	20	1	13
B-077-4-18 SS-1			41.060741	-81.557344	1087.2	18.78	20	11	20	9	20	10	200
B-078-0-18 SS-1	4+35	23 L	41.065507	-81.573407	985.6	18.23	20	32	20	29	20	33	627
B-079-0-18 SS-1	7+31	36 L	41.066348	-81.573379	976.9	19.82	20	3	20	1	20	2	40
B-080-0-18 SS-2	9+06	27 L	41.066752	-81.572913	979.3	17.72	20	1	20	2	20	2	33
B-081-0-18 SS-1A	5+43	7 R	41.067521	-81.573746	979.6	17.65	20	2	20	2	20	2	40

APPENDIX D

**GEOTECHNICAL BULLETIN 1 (GB1)
ANALYSIS SPREADSHEETS**

OHIO DEPARTMENT OF TRANSPORTATION

OFFICE OF GEOTECHNICAL ENGINEERING

**PLAN SUBGRADES
Geotechnical Bulletin GB1**

SUM-76-6.15

100713

Akron Beltway (Kenmore Leg) - Subgrade Exploration

IR-77/IR-76

NEAS inc

Prepared By: Erich R.G. Beyer
Date prepared: Tuesday, June 25, 2019

**Brendan P. Andrews
2868 East Kemper Road
Cincinnati, OH 45241**

**(920) 427-0671
brendan.andrews@neasinc.com**

NO. OF BORINGS: **33**

#	Boring ID	Alignment	Station	Offset	Dir	Drill Rig	ER	Boring EL.	Proposed Subgrade EL	Cut Fill
1	B-050-0-18	IR-77/IR-76	263+62	63	Rt	CME 55T		0.0	-1.5	1.5 C
2	B-049-0-18	IR-77/IR-76	260+50	10	Rt	CME 45B		0.0	-1.5	1.5 C
3	B-048-0-18	IR-77/IR-76	256+17	70	Rt	CME 55T		0.0	-1.5	1.5 C
4	B-047-0-18	IR-77/IR-76	251+65	53	Rt	CME 55T		0.0	-1.5	1.5 C
5	B-046-0-18	IR-77/IR-76	247+75	52	Rt	CME 55T		0.0	-1.5	1.5 C
6	B-045-0-18	IR-77/IR-76	243+80	66	Rt	CME 55T		0.0	-1.5	1.5 C
7	B-044-0-18	IR-77/IR-76	239+55	9	Rt	CME 45B		0.0	-1.5	1.5 C
8	B-043-0-18	IR-77/IR-76	234+79	43	Lt	CME 45B		0.0	-1.5	1.5 C
9	B-042-0-18	IR-77/IR-76	231+81	41	Lt	CME 45B		0.0	-1.5	1.5 C
10	B-041-0-18	IR-77/IR-76	227+78	10	Lt	CME 45B		0.0	-1.5	1.5 C
11	B-040-0-18	IR-77/IR-76	223+88	37	Lt	CME 45B		0.0	-1.5	1.5 C
12	B-039-0-18	IR-77/IR-76	219+40	45	Rt	CME 55T		0.0	-1.5	1.5 C
13	B-060-0-18	IR-77/IR-76	219+30	76	Lt	CME 55X		0.0	-1.5	1.5 C
14	B-061-0-18	IR-77/IR-76	215+87	54	Lt	CME 45B		0.0	-1.5	1.5 C
15	B-053-0-18	IR-77/IR-76	4+17	30	Lt	CME 45B		0.0	-1.5	1.5 C
16	B-001-0-18	IR-77/IR-76	210+67	52	Lt	CME 45B		0.0	-1.5	1.5 C
17	B-002-0-18	IR-77/IR-76	207+22	51	Rt	CME 45B		0.0	-1.5	1.5 C
18	B-003-0-18	IR-77/IR-76	204+23	50	Lt	CME 45B		0.0	-1.5	1.5 C
19	B-004-0-18	IR-77/IR-76	200+64	8	Lt	CME 45B		0.0	-1.5	1.5 C
20	B-005-0-18	IR-77/IR-76	196+37	7	Lt	CME 45B		0.0	-1.5	1.5 C
21	B-006-0-18	IR-77/IR-76	196+62	13	Lt	CME 45B		0.0	-1.5	1.5 C
22	B-007-0-18	IR-77/IR-76	189+75	74	Lt	CME 55X		0.0	-1.5	1.5 C
23	B-008-0-18	IR-77/IR-76	181+94	76	Lt	CME 55T		0.0	-1.5	1.5 C
24	B-009-0-18	IR-77/IR-76	177+99	66	Lt	CME 55T		0.0	-1.5	1.5 C
25	B-010-0-18	IR-77/IR-76	173+98	60	Lt	CME 55T		0.0	-1.5	1.5 C
26	B-011-0-18	IR-77/IR-76	170+00	60	Lt	CME 55T		0.0	-1.5	1.5 C
27	B-012-0-18	IR-77/IR-76	165+85	59	Lt	CME 55T		0.0	-1.5	1.5 C
28	B-013-0-18	IR-77/IR-76	161+79	60	Lt	CME 55T		0.0	-1.5	1.5 C
29	B-014-0-18	IR-77/IR-76	157+96	60	Lt	CME 55T		0.0	-1.5	1.5 C
30	B-015-0-18	IR-77/IR-76	154+04	73	Lt	CME 55X		0.0	-1.5	1.5 C
31	B-016-0-18	IR-77/IR-76	150+15	60	Lt	CME 55T		0.0	-1.5	1.5 C
32	B-018-0-18	IR-77/IR-76	146+83	59	Lt	CME 55T		0.0	-1.5	1.5 C
33	B-019-0-18	IR-77/IR-76	143+71	60	Lt	CME 55T		0.0	-1.5	1.5 C

#	Boring	Sample	Sample Depth		Subgrade Depth		Standard Penetration		HP (tsf)	Physical Characteristics					Moisture		Ohio DOT		Sulfate Content (ppm)	Problem		Excavate and Replace (Item 204)		Recommendation (Enter depth in inches)		
			From	To	From	To	N ₆₀	N _{60L}		LL	PL	PI	% Silt	% Clay	P200	M _c	M _{OPT}	Class		GI	Unsuitable	Unstable	Unsuitable		Unstable	
1	B 050-0 18	SS-1	2.5	4.0	1.0	2.5	26	17		22	15	7	35	17	52	8	10	A-4a	3	1520						
		SS-2	5.0	6.5	3.5	5.0	17			27	18	9	44	24	68	14	13	A-4a	7							
		SS-3	7.5	9.0	6.0	7.5	36																			
		SS-4	10.0	11.5	8.5	10.0	42									9	10	A-4a								
2	B 049-0 18	SS-1	1.5	3.0	0.0	1.5	21	14	4.5	23	16	7	35	21	56	10	11	A-4a	4							
		SS-2	3.0	4.5	1.5	3.0	25		4.5	24	17	7	38	20	58	10	12	A-4a	5	1587						
		SS-3	4.5	6.0	3.0	4.5	15		4							15	10	A-4a	8							
		SS-4	6.0	7.5	4.5	6.0	14		3.75							13	10	A-4a	8							
3	B 048-0 18	SS-1	0.0	1.5	-1.5	0.0	10	30	4.5							11	10	A-4a	8	40						
		SS-2	2.5	4.0	1.0	2.5	109									0	Rock	0			Rock		30"			
		SS-3	5.0	5.9	3.5	4.4										0	Rock	0								
		SS-4	7.5	9.0	6.0	7.5	73									0	Rock									
4	B 047-0 18	SS-1	2.5	5.4	1.0	3.9	39	30	4.5	21	15	6	33	22	55	9	10	A-4a	4	1393						
		SS-2B	5.4	6.5	3.9	5.0	57									5	6	A-1-b	0							
		SS-3	7.5	8.0	6.0	6.5										0	Rock									
		SS-4	10.0	10.4	8.5	8.9										0	Rock									
5	B 046-0 18	SS-1	1.5	3.0	0.0	1.5	18	18	4.5	24	18	6	47	20	67	8	13	A-4a	6	1173						
		SS-2	3.0	4.5	1.5	3.0	43									7	8	A-3a	0							
		SS-3	4.5	6.0	3.0	4.5	25		4.5	29	18	11	43	23	66	8	14	A-6a	7							
		SS-4	6.0	7.5	4.5	6.0	29		4.5							10	14	A-6a	10							
6	B 045-0 18	SS-1	2.5	3.0	1.0	1.5		30								0	Rock	0			Rock		N ₆₀	18"	0"	
		SS-2	5.0	5.5	3.5	4.0										0	Rock	0								
		SS-3	7.5	9.0	6.0	7.5	64									0	Rock									
		SS-4	10.0	11.5	8.5	10.0	60									0	Rock									
7	B 044-0 18	SS-1	1.5	3.0	0.0	1.5	13	13	4.5							14	14	A-6a	10							
		SS-2	3.0	4.5	1.5	3.0	24		4.5	35	21	14	43	40	83	16	16	A-6a	10	133						
		SS-3	4.5	6.0	3.0	4.5	21		4.5	34	23	11	45	35	80	10	18	A-6a	8							
		SS-4	6.0	7.5	4.5	6.0	29		4.5							16	14	A-6a	10							
8	B 043-0 18	SS-1	1.5	3.0	0.0	1.5	95	22		23	17	6	17	12	29	10	10	A-2-4	0							
		SS-2	3.0	4.5	1.5	3.0	22		4.5	25	18	7	31	22	53	11	13	A-4a	4	400						
		SS-3	4.5	6.0	3.0	4.5	95		4.5							12	10	A-4a	8							
		SS-4	6.0	7.5	4.5	6.0	60		4.5							11	10	A-4a	8							
9	B 042-0 18	SS-1	1.5	3.0	0.0	1.5	85		4.5	23	16	7	23	16	39	9	11	A-4a	1	900						
		SS-2	3.0	4.5	1.5	3.0	88									4	6	A-1-b	0							
		SS-3	4.5	6.0	3.0	4.5	52		4.5	23	15	8	36	25	61	10	10	A-4a	5							

#	Boring	Sample	Sample Depth		Subgrade Depth		Standard Penetration		HP (tsf)	Physical Characteristics					Moisture		Ohio DOT		Sulfate Content (ppm)	Problem		Excavate and Replace (Item 204)		Recommendation (Enter depth in inches)	
			From	To	From	To	N ₆₀	N _{60L}		LL	PL	PI	% Silt	% Clay	P200	M _c	M _{OPT}	Class		GI	Unsuitable	Unstable	Unsuitable		Unstable
		SS-4	6.0	6.5	4.5	5.0		30	4.5							7	10	A-4a	8						
10	B 041-0 18	SS-1	1.5	3.0	0.0	1.5	29								5	6	A-1-b	0	333						
		SS-2	3.0	3.1	1.5	1.6									0		Rock	0		Rock	N ₆₀				
		SS-3	4.5	4.6	3.0	3.1									0		Rock	0			N ₆₀				
		SS-4	6.0	6.1	4.5	4.6		29							0		Rock	0							
11	B 040-0 18	SS-1	1.5	3.0	0.0	1.5	28							9	10	A-4a	8								
		SS-2	3.0	4.5	1.5	3.0	42		NP	NP	NP	19	14	33	8	8	A-3a	0	80						
		SS-3	4.5	6.0	3.0	4.5	105							8	8	A-3a	0								
		SS-4	6.0	7.5	4.5	6.0	98	28		NP	NP	NP	26	18	44	7	11	A-4a	2						
12	B 039-0 18	SS-1	1.5	3.0	0.0	1.5	22		4.5	23	15	8	21	16	37	9	10	A-4a	0						
		SS-2	3.0	4.5	1.5	3.0	20		4.5							11	10	A-4a	8	280					
		SS-3	4.5	6.0	3.0	4.5	21		4	27	17	10	32	24	56	14	12	A-4a	4						
		SS-4	6.0	7.5	4.5	6.0	17	17		3.5						13	10	A-4a	8						
13	B 060-0 18	SS-1	2.5	4.0	1.0	2.5	30		2.5	23	17	6	18	12	30	11	10	A-2-4	0						
		SS-2	5.0	6.5	3.5	5.0	17		2.5							11	10	A-4a	8						
		SS-3	7.5	9.0	6.0	7.5	13		2.5	22	15	7	29	19	48	12	10	A-4a							
		SS-4	10.0	11.5	8.5	10.0	26	13		4.5						9	10	A-4a							
14	B 061-0 18	SS-1	1.5	3.0	0.0	1.5	49			NP	NP	NP	16	12	28	6	10	A-2-4	0	100					
		SS-2	3.0	4.5	1.5	3.0	32		4.5	21	15	6	22	15	37	8	10	A-4a	0						
		SS-3	4.5	6.0	3.0	4.5	35		4.5							9	10	A-4a	8						
		SS-4	6.0	7.5	4.5	6.0	21	21		4.5						13	10	A-4a	8						
15	B 053-0 18	SS-1	1.5	3.0	0.0	1.5	11		4.5	23	17	6	41	24	65	13	12	A-4a	6	273		N ₆₀		12"	
		SS-2	3.0	4.5	1.5	3.0	17		4.5							16	10	A-4a	8		Mc				
		SS-3	4.5	6.0	3.0	4.5	15		4.5	28	19	9	43	32	75	15	14	A-4a	8						
		SS-4	6.0	7.5	4.5	6.0	36	11								6	10	A-2-4	0						
16	B 001-0 18	SS-1	1.5	3.0	0.0	1.5	24			NP	NP	NP	11	6	17	10	8	A-3a	0	520					
		SS-2	3.0	4.5	1.5	3.0	11									10	8	A-3a	0						
		SS-3	4.5	6.0	3.0	4.5	14		2.25	28	18	10	38	23	61	15	13	A-4a	5						
		SS-4	6.0	7.5	4.5	6.0	21	11		4.25						17	10	A-4a	8						
17	B 002-0 18	SS-1	1.5	3.0	0.0	1.5	7		0.75							17	14	A-6a	10	387		HP & Mc		18"	
		SS-2	3.0	4.5	1.5	3.0	34			NP	NP	NP	14	12	26	6	10	A-2-4	0						
		SS-3	4.5	6.0	3.0	4.5	35			19	13	6	17	14	31	8	10	A-2-4	0						
		SS-4	6.0	7.5	4.5	6.0	49	7								5	10	A-2-4	0						
18	B 003-0	SS-1	1.5	3.0	0.0	1.5	38								7	10	A-2-4	0	140						
		SS-2	3.0	4.5	1.5	3.0	39			17	13	4	18	13	31	5	10	A-2-4	0						

#	Boring	Sample	Sample Depth		Subgrade Depth		Standard Penetration		HP (tsf)	Physical Characteristics					Moisture		Ohio DOT		Sulfate Content (ppm)	Problem		Excavate and Replace (Item 204)		Recommendation (Enter depth in inches)	
			From	To	From	To	N ₆₀	N _{60L}		LL	PL	PI	% Silt	% Clay	P200	M _c	M _{OPT}	Class		GI	Unsuitable	Unstable	Unsuitable		Unstable
	18	SS-3	4.5	6.0	3.0	4.5	34	27		NP	NP	NP	13	10	23	5	10	A-2-4	0						
		SS-4	6.0	7.5	4.5	6.0	27									4	10	A-2-4	0						
19	B 004-0 18	SS-1	1.5	3.0	0.0	1.5	15	15		29	19	10	24	15	39	14	14	A-4a	1	167					
		SS-2	3.0	4.5	1.5	3.0	36									16	14	A-6a	10						
		SS-3	4.5	6.0	3.0	4.5	34			29	18	11	38	26	64	16	14	A-6a	6						
		SS-4	6.0	7.5	4.5	6.0	27									16	14	A-6a	10						
20	B 005-0 18	SS-1	1.5	3.0	0.0	1.5	27	25		NP	NP	NP	6	2	8	9	6	A-1-a	0	1267					
		SS-2	3.0	4.5	1.5	3.0	25									7	6	A-1-a	0						
		SS-3	4.5	6.0	3.0	4.5	29									7	6	A-1-a	0						
		SS-4	6.0	7.5	4.5	6.0	27			25	18	7	24	14	38	12	13	A-4a	1						
21	B 006-0 18	SS-1	1.5	3.0	0.0	1.5	21	15		NP	NP	NP	5	2	7	11	6	A-1-a	0	2653					
		SS-2	3.0	4.5	1.5	3.0	28									8	6	A-1-a	0						
		SS-3	4.5	6.0	3.0	4.5	15									8	6	A-1-a	0						
		SS-4	6.0	7.5	4.5	6.0	22			24	17	7	21	20	41	21	12	A-4a	1						
22	B 007-0 18	SS-1	2.5	4.0	1.0	2.5	9	7								14	8	A-3a	0	7					
		SS-2	5.0	6.5	3.5	5.0	7			NP	NP	NP	17	11	28	16	8	A-3a	0						
		SS-3	7.5	9.0	6.0	7.5	10									17	8	A-3a							
		SS-4	9.0	10.5	7.5	9.0	10			NP	NP	NP	61	8	69	21	11	A-4b							
23	B 008-0 18	SS-1	0.0	1.5	-1.5	0.0	18	12								9	10	A-2-4	0	233					
		SS-2	2.5	4.0	1.0	2.5	13			2.25	25	14	11	22	17	39	13	14	A-6a	1					
		SS-3	5.0	6.5	3.5	5.0	21			4.5							11	10	A-4a	8					
		SS-4	7.5	9.0	6.0	7.5	12			4.5	23	15	8	24	16	40	16	10	A-4a						
24	B 009-0 18	SS-1	0.0	0.3	-1.5	-1.2		14								7	10	A-2-4	0						
		SS-2	2.5	4.0	1.0	2.5	16			4.5	20	17	3	18	12	30	12	8	A-3a	0					
		SS-3	5.0	6.5	3.5	5.0	17			2.75	21	14	7	29	19	48	13	10	A-4a	3					
		SS-4	7.5	9.0	6.0	7.5	14										15	10	A-4a						
25	B 010-0 18	SS-1	0.0	1.5	-1.5	0.0	31	16								12	10	A-2-4	0	93					
		SS-2	2.5	4.0	1.0	2.5	18			2	23	16	7	26	17	43	15	11	A-4a	2		Mc			
		SS-3	5.0	6.5	3.5	5.0	18				22	17	5	21	11	32	14	10	A-2-4	0					
		SS-4	7.5	9.0	6.0	7.5	16			3							16	10	A-4a						
26	B 011-0 18	SS-1	0.0	1.5	-1.5	0.0	34	9		4.5						9	10	A-4a	8	180					
		SS-2	2.5	4.0	1.0	2.5	23			3	25	19	6	29	15	44	16	14	A-4a	2					
		SS-3	5.0	6.5	3.5	5.0	9			4	25	16	9	22	16	38	14	11	A-4a	1					
		SS-4	7.5	9.0	6.0	7.5	12			3.25							16	10	A-4a						
27	B	SS-1	0.0	1.5	-1.5	0.0	30		4.25						11	10	A-4a	8	27						

#	Boring	Sample	Sample Depth		Subgrade Depth		Standard Penetration		HP (tsf)	Physical Characteristics					Moisture		Ohio DOT		Sulfate Content (ppm)	Problem		Excavate and Replace (Item 204)		Recommendation (Enter depth in inches)		
			From	To	From	To	N ₆₀	N _{60L}		LL	PL	PI	% Silt	% Clay	P200	M _c	M _{OPT}	Class		GI	Unsuitable	Unstable	Unsuitable		Unstable	
	012-0	SS-2	2.5	4.0	1.0	2.5	23	16	4.25	21	14	7	23	15	38	10	10	A-4a	1							
		18	SS-3	5.0	6.5	3.5	5.0		17	1.25	26	20	6	27	14	41	18	15	A-4a	1						
			SS-4	7.5	9.0	6.0	7.5		16	2							17	10	A-4a							
28	B	SS-1	0.0	1.5	-1.5	0.0	25	9								13	10	A-2-4	0	113						
		013-0	SS-2	2.5	4.0	1.0	2.5		23		NP	NP	NP	9	5	14	7	10	A-2-4	0						
		18	SS-3	5.0	6.5	3.5	5.0		36		NP	NP	NP	8	6	14	8	10	A-2-4	0						
			SS-4	7.5	9.0	6.0	7.5		9							17	8	A-3a								
29	B	SS-1	0.0	1.5	-1.5	0.0	16	10	1.25	25	15	10	30	19	49	16	10	A-4a	3							
		014-0	SS-2	2.5	4.0	1.0	2.5		10							12	8	A-3a	0	60						
		18	SS-3	5.0	6.5	3.5	5.0		12		23	18	5	18	11	29	15	8	A-3a	0						
			SS-4	7.5	9.0	6.0	7.5		12							18	8	A-3a								
30	B	SS-1	2.5	4.0	1.0	2.5	23	6	3	25	15	10	24	16	40	13	10	A-4a	1	80		Mc				
		015-0	SS-2	5.0	6.5	3.5	5.0		7	2.5	27	17	10	28	18	46	15	12	A-4a	2						
		18	SS-3	7.5	9.0	6.0	7.5		6							21	8	A-3a								
			SS-4	9.0	10.5	7.5	9.0		7							20	8	A-3a								
31	B	SS-1	0.0	1.5	-1.5	0.0	22	30		NP	NP	NP	12	6	18	11	10	A-2-4	0	33						
		016-0	SS-2	2.5	4.0	1.0	2.5		51		NP	NP	NP	16	9	25	8	6	A-1-b	0						
		18	SS-3	5.0	6.5	3.5	5.0		42							15	6	A-1-b	0							
			SS-4	7.5	9.0	6.0	7.5		60							7	6	A-1-b								
32	B	SS-1	0.0	1.5	-1.5	0.0	22	23		20	17	3	18	12	30	9	10	A-2-4	0							
		018-0	SS-2	2.5	4.0	1.0	2.5		25	2.5						12	10	A-4a	8	1320						
		18	SS-3	5.0	6.5	3.5	5.0		23	3.5						13	10	A-4a	8							
			SS-4	7.5	9.0	6.0	7.5		38							9	10	A-2-4								
33	B	SS-1	0.0	1.5	-1.5	0.0	21	20		21	16	5	19	12	31	11	10	A-2-4	0							
		019-0	SS-2	2.5	4.0	1.0	2.5		46							8	6	A-1-b	0	0						
		18	SS-3	5.0	6.5	3.5	5.0		55							6	6	A-1-b	0							
			SS-4	7.5	9.0	6.0	7.5		20							12	6	A-1-b								

PID: 100713

County-Route-Section: SUM-76-6.15

No. of Borings: 33

Geotechnical Consultant: NEAS inc

Prepared By: Erich R.G. Beyer

Date prepared: 6/25/2019

Chemical Stabilization Options		
320	Rubblize & Roll	Option
206	Cement Stabilization	Option
	Lime Stabilization	No
206	Depth	NA

Excavate and Replace Stabilization Options	
Global Geotextile Average(N60L): Average(HP):	0" 0"
Global Geogrid Average(N60L): Average(HP):	0" 0"

Design CBR	9
-----------------------	----------

% Samples within 6 feet of subgrade			
$N_{60} \leq 5$	0%	$HP \leq 0.5$	0%
$N_{60} < 12$	10%	$0.5 < HP \leq 1$	1%
$12 \leq N_{60} < 15$	9%	$1 < HP \leq 2$	3%
$N_{60} \geq 20$	61%	$HP > 2$	41%
M+	3%		
Rock	5%		
Unsuitable	11%		


Excavate and Replace at Surface	
Average	0"
Maximum	0"
Minimum	0"

% Proposed Subgrade Surface	
Unstable & Unsuitable	18%
Unstable	13%
Unsuitable	5%

	N_{60}	N_{60L}	HP	LL	PL	PI	Silt	Clay	P 200	M_C	M_{OPT}	GI
Average	30	18	3.75	24	17	8	26	17	43	12	9	3
Maximum	109	30	4.50	35	23	14	61	40	83	21	18	10
Minimum	6	6	0.75	17	13	3	5	2	7	4	0	0

Classification Counts by Sample																			
ODOT Class	Rock	A-1-a	A-1-b	A-2-4	A-2-5	A-2-6	A-2-7	A-3	A-3a	A-4a	A-4b	A-5	A-6a	A-6b	A-7-5	A-7-6	A-8a	A-8b	Totals
Count	12	6	9	15	0	0	0	0	15	51	1	0	11	0	0	0	0	0	120
Percent	10%	5%	8%	13%	0%	0%	0%	0%	13%	43%	1%	0%	9%	0%	0%	0%	0%	0%	100%
% Rock Granular Cohesive	10%	80%										10%							100%
Surface Class Count	3	4	4	14	0	0	0	0	7	23	0	0	5	0	0	0	0	0	60
Surface Class Percent	5%	7%	7%	23%	0%	0%	0%	0%	12%	38%	0%	0%	8%	0%	0%	0%	0%	0%	100%

GB1 Figure B – Subgrade Stabilization



OVERRIDE TABLE

Calculated Average	New Values	Check to Override
3.75		<input type="checkbox"/> HP
18.03		<input type="checkbox"/> N60L

Average HP —
 Average N_{60L} —

OHIO DEPARTMENT OF TRANSPORTATION

OFFICE OF GEOTECHNICAL ENGINEERING

**PLAN SUBGRADES
Geotechnical Bulletin GB1**

**SUM-76-6.15
100713**

**Akron Beltway (Kenmore Leg) - Subgrade Exploration
IR-277**

NEAS inc

Prepared By: Erich R.G. Beyer
Date prepared: Tuesday, June 25, 2019

**Brendan P. Andrews
2868 East Kemper Road
Cincinnati, OH 45241**

**(920) 427-0671
brendan.andrews@neasinc.com**

NO. OF BORINGS: 16

#	Boring ID	Alignment	Station	Offset	Dir	Drill Rig	ER	Boring EL.	Proposed Subgrade EL	Cut Fill
1	B-020-0-18	IR-277	43+79	49	Lt	CME 45B		0.0	-1.5	1.5 C
2	B-022-0-18	IR-277	47+81	68	Lt	CME 55X		0.0	-1.5	1.5 C
3	B-023-0-18	IR-277	51+80	49	Lt	CME 45B		0.0	-1.5	1.5 C
4	B-025-0-18	IR-277	55+67	60	Lt	CME 45B		0.0	-1.5	1.5 C
5	B-026-0-18	IR-277	58+92	72	Lt	CME 45B		0.0	-1.5	1.5 C
6	B-027-0-18	IR-277	63+44	55	Lt	CME 55X		0.0	-1.5	1.5 C
7	B-028-0-18	IR-277	65+78	65	Rt	CME 55X		0.0	-1.5	1.5 C
8	B-029-0-18	IR-277	69+70	66	Rt	CME 55T		0.0	-1.5	1.5 C
9	B-030-0-18	IR-277	73+70	61	Rt	CME 55T		0.0	-1.5	1.5 C
10	B-031-0-18	IR-277	75+72	61	Rt	CME 55T		0.0	-1.5	1.5 C
11	B-032-0-18	IR-277	77+74	58	Rt	CME 55T		0.0	-1.5	1.5 C
12	B-033-0-18	IR-277	81+72	68	Rt	CME 55X		0.0	-1.5	1.5 C
13	B-035-0-18	IR-277	85+67	68	Rt	CME 55X		0.0	-1.5	1.5 C
14	B-036-0-18	IR-277	89+69	67	Rt	CME 55X		0.0	-1.5	1.5 C
15	B-037-0-18	IR-277	93+64	62	Rt	CME 55X		0.0	-1.5	1.5 C
16	B-038-0-18	IR-277	96+70	66	Rt	CME 55X		0.0	-1.5	1.5 C

#	Boring	Sample	Sample Depth		Subgrade Depth		Standard Penetration		HP (tsf)	Physical Characteristics					Moisture		Ohio DOT		Sulfate Content (ppm)	Problem		Excavate and Replace (Item 204)		Recommendation (Enter depth in inches)	
			From	To	From	To	N ₆₀	N _{60L}		LL	PL	PI	% Silt	% Clay	P200	M _c	M _{OPT}	Class		GI	Unsuitable	Unstable	Unsuitable		Unstable
		SS-4	10.0	11.5	8.5	10.0	5	7							25	8	A-3								
10	B 031-0 18	SS-1	0.0	1.5	-1.5	0.0	10			22	19	3	57	12	69	18	14	A-4b	7						
		SS-2	2.5	4.0	1.0	2.5	8			NP	NP	NP	7	5	12	19	8	A-3a	0						
		SS-3	5.0	6.5	3.5	5.0	3									24	8	A-3	0						
		SS-4	7.5	9.0	6.0	7.5	0	0			NP	NP	NP	7	3	10	26	8	A-3						
11	B 032-0 18	SS-1	0.0	1.5	-1.5	0.0	9			NP	NP	NP	10	4	14	10	8	A-3a	0						
		SS-2	2.5	4.0	1.0	2.5	8								15	8	A-3a	0	13						
		SS-3	5.0	6.5	3.5	5.0	5								17	8	A-3a	0							
		SS-4	7.5	9.0	6.0	7.5	0	0							19	8	A-3a								
12	B 033-0 18	SS-1	2.5	4.0	1.0	2.5	9								19	8	A-3a	0	0						
		SS-2	5.0	6.5	3.5	5.0	4		0.5	NP	NP	NP	35	9	44	40	11	A-4a	2						
		SS-3	7.5	9.0	6.0	7.5	0		0						40	10	A-4a								
		SS-4	10.0	11.5	8.5	10.0	0	0		NP	NP	NP	9	6	15	18	8	A-3a							
13	B 035-0 18	SS-1	2.5	4.0	1.0	2.5	11			NP	NP	NP	71	11	82	24	11	A-4b	8		A-4b	N ₆₀ & Mc	30"	12"	
		SS-2	5.0	6.5	3.5	5.0	6		2	25	21	4	44	12	56	20	16	A-4a	4	1160					
		SS-3	7.5	9.0	6.0	7.5	4		1.25						24	10	A-4a								
		SS-4	10.0	11.5	8.5	10.0	17	4		NP	NP	NP	15	10	25	16	8	A-3a							
14	B 036-0 18	SS-1	2.5	4.0	1.0	2.5	14			NP	NP	NP	81	13	94	29	11	A-4b	8		A-4b	N ₆₀ & Mc	30"	12"	
		SS-2	5.0	6.5	3.5	5.0	9			NP	NP	NP	79	12	91	27	11	A-4b	8						
		SS-3	7.5	11.2	6.0	9.7	14								11	8	A-3a								
		SS-4B	11.2	11.5	9.7	10.0	14	9		3					21	10	A-4a								
15	B 037-0 18	SS-1	2.5	4.0	1.0	2.5	35			NP	NP	NP	79	17	96	19	11	A-4b	8		A-4b	Mc	30"		
		SS-2A	5.0	6.0	3.5	4.5	14								8	8	A-3a	0							
		SS-2B	6.0	6.5	4.5	5.0	14								20	10	A-4a	8	20						
		SS-3	7.5	9.0	6.0	7.5	20	14		NP	NP	NP	49	10	59	17	11	A-4a							
16	B 038-0 18	SS-1	2.5	4.0	1.0	2.5	28		4.5	19	15	4	29	14	43	12	10	A-4a	2						
		SS-2	5.0	6.5	3.5	5.0	21		3						14	10	A-4a	8	327						
		SS-3	7.5	9.0	6.0	7.5	9		3.75						19	10	A-4a								
		SS-4	10.0	11.5	8.5	10.0	7	9		2.75	35	26	9	75	24	99	29	21	A-4b						

PID: 100713

County-Route-Section: SUM-76-6.15

No. of Borings: 16

Geotechnical Consultant: NEAS inc

Prepared By: Erich R.G. Beyer

Date prepared: 6/25/2019

Chemical Stabilization Options		
320	Rubblize & Roll	No
206	Cement Stabilization	Option
	Lime Stabilization	No
206	Depth	14"

Excavate and Replace Stabilization Options	
Global Geotextile Average(N60L): Average(HP):	15" 0"
Global Geogrid Average(N60L): Average(HP):	0" 0"

Design CBR	9
-----------------------	----------

% Samples within 6 feet of subgrade			
$N_{60} \leq 5$	20%	$HP \leq 0.5$	4%
$N_{60} < 12$	57%	$0.5 < HP \leq 1$	0%
$12 \leq N_{60} < 15$	16%	$1 < HP \leq 2$	4%
$N_{60} \geq 20$	20%	$HP > 2$	10%
M+	12%		
Rock	0%		
Unsuitable	11%		


Excavate and Replace at Surface	
Average	0"
Maximum	0"
Minimum	0"

% Proposed Subgrade Surface	
Unstable & Unsuitable	43%
Unstable	29%
Unsuitable	14%

	N_{60}	N_{60L}	HP	LL	PL	PI	Silt	Clay	P 200	M_C	M_{OPT}	GI
Average	12	7	2.58	28	20	8	30	10	40	18	9	3
Maximum	35	27	4.50	35	26	14	89	41	99	40	21	10
Minimum	0	0	0.00	19	15	3	3	3	7	3	6	0

Classification Counts by Sample																			
ODOT Class	Rock	A-1-a	A-1-b	A-2-4	A-2-5	A-2-6	A-2-7	A-3	A-3a	A-4a	A-4b	A-5	A-6a	A-6b	A-7-5	A-7-6	A-8a	A-8b	Totals
Count	0	0	5	0	0	0	0	14	21	13	7	0	2	0	0	0	0	0	62
Percent	0%	0%	8%	0%	0%	0%	0%	23%	34%	21%	11%	0%	3%	0%	0%	0%	0%	0%	100%
% Rock Granular Cohesive	0%	85%										15%							100%
Surface Class Count	0	0	1	0	0	0	0	1	11	3	4	0	1	0	0	0	0	0	21
Surface Class Percent	0%	0%	5%	0%	0%	0%	0%	5%	52%	14%	19%	0%	5%	0%	0%	0%	0%	0%	100%

GB1 Figure B – Subgrade Stabilization



OVERRIDE TABLE

Calculated Average	New Values	Check to Override
2.58		<input type="checkbox"/> HP
7.25		<input type="checkbox"/> N60L

Average HP —
Average N_{60L} —

OHIO DEPARTMENT OF TRANSPORTATION

OFFICE OF GEOTECHNICAL ENGINEERING

PLAN SUBGRADES
Geotechnical Bulletin GB1

SUM-76-6.15
100713

Akron Beltway (Kenmore Leg) - Subgrade Exploration
Ramp B and Ramp A2

NEAS inc

Prepared By: Erich R.G. Beyer
Date prepared: Tuesday, June 25, 2019


Brendan P. Andrews
2868 East Kemper Road
Cincinnati, OH 45241

(920) 427-0671
brendan.andrews@neasinc.com

NO. OF BORINGS: **6**

#	Boring ID	Alignment	Station	Offset	Dir	Drill Rig	ER	Boring EL.	Proposed Subgrade EL.	Cut Fill
1	B-029-0-18	Ramp B	10+53	12	Rt	CME 55T		0.0	-1.5	1.5 C
2	B-028-0-18	Ramp B	6+60	3	Rt	CME 55X		0.0	-1.5	1.5 C
3	B-062-0-18	Ramp B	2+43	28	Lt	CME 55X		0.0	-1.5	1.5 C
4	B-063-0-18	Ramp A2	10+02	57	Lt	CME 55X		0.0	-1.5	1.5 C
5	B-064-0-18	Ramp A2	14+79	63	Lt	CME 55X		0.0	-1.5	1.5 C
6	B-066-0-18	Ramp A2	17+39	30	Lt	CME 45B		0.0	-1.5	1.5 C

GB1 Figure B – Subgrade Stabilization



OVERRIDE TABLE

Calculated Average	New Values	Check to Override
		<input type="checkbox"/> HP
4.50		<input type="checkbox"/> N60L

Average HP —
Average N_{60L} —

OHIO DEPARTMENT OF TRANSPORTATION

OFFICE OF GEOTECHNICAL ENGINEERING

**PLAN SUBGRADES
Geotechnical Bulletin GB1**

**SUM-76-6.15
100713**

**Akron Beltway (Kenmore Leg) - Subgrade Exploration
Ramp J**

NEAS inc

Prepared By: Erich R.G. Beyer
Date prepared: Tuesday, June 25, 2019

**Brendan P. Andrews
2868 East Kemper Road
Cincinnati, OH 45241


(920) 427-0671
brendan.andrews@neasinc.com**

NO. OF BORINGS: **5**

#	Boring ID	Alignment	Station	Offset	Dir	Drill Rig	ER	Boring EL.	Proposed Subgrade EL	Cut Fill
1	B-045-1-18	Ramp J				CME 55T		1.5	0.0	1.5 C
2	B-077-1-18	Ramp J				CME 55T		1.5	0.0	1.5 C
3	B-077-2-18	Ramp J				CME 55T		1.5	0.0	1.5 C
4	B-077-3-18	Ramp J				CME 55T		1.5	0.0	1.5 C
5	B-077-4-18	Ramp J				CME 55T		1.5	0.0	1.5 C

#	Boring	Sample	Sample Depth		Subgrade Depth		Standard Penetration		HP (tsf)	Physical Characteristics					Moisture		Ohio DOT		Sulfate Content (ppm)	Problem		Excavate and Replace (Item 204)		Recommendation (Enter depth in inches)			
			From	To	From	To	N ₆₀	N _{60L}		LL	PL	PI	% Silt	% Clay	P200	M _c	M _{OPT}	Class		GI	Unsuitable	Unstable	Unsuitable		Unstable		
1	B 045-1 18	SS-1	1.5	3.0	0.0	1.5	40	30								0	0	Rock	0		Rock						
		SS-2	3.0	4.5	1.5	3.0	60									0	0	Rock	0		Rock			36"			
		SS-3	4.5	5.5	3.0	4.0										0	0	Rock	0								
		SS-4	6.0	6.7	4.5	5.2										0	0	Rock	0								
2	B 077-1 18	SS-1	1.5	3.0	0.0	1.5	21	21		19	15	4	23	11	34	9	10	A-2-4	0	100							
		SS-2	3.0	4.5	1.5	3.0	51			NP	NP	NP	21	9	30	7	8	A-3a	0								
		SS-3	4.5	6.0	3.0	4.5	34									6	8	A-3a	0								
		SS-4	6.0	7.5	4.5	6.0	44		4.5							10	10	A-4a	8								
3	B 077-2 18	SS-1	1.5	3.0	0.0	1.5	14	13	4.25	27	17	10	47	29	76	14	12	A-4a	8	233							
		SS-2	3.0	4.5	1.5	3.0	18		4.25	26	18	8	38	21	59	17	13	A-4a	5			Mc					
		SS-3	4.5	6.0	3.0	4.5	16		4.25							16	10	A-4a	8								
		SS-4	6.0	7.5	4.5	6.0	13		4							17	10	A-4a	8								
4	B 077-3 18	SS-1	1.5	3.5	0.0	2.0	9	9		NP	NP	NP	4	4	8	6	6	A-1-b	0	13							
		SS-2B	3.5	4.5	2.0	3.0	10		4.25							18	10	A-4b	8		A-4b	N ₆₀ & Mc					
		SS-3	4.5	6.0	3.0	4.5	13		4.25	22	18	4	58	15	73	19	13	A-4b	8								
		SS-4	6.0	7.5	4.5	6.0	22		3.25							19	10	A-4b	8								
5	B 077-4 18	SS-1	1.5	3.5	0.0	2.0	14	13	4.25	29	19	10	53	33	86	16	14	A-4b	8	200		A-4b					
		SS-2	3.5	4.5	2.0	3.0	21		4.25							22	10	A-4b	8		A-4b	Mc	36"				
		SS-3	4.5	6.0	3.0	4.5	13		4	30	23	7	69	28	97	22	18	A-4b	8								
		SS-4	6.0	7.5	4.5	6.0	13		3.75							27	10	A-4b	8								

GB1 Figure B – Subgrade Stabilization



OVERRIDE TABLE


Calculated Average	New Values	Check to Override
4.10		<input type="checkbox"/> HP
17.20		<input type="checkbox"/> N60L

Average HP —
 Average N_{60L} —

OHIO DEPARTMENT OF TRANSPORTATION**OFFICE OF GEOTECHNICAL ENGINEERING****PLAN SUBGRADES
Geotechnical Bulletin GB1****SUM-76-6.15
100713****Akron Beltway (Kenmore Leg) - Subgrade Exploration
Ramp L****NEAS inc****Prepared By:** Erich R.G. Beyer
Date prepared: Tuesday, June 25, 2019**Brendan P. Andrews
2868 East Kemper Road
Cincinnati, OH 45241****(920) 427-0671
brendan.andrews@neasinc.com****NO. OF BORINGS:** **3**

#	Boring ID	Alignment	Station	Offset	Dir	Drill Rig	ER	Boring EL.	Proposed Subgrade EL	Cut Fill
1	B-077-0-18	Ramp L	4+70	22	Lt	CME 55T		0.0	-1.5	1.5 C
2	B-047-0-18	Ramp L	9+10	35	Lt	CME 55T		0.0	-1.5	1.5 C
3	B-048-0-18	IR-77/76	256+17	70	Rt	CME 55T		0.0	-1.5	1.5 C

GB1 Figure B – Subgrade Stabilization



OVERRIDE TABLE

Calculated Average	New Values	Check to Override
4.15		<input type="checkbox"/> HP
25.67		<input type="checkbox"/> N60L

Average HP —
Average N_{60L} —

OHIO DEPARTMENT OF TRANSPORTATION

OFFICE OF GEOTECHNICAL ENGINEERING

**PLAN SUBGRADES
Geotechnical Bulletin GB1**

**SUM-76-6.15
100713**

**Akron Beltway (Kenmore Leg)- Subgrade Exploration
Ramp N & M**

NEAS inc

Prepared By: Erich R.G. Beyer
Date prepared: Tuesday, June 25, 2019

**Brendan P. Andrews
2868 East Kemper Road
Cincinnati, OH 45241**

**(920) 427-0671
brendan.andrews@neasinc.com**

NO. OF BORINGS: **4**

#	Boring ID	Alignment	Station	Offset	Dir	Drill Rig	ER	Boring EL.	Proposed Subgrade EL	Cut Fill
1	B-078-0-18	Ramp N	4+35	23	Lt	CME 55X		0.0	-1.5	1.5 C
2	B-079-0-18	Ramp N	7+31	36	Lt	CME 55X		0.0	-1.5	1.5 C
3	B-080-0-18	Ramp N	9+06	27	Lt	CME 55X		0.0	-1.5	1.5 C
4	B-081-0-18	Ramp M	5+43	7	Rt	CME 55X		0.0	-1.5	1.5 C

#	Boring	Sample	Sample Depth		Subgrade Depth		Standard Penetration		HP (tsf)	Physical Characteristics					Moisture		Ohio DOT		Sulfate Content (ppm)	Problem		Excavate and Replace (Item 204)		Recommendation (Enter depth in inches)	
			From	To	From	To	N ₆₀	N _{60L}		LL	PL	PI	% Silt	% Clay	P200	M _c	M _{OPT}	Class		GI	Unsuitable	Unstable	Unsuitable		Unstable
1	B 078-0 18	SS-1	2.5	4.0	1.0	2.5	16	16	4.5	23	16	7	32	19	51	12	11	A-4a	3	627					
		SS-2	5.0	6.5	3.5	5.0	21		4.5	23	15	8	31	18	49	12	10	A-4a	3						
		SS-3	7.5	9.0	6.0	7.5	24		4.5							11	10	A-4a							
		SS-4	9.0	10.5	7.5	9.0	9		2							15	10	A-4a							
2	B 079-0 18	SS-1	2.5	4.0	1.0	2.5	7	6							20	8	A-3a	0	40						
		SS-2	5.0	6.5	3.5	5.0	7			NP	NP	NP	17	10	27	17	8	A-3a	0						
		SS-3	7.5	9.0	6.0	7.5	6			22	18	4	25	10	35	21	8	A-3a							
		SS-4	9.0	10.5	7.5	9.0	6									26	8	A-3a							
3	B 080-0 18	SS-1	0.0	1.5	-1.5	0.0	28	23		NP	NP	NP	13	8	21	9	6	A-1-b	0						
		SS-2	1.5	3.0	0.0	1.5	44			NP	NP	NP	18	12	30	9	8	A-3a	0	33					
		SS-3	3.0	4.5	1.5	3.0	33								9	8	A-3a	0							
		SS-4	4.5	6.0	3.0	4.5	23								11	8	A-3a	0							
4	B 081-0 18	SS-1A	0.0	0.8	-1.5	-0.7	13	10							5	8	A-3a	0	40						
		SS-1B	0.8	1.5	-0.7	0.0	13		4.5	28	16	12	21	19	40	12	14	A-6a	2						
		SS-2	1.5	3.0	0.0	1.5	14		3.25	36	17	19	30	30	60	18	16	A-6b	9						
		SS-3	3.0	4.5	1.5	3.0	10		2.75							21	16	A-6b	16			N ₆₀ & Mc			

PID: 100713

County-Route-Section: SUM-76-6.15

No. of Borings: 4

Geotechnical Consultant: NEAS inc

Prepared By: Erich R.G. Beyer

Date prepared: 6/25/2019

Chemical Stabilization Options		
320	Rubblize & Roll	Option
206	Cement Stabilization	Option
	Lime Stabilization	No
206	Depth	12"

Excavate and Replace Stabilization Options	
Global Geotextile Average(N60L):	12"
Average(HP):	0"
Global Geogrid Average(N60L):	0"
Average(HP):	0"

Design CBR	9
-------------------	----------

% Samples within 6 feet of subgrade			
$N_{60} \leq 5$	0%	$HP \leq 0.5$	0%
$N_{60} < 12$	36%	$0.5 < HP \leq 1$	0%
$12 \leq N_{60} < 15$	9%	$1 < HP \leq 2$	0%
$N_{60} \geq 20$	46%	$HP > 2$	45%
M+	9%		
Rock	0%		
Unsuitable	0%		


Excavate and Replace at Surface	
Average	0"
Maximum	0"
Minimum	0"

% Proposed Subgrade Surface	
Unstable & Unsuitable	11%
Unstable	11%
Unsuitable	0%

	N_{60}	N_{60L}	HP	LL	PL	PI	Silt	Clay	P 200	M_C	M_{OPT}	GI
Average	17	14	3.58	26	17	10	26	17	42	16	10	3
Maximum	44	23	4.50	36	18	19	32	30	60	26	16	16
Minimum	6	6	2.00	22	15	4	13	8	21	5	6	0

Classification Counts by Sample																			
ODOT Class	Rock	A-1-a	A-1-b	A-2-4	A-2-5	A-2-6	A-2-7	A-3	A-3a	A-4a	A-4b	A-5	A-6a	A-6b	A-7-5	A-7-6	A-8a	A-8b	Totals
Count	0	0	0	0	0	0	0	0	7	4	0	0	0	2	0	0	0	0	13
Percent	0%	0%	0%	0%	0%	0%	0%	0%	54%	31%	0%	0%	0%	15%	0%	0%	0%	0%	100%
% Rock Granular Cohesive	0%	85%										15%							100%
Surface Class Count	0	0	1	0	0	0	0	0	4	1	0	0	1	2	0	0	0	0	9
Surface Class Percent	0%	0%	11%	0%	0%	0%	0%	0%	44%	11%	0%	0%	11%	22%	0%	0%	0%	0%	100%

GB1 Figure B – Subgrade Stabilization



OVERRIDE TABLE

Calculated Average	New Values	Check to Override
3.58		<input type="checkbox"/> HP
13.75		<input type="checkbox"/> N60L

Average HP —
 Average N₆₀L —

OHIO DEPARTMENT OF TRANSPORTATION

OFFICE OF GEOTECHNICAL ENGINEERING

**PLAN SUBGRADES
Geotechnical Bulletin GB1**

**SUM-76-6.15
100713**

**Akron Beltway (Kenmore Leg) - Subgrade Exploration
Ramp P**

NEAS inc

Prepared By: Erich R.G. Beyer
Date prepared: Tuesday, June 25, 2019

**Brendan P. Andrews
2868 East Kemper Road
Cincinnati, OH 45241

(920) 427-0671
brendan.andrews@neasinc.com**

NO. OF BORINGS: **3**

#	Boring ID	Alignment	Station	Offset	Dir	Drill Rig	ER	Boring EL.	Proposed Subgrade EL.	Cut Fill
1	B-004-0-18	IR-77/IR-76	200+64	8	Lt	CME 45B		0.0	-1.5	1.5 C
2	B-005-0-18	Ramp P	14+34	78	Lt	CME 45B		0.0	-1.5	1.5 C
3	B-006-0-18	Ramp P	12+42	131	Lt	CME 45B		0.0	-1.5	1.5 C

#	Boring	Sample	Sample Depth		Subgrade Depth		Standard Penetration		HP (tsf)	Physical Characteristics					Moisture		Ohio DOT		Sulfate Content (ppm)	Problem		Excavate and Replace (Item 204)		Recommendation (Enter depth in inches)	
			From	To	From	To	N ₆₀	N _{60L}		LL	PL	PI	% Silt	% Clay	P200	M _c	M _{OPT}	Class		GI	Unsuitable	Unstable	Unsuitable		Unstable
1	B 004-0 18	SS-1	1.5	3.0	0.0	1.5	15	15		29	19	10	24	15	39	14	14	A-4a	1	140					
		SS-2	3.0	4.5	1.5	3.0	36									16	14	A-6a	10						
		SS-3	4.5	6.0	3.0	4.5	34			29	18	11	38	26	64	16	14	A-6a	6						
		SS-4	6.0	7.5	4.5	6.0	27									16	14	A-6a	10						
2	B 005-0 18	SS-1	1.5	3.0	0.0	1.5	27	25		NP	NP	NP	6	2	8	9	6	A-1-a	0	1267					
		SS-2	3.0	4.5	1.5	3.0	25									7	6	A-1-a	0						
		SS-3	4.5	6.0	3.0	4.5	29									7	6	A-1-a	0						
		SS-4	6.0	7.5	4.5	6.0	27			25	18	7	24	14	38	12	13	A-4a	1						
3	B 006-0 18	SS-1	1.5	3.0	0.0	1.5	21	15		NP	NP	NP	5	2	7	11	6	A-1-a	0	2653					
		SS-2	3.0	4.5	1.5	3.0	28									8	6	A-1-a	0						
		SS-3	4.5	6.0	3.0	4.5	15									8	6	A-1-a	0						
		SS-4	6.0	7.5	4.5	6.0	22			24	17	7	21	20	41	21	12	A-4a	1						

PID: 100713

County-Route-Section: SUM-76-6.15

No. of Borings: 3

Geotechnical Consultant: NEAS inc

Prepared By: Erich R.G. Beyer

Date prepared: 6/25/2019

Chemical Stabilization Options		
320	Rubblize & Roll	Option
206	Cement Stabilization	Option
	Lime Stabilization	No
206	Depth	NA

Excavate and Replace Stabilization Options	
Global Geotextile Average(N60L): Average(HP):	#N/A
Global Geogrid Average(N60L): Average(HP):	#N/A

Design CBR	10
-----------------------	-----------

% Samples within 6 feet of subgrade			
$N_{60} \leq 5$	0%	$HP \leq 0.5$	0%
$N_{60} < 12$	0%	$0.5 < HP \leq 1$	0%
$12 \leq N_{60} < 15$	0%	$1 < HP \leq 2$	0%
$N_{60} \geq 20$	83%	$HP > 2$	0%
M+	0%		
Rock	0%		
Unsuitable	0%		


Excavate and Replace at Surface	
Average	0"
Maximum	0"
Minimum	0"

% Proposed Subgrade Surface	
Unstable & Unsuitable	0%
Unstable	0%
Unsuitable	0%

	N_{60}	N_{60L}	HP	LL	PL	PI	Silt	Clay	P 200	M_C	M_{OPT}	GI
Average	26	18		27	18	9	20	13	33	12	10	2
Maximum	36	25	0.00	29	19	11	38	26	64	21	14	10
Minimum	15	15	0.00	24	17	7	5	2	7	7	6	0

Classification Counts by Sample																			
ODOT Class	Rock	A-1-a	A-1-b	A-2-4	A-2-5	A-2-6	A-2-7	A-3	A-3a	A-4a	A-4b	A-5	A-6a	A-6b	A-7-5	A-7-6	A-8a	A-8b	Totals
Count	0	6	0	0	0	0	0	0	0	3	0	0	3	0	0	0	0	0	12
Percent	0%	50%	0%	0%	0%	0%	0%	0%	0%	25%	0%	0%	25%	0%	0%	0%	0%	0%	100%
% Rock Granular Cohesive	0%	75%										25%							100%
Surface Class Count	0	4	0	0	0	0	0	0	0	1	0	0	1	0	0	0	0	0	6
Surface Class Percent	0%	67%	0%	0%	0%	0%	0%	0%	0%	17%	0%	0%	17%	0%	0%	0%	0%	0%	100%

GB1 Figure B – Subgrade Stabilization



OVERRIDE TABLE

Calculated Average	New Values	Check to Override
		<input type="checkbox"/> HP
18.33		<input type="checkbox"/> N60L

Average HP —
Average N_{60L} —

OHIO DEPARTMENT OF TRANSPORTATION

OFFICE OF GEOTECHNICAL ENGINEERING

**PLAN SUBGRADES
Geotechnical Bulletin GB1**

**SUM-76-6.15
100713**

**Akron Beltway (Kenmore Leg)- Subgrade Exploration
Ramp T**

NEAS inc

Prepared By: Erich R.G. Beyer
Date prepared: Tuesday, June 25, 2019

**Brendan P. Andrews
2868 East Kemper Road
Cincinnati, OH 45241**


**(920) 427-0671
brendan.andrews@neasinc.com**

NO. OF BORINGS: **3**

#	Boring ID	Alignment	Station	Offset	Dir	Drill Rig	ER	Boring EL.	Proposed Subgrade EL.	Cut Fill
1	B-051-0-18	Ramp T	10+73	15	Rt	CME 45B		0.0	-1.5	1.5 C
2	B-052-0-18	Ramp T	8+07	32	Lt	CME 55X		0.0	-1.5	1.5 C
3	B-053-0-18	Ramp T	4+17	30	Lt	CME 45B		0.0	-1.5	1.5 C

#	Boring	Sample	Sample Depth		Subgrade Depth		Standard Penetration		HP (tsf)	Physical Characteristics					Moisture		Ohio DOT		Sulfate Content (ppm)	Problem		Excavate and Replace (Item 204)		Recommendation (Enter depth in inches)	
			From	To	From	To	N ₆₀	N _{60L}		LL	PL	PI	% Silt	% Clay	P200	M _c	M _{OPT}	Class		GI	Unsuitable	Unstable	Unsuitable		Unstable
1	B 051-0 18	SS-1	1.5	3.0	0.0	1.5	14		4.5	26	18	8	36	23	59	13	13	A-4a	5	987					
		SS-2	3.0	4.5	1.5	3.0	21		4.5	21	14	7	30	20	50	10	10	A-4a	3						
		SS-3	4.5	6.0	3.0	4.5	14		3.75							11	10	A-4a	8						
		SS-4	6.0	7.5	4.5	6.0	21	14	1							14	10	A-4a	8						
2	B 052-0 18	SS-1	2.5	4.0	1.0	2.5	62									7	6	A-1-a	0						
		SS-2	5.0	6.5	3.5	5.0	85			NP	NP	NP	7	3	10	7	6	A-1-a	0						
		SS-3	6.5	6.9	5.0	5.4										7	6	A-1-a	0						
								30																	
3	B 053-0 18	SS-1	1.5	3.0	0.0	1.5	11		4.5	23	17	6	41	24	65	13	12	A-4a	6	273		N ₆₀		12"	
		SS-2	3.0	4.5	1.5	3.0	17		4.5							16	10	A-4a	8			Mc			
		SS-3	4.5	6.0	3.0	4.5	15		4.5	28	19	9	43	32	75	15	14	A-4a	8						
		SS-4	6.0	7.5	4.5	6.0	36	11								6	10	A-2-4	0						

GB1 Figure B – Subgrade Stabilization



OVERRIDE TABLE

Calculated Average	New Values	Check to Override
3.89		<input type="checkbox"/> HP
18.33		<input type="checkbox"/> N60L


Average HP —
Average N_{60L} —

OHIO DEPARTMENT OF TRANSPORTATION**OFFICE OF GEOTECHNICAL ENGINEERING****PLAN SUBGRADES
Geotechnical Bulletin GB1****SUM-76-6.15
100713****Akron Beltway (Kenmore Leg) - Subgrade Exploration
Ramp U****NEAS inc****Prepared By:** Erich R.G. Beyer
Date prepared: Tuesday, June 25, 2019**Brendan P. Andrews
2868 East Kemper Road
Cincinnati, OH 45241****(920) 427-0671
brendan.andrews@neasinc.com****NO. OF BORINGS:** **4**

#	Boring ID	Alignment	Station	Offset	Dir	Drill Rig	ER	Boring EL.	Proposed Subgrade EL.	Cut Fill
1	B-067-0-18	Ramp U	8+40	5	Rt	CME 55T		0.0	-1.5	1.5 C
2	B-068-0-18	Ramp U	12+37	19	Rt	CME 55T		0.0	-1.5	1.5 C
3	B-069-0-18	Ramp U	16+94	19	Rt	CME 55T		0.0	-1.5	1.5 C
4	B-070-0-18	IR-77/IR-76	231+79	79	Rt	CME 55T		0.0	-1.5	1.5 C

#	Boring	Sample	Sample Depth		Subgrade Depth		Standard Penetration		HP (tsf)	Physical Characteristics					Moisture		Ohio DOT		Sulfate Content (ppm)	Problem		Excavate and Replace (Item 204)		Recommendation (Enter depth in inches)	
			From	To	From	To	N ₆₀	N _{60L}		LL	PL	PI	% Silt	% Clay	P200	M _c	M _{OPT}	Class		GI	Unsuitable	Unstable	Unsuitable		Unstable
1	B 067-0 18	SS-1	2.5	4.0	1.0	2.5	17	12	3.25	20	13	7	28	18	46	10	10	A-4a	2	473					
		SS-2	5.0	6.5	3.5	5.0	12									6	10	A-4a	8						
		SS-3	7.5	9.0	6.0	7.5	20		3							9	10	A-4a							
		SS-4	10.0	11.5	8.5	10.0	29			18	13	5	19	13	32	8	10	A-2-4							
2	B 068-0 18	SS-1	0.0	2.8	-1.5	1.3	27	27	4.5	23	16	7	23	13	36	10	11	A-4a	0	1507					
		SS-2B	2.8	4.0	1.3	2.5	43									5	6	A-1-b	0						
		SS-3	5.0	6.5	3.5	5.0	77									7	6	A-1-b	0						
		SS-4	7.5	9.0	6.0	7.5	51									7	6	A-1-b							
3	B 069-0 18	SS-1	2.5	4.0	1.0	2.5	40	30							17	10	A-2-4	0	13		Mc				
		SS-2	5.0	8.0	3.5	6.5	40		4.25	49	22	27	7	66	73	16	19	A-7-6	16						
		SS-3B	8.0	8.1	6.5	6.6										0	0	Rock							
		SS-4	10.0	10.1	8.5	8.6										7	0	Rock							
4	B 070-0 18	SS-1	0.0	1.5	-1.5	0.0	29	0		NP	NP	NP	22	8	30	17	8	A-3a	0						
		SS-2	2.5	2.8	1.0	1.3										12	0	Rock	0	Rock	N ₆₀ & Mc	16"	0"		
		SS-3	5.0	5.3	3.5	3.8										8	0	Rock	0						

GB1 Figure B – Subgrade Stabilization



OVERRIDE TABLE

Calculated Average	New Values	Check to Override
3.75		<input type="checkbox"/> HP
17.25		<input type="checkbox"/> N60L

Average HP —
Average N_{60L} —


OHIO DEPARTMENT OF TRANSPORTATION**OFFICE OF GEOTECHNICAL ENGINEERING****PLAN SUBGRADES
Geotechnical Bulletin GB1****SUM-76-6.15
100713****Akron Beltway (Kenmore Leg) - Subgrade Exploration
Ramp V****NEAS inc****Prepared By:** Erich R.G. Beyer
Date prepared: Tuesday, June 25, 2019**Brendan P. Andrews
2868 East Kemper Road
Cincinnati, OH 45241****(920) 427-0671
brendan.andrews@neasinc.com****NO. OF BORINGS:** **9**

#	Boring ID	Alignment	Station	Offset	Dir	Drill Rig	ER	Boring EL.	Proposed Subgrade EL	Cut Fill
1	B-051-0-18	IR-76	92+46	73	Lt	CME 45B		0.0	-1.5	1.5 C
2	B-054-0-18	IR-76	94+72	25	Rt	CME 45B		0.0	-1.5	1.5 C
3	B-056-0-18	IR-76	97+76	30	Rt	CME 45B		0.0	-1.5	1.5 C
4	B-072-0-18	IR-76	99+85	38	Lt	CME 55T		0.0	-1.5	1.5 C
5	B-073-0-18	IR-76	103+14	39	Lt	CME 55T		0.0	-1.5	1.5 C
6	B-074-0-18	Ramp V	18+11	7	Rt	CME 45B		0.0	-1.5	1.5 C
7	B-075-0-18	Ramp V	14+42	77	Lt	CME 55X		0.0	-1.5	1.5 C
8	B-076-0-18	Ramp V	10+85	59	Lt	CME 55X		0.0	-1.5	1.5 C
9	B-043-0-18	Ramp V	8+09	37	Lt	CME 45B		0.0	-1.5	1.5 C

#	Boring	Sample	Sample Depth		Subgrade Depth		Standard Penetration		HP (tsf)	Physical Characteristics					Moisture		Ohio DOT		Sulfate Content (ppm)	Problem		Excavate and Replace (Item 204)		Recommendation (Enter depth in inches)		
			From	To	From	To	N ₆₀	N _{60L}		LL	PL	PI	% Silt	% Clay	P200	M _c	M _{OPT}	Class		GI	Unsuitable	Unstable	Unsuitable		Unstable	
1	B 051-0 18	SS-1	1.5	3.0	0.0	1.5	14	14	4.5	26	18	8	36	23	59	13	13	A-4a	5	987						
		SS-2	3.0	4.5	1.5	3.0	21		4.5	21	14	7	30	20	50	10	10	A-4a	3							
		SS-3	4.5	6.0	3.0	4.5	14		3.75							11	10	A-4a	8							
		SS-4	6.0	7.5	4.5	6.0	21		1							14	10	A-4a	8							
2	B 054-0 18	SS-1	1.5	3.0	0.0	1.5	28	22	4.5	25	18	7	29	17	46	9	13	A-4a	2	393						
		SS-2	3.0	4.5	1.5	3.0	38			23	17	6	19	12	31	7	10	A-2-4	0							
		SS-3	4.5	6.9	3.0	5.4	22									2	6	A-1-b	0							
		SS-4B	6.9	7.5	5.4	6.0	48		4.5							12	10	A-4a								
3	B 056-0 18	SS-1	1.5	3.0	0.0	1.5	20	4							8	8	A-3a	0								
		SS-2	3.0	4.5	1.5	3.0	11			17	12	5	18	14	32	11	8	A-3a	0							
		SS-3	4.5	6.0	3.0	4.5	6			18	12	6	17	14	31	10	8	A-3a	0	273						
		SS-4	6.0	7.5	4.5	6.0	4		1.75							16	14	A-6a	10							
4	B 072-0 18	SS-1	2.5	4.0	1.0	2.5	23	14	4.5	21	15	6	29	17	46	10	10	A-4a	2	73						
		SS-2	5.0	6.5	3.5	5.0	21									9	10	A-2-4								
		SS-3	7.5	10.3	6.0	8.8	14									5	6	A-1-b								
		SS-4	10.3	11.5	8.8	10.0	31																			
5	B 073-0 18	SS-1	1.5	3.0	0.0	1.5	34	26		NP	NP	NP	7	5	12	6	6	A-1-b	0	13						
		SS-2	3.0	4.5	1.5	3.0	26			NP	NP	NP	11	7	18	5	6	A-1-b	0							
		SS-3	4.5	6.0	3.0	4.5	52								5	0	Rock	0								
		SS-4	6.0	6.9	4.5	5.4									12	0	Rock	0								
6	B 074-0 18	SS-1	2.5	4.0	1.0	2.5	60	30		NP	NP	NP	5	3	8	6	6	A-1-b	0	13						
		SS-2	5.0	5.5	3.5	4.0									7	0	Rock	0								
		SS-3	7.5	7.6	6.0	6.1										0	0	Rock								
		SS-4	10.0	10.1	8.5	8.6										0	0	Rock								
7	B 075-0 18	SS-1	2.5	4.0	1.0	2.5	23	23		25	16	9	57	26	83	5	11	A-4b	8	20	A-4b		30"			
		SS-2	5.0	5.9	3.5	4.4					24	15	9	37	23	60	5	10	A-4a	5						
8	B 076-0 18	SS-1	2.5	4.0	1.0	2.5	51	30		NP	NP	NP	21	10	31	7	10	A-2-4	0	1133						
		SS-2A	5.0	5.7	3.5	4.2					19	15	4	24	14	38	9	10	A-4a	1						
		SS-2B	5.7	6.0	4.2	4.5										0	0	Rock	0							
9	B 043-0 18	SS-1	1.5	3.0	0.0	1.5	95			23	17	6	17	12	29	10	10	A-2-4	0							
		SS-2	3.0	4.5	1.5	3.0	22		4.5	25	18	7	31	22	53	11	13	A-4a	4	400						
		SS-3	4.5	6.0	3.0	4.5	95		4.5							12	10	A-4a	8							

#	Boring	Sample	Sample Depth		Subgrade Depth		Standard Penetration		HP (tsf)	Physical Characteristics					Moisture		Ohio DOT		Sulfate Content (ppm)	Problem		Excavate and Replace (Item 204)		Recommendation (Enter depth in inches)	
			From	To	From	To	N ₆₀	N _{60L}		LL	PL	PI	% Silt	% Clay	P200	M _c	M _{OPT}	Class		GI	Unsuitable	Unstable	Unsuitable		Unstable
					SS-4	6.0	7.5	4.5		6.0	60	22	4.5							11	10	A-4a	8		

GB1 Figure B – Subgrade Stabilization



OVERRIDE TABLE

Calculated Average	New Values	Check to Override
3.86		<input type="checkbox"/> HP
20.56		<input type="checkbox"/> N60L

Average HP —
Average N_{60L} —


OHIO DEPARTMENT OF TRANSPORTATION**OFFICE OF GEOTECHNICAL ENGINEERING****PLAN SUBGRADES
Geotechnical Bulletin GB1****SUM-76-6.15
100713****Akron Beltway (Kenmore Leg) - Subgrade Exploration
Ramp W****NEAS inc****Prepared By:** Erich R.G. Beyer
Date prepared: Tuesday, June 25, 2019**Brendan P. Andrews
2868 East Kemper Road
Cincinnati, OH 45241****(920) 427-0671
brendan.andrews@neasinc.com****NO. OF BORINGS:** **9**

#	Boring ID	Alignment	Station	Offset	Dir	Drill Rig	ER	Boring EL.	Proposed Subgrade EL	Cut Fill
1	B-051-0-18	IR-76	92+46	73	Lt	CME 45B		0.0	-1.5	1.5 C
2	B-054-0-18	IR-76	94+72	25	Rt	CME 45B		0.0	-1.5	1.5 C
3	B-056-0-18	IR-76	97+76	30	Rt	CME 45B		0.0	-1.5	1.5 C
4	B-072-0-18	IR-76	99+85	38	Lt	CME 55T		0.0	-1.5	1.5 C
5	B-057-0-18	IR-76	102+30	28	Rt	CME 55X		0.0	-1.5	1.5 C
6	B-058-0-18	Ramp W	106+50	1	Rt	CME 55X		0.0	-1.5	1.5 C
7	B-059-0-18	Ramp W	110+72	15	Rt	CME 55X		0.0	-1.5	1.5 C
8	B-040-0-18	Ramp W	110+98	46	Lt	CME 45B		0.0	-1.5	1.5 C
9	B-060-0-18	IR-76/IR-77	219+30	76	Lt	CME 55X		0.0	-1.5	1.5 C

#	Boring	Sample	Sample Depth		Subgrade Depth		Standard Penetration		HP (tsf)	Physical Characteristics					Moisture		Ohio DOT		Sulfate Content (ppm)	Problem		Excavate and Replace (Item 204)		Recommendation (Enter depth in inches)	
			From	To	From	To	N ₆₀	N _{60L}		LL	PL	PI	% Silt	% Clay	P200	M _c	M _{OPT}	Class		GI	Unsuitable	Unstable	Unsuitable		Unstable
1	B 051-0 18	SS-1	1.5	3.0	0.0	1.5	14	14	4.5	26	18	8	36	23	59	13	13	A-4a	5	987					
		SS-2	3.0	4.5	1.5	3.0	21		4.5	21	14	7	30	20	50	10	10	A-4a	3						
		SS-3	4.5	6.0	3.0	4.5	14		3.75							11	10	A-4a	8						
		SS-4	6.0	7.5	4.5	6.0	21		1							14	10	A-4a	8						
2	B 054-0 18	SS-1	1.5	3.0	0.0	1.5	28	22	4.5	25	18	7	29	17	46	9	13	A-4a	2	393					
		SS-2	3.0	4.5	1.5	3.0	38			23	17	6	19	12	31	7	10	A-2-4	0						
		SS-3	4.5	6.9	3.0	5.4	22									2	6	A-1-b	0						
		SS-4B	6.9	7.5	5.4	6.0	48		4.5							12	10	A-4a							
3	B 056-0 18	SS-1	1.5	3.0	0.0	1.5	20	4							8	8	A-3a	0							
		SS-2	3.0	4.5	1.5	3.0	11			17	12	5	18	14	32	11	8	A-3a	0						
		SS-3	4.5	6.0	3.0	4.5	6			18	12	6	17	14	31	10	8	A-3a	0	273					
		SS-4	6.0	7.5	4.5	6.0	4		1.75							16	14	A-6a	10						
4	B 072-0 18	SS-1	2.5	4.0	1.0	2.5	23	14	4.5	21	15	6	29	17	46	10	10	A-4a	2	73					
		SS-2	5.0	6.5	3.5	5.0	21									9	10	A-2-4							
		SS-3	7.5	10.3	6.0	8.8	14									5	6	A-1-b							
		SS-4B	10.3	11.5	8.8	10.0	31																		
5	B 057-0 18	SS-1A	2.0	2.5	0.5	1.0		0	3.75	NP	NP	NP	13	8	21	9	8	A-3a	0						
		SS-1B	2.5	2.5	1.0	1.0										0	0	Rock	0		Rock	N ₆₀	12"	0"	
6	B 058-0 18	SS-1	2.5	2.9	1.0	1.4		30		NP	NP	NP	9	4	13	6	6	A-1-b	0	33					
		SS-2	4.0	4.2	2.5	2.7	50									4	0	Rock	0			Mc			
7	B 059-0 18	SS-1	2.7	4.0	1.2	2.5	85	30		NP	NP	NP	23	14	37	11	11	A-4a	0	53					
		SS-2	5.0	6.5	3.5	5.0										6	0	Rock	0						
		SS-3	6.5	6.6	5.0	5.1										8	0	Rock	0						
8	B 040-0 18	SS-1	1.5	3.0	0.0	1.5	28	28								9	10	A-4a	8						
		SS-2	3.0	4.5	1.5	3.0	42			NP	NP	NP	19	14	33	8	8	A-3a	0	80					
		SS-3	4.5	6.0	3.0	4.5	105									8	8	A-3a	0						
		SS-4	6.0	7.5	4.5	6.0	98			NP	NP	NP	26	18	44	7	11	A-4a	2						
9	B 060-0 18	SS-1	2.5	4.0	1.0	2.5	30		2.5	23	17	6	18	12	30	11	10	A-2-4	0						
		SS-2	5.0	6.5	3.5	5.0	17		2.5							11	10	A-4a	8						
		SS-3	7.5	9.0	6.0	7.5	13		2.5	22	15	7	29	19	48	12	10	A-4a							

#	Boring	Sample	Sample Depth		Subgrade Depth		Standard Penetration		HP (tsf)	Physical Characteristics					Moisture		Ohio DOT		Sulfate Content (ppm)	Problem		Excavate and Replace (Item 204)		Recommendation (Enter depth in inches)
			From	To	From	To	N ₆₀	N _{60L}		LL	PL	PI	% Silt	% Clay	P200	M _c	M _{OPT}	Class		GI	Unsuitable	Unstable	Unsuitable	
		SS-4	10.0	11.5	8.5	10.0	26	13	4.5							9	10	A-4a						

GB1 Figure B – Subgrade Stabilization



OVERRIDE TABLE


Calculated Average	New Values	Check to Override
3.44		<input type="checkbox"/> HP
17.22		<input type="checkbox"/> N60L


Average HP —
Average N_{60L} —


APPENDIX E

EMBANKMENT STABILITY ANALYSIS

IR-76 EB – STA. 98+00









	Project			
	SUM-76-6.15, PID 100713			
	Analysis Description			
	Embankment Stability - IR-76, STA. 98+00 - Effective Stress - Circular Failure			
Drawn By		Scale	Company	
KCA		1:200	NEAS Inc.	
Date			File Name	
7/24/2019, 12:12:45 PM			STA98+00_EffectiveCircular.slim	




Material Name	Color	Unit Weight (lbs/ft3)	Strength Type	Cohesion (psf)	Phi (deg)
Silt and Clay 1		112	Mohr-Coulomb	50	20
Bedrock		145	Infinite strength		
Coarse and Fine Sand 1		125	Mohr-Coulomb	0	36
Coarse and Fine Sand 2		120	Mohr-Coulomb	0	32
Silt and Clay 2		122	Mohr-Coulomb	200	25

	Project				
	SUM-76-6.15, PID 100713				
	Analysis Description				
	Embankment Stability - IR-76, STA. 98+00 - Effective Stress - Block Failure				
	Drawn By	KCA	Scale	1:200	Company
Date	7/24/2019, 12:12:45 PM		File Name	STA98+00_EffectiveBlock.slim	





Material Name	Color	Unit Weight (lbs/ft3)	Strength Type	Cohesion (psf)	Phi (deg)
Silt and Clay 1		112	Mohr-Coulomb	500	0
Bedrock		145	Infinite strength		
Coarse and Fine Sand 1		125	Mohr-Coulomb	0	36
Coarse and Fine Sand 2		120	Mohr-Coulomb	0	32
Silt and Clay 2		122	Mohr-Coulomb	2400	0



5.18


240.00 lbs/ft2


	Project			SUM-76-6.15, PID 100713			
	Analysis Description					Embankment Stability - IR-76, STA. 98+00 - Total Stress - Circular Failure	
	Drawn By		KCA	Scale		1:200	
	Date		7/24/2019, 12:12:45 PM		Company		NEAS Inc.
	Date				File Name		STA98+00_TotalCircular.slim




	Project				
	SUM-76-6.15, PID 100713				
	Analysis Description				
	Embankment Stability - IR-76, STA. 98+00 - Total Stress - Block Failure				
Drawn By	KCA	Scale	1:200	Company	NEAS Inc.
Date	7/24/2019, 12:12:45 PM		File Name	STA98+00_TotalBlock.slim	


IR-77 SB/IR-76 EB – STA. 242+00




	Project			
	SUM-76-6.15, PID 100713			
	Analysis Description			
	Embankment Stability - IR-77, STA. 242+00 - Effective Stress - Circular Failure			
Drawn By	KCA	Scale	1:100	Company
				NEAS Inc.
Date	7/23/2019, 9:11:24 AM		File Name	STA242+00_EffectiveCircular.slim




	<i>Project</i> SUM-76-6.15, PID 100713			
	<i>Analysis Description</i> Embankment Stability - IR-77, STA. 242+00 - Effective Stress - Block Failure			
	<i>Drawn By</i> KCA	<i>Scale</i> 1:100	<i>Company</i> NEAS Inc.	
	<i>Date</i> 7/23/2019, 9:11:24 AM		<i>File Name</i> STA242+00_EffectiveBlock.slim	






	<i>Project</i> SUM-76-6.15, PID 100713			
	<i>Analysis Description</i> Embankment Stability - IR-77, STA. 242+00 - Total Stress - Circular Failure			
	<i>Drawn By</i> KCA	<i>Scale</i> 1:100	<i>Company</i> NEAS Inc.	
	<i>Date</i> 7/23/2019, 9:11:24 AM	<i>File Name</i> STA242+00_TotalCircular.slim		





	Project			SUM-76-6.15, PID 100713			
	Analysis Description					Embankment Stability - IR-77, STA. 242+00 - Total Stress - Block Failure	
	Drawn By		KCA	Scale	1:150	Company	NEAS Inc.
	Date			7/23/2019, 9:11:24 AM		File Name	STA242+00_TotalBlock.slim




IR-277 WB/IR-76 WB – STA. 50+00




Material Name	Color	Unit Weight (lbs/ft3)	Strength Type	Cohesion (psf)	Phi (deg)
Fine Sand 1		122	Mohr-Coulomb	0	34
Fine Sand 2		120	Mohr-Coulomb	20	31
Fine Sand 3		110	Mohr-Coulomb	0	30


	Project				SUM-76-6.15, PID 100713			
	Analysis Description						Embankment Stability - IR-277, STA. 50+00 - Effective Stress - Circular Failure	
	Drawn By		KCA		Scale		1:200	
	Date		7/23/2019, 9:11:24 AM		Company		NEAS Inc.	
				File Name		STA50+00_EffectiveCircular.slim		







Material Name	Color	Unit Weight (lbs/ft3)	Strength Type	Cohesion (psf)	Phi (deg)
Fine Sand 1		122	Mohr-Coulomb	0	34
Fine Sand 2		120	Mohr-Coulomb	20	31
Fine Sand 3		110	Mohr-Coulomb	0	30


	Project				SUM-76-6.15, PID 100713		
	Analysis Description						Embankment Stability - IR-277, STA. 50+00 - Effective Stress - Block Failure
	Drawn By		KCA	Scale		1:200	Company
	Date		7/23/2019, 9:11:24 AM			File Name	
						NEAS Inc.	
						STA50+00_EffectiveBlock.slim	



RAMP A2 – STA. 15+00




Material Name	Color	Unit Weight (lbs/ft ³)	Strength Type	Cohesion (psf)	Phi (deg)
Fine Sand 1		120	Mohr-Coulomb	0	33
Fine Sand 2		110	Mohr-Coulomb	0	30
Silt 1		110	Mohr-Coulomb	0	28


	Project			
	SUM-76-6.15, PID 100713			
	Analysis Description			
	Embankment Stability - Ramp A2, STA. 15+00 - Effective Stress - Circular Failure			
	Drawn By	KCA	Scale	1:150
Date		7/24/2019, 12:12:45 PM		
		Company		
		NEAS Inc.		
		File Name		
		STA15+00_EffectiveCircular.slim		





Material Name	Color	Unit Weight (lbs/ft3)	Strength Type	Cohesion (psf)	Phi (deg)
Fine Sand 1		120	Mohr-Coulomb	0	33
Fine Sand 2		110	Mohr-Coulomb	0	30
Silt 1		110	Mohr-Coulomb	0	28


	Project				
	SUM-76-6.15, PID 100713				
	Analysis Description				
	Embankment Stability - Ramp A2, STA. 15+00 - Effective Stress - Block Failure				
Drawn By	KCA	Scale	1:150	Company	NEAS Inc.
Date	7/24/2019, 12:12:45 PM		File Name		STA15+00_EffectiveBlock.slim


RAMP A2 – STA. 17+00






Material Name	Color	Unit Weight (lbs/ft3)	Strength Type	Cohesion (psf)	Phi (deg)
Fine Sand 1		120	Mohr-Coulomb	0	33
Fine Sand 2		110	Mohr-Coulomb	0	30

Method Name	Min FS
Bishop simplified	1.48

	Project				
	SUM-76-6.15, PID 100713				
	Analysis Description				
	Embankment Stability - Ramp A2, STA. 17+00 - Effective Stress - Circular Failure				
	Drawn By	KCA	Scale	1:150	Company
Date	7/24/2019, 12:12:45 PM		File Name	STA17+00_EffectiveCircular.slim	



Material Name	Color	Unit Weight (lbs/ft ³)	Strength Type	Cohesion (psf)	Phi (deg)
Fine Sand 1		120	Mohr-Coulomb	0	33
Fine Sand 2		110	Mohr-Coulomb	0	30

	Project				SUM-76-6.15, PID 100713			
	Analysis Description						Embankment Stability - Ramp A2, STA. 17+00 - Effective Stress - Block Failure	
	Drawn By		KCA	Scale		1:150	Company	NEAS Inc.
	Date		7/24/2019, 12:12:45 PM			File Name		STA17+00_EffectiveBlock.slim

APPENDIX F

ODNR OIL WELL REPORTS

R KB

R

WELL COMPLETION RECORD (Form 8)

Ohio Department of Natural Resources
 Division of Mineral Resources Management
 2045 Morse Road, Bldg. H-3, Columbus, OH 43229-6693
 Telephone: 614-265-6633 Fax: 614-265-7998

This report is due in duplicate 60 days after completion of the well. If the permit has expired and the well was not drilled, check the box below, sign on reverse side (Back), and return to our office within 30 days after expiration.

1. Owner #: 1639		3. API #: 34-153-2-3145-00-00																																				
2. Owner name, address and telephone numbers: Bass Energy, Inc. 130 Merz Blvd., Akron, OH 44333 330-869-0870		4. Type of Permit: Drill New Well Urban UC2																																				
<div style="border: 2px solid black; padding: 5px; display: inline-block;"> RECEIVED MAY 16 2013 Division of Oil & Gas Columbus </div>		5. County: Summit																																				
		6. Civil Township: Conventry																																				
		7. Footage: 135'NL & 5185'WL of Lot 13, Tract 2																																				
8. Type of Well: Division of Oil & Gas Columbus		21. Date drilling commenced: 2/8/2012																																				
9. X: 2259865 Y: 499315		22. Date drilling completed: 3/20/2012																																				
10. Quad: AKRON WEST		23. Date put into production: 6/7/2012																																				
11. Section: 12. Lot: 13		24. Date plugged if dry:																																				
13. Fraction: 14. Qtr. Twp:		25. Producing formation: Clinton Sandstone																																				
15. Tract: 2		26. Deepest formation: Queenston Shale																																				
16. Allot:		27. Driller's total depth: 4008'																																				
17. Well #: 1		28. Logger's total depth: 4000'																																				
18. Lease Name: ABINGTON PROPERTIES		29. Lost hole at _____ feet.																																				
19. PTD: 3999' 20. Drilling Unit: 25.33																																						
30. Type of tools: <input type="checkbox"/> Cable <input type="checkbox"/> Air Rotary <input type="checkbox"/> Fluid Rotary <input checked="" type="checkbox"/> Air/Fluid Rotary <input type="checkbox"/> Cable/Air Rotary <input type="checkbox"/> Service Rig <input type="checkbox"/> Cable/Fluid Rotary <input type="checkbox"/> Cable/Air Rotary/Fluid Rotary		31. Type of completion: 32. Elevation: <input type="checkbox"/> Open Hole Ground Level 973 <input checked="" type="checkbox"/> Through Casing Derrick Floor <input type="checkbox"/> Slotted Liner Kelly Bushing 979																																				
33. Perforated intervals and number of shots: 3798' - 3812' with 53 shots																																						
34. Name of Frac Company: Superior Well Service																																						
35. Method of shot, acid, or fracture treatments, production tests, pressures, etc.:																																						
<table style="width:100%; border-collapse: collapse;"> <tr> <td style="width:25%;">SHOT:</td> <td style="width:25%;">ACID:</td> <td style="width:25%;">FRAC FLUIDS:</td> <td style="width:25%;">SAND:</td> <td style="width:20%;">PRESSURES (psi):</td> </tr> <tr> <td>Lbs. _____</td> <td>Gals. 500</td> <td>Water (gals) 70,080</td> <td>Lbs. 40,000</td> <td>Breakdown 1475</td> </tr> <tr> <td>Qts. _____</td> <td>Type HCL</td> <td>Water (bbl) _____</td> <td>Sks. _____</td> <td>ATP 1375</td> </tr> <tr> <td>Type _____</td> <td>Percent 15%</td> <td>CO2 (tons) _____</td> <td></td> <td>ISIP 1400</td> </tr> <tr> <td></td> <td></td> <td>N2 (mscf) _____</td> <td></td> <td>5 min. SIP 1294</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>Avg. Rate 26</td> </tr> </table>				SHOT:	ACID:	FRAC FLUIDS:	SAND:	PRESSURES (psi):	Lbs. _____	Gals. 500	Water (gals) 70,080	Lbs. 40,000	Breakdown 1475	Qts. _____	Type HCL	Water (bbl) _____	Sks. _____	ATP 1375	Type _____	Percent 15%	CO2 (tons) _____		ISIP 1400			N2 (mscf) _____		5 min. SIP 1294					Avg. Rate 26					
SHOT:	ACID:	FRAC FLUIDS:	SAND:	PRESSURES (psi):																																		
Lbs. _____	Gals. 500	Water (gals) 70,080	Lbs. 40,000	Breakdown 1475																																		
Qts. _____	Type HCL	Water (bbl) _____	Sks. _____	ATP 1375																																		
Type _____	Percent 15%	CO2 (tons) _____		ISIP 1400																																		
		N2 (mscf) _____		5 min. SIP 1294																																		
				Avg. Rate 26																																		
METHOD OF FLUID CONTAINMENT FLUIDS: PIT: FRAC TANK: Swab <input type="checkbox"/> <input checked="" type="checkbox"/> Flowback <input type="checkbox"/> <input checked="" type="checkbox"/>																																						
DATE TREATED: 3/20/2012																																						
36. Amount of initial production per day:																																						
<table style="width:100%; border-collapse: collapse;"> <tr> <td style="width:33%;"></td> <td style="width:16.5%; text-align: center;">(MCF.)</td> <td style="width:16.5%; text-align: center;">(Bbls.)</td> <td style="width:35%; text-align: center;">(Bbls.)</td> </tr> <tr> <td>Natural:</td> <td>Gas 0</td> <td>Oil 0</td> <td>Brine 0</td> </tr> <tr> <td>After Treatment:</td> <td>Gas 15 MCF</td> <td>Oil 10 BO</td> <td>Brine 1</td> </tr> <tr> <td>SERC Data:</td> <td>Number of Tanks: 2</td> <td>Maximum Storage Capacity of all Tanks (bbls.):</td> <td>440 BBLs</td> </tr> </table>					(MCF.)	(Bbls.)	(Bbls.)	Natural:	Gas 0	Oil 0	Brine 0	After Treatment:	Gas 15 MCF	Oil 10 BO	Brine 1	SERC Data:	Number of Tanks: 2	Maximum Storage Capacity of all Tanks (bbls.):	440 BBLs																			
	(MCF.)	(Bbls.)	(Bbls.)																																			
Natural:	Gas 0	Oil 0	Brine 0																																			
After Treatment:	Gas 15 MCF	Oil 10 BO	Brine 1																																			
SERC Data:	Number of Tanks: 2	Maximum Storage Capacity of all Tanks (bbls.):	440 BBLs																																			
37. Casing and tubing record: Please indicate which is used (cement or mudding)																																						
<table style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>Type</th> <th>Size</th> <th>Feet Used in Drilling</th> <th>Amount of Cement or Mud</th> <th>Feet Left in Well</th> </tr> </thead> <tbody> <tr> <td>Conductor/Drive Pipe:</td> <td>11"</td> <td>120'</td> <td>315 sks</td> <td>120'</td> </tr> <tr> <td>Surface:</td> <td>8 5/8"</td> <td>451'</td> <td>240 sks</td> <td>451'</td> </tr> <tr> <td>Intermediate:</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Production:</td> <td>4 1/2" 11.6#</td> <td>3984'</td> <td>175 sks</td> <td>3984'</td> </tr> <tr> <td>Tubing:</td> <td>1 1/2"</td> <td>3788'</td> <td></td> <td>3788'</td> </tr> <tr> <td colspan="5">Comments:</td> </tr> </tbody> </table>				Type	Size	Feet Used in Drilling	Amount of Cement or Mud	Feet Left in Well	Conductor/Drive Pipe:	11"	120'	315 sks	120'	Surface:	8 5/8"	451'	240 sks	451'	Intermediate:					Production:	4 1/2" 11.6#	3984'	175 sks	3984'	Tubing:	1 1/2"	3788'		3788'	Comments:				
Type	Size	Feet Used in Drilling	Amount of Cement or Mud	Feet Left in Well																																		
Conductor/Drive Pipe:	11"	120'	315 sks	120'																																		
Surface:	8 5/8"	451'	240 sks	451'																																		
Intermediate:																																						
Production:	4 1/2" 11.6#	3984'	175 sks	3984'																																		
Tubing:	1 1/2"	3788'		3788'																																		
Comments:																																						
38. Name of drilling contractor: Poulson Driling																																						
39. Type of electrical and/or radioactivity logs run: (all logs must be submitted) Gamma Ray, Neutron, Density, Resistivity & Gamma Ray CCL, VDL Bond, Perforating																																						
40. Name of logging company: Appalachian Well Surveys																																						

DIVISION USE ONLY		FRAC DATA SUBMITTED: _____ Well Class: _____	
Log Submitted: Y / N	Confidential: Y / N	Pressure/Rate Graph Record <input type="checkbox"/>	Invoice <input type="checkbox"/>
		<div style="border: 2px solid black; padding: 5px; display: inline-block;"> RECEIVED MAY 16 2013 Division of Oil & Gas Columbus </div>	

FORMATION	TOP	BASE	Shows of oil, gas, fresh water, or brine; indicate depth or interval	REMARKS
Freshwater Strata				
Glacial Deposits	0'	20'		
Coal Seams				
1st Cow Run				
Buell Run				
2nd Cow Run				
Salt Sand				
Maxton Sand				
Keener Sand				
Big Injun Sand				
Squaw Sand				
Mississippian Shale	50'	396'		
Weir Sand				
Berea Sand	396'	450'		
Bedford Shale	450'	520'		
2nd Berea				
Ohio Shale	520'	2168'		
Gantz				
Thirty Foot				
Gordon				
Cinnamon				
Marcellus				
Big Lime	2168'	3638'		
Sylvania				
Oriskany	2400'	2540'		
Bass Island	2540'	2554'		
Salina				
Salt Section	2790'	3162'		
Newburg				
Lockport	3360'	3638'		
Little Lime				
Packer Shell	3702'	3758'		
Stray Clinton				
Red Clinton	3794'	3820'		
White Clinton	3869'	3880'		
Medina	3938'	3948'		
Queenston	3948'	T.D.		
Utica				
Trenton				
Black River				
Gull River				
Glenwood Shale				
Knox Unconformity				
Beekmantown				
Rose Run				
Trempealeau/Copper Ridge				
"B" Zone				
Krysik				
Kerbel				
Conasauga				
Rome				
Mt. Simon				
Granite Wash				
Middle Run				
Granite				

RECEIVED
MAY 18 2013
Division of Oil & Gas
Columbus

I certify that the above information is true and correct, to the best of my knowledge:

William J. Hlavin GEOLOGIST

3-20-13

(SIGNATURE)

(DATE)

William J. Hlavin
(NAME typed or printed)

Geologist
(TITLE)

Bass Energy, Inc.
(REPRESENTING)

RECEIVED
MAY 18 2013
Division of Oil & Gas
Columbus

OHIO DIVISION OF GEOLOGICAL SURVEY

PSI:GRN, Ca1, D

22792

Permit No. 2792

Permit Issued 08/23/94

County SUMMIT Township COVENTRY Quad. AKRON WEST
 Section _____ Lot _____ Tract 2 Twp. Qtr. _____ X Coord. 2256720 Y Coord. 508830
 Measured 872' NL & 5500' WL OF TWP. (CIN LOT 2, Proposed TD 3950 Class _____ Tool RTAF
 Acres 20 TRACT 2)
 Landowner FORD-BAKER UNIT Well No. 1 Date Commenced 11-20-94
NORTH AMERICAN PETROLEUM Well No. _____ Date Completed 11-27-94
 Operator _____ Date PB _____
 GL 990 DF 994 KB 996 LTD 3952 DTD 3940 PB Depth _____
 TD Formation Queenston Prod. Formation Clinton
 Perforations (9) 3755-63; (7) 3769-75; (4) 3796-99; IP Natural _____ IP AT 50MCFG & 5B0
 Stimulation 40M gal wtr, 30M# sand, 500 gal acid; Initial Rock Pressure _____
 Casing Record 8 5/8" 501' 200sks, 4 1/2" 3901' 125sks Date Abandoned _____

FORMATION	TOP	BOTTOM	REMARKS	FORMATION	TOP	BOTTOM	REMARKS
COMPLETION	5-24-95						
Date put into production		12/8/94					
Big lime	2107	3594					
Packer shell	3674	3711					
Clinton stray	3725	3734					
Clinton red	3744	3776					
Clinton white	3795	3802					
Queenston	3902						
		3940	DTD; 3952'LTD				

FORMATION	TOP	BOTTOM	REMARKS	FORMATION	TOP	BOTTOM	REMARKS

EAST:GRN,Ca1,D,CCL

OHIO DIVISION OF GEOLOGICAL SURVEY

RI/RL 7-22-95

22803

Permit No. 2803

Permit Issued 12/22/94

County SUMMIT Township (PORTAGE) COVENTRY Quad. AKRON WEST

Section Lot Tract 2 Twp. Qtr. X Coord. (2258150) Y Coord. 508800

Measured (800' NL & 6920' WL OF TWP. (IN LOT 2, Proposed TD 3990 Class POOL Tool RTAF

Acres 21.740 TRACT 2}) 800' NL & 7055' WL of twp. Clinton - Pool - Fluid RT

Landowner LANGLEY UNIT Well No. 1 Date Commenced 9-22-95

Operator (VIKING RESOURCES CORP)* Well No. Date Completed 9-28-95

GL (1040) DF KB 986 LTD 3985 DTD 3990 PB Depth Date PB

TD Formation Queenston Prod. Formation Clinton

Perforations (4) 3792-95; (7) 3802-08; (4) 3811-14;* IP Natural IP AT 50MCFG & 2B0

Stimulation 250 gal 7½% HCL, 800sks 20/40 sand, 30M gal water; Initial Rock Pressure

Casing Record 8 5/8" 480' 175sks, 4½" 3908' 150sks Date Abandoned

FORMATION	TOP	BOTTOM	REMARKS	FORMATION	TOP	BOTTOM	REMARKS
COMPLETION 3-21-96				X= 2,258,300			
*(5) 3817-21;				*Whidbey Resources Inc.			
Ohio shale		2116					
Big lime	2134	3628					
Packer shell	3716	3750					
Clinton stray	3772	3778					
Clinton red	3786	3850					
Medina	3930	3944					
		3990	DTD; 3985'LTD				

FORMATION	TOP	BOTTOM	REMARKS	FORMATION	TOP	BOTTOM	REMARKS

OHIO DIVISION OF GEOLOGICAL SURVEY

EAST:GRN, Cal, D

22843

Permit No. 2843

Permit Issued 03/25/96

County SUMMIT Township COVENTRY Quad. AKRON WEST
 Section _____ Lot _____ Tract 2 Twp. Qtr. _____ X Coord. 2257000 Y Coord. 507640
 Measured 2038' NL & 5790' WL OF TWP (IN LOT 4, Proposed TD 3950 Class POOL Tool RTAF
 Acres 20 TRACT 2)
 Landowner MARR Well No. 1 Date Commenced 7-13-96
 Operator NORTH AMERICAN PETROLEUM Well No. _____ Date Completed 7-19-96
 GL 1000 DF _____ KB 1006 LTD 3924 DTD 3921 PB Depth _____ Date PB _____
 TD Formation Queenston Prod. Formation Clinton
 Perforations (9) 3745-53; (12) 3757-68; (9) 3773-81; IP Natural _____ IP AT 50MCFG & 5B0
 Stimulation 72M gal wtr, 50M# 20/40 Ottawa sand; Initial Rock Pressure _____
 Casing Record 8 5/8" 314' 200sks, 4 1/2" 3914' 125sks Date Abandoned _____

FORMATION	TOP	BOTTOM	REMARKS	FORMATION	TOP	BOTTOM	REMARKS
COMPLETION 11-21-96							
Big lime	2110	3596					
Packer shell	3675	3707					
Clinton red	3745	3768					
Clinton white	3773	3782					
Queenston	3902						
		3921	DTD; 3924'LTD				

DNR 4808 (Rev. 5-92)

FORMATION	TOP	BOTTOM	REMARKS	FORMATION	TOP	BOTTOM	REMARKS