



PAVEMENT DATA

ROUTE	FROM	TO	DISTANCE		PAVT WIDTH	TREATMENT WIDTH ***	TYPICAL SECTION	PAVT AREA	407	421
			MILES	FEET					TACK-LESSS TACK COAT **	MICRO-SURFACING, SURFACE COURSE
									TOTAL WIDTH OF PAVEMENT	
	SLM	SLM	MILES	FEET	FEET	FEET		SQ YD	GAL	SQ YD
ALL 75	1.00	1.40	0.40	2112	44 x (2)	24 x (2)	1	11264	1014	11264
ALL 75	2.94	3.40	0.46	2429	44 x (2)	24 x (2)	1	12954	1166	12954
ALL 75	4.60	5.25	0.65	3432	44 x (2)	24 x (2)	1	18304	1647	18304
Totals									3827	42522

ROUTE	FROM	TO	DISTANCE		621		642			REMOVAL OF PAVEMENT MARKING
			MILES	FEET	RPM WHITE/RED	RPM REMOVED	EDGE LINE WHITE 6" (TYPE 1)	EDGE LINE YELLOW 6" (TYPE 1)	LANE LINE 6" (TYPE 1)	
					EACH	EACH	MILE	MILE	MILE	MILE
ALL 75	1.00	1.40	0.40	2112	53	53	0.80	0.80	0.80	2.40
ALL 75	2.94	3.40	0.46	2429	61	61	0.92	0.92	0.92	2.76
ALL 75	4.60	5.25	0.65	3432	86	86	1.30	1.30	1.30	3.90
SUB-TOTALS					199	199	3.02	3.02	3.02	9.06

1,200 FT. of Item 642, Dotted Line, 6", Type 1 has been provided in the General Summary for delineating the entrance ramp from SR 65 to NB IR 75.

** Not carried to General Summary, Item is incidental to Microsurfacing per CMS 421.13. The quantity is provided for informational purposes only.

*** Microsurfacing will only be applied to the driving lanes. Shoulders will not be included.

I:\Projectdata\I4300\Design\Roadway\Sheets\I4300_006.dgn_Sheet 3/12/2021 8:59:37 AM mbrunet