

STATION RANGE			TYPICAL SECTION	SIDE	DISTANCE (D) (D)	AVERAGE WIDTH (W) (W)	SURFACE AREA (A) A=DxW/9 (SY)	CADD GENERATED AREA (SY)	204	301	304	407	442	442		407	441	441		204	203	204		204				
									SUBGRADE COMPACTION (SY)	ASPHALT CONCRETE BASE, PG64-22 (CY)	AGGREGATE BASE (CY)	NON-TRACKING TACK COAT@ 0.055 GAL/SY (GAL)	ASPHALT CONCRETE SURFACE COURSE, 12.5 MM, TYPE A (448) (CY)	ASPHALT CONCRETE INTERMEDIATE COURSE, 19 MM, TYPE A (448) (CY)		NON-TRACKING TACK COAT, @ 0.085 GAL/SY (GAL)	ASPHALT CONCRETE SURFACE COURSE, TYPE 1, (448), PG64-22 (CY)	ASPHALT CONCRETE INTERMEDIATE COURSE, TYPE 2, (448) (CY)		EXCAVATION OF SUBGRADE (CY)	GRANULAR MATERIAL, TYPE C (CY)	GEOTEXTILE FABRIC (SY)		PROOF ROLLING (HOUR)				
LOWES DRIVE																												
50+44.73	TO	50+99.26		LT	54.53	0.00	100.60	100.6	22.4	16.8	11.1	4.2	4.9															
							37.48	37.5		6.2										33.5	33.5	100.6		0.1				
																				12.5	12.5	37.5		0.1				
SHARED USE PATH ALONG US 22																												
96+95.29	TO	116+56.45		RT	1961.16	10.00	2179.07			484.24						185.22	60.53	121.06										
										16.14																		
										40.35																		
LOON @ ELKS DRIVE/PROGRESS WAY																												
115+55.66	TO	118+36.05		LT	280.39	0.00	587.79	587.79	130.6	98.0	64.66	24.5	28.6															
							132.45	132.45		22.1										195.9	195.9	587.8		0.3				
PAVEMENT @ WALMART SIGNAL																												
128+71.59	TO	128+71.59		LT/RT	0.00	0.00	111.53	111.53	24.8	18.6	12.27	4.6	5.4															
							0.93	0.93	0.2	0.2	0.10	0.04	0.05															
							0.83	0.83	0.2	0.1	0.09	0.03	0.04															
SUBTOTALS																												
								971.61	178.15	702.67	88.19	33.40	38.97			185.22	60.53	121.06		241.96	241.96	725.87		1.14				
TOTALS CARRIED TO GENERAL SUMMARY																												
								972	179	703	89	34	39			186	61	122		242	242	726		2				