



ROCK CHANNEL PROTECTION AT CULVERT AND STORM SEWER OUTLETS	1002-4
	REFERENCE SECTION 1002.2.3

Notes:

Rock size (6", 12", 18") indicates the square opening on which 85% of the material by weight is retained.

Provide rock channel protection the width of the headwall with a minimum of 4'.

No rock channel protection is required where the natural stream bed will withstand the calculated velocity without erosion.

Equations for length of protection:

Rise	Length
120"	$L = 0.764996 * V + 21.17502$
108"	$L = 0.0203 * V^2 + 0.3004 * V + 20.765$
96"	$L = 0.0184 * V^2 + 0.3121 * V + 17.892$
84"	$L = 0.0261 * V^2 + 0.1234 * V + 15.970$
72"	$L = 0.0251 * V^2 + 0.0897 * V + 13.798$
60"	$L = 0.0139 * V^2 + 0.3683 * V + 9.4671$
48"	$L = 0.0151 * V^2 + 0.2661 * V + 8.0899$
36"	$L = 0.0262 * V^2 + 0.1341 * V + 8.4794$
24"	$L = 0.0182 * V^2 + 0.1404 * V + 6.983$
12"	$L = 0.0014 * V^2 + 0.0816 * V + 4.1255$

$$L = 12.65' = [0.0182 * (14.21^2)] + (0.1404 * 14.21) + 6.983$$

V=Velocity (f.p.s.)

L=Length of minimum Rock Channel Protection (ft.)