

REF. NO.	ITEM	QTY.	UNITS	DESCRIPTION
6	625	1493	LF	CONDUIT, 1", 713.04
7	625	25	LF	CONDUIT, 1 1/2 ", 713.04
8	625	226	LF	CONDUIT, 2", 713.04
9	625	25	LF	CONDUIT, 3", 713.04
10	625	112	LF	CONDUIT, JACKED OR DRILLED UNDER PVM'T 2"
12	625	1783	LF	TRENCH, APP
15	625	18	EA.	PULL BOX, 713.08, 18"
18	632	2	EA.	GROUND ROD, APP
29	632	4	EA.	VEHICULAR SIGNAL HEAD, 3 SEC, 12" LENS 2 WAY
34	632	4	EA.	COVERING OF VEHICULAR SIGNAL HEAD
36	632	8	EA.	LOOP DETECTOR UNIT, DELAY AND EXTENSION TYPE, APP
38	632	128	LF	MESSANGER WIRE, 7 STRAND, 3/8 " DIAMETER WITH ACCESSORIES
40	632	369	LF	SIGNAL CABLE, 5 CONDUCTOR, NO. 14 AWG
45	632	158	LF	LOOP LEAD-IN CABLE W/ INTEG. MESS.
46	632	1684	LF	LOOP DETECTOR LEAD-IN CABLE, 2 CONDUCTOR, NO. 14 AWG
47	632	25	LF	POWER CABLE, 2 CONDUCTOR, NO. 6 AWG
48	632	20	LF	POWER CABLE, 3 CONDUCTOR NO. 6 AWG
50	632	1	EA.	POWER SERVICE, APP
56	632	2	EA.	STRAIN POLE, TYPE TC-81.10, DESIGN 10, 32'
67	632	1	EA.	REMOVAL OF TRAFFIC SIGNAL INSTALLATION, APP
69	632	1	EA.	SIGNALIZATION, : METER BASE, 100 AMP WITH BYPASS
74	632	466	LF	SIGNALIZATION, MISC.: LOOP DETECTOR PAVEMENT CUTTING, APP
76	632	2315	LF	SIGNALIZATION, MISC.: LOOP DETECTOR WIRE, TYPE E, APP
82	633	1	EA.	CONTROLLER, ACTUATED, 8 PHASE, SOLID STATE DIGITAL MICROPROCESSOR, APP WITH INTERNAL TIME BASE CORD.
88	633	10.4	SF	CONTROLLER WORK PAD (30"x50")

* INHIBIT DELAY DURING PHASE
2 GREEN INTERVAL