

Project Location 1B

Item 202 - Pavement Removed, As Per Plan

For work designated in "LOCATION 1B-PRESSURE RELIEF JOINT REPAIRS",
This item shall be used in repairing pressure relief joints in the existing concrete pavement.

The depth of the removals shall be based on the typical sections in the plans.
The size and location of the repair areas shall be determined by the Engineer.
(For estimating purposes, the width is based on 4 FT.)

The contractor shall take care to avoid damaging surrounding concrete pavement.

All costs associated with this item including the sawcutting, labor, materials and equipment shall be included in Item 202 - Pavement Removed, As Per Plan.

The estimated quantities in the sub-summary shall be carried to the General Summary to be used as outlined above.

Item Special – Pressure Relief Joint, Type A

This item shall be used in replacing pavement pressure relief joints at the designated locations in the plans.

Description: This work consists of furnishing and placing asphalt concrete, Item 442 Asphalt Concrete Intermediate Course, 12.5mm, Type A (449), to reconstruct Pressure Relief Joint, Type A, in accordance with the details shown in the plans.

Place and compact asphalt concrete in equal courses not exceeding 3" with compaction equipment as Approved by the Engineer.

The finished surface of the asphalt concrete shall be flush to 1/4-inch above the adjacent concrete pavement and approach slab surface.

Where an existing curb is present, form asphalt concrete in place to conform with the adjacent curb.

Measurement and Payment: The Department will measure this item by the number of linear feet complete in place and measured along the skew at the end of the bridge approach slab.

The Department will pay for completed and accepted quantities at the contract price per foot for:

Item Special – Pressure Relief Joint, Type A

DESIGN AGENCY



DESIGNER

JAG

REVIEWER

DAB 10/11/24

PROJECT ID

113132

SHEET

P.18

TOTAL

42