

[illegible]

MATERIAL DESCRIPTION AND NOTES		ELEV. 688.0	DEPTHS	SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	SO4 ppm	HOLE SEALED
									GR	CS	FS	SI	CL	LL	PL	PI				
VERY STIFF TO HARD, GRAY, SILTY CLAY , LITTLE SAND AND TRACE GRAVEL, DAMP (continued) @33.5': SOME SAND		682.0																		
			32																	
			33																	
			34	5	9	26	100	SS-16	4.50	-	-	-	-	-	-	-	12	A-6b (V)	-	
			35		11															
			36																	
			37																	
			38																	
			39	17	17	40	100	SS-17	4.00	0	0	4	46	50	21	14	7	14	A-4a (8)	-
			40		14															
HARD, GRAY, SANDY SILT , "AND" CLAY, DAMP		676.0																		
			41																	
			42																	
			43																	
			44	4	7	21	100	SS-18	4.50	-	-	-	-	-	-	-	14	A-6b (V)	-	
			45		9															
			46																	
			47																	
			48																	
			49	9	23	52	100	SS-19	4.25	-	-	-	-	-	-	-	14	A-6b (V)	-	
VERY STIFF TO HARD, GRAY, SILTY CLAY , LITTLE SAND AND TRACE GRAVEL, DAMP @53.5': LITTLE SAND		669.5																		
			50		17															
			51																	
			52																	
			53																	
			54	9	13	39	100	SS-20	4.50	-	-	-	-	-	-	-	14	A-6b (V)	-	
			55		17															
			56																	
			57																	
			58																	
HARD, GRAY, SILT AND CLAY , LITTLE SAND AND TRACE GRAVEL, DAMP		660.5																		
			59	11	17	53	17	SS-21	5.44*	2	3	7	22	66	28	13	15	13	A-6a (10)	-
			60		24															
			61																	
			62																	
			63																	
			64	9																
			65																	
			66																	
			67																	

