

**ITEM 408 - PRIME COAT, AS PER PLAN**

THE CONTRACTOR SHALL APPLY ONE COAT OF MC-70 (AS PER SECTION 702) AT A RATE OF 0.40 GAL/SY TO THE COMPLETED AGGREGATE SHOULDER (ITEM 617) AS DIRECTED BY THE ENGINEER. THE CONTRACTOR SHALL PROVIDE A SHIELD TO PREVENT THE SPRAYING OR DRIFTING OF LIQUID BITUMINOUS MATERIAL ONTO THE EDGE OF PAVEMENT OR EDGE LINE. THE ATTENTION OF THE CONTRACTOR IS DIRECTED TO 107.10 OF THE SPECIFICATIONS.

**PROFILE AND ALIGNMENT**

PLACE THE PROPOSED ASPHALT CONCRETE OVERLAY TO FOLLOW THE ALIGNMENT AND PROFILE OF THE EXISTING PAVEMENT. (PREVIOUS CONSTRUCTION PLANS SHOWING THE ORIGINAL ALIGNMENT AND PROFILE, ARE AVAILABLE FOR INSPECTION AT THE ODOT DISTRICT 3 OFFICE). PLACE THE PROPOSED ASPHALT CONCRETE OVERLAY AS SHOWN ON THE TYPICAL SECTIONS.

**ITEM 254 - PATCHING PLANED SURFACE**

AN ESTIMATED QUANTITY OF ITEM 254 - PATCHING PLANED SURFACE HAS BEEN SET UP TO BE USED AS DIRECTED BY THE ENGINEER AS DESCRIBED IN CMS 254.04. THE LIMIT OF THE PATCHING DEPTH IS 0 TO 2 IN.

**ITEM 254 - PAVEMENT PLANING, ASPHALT CONCRETE**

UNCURBED SECTIONS: THE INTENT OF THE PLANING IS TO MILL 1.5 INCHES AT THE CENTER OF PAVEMENT AT NON-CURBED AREAS. THE PAVEMENT SLOPE SHALL BE 0.010 MINIMUM AND 0.016 PREFERRED, CONTINUOUS BETWEEN THE CROWN AND THE PROPOSED EDGELINE/SHOULDER. THE MILLING DEPTH SHALL BE CONTROLLED FROM THE CENTER OF PAVEMENT IN CONFORMANCE WITH THE ABOVE GUIDELINES.

DRAINAGE SLOTS SHALL BE CUT INTO THE SHOULDER(S) OF UNCURBED SECTIONS AT THE LOW POINT OF EACH PLANED SECTION TO PREVENT TRAPPED WATER PUDDLES AND REFILLED DURING RESURFACING. CUTTING AND FILLING DRAINAGE SLOTS SHALL BE INCLUDED IN PAYMENT WITH ITEM 254 PAVEMENT PLANING, ASPHALT CONCRETE.

CURBED SECTIONS: THE INTENT OF THE PLANING IS TO MILL THE SPECIFIED DEPTH ALONG THE CURB CONTINGENT ON THE FOLLOWING: THE MAXIMUM CROSS SLOPE SHALL BE 0.02 WHILE THE MINIMUM CROSS SLOPE SHALL BE 0.01. THE PREFERRED CROSS SLOPE IS 0.016. THE CROWN OF THE PAVEMENT SHALL BE LOCATED BETWEEN THE TRAVELED LANES, OR AS DIRECTED BY THE ENGINEER. THE MILLING DEPTH SHALL BE CONTROLLED FROM THE CURB, TO PRODUCE A CROSS SLOPE IN CONFORMANCE WITH THE ABOVE GUIDELINES.

CURB & GUTTER SECTIONS: THE INTENT OF THE PLANING IS TO MILL THE SPECIFIED DEPTH ALONG THE INSIDE EDGE OF THE GUTTER PLATE CONTINGENT ON THE FOLLOWING: THE MAXIMUM CROSS SLOPE SHALL BE 0.02 WHILE THE MINIMUM CROSS SLOPE SHALL BE 0.01. THE PREFERRED CROSS SLOPE IS 0.016. THE CROWN OF THE PAVEMENT SHALL BE LOCATED BETWEEN THE TRAVELED LANES, OR AS DIRECTED BY THE ENGINEER. THE MILLING DEPTH SHALL BE CONTROLLED FROM THE CURB, TO PRODUCE A CROSS SLOPE IN CONFORMANCE WITH THE ABOVE GUIDELINES.

**ALL SECTIONS:**

THE CONTRACTOR SHALL MAINTAIN POSITIVE DRAINAGE TO ALL CATCH BASINS AND INLETS.

THE PROGRESSION OF THE PLANING SHALL PROCEED IN SUCH A MANNER THAT NORMAL TRAFFIC WILL NOT BE REQUIRED TO RUN OVER THE PLANED ROADWAY SURFACE MORE THAN FOURTEEN (14) CALENDAR DAYS. FOR EACH CALENDAR DAY BEYOND THE 14 DAYS THAT THE ROADWAY REMAINS EXPOSED TO THE PLANED SURFACE, THE CONTRACTOR WILL BE ASSESSED A DISINCENTIVE FEE OF \$1000 PER DAY.

THE AMOUNT OF GRINDINGS RESULTING FROM THIS WORK MAY PRODUCE UNEXPECTED VOLUMES OF GRINDINGS DUE TO THE EXISTING TRANSVERSE SLOPE OF THE PAVEMENT. THERE WILL BE NO ADDITIONAL COMPENSATION FOR THE DISPOSAL OF EXTRA MILLINGS.

PAYMENT SHALL INCLUDE ALL LABOR, EQUIPMENT, AND MATERIALS NECESSARY TO COMPLETE THE PAVEMENT PLANING, ASPHALT CONCRETE. PAYMENT WILL BE MADE AT THE UNIT BID PRICE PER SQUARE YARD OF ITEM 254 - PAVEMENT PLANING, ASPHALT CONCRETE.

**ITEM 442 - ASPHALT CONCRETE SURFACE COURSE, 9.5 MM, TYPE A (446), AS PER PLAN, PG64-22**

ALL OPEN TRANSVERSE JOINTS SHALL BE TAPERED TO MEET EXISTING PAVEMENT BEFORE INTRODUCING TRAFFIC. A "BUMP" SIGN (W8-1-36) SHALL BE ERCTED ON EACH SIDE OF TRANSVERSE JOINTS LEFT OPEN OVER NIGHT, INCLUDING A SPEED ADVISORY SIGN. THESE SIGNS SHALL BE REMOVED IMMEDIATELY AFTER JOINT HAS BEEN CLOSED. PLACEMENT OF SIGNS SHALL BE INCLUDED IN THE UNIT PRICE BID FOR ITEM 614 MAINTAINING TRAFFIC.

CARE SHALL BE TAKEN TO MATCH EXISTING PAVEMENT ELEVATIONS AT EXISTING PAVED BERMS, DRIVES, INTERSECTIONS, ETC.

REQUIREMENTS OF 442 APPLY EXCEPT AS FOLLOWS:  
MIX DESIGN: FOR Ndes USE 50 GYRATIONS, FOR Nmax USE 75 GYRATIONS.  
CHOOSE OPTIMUM BINDER CONTENT AT DESIGN AIR VOIDS OF 3.5%.  
MINIMUM TOTAL PG BINDER CONTENT IS 6.3 PERCENT.  
MINIMUM VIRGIN PG BINDER CONTENT IS 5.2 PERCENT.  
USE A PG 64-22 BINDER.

WHEN AN AGGREGATE SOURCE IS SPECIALLY DESIGNATED WITH AN SR ON THE AGGREGATE GRAVITY LIST DO NOT USE THE AGGREGATE EXCEPT AS ALLOWED FOR MEDIUM TRAFFIC IN THE GUIDELINES FOR MAINTAINING ADEQUATE PAVEMENT FRICTION IN SURFACE PAVEMENT.  
QUALITY CONTROL: DO NOT PERFORM Nmax IN QUALITY CONTROL TESTING. DO NOT TAKE EXTRA ASPHALT BINDER SAMPLES AS OUTLINED IN CMS 442.05.

**SAWCUTS**

ALL REQUIRED SAWCUTS ON THE PROJECT SHALL BE INCIDENTAL TO ASSOCIATED PROJECT ITEMS. NO SEPARATE PAYMENTS WILL BE MADE.

**ITEM 251 - PARTIAL DEPTH PAVEMENT REPAIR (442), AS PER PLAN  
ITEM 253 - PAVEMENT REPAIR, AS PER PLAN**

THESE ITEMS OF WORK SHALL CONSIST OF THE REMOVAL OF THE EXISTING PAVEMENT OR PAVED BERM WHICH MAY BE ASPHALT, BRICK, CONCRETE, OR A COMBINATION OF EACH, IN AREAS OF EXISTING PAVEMENT FAILURE. CORING HAS BEEN PERFORMED TO HELP DETERMINE THE COMPONENTS THAT MAY BE ENCOUNTERED DURING THESE ITEMS OF WORK. THE PAVEMENT CORING INFORMATION IS SHOWN ON SHEET 10.

PAVEMENT REPAIR SHALL BE PERFORMED AFTER PAVEMENT PLANING AND BEFORE PLACEMENT OF THE INTERMEDIATE AND SURFACE COURSES. THE DEPTH OF REMOVAL SHALL BE SUFFICIENT TO REMOVE ALL DETERIORATED PAVEMENT WITH A MAXIMUM DEPTH OF 12", BASED ON THE PAVEMENT DESIGN AND AN AVERAGE DEPTH OF 4" AND AN AVERAGE WIDTH OF 4 FT FOR ESTIMATING PURPOSES. THE CONTRACTOR SHALL BE CAPABLE OF PERFORMING PAVEMENT REPAIRS 2 FT WIDE.

REPLACEMENT MATERIAL SHALL BE ITEM 301, OR ITEM 442 19MM, AS PER PLAN MATERIAL AND SHALL BE PLACED AND COMPACTED TO FINISH FLUSH WITH THE ADJACENT PAVEMENT SURFACE. ITEM 301 ASPHALT CONCRETE CAN BE USED WHEN THE DEPTH OF THE REPAIR IS BETWEEN 3" AND 12" WITH A MAXIMUM PAVEMENT LIFT OF 6". ITEM 442 19MM, AS PER PLAN CAN BE USED WHEN THE DEPTH OF THE REPAIR IS BETWEEN 1.5" AND 3". PG 64-22 ASPHALT BINDER SHALL BE USED FOR ALL OF THE ASPHALT CONCRETE MATERIALS FOR THESE REPAIRS.

FOR THE ITEM 442 19MM, AS PER PLAN MATERIAL, REQUIREMENTS OF 442 APPLY EXCEPT AS FOLLOWS:

MIX DESIGN: FOR Ndes USE 50 GYRATIONS, FOR Nmax USE 75 GYRATIONS.  
CHOOSE OPTIMUM BINDER CONTENT AT DESIGN AIR VOIDS OF 3.5%.  
MINIMUM TOTAL PG BINDER CONTENT IS 6.3 PERCENT.  
MINIMUM VIRGIN PG BINDER CONTENT IS 5.2 PERCENT.  
USE A PG 64-22 BINDER.

PAYMENT SHALL INCLUDE ALL LABOR, EQUIPMENT, AND MATERIALS NECESSARY TO COMPLETE THE PAVEMENT REPAIR. FOR PAYMENT PURPOSES ITEM 251 PARTIAL DEPTH PAVEMENT REPAIR (442) IS TO BE A MAXIMUM OF 4" DEEP AND ITEM 253 IS FOR DEPTHS GREATER THAN 4". PAYMENT WILL BE MADE AT THE UNIT BID PRICE PER CUBIC YARD, (BY TICKET WEIGHT CONVERSION), OF ITEM 251 - PARTIAL DEPTH PAVEMENT REPAIR (ASPHALT CONCRETE BASE) OR ITEM 253 - PAVEMENT REPAIR. THE FOLLOWING ESTIMATED QUANTITIES ARE PROVIDED IN THE GENERAL SUMMARY TO BE USED AS DIRECTED BY THE ENGINEER.

RIC-309-3.93 TO 6.40:  
ITEM 251, PARTIAL DEPTH PAVEMENT REPAIR (442) 350 CU. YDS. (02/S<2/PV)  
ITEM 253, PAVEMENT REPAIR (FULL DEPTH) 190 CU. YDS. (02/S<2/PV)

RIC-430-0.00 TO 2.19:  
ITEM 251, PARTIAL DEPTH PAVEMENT REPAIR (442) 650 CU. YDS. (02/S<2/PV)  
ITEM 253, PAVEMENT REPAIR (FULL DEPTH) 360 CU. YDS. (02/S<2/PV)

TOTAL:  
ITEM 251, PARTIAL DEPTH PAVEMENT REPAIR (442) 1000 CU. YDS. (02/S<2/PV)  
ITEM 253, PAVEMENT REPAIR (FULL DEPTH) 550 CU. YDS. (02/S<2/PV)

**ITEM 623 - MONUMENT BOX ADJUSTED TO GRADE AS PER PLAN &  
ITEM 638 - VALVE BOX ADJUSTED TO GRADE AS PER PLAN**

PRIOR TO PERFORMING ITEM 254, PAVEMENT PLANING, ASPHALT CONCRETE, THE CONTRACTOR SHALL LOWER THE MONUMENT BOX OR VALVE BOX, OR REMOVE THE MONUMENT BOX OR VALVE BOX FOR STORAGE AND REMOVE AND DISPOSE OF ANY ASSOCIATED MATERIAL. THE OPEN AREA SHALL BE PLATED AND FILLED WITH ASPHALT MATERIAL, MATCHING THE ADJACENT GRADE. FOLLOWING THE SURFACE COURSE PAVING OPERATION, THE CONTRACTOR SHALL LOCATE AND EXPOSE THE MONUMENT BOX OR VALVE BOX LOCATION. THE CONTRACTOR SHALL RAISE OR INSTALL THE STORED MONUMENT BOX OR VALVE BOX. IF THE ORIGINAL MONUMENT BOX OR VALVE BOX IS UNSUITABLE FOR REUSE, AS DETERMINED BY THE ENGINEER, THE CONTRACTOR SHALL OBTAIN A SUITABLE MONUMENT BOX OR VALVE BOX. A QUANTITY OF MISCELLANEOUS METAL HAS BEEN PROVIDED FOR USE AS DIRECTED BY THE ENGINEER FOR REPLACEMENT OF UNSUITABLE MONUMENT BOXES OR VALVE BOXES.

THE ADJACENT PAVEMENT SHALL BE FLUSH WITH THE MONUMENT BOX OR VALVE BOX AND MONUMENT BOX OR VALVE BOX APRON WITH A DIFFERENCE IN ELEVATION NOT TO EXCEED 1/8 INCH. THE ENGINEER WILL INSPECT EACH MONUMENT BOX OR VALVE BOX USING A 10 ROOT HAND LEVEL PROVIDED BY THE CONTRACTOR.

PAYMENT FOR ITEM 623, MONUMENT BOX ADJUSTED TO GRADE, AS PER PLAN AND ITEM 638, VALVE BOX ADJUSTED TO GRADE, AS PER PLAN SHALL INCLUDE ALL LABOR, MATERIAL AND EQUIPMENT REQUIRED TO PERFORM THE ITEM OF WORK AS DESCRIBED IN THIS SECTION. BASIS OF PAYMENT WILL BE AT THE CONTRACT BID PRICE FOR EACH. THE FOLLOWING ESTIMATED QUANTITY HAS BEEN CARRIED TO THE GENERAL SUMMARY FOR USE AS DIRECTED BY THE ENGINEER. THE FINAL QUANTITY SHALL BE AS AGREED UPON DURING A FIELD REVIEW BETWEEN CONTRACTOR AND ENGINEER.

ITEM 623 - MONUMENT BOX ADJUSTED TO GRADE, AS PER PLAN 1 EACH (01/S<2/PV)  
ITEM 638 - VALVE BOX ADJUSTED TO GRADE, AS PER PLAN 31 EACH (01/S<2/PV)

**INTERSECTIONS AND DRIVES**


INTERSECTIONS LISTED BELOW SHALL BE PLANED AND PAVED TO THE END OF THE RADII OR AS DIRECTED BY THE ENGINEER. (TO PROVIDE A SMOOTH TRANSITION BETWEEN THE TWO HIGHWAYS, AND TO ELIMINATE WATER POCKETS).

EXISTING PAVED DRIVES SHALL BE PAVED SO AS TO PROVIDE A SMOOTH TRANSITION BETWEEN THE HIGHWAY AND THE DRIVE, (DISTANCE FROM EDGE OF ROADWAY MAY VARY AT EACH DRIVE) AS DIRECTED BY THE ENGINEER.

EXISTING AGGREGATE DRIVES SHALL BE PAVED WITH AN APRON AN AVERAGE WIDTH OF 4 FT. THE SLOPE OF THIS APRON SHALL BE THE SAME AS THE ADJACENT PAVEMENT SLOPE OR AS DIRECTED BY THE ENGINEER. ANY GRADING NEEDED TO PAVE THE APRON SHALL BE INCLUDED IN THE RELATED ASPHALT ITEM FOR PAYMENT. ITEM 617 COMPACTED AGGREGATE SHALL BE PLACED ADJACENT TO THIS APRON TO PROVIDE A SMOOTH TRANSITION FROM THE APRON TO THE EXISTING DRIVE, (WIDTH OF THIS 617 APPLICATION MAY VARY) AS DIRECTED BY THE ENGINEER. AN ADDITIONAL QUANTITY OF ITEM 617 HAS BEEN ESTIMATED TO COMPLETE THIS WORK AND IS SHOWN AS AN EXTRA AREA ON THE PAVEMENT & SHOULDER DATA SHEET.

ANY HAZARD OR UNSAFE CONDITION RESULTING FROM THE ABOVE WORK MUST BE CORRECTED IMMEDIATELY. THE CONTRACTOR IS REMINDED OF SECTIONS 105.01, 107.07 & 614.02A OF THE CONSTRUCTION AND MATERIALS SPECIFICATIONS.

THE PAVING DIMENSIONS FOR THE INTERSECTIONS ARE SHOWN IN THE CHART BELOW.



Intersection Name	A (FT)	B (FT)	C (FT)	Area (SY)
<b>S.R. 309</b>				
BEMILLER DR	12	60	90	93
<b>S.R. 430</b>				
HARDING HEIGHTS BLVD	23	25	74	106
HILLTOP RD	17	27	65	75
CLARE RD	20	30	72	98
GEARY RD	20	21	59	75
FRAZIER RD	23	25	71	103
SUNSET RD N	15	33	68	74
SUNSET RD S	24	21	59	90
BETHEL LN	16	25	60	65
IRELAND BLVD N	16	22	44	52
IRELAND BLVD S	19	29	64	86
SCOTLAND BLVD	18	30	81	94
WESTLAWN DR	18	30	63	82
MAPLE LN	23	28	62	101
WILLOWDELL DR	15	21	37	44
WOODBINE DR	20	30	66	93
LYNN DR	17	30	62	77
<b>Total Intersection Areas</b>				<b>1408</b>

**ITEM 606 - ANCHOR ASSEMBLY, TYPE E**

THIS ITEM SHALL CONSIST OF FURNISHING AND INSTALLING ANY OF THE GUARDRAIL END TERMINALS AS LISTED ON ROADWAY ENGINEERING'S WEB PAGE UNDER ROADSIDE SAFETY DEVICES FOR APPROVED GUARDRAIL END TREATMENTS. INSTALLATION SHALL BE AT THE LOCATIONS SPECIFIED IN THE PLANS, IN ACCORDANCE WITH THE MANUFACTURER'S SPECIFICATIONS.

THE FACE OF THE TYPE E IMPACT HEAD SHALL BE COVERED WITH A SHEET OF TYPE G REFLECTIVE SHEETING, PER CMS 730.19.

THE CONTRACTOR MAY USE A SALVAGED EXTRUDER WHEN ASSEMBLING THE ITEM 606 ANCHOR ASSEMBLY, TYPE E. ALL WELDS ON THE EXTERIOR OF THE SALVAGED EXTRUDER SHALL NOT BE DAMAGED AND THE FEEDER SHUTE SHALL NOT BE BENT.

REFER TO THE MANUFACTURER'S INSTRUCTIONS REGARDING THE INSTALLATION OF, AND THE GRADING AROUND, THE FOUNDATION TUBES AND GROUND STRUT. THE TOP OF ANY FOUNDATION TUBE SHOULD BE LESS THAN 4 INCHES ABOVE THE GROUND. THE PLACEMENT OF THE FOUNDATION TUBES SHOULD BE AN APPROPRIATE DEPTH BELOW THE LEVEL LINE IN ORDER TO MAINTAIN THE FINISHED GUARDRAIL HEIGHT OF 27 3/4 INCHES FROM THE EDGE OF THE SHOULDER. ON SITE GRADING IS REQUIRED IF THE TOP OF THE FOUNDATION TUBES OR TOP OF THE GROUND STRUT PROJECT MORE THAN 4 INCHES ABOVE THE GROUND LINE.

PAYMENT FOR THE ABOVE WORK SHALL BE MADE AT THE UNIT PRICE BID FOR ITEM 606, ANCHOR ASSEMBLY, TYPE E, EACH, AND SHALL INCLUDE ALL LABOR, TOOLS, EQUIPMENT AND MATERIALS NECESSARY TO CONSTRUCT A COMPLETE AND FUNCTIONAL ANCHOR ASSEMBLY SYSTEM, INCLUDING ALL RELATED TRANSITIONS, REFLECTIVE SHEETING, HARDWARE, GRADING, EMBANKMENT AND EXCAVATION NOT SEPARATELY SPECIFIED, AS REQUIRED BY THE MANUFACTURER.

ALL TYPE E ANCHOR ASSEMBLIES SUPPLIED ON THIS PROJECT SHALL MEET THE REQUIREMENTS OF MASH 2016 TESTING.

I:\ProjectData\01442\Design\Roadway\Sheets\01442\_GN001.dgn GENNOTES 2 4/1/2020 1:41:29 PM jclarke

CALCULATED  
JNC  
CHECKED  
NRF

GENERAL NOTES

RIC - 309 - 3.93

8  
24