

STATION RANGE	TYPICAL SECTION	SIDE	DISTANCE (D) FT	AVERAGE WIDTH (W) FT	SURFACE AREA (A) A=D*W/9 SQ YD	CADD GENERATED AREA SQ YD	204	204	304	407	441	204	204	204	832				
							SUBGRADE COMPACTION	PROOF ROLLING	AGGREGATE BASE	TACK COAT	ASPHALT CONCRETE SURFACE COURSE, TYPE 1, (449), PG64-22	EXCAVATION OF SUBGRADE	GRANULAR MATERIAL, TYPE B	GEOTEXTILE FABRIC	EROSION CONTROL				
							SY	HOUR	CY	GAL	CY	CY	CY	SY	EACH				
	TO																		
3+47.74			120.01	10.00	133.34		173.35	0.06	22.22	16.00	11.11	2.89	2.89	8.67					
5+32.25			142.75	10.00	158.61		206.19	0.07	26.44	19.03	13.22	3.44	3.44	10.31					
9+39.11			107.64	6.00	71.76		107.64	0.04	11.96	8.61	5.98	1.79	1.79	5.38					
			0.00			117.72	117.72	0.04	19.62	14.13	9.81	1.96	1.96	5.89					
3+47.74			327.26		0.00										8500.00				
SUBTOTALS							604.90	0.20	80.24	57.77	40.12	10.08	10.08	30.25	8500.00				
TOTALS CARRIED TO GENERAL SUMMARY							605	1	80.3	58	40.2	11	11	31	8500				