STATE OF OHIO - DEPT. OF HIGHWAYS
BUREAU OF BRIDGES

RAILROAD GRADE SEPARATIONS

DATE

-BR.
ACME 14803-8

TYPE OF SEPARATION - OVERHEAD ✓ SUBWAY HIGHWAY RELOCATION

RAILROAD COMPANY OR COMPANIES ~~B&O~~ CSX R.R. & R.R. St. Under I.R. 77

IF MAINTAINED OVERHEAD TYPE, SEE SEPARATE STRUCTURAL CARD, OTHERWISE SEE DESCRIPTION ON THIS CARD.

MAINTENANCE OF STRUCTURE BY State of Ohio.

MAINTENANCE OF APPROACHES AND ROADWAY BY " " "

MAINTENANCE OF DRAINAGE BY " " "

MAINTENANCE OF PIER LIGHTS BY

PROVISION FOR FUTURE R.R. DEVELOPMENT Provision for two future tracks.

LEGAL HISTORY

AGREEMENT DATED AGREEMENT FILE NO.

SEPARATED GRADES PUT IN SERVICE

TOTAL COST OF PROJECT

APPORTIONMENT OF COST

VACATION AND RELOCATION PROCEEDINGS RECORDED IN

DIRECTOR'S JOURNAL	YEAR	VOLS.	PAGES

ADDITIONAL INFORMATION Min. R.R. Clearance ~~22'-3¾"~~ ~~22'-5~~ N.B. Bridge (R)
" " " ~~21'-89"~~ 21'-11½" S.B. Bridge (L)

3002977
0900R
GUE-077-~~0892R~~

Rear Br. Sta. 517+53.11 (℄ N.B Lanes) = 10.101

GRADE SEPARATION	COUNTY	ROUTE NO.	R.R. AND METHOD OF ELIM.	STRENGTH				ROADWAY			CLEARANCE				TYPE				
				H10	H12	H15	H20	15-18	19-22	23 +	12	12-14	14 +	OPEN	A	B	G	S	T
GUE-77-0900-R	Guernsey	77	B&O. Overhead				X			X				X		27			