

INDEX

A

- AAADT. *See* Average Annual Daily Traffic
- Accessibility considerations
 - temporary traffic control, 563–564
- Accessibility parking space marking, 387, 387f
- Accessible pedestrian signals/detectors, 504–508
 - defined, 11
 - extended pushbutton press features for, 507–508
 - location for, 505
 - locator tones for, 507
 - tactile arrows for, 507
 - walk indications with, 505–507
- Acknowledgement signs, 297–298, 298f
- Active Grade Crossing Warning System
 - defined, 11
- Active traffic control devices
 - grade crossing with, 770f
- Activity area
 - safety with, 564
- Actuated Operation
 - defined, 11
- Actuation
 - defined, 11
- ADAAG. *See* Americans with Disabilities Act Accessibility Guidelines for Buildings and Facilities
- Added lane sign (W4-3), 125f, 126
- Adjacent to roadway object markers, 135–136, 135f
- Adult crossing guards, 745–746
- Advance crossing assembly, 736, 741f
 - ahead plaque with, 736, 741f
- Advance guide signs, 216–218, 217f
- Advance intersection lane control sign, 64
- Advance Preemption
 - defined, 11
- Advance Preemption Time
 - defined, 11
- Advance ramp control sign, 121f, 124
- Advance speed hump markings, 395, 398f
- Advance street name plaque, 132f, 133
- Advance street name signs (D3-2), 163–164
- Advance traffic control sign (W3-1), 121f, 123–124
- Advance turn arrow auxiliary signs (M5-1), 147, 147f
- Advance turn arrow signs (M5 series), 792t, 800f, 802
- Advance warning area, 552–554, 554t
 - minimum spacing for, 554t
- Advisory exit/ramp speed sign, 109f, 114–115, 116f
- Advisory Speed
 - defined, 11
 - plaque, 109f, 110t, 111f, 112, 589f, 596
- AFAD. *See* Automated Flagger Assistance Device
- Ahead plaque (W16-9P), 736, 741f
- Alley
 - defined, 11
- All-terrain trail sign, 339f
- All way plaque, 51–52, 51f
- All year plaque, 735f, 736
- Altered Speed Zone
 - defined, 11
- Alternate auxiliary signs, 145–146, 145f
- Alternative fuel - compressed natural gas sign, 299t, 301f
- Alternative fuel - ethanol sign, 299t, 301f
- Alternative route signs (M4 series), 792t, 800f, 802
- AMBER alert. *See* America's Missing: Broadcast Emergency Response
- Ambulance station plaque, 300t, 301f
- American Association of State Highway and Transportation Officials (AASHTO)
 - "American Railway Engineering and Maintenance-of-Way Association's Engineering Manual," 764
 - "Guide for Development of Bicycle Facilities," 789
 - "Guidelines for the Selection of Supplemental Guide Signs for Traffic Generators Adjacent to Freeways," 218–219
 - highway numbering by, 142
 - "Policy on Geometric Design of Streets and Highways," 352, 710, 714, 716
 - "Purpose and Policy" statement of, 179
 - "Roadside Design Guide," 41–42, 493, 562, 576, 617–618
 - "Specifications for Structural Supports for Highway Signs, Luminaires, and Traffic Signals," 44
 - "Standard Specifications for Movable Highway Bridges," 519
 - supports for signs standardized by, 206
- Americans with Disabilities Act Accessibility Guidelines for Buildings and Facilities (ADAAG)
 - temporary traffic control devices in, 581
- America's Missing: Broadcast Emergency Response (AMBER alert), 325
- Amphitheater sign, 339f
- Approach
 - defined, 11
- Archery sign, 339f
- Area closed sign, 343f, 343t, 344
- Arrow boards
 - alternating diamond caution in, 602f, 603
 - color of, 601
 - dimming of, 601
 - elements of, 601, 602f
 - flashing arrow in, 602f, 603
 - flashing caution in, 602f, 603
 - flashing double arrow in, 602f, 603
 - legibility distance of, 601, 602f
 - modes of, 603
 - sequential arrow in, 602f, 603
 - sequential chevron in, 602f, 603
 - size of, 601, 602f
 - temporary traffic control with, 601–603, 602f
- Arrows
 - advance turn, 147, 147f
 - conventional road guide signs with, 140–142, 141f
 - directional, 147f, 148
 - double, 118f, 119
 - DOWNWARD GREEN, 525
 - Dual-Arrow Signal Section, 13
 - interchange guide signs, 192–193
 - lane-reduction, 392f
 - through lane-use, 392f
 - one-direction large, 109f, 111f, 113–114
 - one-way left turn, 525, 526f
 - overhead per-lane, 193–198, 194f–197f
 - pavement markings, 387–393, 389f, 392f
 - roundabout lane-use, 400f
 - roundabout markings with, 413–414
 - supplemental warning plaques, 132–133, 132f

- tactile, 507
 - turn and through lane-use, 392f
 - turn lane-use, 392f
 - two-direction large, 127f, 128
 - two-way left turn, 525, 526f
 - wrong-way, 23, 392f
 - Arterial Highway**
 - defined, 11
 - Attended Lane**
 - defined, 11
 - Automated Flagger Assistance Device (AFAD), 567–569**
 - night time use of, 568
 - policy for use of, 568–569
 - red/yellow lens, 571–573, 572f
 - STOP/SLOW, 569–571, 570f
 - types of, 568
 - use of, 568
 - Automatic gates**
 - rail grade crossing traffic control with, 772–773
 - Automatic Lane**
 - defined, 11
 - Auto tour route signs, 297**
 - Auxiliary signs, 142–144, 143f**
 - advance turn arrow, 147, 147f
 - alternate, 145–146, 145f
 - begin, 145f, 146–147
 - business, 145f, 146
 - by-pass, 145f, 146
 - cardinal direction, 145, 145f
 - directional arrow, 147f, 148
 - end, 145f, 146
 - junction, 144, 145f
 - lane designation, 147f, 148
 - temporary, 145f, 147
 - temporary detour, 147
 - truck, 145f, 146
 - Auxiliary signs for alternative routes (M4 series), 145, 145f**
 - Average Annual Daily Traffic (AADT)**
 - defined, 11
 - Average Day**
 - defined, 11
 - Axle weight limit sign (R12-2), 578t, 585, 585f**
- B**
- Baby changing station sign, 338f**
 - Barricades, 101**
 - direction indicator, 605f, 608–610
 - low-volume road, 539
 - temporary traffic control with, 605f, 607–608
 - type 1, 2, or 3, 605f, 607–608
 - Barriers**
 - movable, 632t, 722, 723f
 - offset grade crossing pedestrian, 784f
 - offset grade crossing pedestrian, non-intersection, 785f
 - pedestrian, 784f
 - temporary reversible lane using movable, 632t, 722, 723f
 - temporary traffic, 564, 616–617, 632t, 700, 701f
 - warning signs on median, 263–264, 264f
 - Barrier-Separated Lane**
 - defined, 11
 - Barrier-separated preferential lanes, 285f**
 - edge line for, 417t
 - lane line markings for, 417t
 - non-reversible, 416, 417t, 418f
 - reversible, 416, 417t, 418f
 - Baseball sign, 339f**
 - Beach sign, 340f**
 - Beacon**
 - defined, 11
 - emergency-vehicle hybrid, 13, 513–515, 515f
 - flashing, 523–524
 - hybrid, 15, 19, 513–515, 515f
 - intersection control, 15
 - pedestrian hybrid, 17, 509–512
 - speed limit sign, 21, 524
 - stop, 21, 524
 - toll plaza warning, 522
 - warning, 22, 523–524
 - Bear viewing area sign, 337f**
 - Begin auxiliary signs (M4-14), 145f, 146–147**
 - Begin higher fines sign (R2-10), 578t, 584f, 586**
 - school, 735f, 736
 - Begin plaque, 64**
 - Begin right turn lane yield to bikes sign (R4-4), 791t, 793f, 794**
 - Be prepared to stop sign (W3-4), 532t**
 - temporary traffic control zones with, 545f
 - Bicycle**
 - defined, 11, 789
 - LRT grade signal/crossing for, 780
 - signal operations for, 816
 - Bicycle detector symbol, 810, 814f**
 - Bicycle Facilities**
 - defined, 11
 - guide for development of, 789
 - traffic control for, 789–816
 - work affecting TTC zones with, 622
 - Bicycle lane**
 - bike symbol markings for, 808, 809f
 - defined, 11
 - markings for, 806–810, 807f–809f
 - not provided on roundabout, 809
 - pavement markings for, 806, 807f, 809f
 - pavement markings for two-way street, 813f
 - preferential lane markings for, 415
 - right turn only lane with, 811f, 812f
 - word legend markings for, 808, 809f
 - Bicycle parking area sign (D4-3), 792t, 799f, 804**
 - Bicycle/pedestrian sign (W11-15), 791t, 796–798, 797f**
 - Bicycle route sign (M1-8), 792t, 800–801, 800f**
 - Bicycle route sign auxiliary plaques, 792t, 800f, 802–804**
 - Bicycle signal actuation sign (R10-22), 791t, 793f, 796**
 - Bicycles may use full lane sign (R4-11), 791t, 793f, 794**
 - Bicycle surface condition warning sign (W8-10), 791t, 796, 797f**
 - Bicycles wrong way sign (R5-1b), 791t, 793f, 794–795**
 - Bicycle traffic control, 789–816**
 - colors for, 789
 - documents relating to, 789
 - government design guides relating to, 789
 - guidance in manual for, 789
 - maintenance for, 789
 - markings for, 806–815, 807f–809f, 811f–815f
 - option in manual for, 789
 - placement authority for, 789

- requirements for, 789
 - scope, 789
 - signals for, 816
 - signs for, 790–805, 790f, 791t–792t, 793f, 797f, 799f–803f, 805f
 - standard in manual for, 789
 - support in manual for, 789
 - “The Uniform Vehicle Code and Model Traffic Ordinance” relating to, 789
 - Bicycle traffic control markings, 806–815, 807f–809f, 811f–815f
 - bicycle detector symbol, 810, 814f
 - bicycle lane, 806–810, 807f–809f
 - bicycle lane pavement markings for, 806, 807f, 809f, 813f
 - color with, 806
 - functions of, 806
 - pavement marking for obstructions, 810
 - principles of, 806
 - retroreflection with, 806
 - shared lane marking, 810
 - shared-use path patterns/colors with, 806
 - Bicycle traffic control signs, 790–805, 790f, 791t–792t, 793f, 797f, 799f–803f, 805f
 - advance turn arrow signs, 792t, 800f, 802
 - alternative route signs, 792t, 800f, 802
 - application, 790
 - begin right turn lane yield to bikes sign, 791t, 793f, 794
 - bicycle parking area sign, 792t, 799f, 804
 - bicycle/pedestrian sign, 791t, 796–798, 797f
 - bicycle route sign, 792t, 800–801, 800f
 - bicycle route sign auxiliary plaques, 792t, 800f, 802–804
 - bicycle signal actuation sign, 791t, 793f, 796
 - bicycles may use full lane sign, 791t, 793f, 794
 - bicycle surface condition warning sign, 791t, 796, 797f
 - bicycles wrong way sign, 791t, 793f, 794–795
 - bicycle warning sign, 791t, 796–798, 797f
 - bike lane plaque, 791t, 793f, 794
 - bike lane sign, 791t, 793f, 794
 - cardinal direction signs, 792t, 800f, 802
 - design of, 790–792
 - directional arrow signs, 792t, 800f, 802
 - guide, 792t, 798–799, 799f–800f
 - hill sign, 791t, 796–798, 797f
 - intersection warning sign, 791t, 796, 797f
 - junction sign, 792t, 800f, 802
 - mode-specific guide signs for shared use paths, 792t, 799f, 805, 805f
 - no bicycles sign, 791t, 793f, 795
 - no motor vehicles sign, 791t, 793f, 795
 - no parking bike lane bicycles sign, 791t, 793f, 795
 - object marker, 805
 - path narrows sign, 791t, 796–798, 797f
 - placement of, 790, 790f
 - reference location signs, 792t, 799f, 804
 - regulatory signs, 791t, 793f, 795
 - ride with traffic plaque, 791t, 793f, 794–795
 - route signs, 792t, 800–801, 800f
 - shared-use path sign, 791t, 793f, 795
 - share the road plaque, 791t, 796–798, 797f
 - sizes of, 791t–792t
 - stop signs, 791t, 792–794, 793f
 - turn or curve warning sign, 791t, 796, 797f
 - U.S. bicycle route sign, 792t, 800f, 801
 - warning signs, 791t, 796–798, 797f
 - yield signs, 791t, 792–794, 793f
 - Bicycle warning sign (W11-1), 791t, 796–798, 797f
 - Bike lane plaque (R3-17aP), 791t, 793f, 794
 - Bike lane sign (R3-17), 791t, 793f, 794
 - Bikeway
 - defined, 11
 - Black
 - meaning for traffic control devices of, 10
 - Blasting area signs, 590f, 594–595
 - blasting zone ahead, 590f, 595
 - end blasting zone, 589f, 595
 - turn off 2 way radio, 590f, 595
 - Blasting zone
 - TTC at, 632t, 636, 637f
 - Blasting zone ahead sign (W22-1), 590f, 595
 - Blue
 - meaning for traffic control devices of, 10
 - Boat motor sign, 340f
 - Boat ramp sign, 340f
 - Borders
 - sign, 36
 - Brake check area signs, 308, 308f
 - Bridge out sign (R11-3b)
 - sizes for low-volume roads of, 532t, 534f
 - Broken white line pavement markings, 356
 - Brown
 - meaning for traffic control devices of, 10
 - Buffer-Separated Lane
 - defined, 12
 - Buffer-separated preferential lanes
 - edge line for, 417t
 - enter/exit movements discouraged in, 418f
 - enter/exit movements permitted in, 419f
 - enter/exit movements prohibited in, 418f
 - lane line markings for, 417t
 - left-hand side, 416, 417t, 418f–419f
 - right-hand side, 416, 417t, 419f
 - Buffer spaces
 - tapers with, 556f
 - temporary traffic control zones with, 553f
 - Bump sign (W8-1), 120, 121f
 - Business auxiliary signs (M4-3), 145f, 146
 - Bus only lane
 - preferential lane markings for, 415
 - Bus stop sign, 337f
 - By-pass auxiliary signs (M4-2), 145f, 146
- ## C
- Campfires sign, 337f
 - Camping sign, 299t, 301f
 - Canoeing sign, 340f
 - Cans or bottles sign, 337f
 - Cantilevered Signal Structure
 - defined, 12
 - Cardinal direction auxiliary signs (M3-1 through M3-4), 145, 145f
 - Cardinal direction signs (M3 series), 792t, 800f, 802
 - Carpool signs, 310f, 311
 - Center lane closed sign (W9-3), 589f, 592
 - Center line markings
 - defined, 12

- low-volume roads, 541
 - shared-use path, 808f
- Chain-up area signs, 308, 308f
- Chair lift/ski lift sign, 341f
- Changeable message signs, 325–329
 - AMBER alert with, 325
 - applications of, 325–326
 - colors used with, 327
 - defined, 12
 - description of, 325
 - design characteristics of, 326–327
 - installation of permanent, 329
 - legibility of, 326
 - message length with, 328–329
 - units of information with, 328–329, 328t
 - visibility of, 326
- Channelizing devices, 429
 - barricades for, 605f, 607–608
 - color with, 429
 - cones for, 605f, 606
 - designs of, 604
 - direction indicator barricade for, 605f, 608–610
 - drums for, 605f, 607
 - island with, 430
 - longitudinal, 609–610
 - retroreflection with, 429
 - temporary lane separators for, 610
 - temporary traffic barriers for, 609
 - temporary traffic control with, 604–610, 605f
 - temporary traffic control zones with, 544
 - tubular markers for, 605f, 606–607
 - vertical panels for, 605f, 607
 - warning lights with, 604
- Channelizing Line Marking
 - defined, 12
- Chemical shelter directional signs, 343f, 346
- Chevron Alignment signs (W1-8), 109f, 110t, 111f, 112–113
 - sizes for low-volume roads of, 532t
- Chevron crosshatch pavement markings, 371, 395, 396f
- Circular green signal
 - application of, 453
 - meaning of, 450–451
 - vertical position within signal face of, 458, 458f
- Circular intersections
 - defined, 12
 - destination signs at, 157–158, 158f–160f
- Circular intersections warning sign, 536f, 537
- Circular red signal
 - application of, 453
 - meaning of, 451
 - pedestrian hybrid beacon with, 509
 - red/yellow lens automated flagger assistance device with, 571
 - vertical position within signal face of, 458, 458f
 - yellow change and red clearance intervals with, 485, 489
- Circular yellow signal
 - application of, 453–454
 - meaning of, 451
 - pedestrian hybrid beacon with, 509
 - red/yellow lens automated flagger assistance device, 571
 - vertical position within signal face of, 458, 458f
 - yellow change and red clearance intervals with, 485, 489
- Circulatory Roadway. *See also* Roundabout
 - bicycle lane not provided on, 809
 - defined, 12
- Clear Storage Distance
 - defined, 12
- Clear Zone
 - defined, 12
- Climbing sign, 339f
- Collector Highway
 - defined, 12
- Color
 - arrow board, 601
 - bicycle traffic control, 789
 - bicycle traffic control markings, 806
 - changeable message signs, 327
 - channelizing devices with, 429
 - code, 10
 - community wayfinding sign, 174f, 175–176, 176f
 - conventional road guide signs, 137, 138f
 - delineator, 424–426
 - edge line with rumble strip markings, 452
 - freeway/expressway guide signs, 182
 - island, 430
 - markings, 348
 - portable changeable message sign, 599
 - school area traffic control sign, 734
 - signs, 32, 33t
 - street name signs, 163
 - toll road sign background, 238
 - traffic control signal, 456
- Colored pavements, 428
- Combination Horizontal Alignment/advisory exit/ramp speed sign, 109f, 114–115, 116f
- Combination Horizontal Alignment/advisory speed sign, 113
- Combination Horizontal Alignment/intersection sign, 113
- Combination junction sign (M2-2), 145, 145f
- Community interchange identification signs, 225, 225f
- Community wayfinding signs, 172–176, 174f–176f
 - color coding with, 174f, 175
 - enhancement markers with, 174f
 - expressway/freeway, 175f
 - lettering with, 177
 - pictograph used with, 177
- Comparative travel time information sign, 282f
- Concurrent Flow Preferential Lane
 - defined, 12
- Cones
 - temporary traffic control with, 605f, 606
- Conflict Monitor
 - defined, 12
- Congressional legislation, A1–1–A1–2
- Constant Warning Time Detection
 - defined, 12
- Contiguous Lane
 - defined, 12
- Contiguous preferential lanes
 - edge line for, 417t
 - enter/exit movements discouraged in, 420f
 - enter/exit movements permitted in, 420f
 - enter/exit movements prohibited in, 420f
 - lane line markings for, 417t
 - left-hand side, 417, 417t, 420f
 - right-hand side, 417, 417t, 420f
- Controller Assembly
 - defined, 12
- Controller Unit
 - defined, 12

- Conventional Road
 - defined, 12
 - recreational and cultural interest area signs for, 334f
 - Conventional road guide signs, 137–180
 - advanced route turn assembly, 153
 - alternate auxiliary signs, 145–146, 145f
 - amount of legend with, 140
 - application, 137
 - arrows for use on, 140–142, 141f
 - auxiliary signs, 142–148, 143f, 145f, 147f
 - cardinal direction auxiliary signs, 145, 145f
 - color with, 137, 138f
 - combination junction sign, 145, 145f
 - combination lane-use/destination overhead guide sign, 154
 - community wayfinding, 172–178, 174f–176f
 - confirming/reassurance assembly, 155
 - crossover, 178f, 179
 - destination and distance signs, 156–161, 158f–160f
 - directional assembly, 153–154
 - freeway entrance, 170–171
 - Illumination of, 137
 - interchange approaches, 164–170, 165f–170f
 - junction assembly, 153
 - junction auxiliary sign, 144, 145f
 - lettering style with, 138
 - named highways, 179
 - national scenic byways, 179–180, 180f
 - numbering system for, 142
 - parking area guide, 171
 - PARK - RIDE, 171
 - retroreflection of, 137
 - route signs, 142–144, 143f, 148, 149f–152f
 - scope of, 137
 - size of, 137–138, 139t
 - size of lettering with, 138–140
 - slow vehicle turn-out, 178, 178f
 - street name signs, 161–164, 162f, 163t
 - trailblazer assembly, 155–156
 - truck lane, 178, 178f
 - weigh station, 172, 173f
 - Coordinated signal system, 445
 - Coral
 - meaning for traffic control devices of, 10
 - Corral sign, 339f
 - Countdown signals
 - pedestrian control with, 499–500
 - Counter-Flow Lane
 - defined, 12
 - Crash cushions
 - temporary traffic control with, 617–618
 - Crash experience signal warrant, 445–446
 - Crashworthy
 - defined, 13
 - Cross country skiing sign, 341f
 - Crossing supervision
 - adult guard qualifications for, 745
 - adult guards for, 745–746
 - operating procedures for, 745–746
 - school area traffic control with, 745–746
 - types of, 745
 - Crossovers
 - temporary traffic control zones with, 628
 - TTC with freeway median, 632t, 710, 711f
 - TTC with median, entrance ramp, 632t, 712, 713f
 - TTC with median, exit ramp, 632t, 714, 715f
 - Crossover signs (D13-1), 178f, 179
 - Crossroad warning sign (W2-1), 536f, 537
 - Cross traffic does not stop plaque, 133
 - Crosswalk. *See also* Pedestrian crosswalk signs
 - defined, 13
 - in-roadway lights for, 528–529
 - low-volume roads with, 541
 - markings, 383–385, 384f, 385f
 - roundabout markings, 413
 - speed hump markings with, 397f
 - TTC with closure of, 632t, 690, 691f
 - Crosswalk Lines
 - defined, 13
 - Crosswalk markings
 - school area, 744
 - CROSSWALK STOP ON RED sign
 - pedestrian hybrid beacon with, 511
 - Cultural interest area sign, 337f
 - Curb markings, 394–395
 - Cycle Length
 - defined, 13
- ## D
- D1 series. *See* Destination signs
 - D2 series. *See* Distance signs
 - D3-1 sign. *See* Street name signs
 - D3-2 sign. *See* Advance street name signs
 - D4-3. *See* Bicycle parking area sign
 - D6-4 sign. *See* National scenic byways sign
 - D10-1. *See* Reference location signs
 - D13-1 sign. *See* Crossover signs
 - D17-1 sign. *See* Truck lane sign
 - D17-7 sign. *See* Slow vehicle turn-out sign
 - Dam sign, 337f
 - Dark Mode
 - defined, 13
 - Dead end sign (W14-1), 118f, 119–120
 - sizes for low-volume roads of, 532t, 538f, 539
 - Dedication signs, 339–341
 - Deer viewing area sign, 337f
 - Delineators, 424–427
 - application, 424–426
 - bridge rail or obstruction with, 428f
 - color of, 424–426
 - defined, 13
 - design, 424
 - edge of roadway with placement of, 428f
 - low-volume roads, 541
 - placement of, 425, 426–427
 - retroreflection with, 424
 - spacing for, 426–427, 427t
 - temporary traffic control with, 613
 - truck escape ramp, 427
 - Designated Bicycle Route
 - defined, 13
 - Design Vehicle
 - defined, 13
 - Destination signs (D1 series), 156–161, 158f–160f
 - circular intersections with, 157–158, 158f–160f

- at jughandles, 158
 - location of, 158
 - Detectable edging for pedestrians, 610–611
 - pathway grade crossing, 786–787
 - Detectors
 - accessible pedestrian control with, 504–508
 - defined, 13
 - pedestrian control with, 500–501, 501f–503f
 - pushbutton for pedestrian control with, 500–501, 501f–503f
 - Detours
 - temporary traffic control with, 558
 - TTC - closed street, 632t, 672, 673f
 - TTC - one-travel direction, 632t, 670, 671f
 - TTC - overlapping routes, 632t, 650, 651f
 - TTC - pedestrian, 632t, 690, 691f
 - TTC - road closure with off-site, 632t, 648, 649f
 - TTC - sidewalk, 632t, 688, 689f
 - Detour signs (W20-2, M4-8 through M4-10), 590f, 591
 - end, 592f, 598
 - pedestrian/bicycle, 592f, 598
 - Diagrammatic guide
 - optional lanes signing, 198–202, 199f–202f
 - Diesel fuel sign, 299t, 301f
 - Dip sign (W8-2), 120, 121f
 - Directional arrow auxiliary signs, 147f, 148
 - Directional arrow signs (M6 series), 792t, 800f, 802
 - Directional assemblies
 - recreational and cultural interest area, 333f
 - Directional signs
 - recreational and cultural interest area, 333f
 - Direction indicator barricade
 - temporary traffic control with, 605f, 608–610
 - Distance plaques, 132, 132f
 - Distance signs (D2 series), 156, 161
 - location of, 161
 - Diversions
 - temporary traffic control with, 558
 - TTC - sidewalk, 632t, 688, 689f
 - Divided highway
 - counter-flow preferential lanes on, 421, 422f
 - Divided highway crossing sign, 82
 - Divided highway ends sign (W6-2), 118f, 119
 - Divided highway light rail crossing sign (R15-7 series), 753f, 762
 - Divided highway sign (W6-1), 118f, 119
 - Diving sign, 340f
 - Dog sledding sign, 341f
 - Do not block intersection pavement markings, 382, 384f
 - Do not drive on shoulder sign (R4-17), 72f, 75
 - Do not enter sign (R5-1), 75–76, 75f, 76f
 - sizes for low-volume roads of, 532t, 534f
 - Do not pass light rail transit sign (R15-5), 753f, 761
 - Do not pass on shoulder sign (R4-18), 72f, 75
 - Do not pass sign (R4-2), 72, 72f
 - sizes for low-volume roads of, 532t, 534f
 - Do not stop on tracks sign (R8-8), 753f, 760
 - Dotted white line pavement markings, 358f–361f, 362, 372f–378
 - freeway route splits with, 362, 366f
 - lane continuing beyond interchange with, 362, 367f
 - lane drop in advance of exit ramp with, 362, 363f–365f
 - lane drop in advance of interchange with, 362, 368f
 - Double arrow sign (W12-1), 118f, 119
 - Double-exit interchange service signs, 318
 - Double reverse curve sign (W24-1 series), 590f, 596
 - Downhill skiing sign, 341f
 - Downstream tapers, 557, 557t
 - DOWNWARD GREEN arrow
 - lane-use control with, 525
 - DRAW BRIDGE sign (W3-6), 125, 519
 - Drinking water sign, 338f
 - Driving tour sign, 339f
 - Dropped Lane
 - defined, 13
 - Drums
 - temporary traffic control with, 605f, 607
 - Dual-Arrow Signal Section
 - defined, 13
 - Dynamic Envelope
 - defined, 13
 - Dynamic Exit Gate Operating Mode
 - defined, 13
- ## E
- E5-2 sign. *See* Exit open sign
 - E5-3 sign. *See* Exit only sign
 - Edge Line Markings
 - color with rumble strip, 452
 - defined, 13
 - low-volume roads, 541
 - pathway grade crossing, 786–787
 - pavement markings, 371
 - preferential lanes, 417t
 - roundabout, 413
 - Educational plaques, 332
 - Eight-hour vehicular volume, 437–439, 438f
 - Eisenhower interstate system signs (M1-10), 211, 211f
 - Electrical hook-up sign, 338f
 - Electric vehicle charging sign, 299t, 301f
 - Electronic Toll Collection (ETC)
 - account-only auxiliary signs, 243, 243f
 - account-only lane, 13
 - account pictographs, 238, 239f
 - advance sign for diverging alignment from, 249, 251f
 - defined, 13
 - guide signs for entrances to, 252
 - preferential lane markings for, 415
 - program information signs, 252
 - toll plaza markings for, 423
 - Emergency aid center signs, 343f, 343t, 345
 - Emergency management signs, 342–346
 - area closed sign, 343f, 343t, 344
 - design of, 342
 - emergency aid center signs, 343f, 343t, 345
 - evacuation route signs, 342–344, 343f, 343t
 - maintain top safe speed sign, 343f, 343t, 344–345
 - road (area) use permit required for thru traffic sign, 343f, 343t, 345
 - shelter directional signs, 343f, 343t, 346
 - size of, 343t
 - traffic control point sign, 343f, 343t, 344
 - Emergency medical care plaque, 300t, 301f, 302
 - Emergency medical services sign, 299t, 301f, 302
 - Emergency notification sign (I-13), 762–763, 762f
 - Emergency responder
 - temporary traffic control with safety for, 565

- Emergency restriction signs, 90f, 92
 - Emergency-vehicle access
 - application of control signals for, 513
 - design of control signals for, 513
 - operation of control signals for, 513–514
 - traffic control signal for, 513–515
 - Emergency-vehicle hybrid beacon, 513–515, 515f
 - defined, 13
 - Emergency-Vehicle Traffic Control Signal
 - defined, 13
 - End auxiliary signs (M4-6), 145f, 146
 - End blasting zone sign (W22-3), 589f, 595
 - End detour sign, 592f, 598
 - End higher fines sign (R2-11), 578t, 584f, 586
 - End higher fines zone sign (R2-11)
 - school speed limit assembly with, 742–743
 - End-of-Roadway Marker
 - defined, 13
 - object marker for, 135f, 136
 - End plaque, 64
 - End road work miles sign (G20-2)
 - temporary traffic control with, 590f, 598
 - End school speed limit sign (S5-3)
 - school speed limit assembly with, 742–743
 - End school zone plaque, 735f, 736
 - End school zone sign (S5-2)
 - school speed limit assembly with, 742–743
 - End work zone speed limit sign (R2-12), 578t, 584f, 586
 - Engineering judgment
 - defined, 14
 - definition of, 4
 - location/design of traffic control devices with, 4
 - Engineering study
 - defined, 14
 - definition of, 4
 - Enhanced reference location, 296, 296f
 - Entrance Gate
 - defined, 14
 - Entrance ramps
 - direct, 290f
 - freeway, 517–518
 - managed lane signs, 288f
 - separate, 291f
 - TTC - crossover of median by, 632t, 712, 713f
 - white line pavement markings on, 356, 360f–361f
 - ETC. *See* Electronic Toll Collection
 - Evacuation route signs, 342–344, 343f, 343t
 - Exact Change Lane
 - defined, 14
 - Exempt plaque (R15-3PW10-1aP), 753f, 759–760, 759f
 - Exercise/fitness sign, 339f
 - Exit closed sign (E5-2a), 592, 592f
 - Exit destinations sign, 282f
 - Exit direction signs, 220–222, 220f, 221f
 - Exit Gate
 - defined, 14
 - Exit Gate Operating Mode
 - defined, 14
 - Exit gore signs, 222, 222f
 - Exit only sign (E5-3), 203, 204f, 206f
 - temporary traffic control devices, 592f, 593
 - Exit open sign (E5-2)
 - temporary traffic control devices, 592, 592f
 - Exit ramps
 - advisory speed sign for, 109f, 114–115, 116f
 - dotted line for lane drop in advance of, 362, 363f–365f
 - lane drop in advance of, 362, 363f–365f
 - managed lane signs, 288f
 - TTC - crossover of median by, 632t, 714, 715f
 - TTC - partial closure of, 632t, 718, 719f
 - white line pavement markings with, 358f–359f
 - Experimentations with devices, 4–7, 5f
 - process for, 5f
 - Expressway. *See* Freeway/expressway
- ## F
- Falling rocks sign, 337f
 - Fallout shelter directional signs, 343f, 346
 - Federal Highway Administration (FHWA), 4
 - Feeder bender sign (R16-4), 101, 101f
 - Feet to meters conversion, A2–1
 - FHWA. *See* Federal Highway Administration
 - Fines double plaque (R2-6aP), 578t, 584f, 586
 - school, 735f, 736
 - school speed limit assembly with, 742–743
 - Fines higher plaque (R2-6P), 578t, 584f, 586
 - school signs, 735f, 736
 - school speed limit assembly with, 742–743
 - Fines higher zone, school, 735f, 736, 737f–740f
 - Fire extinguisher sign, 337f
 - Firefighter
 - temporary traffic control with safety for, 565
 - Firewood cutting sign, 338f
 - First aid sign, 338f
 - Fish cleaning sign, 340f
 - Fish hatchery sign, 340f
 - Fishing area sign, 340f
 - Fishing pier sign, 340f
 - Flagger
 - automated assistance device for, 567–569
 - defined, 14
 - hand-signaling devices for, 566–567, 574f
 - high-visibility safety apparel for, 566
 - method, 558
 - methods to alert/slow traffic by, 574f
 - methods to let traffic proceed by, 574f
 - methods to stop traffic by, 574f
 - procedures, 573–575, 574f
 - qualifications for, 566
 - red/yellow lens automated assistance device for, 571–573, 572f
 - stations, 575, 575t
 - stopping sight distance needed for, 575t
 - STOP/SLOW automated assistance device for, 569–571, 570f
 - stop/slow paddle for, 566–567
 - temporary traffic control with, 566–575, 570f, 572f, 574f, 575t
 - TTC - lane closure on two-lane road using, 632t, 652, 653f
 - Flagger sign (W20-7), 592f, 593
 - Flag transfer method, 558
 - Flag trees. *See* High-level warning devices
 - Flasher
 - defined, 14

- Flashing beacon, 523–524
 - design of, 523
 - intersection control, 523
 - operation of, 523
 - speed limit sign, 524
 - stop, 524
 - warning, 523–524
 - Flashing-light signals
 - defined, 14
 - pathway grade crossing, 788
 - pedestrian crossing with, 781f
 - railroad grade crossing traffic control with, 769–785, 770f
 - Flashing Mode
 - defined, 14
 - Flashing operation, 491–492
 - signal induction during, 491–492
 - transition out of, 492
 - Flashing red
 - meaning of, 452
 - Flashing yellow
 - meaning of, 452
 - Floodlights
 - temporary traffic control with, 614
 - Fluorescent pink
 - meaning for traffic control devices of, 10
 - Fluorescent yellow-green
 - meaning for traffic control devices of, 10
 - Food sign, 299t, 301f
 - Four-hour vehicular volume, 439, 440f
 - Four-lane road
 - yellow center line markings on, 351f
 - Four-quadrant gate systems
 - rail grade crossing traffic control with, 773–775, 774f
 - Freeway entrance ramps control signals, 517–518
 - application of, 517
 - design of, 517
 - operation of, 518
 - Freeway/expressway
 - community wayfinding signs showing from, 175f
 - defined, 14
 - ends sign, 118f, 119
 - entrance signs, 170–171
 - general service signs for, 303–306, 304f
 - lane drop markings for, 362, 363f–365f
 - recreational and cultural interest area signs for, 334f
 - TTC - double lane closure on, 632t, 706, 707f
 - TTC - interior lane closure on, 632t, 708, 709f
 - TTC - lane shift of, 632t, 704, 705f
 - TTC - median crossover on, 632t, 710, 711f
 - TTC - shoulder closure on, 632t, 642, 643f
 - TTC zone - work within, 627–628
 - Freeway/expressway guide signs, 181–236
 - abbreviations on, 192
 - advance, 216–218, 217f
 - amount of legend on, 183
 - arrows on, 192–193
 - borders of, 192
 - characteristics of rural, 183
 - characteristics of urban, 182–183
 - classification of, 181
 - closely-spaced interchange, 234
 - cloverleaf interchange, 226, 229f, 230, 231f
 - color of, 182
 - community interchange identification, 225, 225f
 - connecting roadways, 235
 - conventional road approaches, 235
 - destination designation, 184–185
 - diamond interchange, 230, 233f, 234, 235f
 - Eisenhower interstate system, 211, 211f
 - exit direction, 220–222, 220f, 221f
 - exit gore, 222, 222f
 - exit only, 203, 204f, 206f
 - freeway-to-freeway interchange, 226, 227f, 228f
 - illumination of, 182
 - interchange exit numbering, 212–216, 213f–215f
 - interchange grade, 211–212
 - interchange lane drops, 203, 204f, 206, 208f, 209f
 - interchange sequence, 223–225, 224f, 225f
 - interline/edge spacing with, 185
 - intersection at grade, 211
 - lateral offset of, 210
 - lettering size/style with, 185, 188f–191f
 - minor interchange, 234, 236f
 - named highways, 183
 - next exit, 218, 218f, 225, 225f
 - optional lanes, 193–198, 194f–197f
 - optional lanes, diagrammatic guide for, 198–202, 199f–202f
 - optional lanes, interchange multi-lane exit, 203, 204f, 205f
 - overhead arrow-per-lane, 193–198, 194f–197f
 - overhead installations of, 206
 - partial cloverleaf interchange, 230, 232f
 - post-interchange, 222–223
 - post-interchange distance, 223, 223f
 - principles of, 181
 - pull-through, 184, 184f
 - retroreflection of, 182
 - route signs, 210–211, 210f
 - scope of standards for, 181
 - size of, 186f–188f
 - spreading of, 183, 184f
 - supplemental, 218–219, 219f
 - symbols on, 192
 - trailblazer assemblies, 210–211
 - type of interchange, 226
 - weigh station, 236
 - wrong-way traffic control, 235–236
 - Fresh oil sign (W21-2), 533t
 - temporary traffic control with, 592f, 593
 - temporary traffic control zones with, 545f
 - Full-actuated operation
 - defined, 14
- ## G
- G20-1 sign. *See* Road work next XX miles sign
 - G20-2 sign. *See* End road work miles sign
 - G20-4 sign. *See* Pilot car follow me sign
 - G20-5aP plaque. *See* Work zone plaque
 - Gas sign, 299t, 301f
 - Gate, 101–102
 - automatic, 772–773
 - defined, 14
 - four-quadrant, 773–775, 774f
 - pedestrian, 782f–785f

- rail grade crossing traffic control with, 769–785, 770f, 774f swing, 784f
- General information signs, 292–298
 - acknowledgement signs, 297–298, 298f
 - auto tour route, 297
 - enhanced reference location, 296, 296f
 - intermediate reference location, 294–296, 295f
 - I series of, 292–294, 293f
 - miscellaneous, 293f, 294
 - reference location, 294–296, 295f
 - sizes of, 292, 292f
- General service signs, 299–311
 - brake check area, 308, 308f
 - carpool, 310f, 311
 - chain-up area, 308, 308f
 - conventional roads, 300–303, 301f, 302f
 - freeways/expressways, 303–306, 304f
 - interstate oasis, 306–307, 306f
 - next services, 302, 302f
 - radio information, 310–311, 310f
 - rest area, 307–308, 307f
 - ridesharing, 310f, 311
 - roadside area, 307–308, 307f
 - sizes of, 299, 299t–300t
 - tourist information, 308–309, 309f
 - TRAVEL INFO CALL 511, 310f, 311
 - welcome area, 308–309, 309f
- Golfing sign, 339f
- Grade crossing. *See also* Highway rail grade crossing; Light rail transit grade crossing traffic control; Railroad transit grade crossing traffic control
 - active traffic control devices, 770f
 - defined, 14
 - highway traffic signal needs study based on, 446–448, 447f, 448t
 - low-volume roads traffic control for, 542–543, 542f
 - pathway, 786–788, 787f
 - pedestrian barrier at, 784f
 - pedestrian barrier at, non-intersection, 785f
 - TTC zone - work in vicinity of, 629
- Grade crossing advance warning signs (W10 series), 532t, 542, 542f, 758–759, 759f
- Grade crossing (crossbuck) sign (R15-1), 532t, 751, 752t, 753f
- Green. *See also* Circular green signal
 - meaning for traffic control devices of, 10
- Green arrow
 - application of, 453–454
 - meaning of, 451
 - vertical position within signal face of, 458, 458f
- Grocery store sign, 338f
- “Guide for Development of Bicycle Facilities,” 789
- Guide signs. *See also* Conventional road guide signs; Freeway/expressway guide signs
 - bicycle, 792t, 798–799, 799f–800f
 - defined, 14
 - low-volume road, 540
 - temporary traffic control with, 597–598
- Hand-signaling devices, 566–567
 - flashlight, 567
 - stop/slow paddle, 566–567
 - use of, 574f
- Hang gliding sign, 339f
- Hazardous material sign (R14-2), 99–100, 99f
- Headlight use sign (R16-5), 100, 100f
- Higher fines sign/plaque, 57f, 59
- High-level warning devices (Flag trees)
 - temporary traffic control with, 603
- High-occupancy vehicle (HOV)
 - buffer-separated HOV lane sign for, 261f–262f
 - defined, 14
 - direct lane entrance/exit for, 277f
 - overhead sign for, 267f
 - plaque for, 264–265, 264f
 - post-mounted sign for, 267f
 - vehicle occupancy definition regulatory signs for, 258–259
- High-visibility safety apparel, 565
 - flagger with, 566
- Highway
 - counter-flow preferential lanes on divided, 421, 422f
 - defined, 14
 - divided, median opening treatments for, 44
 - freeway/expressway guide signs for named, 183
 - signing for named, 179
 - TTC - half road closure on multi-lane, 632t, 696, 697f
 - TTC - stationary lane closure on divided, 632t, 698, 699f
 - TTC zone - two-way traffic on normally divided, 628
 - TTC zone - work within multi-lane, 626
- Highway-light rail transit grade crossing
 - bicycle signal/crossing for, 780
 - defined, 14
 - flashing-light signals at, 772
 - pedestrian signal/crossing for, 780, 781f–785f
- Highway rail grade crossing
 - advance guide signs for, 542, 542f
 - advance warning signs for, 758–759, 759f
 - crossbuck assemblies with yield/stop signs for, 754–758, 754f–756f
 - defined, 14
 - do not stop on tracks sign for, 753f, 760
 - dynamic envelope markings for, 767, 767f, 768f
 - elimination for, 749–750
 - emergency notification sign with, 762–763, 762f
 - exempt plaque for, 753f, 759–760, 759f
 - grade crossing (crossbuck) sign for, 751, 752t, 753f
 - illumination for, 750
 - look sign with, 753f, 762
 - low ground clearance grade crossing sign with, 759f, 763–764
 - low-volume roads traffic control for, 542–543, 542f
 - no motor vehicles on tracks sign with, 753f, 762
 - no train horn sign with, 759f, 763
 - number of tracks plaque for, 542, 542f, 751, 752t, 753f
 - pathways, 786–788, 787f
 - pavement markings for, 543, 764–767, 765f–768f
 - practices for, 747–748
 - purpose of signs for, 751
 - quiet zone treatments with, 750
 - signs for, 751–768
 - sizes of signs for, 751
 - skewed crossing sign with, 759f, 764
 - standard devices used for control of, 747–748
 - stop here on red sign with, 753f, 761

H

- Handicapped sign, 299t, 301f
- Hand launch/small boat launch sign, 340f

- stop here when flashing sign with, 753f, 761
- stop lines for, 766–767
- stop sign for, 542f, 543
- storage space sign with, 759f, 764
- tracks out of service sign with, 753f, 760–761
- traffic control for, 747–789
- turn restrictions during preemption with, 753f, 760
- uniform provisions for, 749
- yield lines for, 766–767
- yield sign for, 542f, 543
- Highway traffic signal, 433–530
 - adequate roadway capacity for, 435
 - advantages of, 434–435
 - alternatives to, 435
 - defined, 15
 - disadvantages of, 434–435
 - features of, 449–493
 - general, 434–435
 - installation of, 434
 - removal of, 434
 - types, 433
- Highway traffic signal needs study, 436–448
 - warrant 1, eight-hour vehicular volume, 437–439, 438f
 - warrant 2, four-hour vehicular volume, 439, 440f
 - warrant 3, peak hour, 439, 441f
 - warrant 4, pedestrian volume, 442, 443f, 444f
 - warrant 5, school crossing, 442, 445
 - warrant 6, coordinated signal system, 445
 - warrant 7, crash experience, 445–446
 - warrant 8, roadway network, 446
 - warrant 9, intersection near grade crossing, 446–448, 447f, 448t
- Hiking trail sign, 339f
- Hill blocks view sign (W7-6), 117, 117f
- Hill-related plaques, 132f, 133
- Hill sign (W7-1), 115, 117f
 - sizes for low-volume roads of, 532t, 537, 538f
- Hill sign (W7-5)
 - bicycle, 791t, 796–798, 797f
- Horizontal Alignment/Advisory Speed combination sign, 113
- Horizontal Alignment/intersection combination sign, 113
- Horizontal Alignment signs (W1-1), 109–111, 109f, 110t, 111f
 - sizes for low-volume roads of, 532t, 536, 536f
- Horizontal position within signal face of
 - circular green, 458f, 459
 - circular red, 458f, 459
 - circular yellow, 458f, 459
 - green arrow, 458f, 459
 - red arrow, 458f, 459
 - yellow arrow, 458f, 459
- Horse trail sign, 339f
- Hospital plaque, 300t, 301f
- Hospital sign, 299t, 301f
- HOT lane
 - preferential lane markings for, 415
- HOV. *See* High-occupancy vehicle
- HOV lane
 - defined, 15
 - direct access ramp between, 277f
 - preferential lane markings for, 415
 - sign for buffer-separated, 261f–262f
- Hurricane shelter directional signs, 343f, 346
- Hybrid beacon. *See also* Pedestrian hybrid beacon
 - defined, 15
 - emergency-vehicle, 19, 513–515, 515f
- I-12 sign. *See* Light rail transit station sign
- I-13 sign. *See* Emergency notification sign
- Ice fishing sign, 341f
- Ice skating sign, 341f
- ICS. *See* Incident Command System
- ILEV. *See* Inherently low emission vehicle
- Illumination
 - conventional road guide signs, 137
 - freeway/expressway guide signs, 182
 - highway rail grade crossing, 750
 - pedestrian signal heads, 496
 - raised pavement markings, 379
 - school area traffic control, 734
 - sign, 29–30, 29t
 - street name signs, 162
 - traffic control signal, 456
- Inches to millimeters conversion, A2–1
- Incident Command System (ICS), 726
- Incident management areas
 - emergency-vehicle lighting in, 727
 - intermediate traffic in, 728
 - major traffic in, 727
 - minor traffic in, 728
 - traffic control through, 726–729, 730f
- Inherently low emission vehicle (ILEV)
 - defined, 15
 - vehicle occupancy definition regulatory signs for, 259
- In-line skating sign, 339f
- In-roadway lights, 528–529
 - application of, 528
 - crosswalk, 528–529
 - defined, 15
- In-street pedestrian crossing sign (R1-6), 55f, 56
- Interchange
 - arrows for guide signs for, 192–193
 - classification, 216
 - closely-spaced, 234
 - cloverleaf, 226, 229f, 230
 - defined, 15
 - diamond, 167f, 230, 233f, 234, 235f, 412f
 - double-exit, 318
 - exit numbering, 212–216, 213f–215f
 - freeway-to-freeway, 226, 227f, 228f
 - grade signs, 211–212
 - minor, 234, 236f
 - multi-lane exit optional lanes signing for, 203, 204f, 205f
 - partial cloverleaf, 230, 232f
 - roundabout with diamond, 412f
 - service signs, 317–318
 - signing on approaches to, 164–170, 165f–170f
 - signing on cloverleaf, 168f–169f
 - signing on diamond, 167f
 - single-exit, 317–318
 - temporary traffic control zones with, 628–629
 - wrong-way traffic control at, 235–236
- Interchange sequence signs, 223–225, 224f, 225f
- Interim approval of devices, 4–7
- Intermediate interchange
 - defined, 15
- Intermediate reference location signs, 294–296, 295f
- Intermediate traffic incidents, 728

Interpretation of manual, 4–7
 Interpretive trail sign, 339f
 Interruption of continuous traffic, 437, 438f
 Intersection. *See also* Circular intersections
 defined, 15
 at grade signs, 211
 lane control sign, 61–62, 62f
 location of signs for, 39f, 40f
 low-volume roads with warning signs for, 536f, 537
 near grade crossing signal warrant, 446–448, 447f, 448t
 pavement markings with extensions through, 371–374, 372f–373f
 right-of-way at, 49–51
 service signs, 319
 tourist-oriented directional approach signs for, 322f
 TTC - closure at side of, 632t, 686, 687f
 TTC - closure in center of, 632t, 684, 685f
 TTC - half road closure on far side of, 632t, 680, 681f
 TTC - lane closure on near side of, 632t, 674, 675f
 TTC - left lane closure on far side of, 632t, 678, 679f
 TTC - multi-lane closure at, 632t, 682, 683f
 TTC - right lane closure on far side of, 632t, 675, 677f
 TTC zone - work within, 626–627
 warning signs, 127–128, 127f, 536f, 537
 Intersection control beacon, 523
 defined, 15
 Intersection warning
 sizes for low-volume roads of, 532t
 Intersection warning sign (W2 series), 791t, 796, 797f
 Interstate oasis signs, 306–307, 306f
 Interval
 defined, 15
 pedestrian, 497–499, 498f
 Island, 430–431
 approach-end treatment for, 430
 channelizing devices with, 430
 defined, 15
 delineation, 431
 marking application for, 430
 marking colors for, 430
 medians, 431
 pavement markings, 370
 pedestrian, 431
 roundabout, 401f–402f
 temporary raised, 611

J

Jet ski/personal watercraft sign, 340f
 Jughandle regulatory signs, 67–71, 68f–71f
 Junction auxiliary sign (M2-1), 144, 145f
 Junction sign (M2-1), 792t, 800f, 802

K

Kayaking sign, 340f
 Keep left sign (R4-8), 72f, 73–74
 Keep off median sign (R11-1), 97, 98f
 Keep right except to pass sign (R4-16), 72f, 73
 Keep right sign (R4-7), 72f, 73–74
 sizes for low-volume roads of, 532t, 534f
 Kennel sign, 338f

L

Land recreation
 recreational and cultural interest area signs for, 330, 331t, 339f
 Lane designation auxiliary signs, 147f, 148
 Lane drop. *See* Dropped Lane
 Lane ends sign (W4-2), 125f, 126
 temporary traffic control with, 588f, 592
 Lane line markings
 defined, 15
 Lane-reduction arrow, 392f
 Lane-reduction transition markings, 374, 375f
 Lane-use control signals, 522, 525–527, 526f
 application of, 525
 defined, 15
 design of, 526–527
 DOWNWARD GREEN arrow, 525
 meaning of indications with, 525, 526f
 one-way left turn arrow, 525, 526f
 operation of, 527
 RED X signal, 525
 toll plaza with, 522
 two-way left turn arrow, 525, 526f
 YELLOW X signal, 525
 Last exit before toll warning plaque, 242
 Laundromat sign, 338f
 Law enforcement
 temporary traffic control with safety for, 565
 Left-turn indications, 465–474, 467f–473f
 permissive only mode of, 467–469, 467f–469f
 protected only mode of, 469–470, 470f, 471f
 protected/permissive mode of, 469f, 471–474, 472f, 473f
 signal faces for controlling, 466
 variable, 466
 Legend. *See* Sign legend
 Lens. *See* Signal lens
 Lifejackets sign, 340f
 Light blue
 meaning for traffic control devices of, 10
 Lighthouse sign, 337f
 Lighting
 temporary traffic control safety with, 565
 Lighting devices
 temporary traffic control with, 614
 Light rail transit approaching-activated blank out warning sign
 (W10-7), 759f, 763
 Light rail transit grade crossing traffic control, 747–789
 advance warning signs for, 758–759, 759f
 automatic gates for, 772–773
 bicycle signal/crossing for, 780
 crossbuck assemblies with yield/stop signs for, 754–758, 754f–756f
 divided highway with light rail crossing sign with, 753f, 762
 do not pass light rail transit sign with, 753f, 761
 do not stop on tracks sign for, 753f, 760
 dynamic envelope markings for, 767, 767f, 768f
 emergency notification sign with, 762–763, 762f
 exempt plaque for, 753f, 759–760, 759f
 flashing-light signals for, 769–785, 770f
 four-quadrant gate systems for, 773–775, 774f
 grade crossing elimination for, 749–750

- grade crossing illumination for, 750
- grade crossing (crossbuck) sign for, 751, 752t, 753f
- light rail transit approaching-activated blank out warning sign with, 759f, 763
- light rail transit only lane sign with, 753f, 761
- light rail transit station sign with, 759f, 764
- look sign with, 753f, 762
- low ground clearance grade crossing sign with, 759f, 763–764
- no gates or lights plaque with, 759f, 763
- no motor vehicles on tracks sign with, 753f, 762
- no train horn sign with, 759f, 763
- number of tracks plaque for, 751, 752t, 753f
- pathway grade crossing for, 786–788, 787f
- pavement markings for, 764–767, 765f–768f
- pedestrian signal/crossing for, 780, 781f–785f
- practices for, 748–749
- purpose of signs for, 751
- quiet zone treatments with, 750
- rail traffic detection for, 775–776
- signs for, 751–768
- sizes of signs for, 751
- skewed crossing sign with, 759f, 764
- standard devices used for, 748–749
- stop here on red sign with, 753f, 761
- stop here when flashing sign with, 753f, 761
- stop lines for, 766–767
- storage space sign with, 759f, 764
- tracks out of service sign with, 753f, 760–761
- turn restrictions during preemption with, 753f, 760
- uniform provisions, 749
- wayside horn systems for, 775
- yield lines for, 766–767
- Light rail transit only lane sign (R15-4), 753f, 761
- Light rail transit signals, 778–779, 779f
 - single LRT route, 779f
 - three LRT route diversion, 779f
 - two LRT route diversion, 779f
- Light rail transit station sign (I-12), 759f, 764
- Light rail transit traffic (LRT)
 - defined, 16
 - grade crossing traffic control for, 747–789
 - preferential lane markings for, 415
- Litter container sign, 299t, 301f
- Litter receptacle sign, 338f
- Local Technology Assistance Program (LTAP), 4
- Local traffic only sign
 - temporary traffic control with, 578t, 585, 585f
- Lockers/storage sign, 338f
- Locomotive horn
 - defined, 16
- Lodging sign, 299t, 301f
- Logo
 - defined, 16
- Logo sign panels, 313–318, 314f–316f
 - letter and numeral sizes for, 316t, 317
 - locations for, 315f
 - RV Access supplemental messages on, 316, 316f
 - sizes of, 317
 - supplemental messages on, 316, 316f
- Longitudinal channelizing devices, 609–610
- Longitudinal markings
 - defined, 16
- Longitudinal pavement markings
 - patterns of, 348
 - white, 370–371
 - widths of, 348
 - yellow, 354
- Lookout tower sign, 337f
- Look sign (R15-8), 753f, 762
- Loose gravel (W8-7), 532t
 - temporary traffic control zones with, 545f
- Louver. *See* Signal louver
- Low clearance sign (W12-2), 118f, 120
- Low ground clearance grade crossing sign (W10-5), 759f, 763–764
- Low shoulder sign (W8-9), 589f, 595
- Low-volume roads
 - application of traffic control for, 531
 - barricades for, 539
 - be prepared to stop sign for, 532t
 - bridge out sign for, 532t, 534f
 - center line marking for, 541
 - chevron Alignment signs for, 532t
 - circular intersections warning sign for, 536f, 537
 - crossroad warning sign for, 536f, 537
 - crosswalks for, 541
 - dead end sign for, 532t, 538f, 539
 - defined, 531
 - delineators for, 541
 - design of traffic control for, 531–533
 - do not enter sign for, 532t, 534f
 - do not pass sign for, 532t, 534f
 - edge line marking for, 541
 - function of, 531
 - grade crossing advance warning sign for, 532t
 - grade crossing sign for, 532t
 - grade crossing traffic control for, 542–543, 542f
 - guide signs for, 540
 - hill sign for, 532t, 537, 538f
 - Horizontal Alignment signs for, 532t, 536, 536f
 - intersection warning signs for, 536f, 537
 - keep right sign for, 532t, 534f
 - marking for, 541
 - narrow bridge sign for, 532t, 537, 538f
 - non-vehicular traffic warning signs for, 537–539, 538f
 - no outlet sign for, 538f, 539
 - no parking sign for, 532t, 535f
 - no traffic sign for, 533t, 538f, 539
 - no trucks sign for, 532t, 534f
 - object markers for, 539
 - one-direction large arrow sign for, 532t
 - one lane bridge sign for, 532t, 537, 538f
 - one way sign for, 532t, 534f
 - pass with care sign for, 532t, 534f
 - pavement ends sign for, 532t, 537, 538f
 - pavement marking for, 541
 - placement of signs for, 533
 - regulatory signs for, 534–535, 534f–535f
 - road closed sign for, 532t, 534f
 - road closed to thru traffic sign for, 532t, 534f
 - road may flood sign for, 532t
 - rough road sign for, 532t
 - school area traffic control for, 546
 - side road warning sign for, 536f, 537
 - sign/plaque sizes for, 532t
 - skewed crossing sign for, 532t
 - speed limit signs for, 532t, 534, 534f
 - stop ahead sign for, 532t, 537, 538f
 - stop signs for, 532t, 534, 534f

temporary traffic control zones for, 544–545, 545f
 traffic control devices for, 531–546
 trains may exceed 80 mph sign for, 532t
 T-symbol warning sign for, 536f, 537
 two-direction large arrow sign for, 532t
 vehicular traffic warning signs for, 537–539, 538f
 warning signs for, 536–539, 536f, 538f
 weight limit sign for, 532t, 534f
 yield ahead sign for, 532t, 537, 538f
 yield signs for, 532t, 534f
 Y-symbol warning sign for, 536f, 537

LRT. *See* Light rail transit traffic

LTAP. *See* Local Technology Assistance Program

M

M1-8 sign. *See* Bicycle route sign
 M1-9 sign. *See* U.S. bicycle route sign
 M1-10 sign. *See* Eisenhower interstate system signs
 M2-1. *See* Junction sign
 M2-1 sign. *See* Junction auxiliary sign
 M2-2 sign. *See* Combination junction sign
 M3-1 sign. *See* Cardinal direction auxiliary signs
 M3 series. *See* Cardinal direction signs
 M4-2 sign. *See* By-pass auxiliary signs
 M4-3 sign. *See* Business auxiliary signs
 M4-6 sign. *See* End auxiliary signs
 M4-7 sign. *See* Temporary auxiliary signs
 M4-14 sign. *See* Begin auxiliary signs
 M4 series. *See* Alternative route signs; Auxiliary signs for alternative routes
 M5-1 sign. *See* Advance turn arrow auxiliary signs
 M5 series. *See* Advance turn arrow signs
 M6 series. *See* Directional arrow signs
 Maintain top safe speed sign, 343f, 343t, 344–345
 Maintenance
 bicycle traffic control, 789
 sign, 44, 583
 traffic control devices, 2
 traffic control signal, 449–450
 Major interchange
 defined, 16
 Major street
 defined, 16
 Major traffic incidents, 727
 Malfunction Management unit
 defined, 16
 Managed lane
 defined, 16
 Managed lane signs, 253–291
 comparative travel time information, 282f
 direct access ramp, 289f
 direct entrance ramp, 290f
 egress from, 286f, 287f
 entrance/exit ramps, 288f
 entrance to, 283f, 284f
 exit destinations, 282f
 guide signs for priced, 279–282, 281f
 intermediate entry to barrier- or buffer separated, 285f
 priced, 276–279
 regulatory signs for priced, 279, 280f
 separate entrance ramp, 291f

Mandatory movement lane control sign, 62–63
 Manual of Uniform Traffic Control Devices (MUTCD)
 acronyms/abbreviations used in, 23–24, 24t–26t
 incorporating new into, 8f
 interpretation of, 4–7
 relation to other publications of, 7–10
 word/phrases defined for use in, 10–23

Marina sign, 340f

Markings

bicycle traffic control, 806–815, 807f–809f, 811f–815f
 Center Line, 12
 Channelizing Line, 12
 colors for, 348
 curb, 348–398, 394–395
 Edge Line, 13, 371, 413, 417t, 452
 functions of, 347
 functions of longitudinal pavement, 348
 island, 430
 lane line, 15
 limitations of, 347
 longitudinal, 16
 longitudinal pavement, 348, 354, 370–371
 low-volume road, 541
 materials for, 347
 parking space, 385–387, 386f, 387f
 pathway grade crossing, 786, 787f
 patterns of longitudinal pavement, 348
 pavement, 348–398
 roundabout, 399–414
 rumble strip, 452
 school area, 744, 744f
 shared lane, 810
 speed measurement, 21
 standardization of application for, 347
 temporary traffic control zones with, 545
 toll plaza, 423
 transverse, 22
 widths of longitudinal pavement, 348

Maximum highway traffic signal preemption time
 defined, 16

Mechanic sign, 338f

Medians

defined, 16
 island, 431
 TTC - entrance ramp with crossover of, 632t, 712, 713f
 TTC - exit ramp with crossover of, 632t, 714, 715f
 TTC zone - work within, 624

Memorial signs, 339–341

Men's restroom sign, 338f

Merge sign, 125–126, 125f

Merging tapers, 557, 557t

Metric conversion, A2–1

Metric requirements legislation, A1–1

Miles per hour to kilometers/hour conversion, A2–1

Miles to kilometers conversion, A2–1

Millimeters to inches conversion, A2–1

Minimum speed limit plaque, 57f, 59

Minimum track clearance distance
 defined, 16

Minimum vehicular volume, 437, 438f

Minimum warning time

defined, 16

Minor interchange

defined, 16

Minor street
defined, 16

Minor traffic incidents, 728

Mode-specific guide signs for shared use paths, 792t, 799f, 805, 805f

Motorboating sign, 340f

Motorcycle plaque (W8-15P)
temporary traffic control with, 589f, 597

Motorcyclists' signs, 121f, 123

Motorist call box legislation, A1-1-A1-2

Motorized traffic signs
temporary traffic control with, 589f, 594

Movable bridge resistance gate
defined, 16

Movable bridge signal
defined, 16

Movable bridges traffic control, 519-521
application of, 519
design of, 519-520
operation of, 521

Movable bridge warning gate
defined, 16

Movement prohibition signs, 60-61, 60f

Multi-lane
defined, 16

MUTCD. *See* Manual of Uniform Traffic Control Devices

N

Named highways signing, 179, 183

Narrow bridge sign (W5-2), 118, 118f
sizes for low-volume roads of, 532t, 537, 538f

National Cooperative Highway Research Program (NCHRP)
"Recommended Procedures for Safety performance Evaluation of Highway Features," 576

National Incident Management System (NIMS), 726

National network sign (R14-4), 99f, 100

National scenic byways sign (D6-4), 179-180, 180f

Nature study area sign, 337f

NCHRP. *See* National Cooperative Highway Research Program

Neutral area
defined, 17

New plaque, 132f, 134

New traffic pattern ahead sign (W23-2), 131, 592f, 593

Next exit plaque, 218, 218f

Next exit sign, 225, 225f

Next services sign, 302, 302f

Night speed limit plaque, 57f, 58-59

NIMS. *See* National Incident Management System

No bicycles sign (R5-6), 791t, 793f, 795

No center line sign (W8-12), 121f, 123
temporary traffic control with, 589f, 595

No equestrians sign (R9-14), 791t, 793f, 795

No gates or lights plaque (W10-13P), 759f, 763

No hitchhiking sign (R9-4), 92, 93f

No left turn sign, 60-61, 60f

No motor vehicles on tracks sign (R15-6), 753f, 762

No motor vehicles sign (R5-3), 791t, 793f, 795

Non-vehicular traffic warning signs, 130-131, 130f, 537-539, 538f

No outlet sign (W14-2), 118f, 119-120
low-volume roads with, 538f, 539

No parking bike lane bicycles sign (R7-9), 791t, 793f, 795

No parking sign (R8-3)
sizes for low-volume roads of, 532t, 535f

No-passing zone markings, 352-354, 352t, 353f
determining limits of, 353f
at horizontal curve, 353f
minimum sight distances for, 352t
Traffic direction transition in three-lane road with, 354, 355f
at vertical curve, 353f

No passing zone sign (W14-3), 125f, 127
temporary traffic control zones with, 545f

No pedestrians sign (R9-3), 791t, 793f, 795

No right turn sign, 60, 60f

No skaters sign (R9-13), 791t, 793f, 795

No traffic sign (W18-1), 533t, 538f, 539

No train horn sign (W10-9), 759f, 763

No trucks sign (R5-2)
sizes for low-volume roads of, 532t, 534f

No turn on red sign (R10-11), 95-97, 96f, 753f, 760

No U-turn sign (R3-4), 60f, 61

Number of tracks plaque (R15-2P), 542, 542f, 751, 752t, 753f

O

Object markers, 134-136, 135f
adjacent to roadway obstruction, 135-136, 135f
bicycle traffic control with, 805
defined, 17
design of, 134-135
end of roadway obstruction, 135f, 136
low-volume road, 539
placement height of, 134-135
roadway obstruction, 135, 135f
types of, 135f

Obstructions
adjacent to roadway, 135-136, 135f
approach markings for, 376, 377f-378f
delineator for, 428f
pavement marking for, 810
roadway, 135, 135f

Occupancy requirement
defined, 17

Occupant
defined, 17

Off-road vehicle trail sign, 339f

One-direction large arrow sign (W1-6), 109f, 111f, 113-114
sizes for low-volume roads of, 532t

One-lane, two-way tapers, 557, 557t

One-lane, two-way traffic control, 557-560, 557t, 559f
example of, 559f
flagger method of, 558
flag transfer method of, 558
pilot car method of, 560
stop or yield control method of, 560
tapers for, 557, 557t

One lane bridge sign (W5-3), 118, 118f
sizes for low-volume roads of, 532t, 537, 538f

One lane road sign (W20-4), 533t
temporary traffic control with, 590f, 591
temporary traffic control zones with, 545f

One-way left turn arrow
lane-use control with, 525, 526f

One way sign (R6-2), 77–82, 78f–83f
sizes for low-volume roads of, 532t, 534f

On ramp plaque
temporary traffic control with, 589f, 592

Open-road ETC lane
defined, 17

Open-road tolling
defined, 17

Open-road tolling point
defined, 17

Opposing traffic
defined, 17

Opposing traffic lane divider/sign
temporary traffic control with, 611–612

Optional lanes signing, 193–198, 194f–197f
diagrammatic guide, 198–202, 199f–202f
intermediate/minor interchange multi-lane exit, 203, 203f

Optional movement lane control sign, 63–64

Orange
meaning for traffic control devices of, 10

ORT lane
toll plaza markings for, 423

Overhead arrow-per-lane signs, 193–198, 194f–197f

Overhead pedestrian crossing sign (R1-9), 55f, 56

Overhead sign
defined, 17

Overhead signs installation, 41

P

Parking area
defined, 17

Parking area guide sign, 171

Parking at school signs (R7 series), 743

Parking signs (R7 series), 88–92, 88f–90f, 338f

Parking space pavement markings, 385–387, 386f, 387f

PARK - RIDE sign, 171

Passive grade crossing
defined, 17

Pass with care sign (R4-2), 72f, 73
sizes for low-volume roads of, 532t, 534f

Path narrows sign (W5-4a), 791t, 796–798, 797f

Pathway
defined, 17

Pathway grade crossing, 786–788, 787f
active traffic control systems for, 788
defined, 17
detectable warnings for, 786–787
edge lines for, 786–787
flashing lights for, 788
markings for, 786, 787f
passive devices for, 787–788
practices for, 786
purpose of, 786
signs for, 786, 787f
standard devices for, 786
stop lines for, 786–787

Pavement ends sign (W8-3), 121f, 122
sizes for low-volume roads of, 532t, 537, 538f

Pavement markings, 348–398. *See also* Preferential lane markings;
Roundabout markings
accessibility parking space, 387, 387f
advance speed hump, 395, 398f
arrow, 387–393, 389f, 392f
bicycle lane, 806, 807f, 809f, 813f
channelizing devices for, 429
chevron and diagonal cross hatch, 371, 395, 396f
colored pavement as, 428
crosswalk, 383–385, 384f, 385f
curb, 394–395
do not block intersection, 382, 384f
dotted white line, 358f–361f, 362, 372f–378
edge line, 371
functions of longitudinal pavement, 348
highway rail grade crossing, 543, 764–767, 765f–768f
intersections, extensions through, 371–374, 372f–373f
island, 370
lane-reduction transition, 374, 375f
light rail grade crossing traffic control with, 764–767, 765f–768f
low-volume roads, 541
no-passing zone, 352–354, 352t, 353f, 355f
obstructions, approach markings for, 376, 377f–378f
parking space, 385–387, 386f, 387f
patterns of longitudinal pavement, 348
railroad grade crossing traffic control with, 764–767, 765f–768f
raised, 376–380
route shields, 390f
school area, 744, 744f
solid white line where crossing lane discouraged, 362, 370f
speed hump, 395, 396f–398f
speed measurement, 393
speed reduction, 393, 394f
stop lines, 381–382
stop/yield for pedestrians, 381
symbol, 387–393, 388f, 390f–392f
temporary raised, 613
temporary traffic control with, 612
traffic control signal with, 494
transverse, 380
white line, 356–370, 357f–370f, 372f–378
white longitudinal, 370–371
widths of longitudinal pavement, 348
word, 387–393, 387f, 392f
yellow center line, 349–352, 350f–352f
yellow longitudinal, 354
yield ahead, 390–391, 391f
yield lines, 381–382, 382f, 383f

Pay toll warning signs (W9-6), 240–241, 241f

PCMS. *See* Portable changeable message signs

Peak hour signal warrant, 439, 441f

Pedestrian/bicycle detour sign, 592f, 598

Pedestrian change interval
defined, 17
pedestrian control with, 497–499, 498f

Pedestrian clearance time
defined, 17

Pedestrian control, 495–508
accessible signals/detectors for, 504–508
countdown signals for, 499–500
pedestrian detectors for, 500–501, 501f–503f, 504–508
pedestrian intervals for, 497–499, 498f
pushbutton for, 500–501, 501f–503f

- signal heads for, 495–497, 496f
- signal phases for, 497–499, 498f
- Pedestrian crossing**
 - flashing-light signals with, 781f
- Pedestrian crosswalk signs (R9-8), 55–56, 55f**
 - in-street pedestrian crossing, 55f, 56
 - overhead pedestrian crossing, 55f, 56
 - stop here for pedestrian, 54–55, 55f
 - temporary traffic control with, 578t, 584f, 586
 - yield here to pedestrian, 54–55, 55f
- Pedestrian facilities**
 - defined, 17
- Pedestrian gate, 782f–785f**
 - barrier at offset grade crossing, 784f
 - barrier at offset non-intersection grade crossing, 785f
 - roadway with, 782f
 - swing gate, 78f
- Pedestrian hybrid beacon, 509–512**
 - application of, 509
 - circular red signal with, 509
 - circular yellow signal with, 509
 - CROSSWALK STOP ON RED sign with, 511
 - defined, 17
 - design of, 509–511, 510f
 - emergency-vehicle access with, 513–515, 515f
 - installation guidelines, high-speed roadways, 510f
 - installation guidelines, low-speed roadways, 510f
 - operation of, 511–512
 - sequence for, 511f
 - signal heads with, 512
- Pedestrians**
 - bicycle/pedestrian sign for, 791t, 796–798, 797f
 - crossing sign, 55–56, 55f
 - defined, 17
 - detectable edging for, 610–611
 - four-hour volume of, 443f
 - island for, 431
 - LRT grade signal/crossing for, 780, 781f–785f
 - peak hour of, 444f
 - stop here for, sign, 54–55, 55f
 - stop/yield pavement markings for, 381
 - temporary traffic control safety provisions for, 549–550, 561–565
 - traffic control signal provisions for, 450
 - vibrotactile device for, 22
 - work affecting TTC zones with, 622
 - yield here to, sign, 54–55, 55f
- Pedestrians crossing sign (R9-2), 92–94, 93f, 94f**
- Pedestrian signal heads, 495–497**
 - application of, 495
 - defined, 17
 - design of, 496
 - height of, 497
 - illumination for, 496
 - location of, 497
 - meaning of, 495
 - size of, 496
 - UPRAISED HAND, 454, 496, 496f, 512
 - WALKING PERSON, 454, 496, 496f, 512
- Pedestrian volume signal warrant, 442, 443f, 444f**
- Permissive mode**
 - defined, 17
- Pets on leash sign, 337f**
- Pharmacy sign, 300t, 301f**
- Photo enforced plaque, 132f, 134**
- Photo enforced sign (R10-18), 97**
- Physical gore**
 - defined, 18
- Pick-up trucks sign, 337f**
- Picnic shelter sign, 338f**
- Picnic site sign, 338f**
- Pictographs**
 - community wayfinding signs, 177
 - defined, 18
 - ETC account, 238, 239f
 - signs using, 29
 - street name signs, 162
- Pilot car follow me sign (G20-4), 560**
 - temporary traffic control with, 590f, 598
- Pilot car method, 560**
- Pink**
 - meaning for traffic control devices of, 10
- Plaque**
 - advisory speed, 109f, 110t, 111f, 112, 589f, 596
 - ahead, 736, 741f
 - all way, 51–52, 51f
 - all year, 735f, 736
 - ambulance station, 300t, 301f
 - begin, 64
 - bike lane, 791t, 793f, 794
 - defined, 18
 - educational, 332, 333f
 - emergency medical care, 300t, 301f, 302
 - end, 64
 - end school zone, 735f, 736
 - finer double, 578t, 584f, 586, 735f, 736
 - finer higher, 578t, 584f, 586, 735f, 736
 - higher fines, 57f, 59
 - hospital, 300t, 301f
 - last exit before toll warning, 242
 - minimum speed limit, 57f, 59
 - next exit, 218, 218f
 - night speed limit, 57f, 58–59
 - number of tracks, 542, 542f
 - pay toll advance warning, 240–241, 241f
 - preferential lane regulatory, 255f, 256f
 - school, 735f, 736
 - size of, 46t–49t
 - sizes for low-volume roads of, 532t
 - stop ahead pay toll warning, 242
 - supplemental warning, 131–134, 132f
 - toll plazas regulatory, 238–240, 240f
 - trauma center, 300t, 301f
 - truck speed limit, 57f, 58
 - 24-hour, 300t, 301f
 - van accessible, 299t, 301f
 - work zone, 580t, 584f, 586
- Platoon**
 - defined, 18
- Playground sign, 130f, 131**
- Point of interest sign, 337f**
- Police sign, 300t, 301f**
- Portable changeable message signs (PCMS)**
 - brightness adjustment with, 600
 - colors for, 599
 - design of, 599
 - message display techniques for, 600

- mounting of, 600
 - purpose of, 599
 - temporary traffic control with, 598–601
 - urban freeways with, 599
 - Portable traffic control signal, 492–493
 - defined, 18
 - Posted speed limit
 - defined, 18
 - Post-interchange distance signs, 223, 223f
 - Post-interchange signs, 222–223
 - Post-mounted sign
 - defined, 18
 - high-occupancy vehicle, 267f
 - preferential lane, 255f, 257, 267f
 - Post office sign, 338f
 - Preemption
 - defined, 18
 - Preemption control
 - traffic control signal, 489–491
 - Preferential lane
 - defined, 18
 - toll plaza markings for, 423
 - Preferential lane markings, 415–422
 - barrier-separated, non-reversible, 416, 417t, 418f
 - barrier-separated, reversible, 416, 417t, 418f
 - bicycle lane, 415
 - buffer-separated (left-hand side), 416, 417t, 418f–419f
 - buffer-separated (right-hand side), 416, 417t, 419f
 - bus only lane, 415
 - contiguous (left-hand side), 417, 417t, 420f
 - contiguous (right-hand side), 417, 417t, 420f
 - counter-flow on divided highway, 421, 422f
 - ETC account-only lane, 415
 - HOT lane, 415
 - HOV lane, 415
 - light rail transit lane, 415
 - longitudinal motor vehicles, 416–421, 417t, 418f–420f, 422f
 - symbols, 415–416
 - taxi only lane, 415
 - two or more same direction lanes, 421
 - word, 415–416
 - Preferential lane signs, 253–291
 - added continuous-access, 261f–262f
 - advance regulatory signs for, 263
 - buffer-separated HOV lane, 261f–262f
 - direct access ramp between HOV lanes, 277f
 - direct entrances guide signs for, 273
 - direct exit guide signs for, 273, 275f
 - direct HOV lane entrance/exit, 277f
 - egress guide signs for, 270, 272f–274f
 - entrances gore sign for, 268f
 - exit gore sign for, 276f
 - guide signs for, 265–268, 267f, 268f
 - HOV plaque for, 264–265, 264f
 - initial entry point guide signs for, 267–268, 267f, 269f
 - intermediate entry point guide signs for, 268–270, 271f
 - lane ends regulatory signs for, 263
 - overhead, 256f, 267f
 - periods of operation regulatory, 259–260
 - post-mounted, 255f, 257, 267f
 - regulatory signs for, 253–258, 255f, 256f
 - scope of, 253
 - sizes of, 253, 254t
 - vehicle occupancy definition regulatory, 258–259
 - warning signs on median barriers for, 263–264, 264f
 - Pre-signal
 - defined, 18
 - Pretimed operation
 - defined, 18
 - Priced managed lane
 - direct entrance ramp to, 290f
 - egress from, 286f, 287f
 - entrance to, 283f, 284f
 - guide signs for, 279–282, 281f
 - intermediate entry to barrier- or buffer separated, 285f
 - regulatory signs for, 279, 280f
 - separate entrance ramp to, 291f
 - Primary signal face
 - defined, 18
 - Principal legend
 - defined, 18
 - Priority control
 - defined, 18
 - Private road open to public travel
 - defined, 18
 - Prohibitive circle and diagonal slash
 - recreational and cultural interest area signs with, 332, 333f
 - Propane gas sign, 300t, 301f
 - Protected mode
 - defined, 18
 - Publications
 - relation of MUTCD to other, 7–10
 - Public road
 - defined, 18
 - Pull-through signs, 184, 184f
 - Purple
 - meaning for traffic control devices of, 10
 - toll road sign background color with, 238
 - Pushbutton
 - defined, 18
 - Pushbutton information message
 - defined, 18
 - Pushbutton locator tone
 - defined, 18
 - Pushbutton pedestrian detector, 500–501
 - accessible extended press features for, 507–508
 - location of, 501, 501f–503f
 - positioning of, 501
- ## Q
- Queue clearance time
 - defined, 18
 - Quiet zone
 - defined, 19
 - highway rail grade crossing, 750
- ## R
- R1-1 sign. *See* Stop signs
 - R1-2 sign. *See* Yield signs
 - R1-5 series. *See* Stop here for pedestrians sign

- R1-6. *See* In-street pedestrian crossing sign
 R1-9. *See* Overhead pedestrian crossing sign
 R2-1 sign. *See* Speed limit signs
 R2-2P plaque. *See* Truck speed limit plaque
 R2-6aP plaque. *See* Fines double plaque
 R2-6P plaque. *See* Fines higher plaque
 R2-10 sign. *See* Begin higher fines sign
 R2-11 sign. *See* End higher fines sign
 R2-12 sign. *See* End work zone speed limit sign
 R3-4 sign. *See* No U-turn sign
 R3-17aP plaque. *See* Bike lane plaque
 R3-17 sign. *See* Bike lane sign
 R3-33 sign. *See* Right (left) lane must exit sign
 R4-2 sign. *See* Do not pass sign; Pass with care sign
 R4-4 sign. *See* Begin right turn lane yield to bikes sign
 R4-7 sign. *See* Keep right sign
 R4-8 sign. *See* Keep left sign
 R4-9 sign. *See* Stay in lane sign
 R4-10 sign. *See* Runaway vehicles only sign
 R4-11 sign. *See* Bicycles may use full lane sign
 R4-16 sign. *See* Keep right except to pass sign
 R4-17 sign. *See* Do not drive on shoulder sign
 R4-18 sign. *See* Do not pass on shoulder sign
 R5-1b plaque. *See* Ride with traffic plaque
 R5-1b sign. *See* Bicycles wrong way sign
 R5-1 sign. *See* Do not enter sign
 R5-2 sign. *See* No trucks sign
 R5-3 sign. *See* No motor vehicles sign
 R5-6 sign. *See* No bicycles sign
 R6-2 sign. *See* One way sign
 R7 series. *See* Parking at school signs; Parking signs
 R8-3 sign. *See* No parking sign
 R8-8 sign. *See* Do not stop on tracks sign
 R8-9 sign. *See* Tracks out of service sign
 R8-10 sign. *See* Stop here when flashing sign
 R8 series. *See* Stopping at school sign
 R9-1 sign. *See* Walk on left facing traffic sign
 R9-2 sign. *See* Pedestrians crossing sign
 R9-3 sign. *See* No pedestrians sign
 R9-4 sign. *See* No hitchhiking sign
 R9-7 sign. *See* Shared-use path sign
 R9-8. *See* Pedestrian crosswalk signs
 R9-13. *See* No skaters sign
 R9-14. *See* No equestrians sign
 R10-6 sign. *See* STOP HERE ON RED sign; Stop here on red sign
 R10-11 sign. *See* No turn on red sign
 R10-18 sign. *See* Photo enforced sign
 R10-22. *See* Bicycle signal actuation sign
 R10-28 sign. *See* Ramp metering sign
 R11-1 sign. *See* Keep off median sign
 R11-2 sign. *See* Road closed sign
 R11-3b sign. *See* Bridge out sign
 R11-4 sign. *See* Road closed to thru traffic sign
 R12-1 sign. *See* Weight limit sign
 R12-2. *See* Axle weight limit sign
 R13 series. *See* Weigh station signs
 R-14-1 sign. *See* Truck route sign
 R14-2 sign. *See* Hazardous material sign
 R14-4 sign. *See* National network sign
 R15-1 sign. *See* Grade crossing sign; Grade crossing (crossbuck) sign
 R15-2P plaque. *See* Number of tracks plaque
 R15-3P plaque. *See* Exempt plaque
 R15-4 sign. *See* Light rail transit only lane sign
 R15-5 sign. *See* Do not pass light rail transit sign
 R15-6 sign. *See* No motor vehicles on tracks sign
 R15-7 series. *See* Divided highway light rail crossing sign
 R15-8 sign. *See* Look sign
 R16-4 sign. *See* Feeder bender sign
 R16-5 sign. *See* Headlight use sign
 Radiator water sign, 338f
 Radio information signs, 310–311, 310f
 Radios sign, 337f
 Rafting sign, 340f
 Railroad transit grade crossing traffic control, 747–789
 advance warning signs for, 758–759, 759f
 automatic gates for, 772–773
 bicycle signal/crossing for, 780
 crossbuck assemblies with yield/stop signs for, 754–758, 754f–756f
 do not stop on tracks sign for, 753f, 760
 dynamic envelope markings for, 767, 767f, 768f
 emergency notification sign with, 762–763, 762f
 exempt plaque for, 753f, 759–760, 759f
 flashing-light signals for, 769–785, 770f
 four-quadrant gate systems for, 773–775, 774f
 gates for, 769–785, 770f, 774f
 grade crossing elimination for, 749–750
 grade crossing illumination for, 750
 grade crossing (crossbuck) sign for, 751, 752t, 753f
 look sign with, 753f, 762
 low ground clearance grade crossing sign with, 759f, 763–764
 no motor vehicles on tracks sign with, 753f, 762
 no train horn sign with, 759f, 763
 number of tracks plaque for, 751, 752t, 753f
 pathway grade crossing for, 786–788, 787f
 pavement markings for, 764–767, 765f–768f
 pedestrian signal/crossing for, 780, 781f–785f
 practices for, 747–748
 purpose of signs for, 751
 quiet zone treatments with, 750
 rail traffic detection for, 775–776
 signs for, 751–768
 sizes of signs for, 751
 skewed crossing sign with, 759f, 764
 standard devices used for, 747–748
 stop here on red sign with, 753f, 761
 stop here when flashing sign with, 753f, 761
 stop lines for, 766–767
 storage space sign with, 759f, 764
 tracks out of service sign with, 753f, 760–761
 turn restrictions during preemption with, 753f, 760
 uniform provisions, 749
 wayside horn systems for, 775
 yield lines for, 766–767
 Rail traffic
 daily frequency of, 448t
 defined, 19
 Rail traffic detection, 775–776
 Raised pavement marker
 defined, 19
 Raised pavement markings, 376–380
 general, 376, 379
 illumination with, 379
 spacing of, 379

- substituting for other markings with, 380
- supplementing other markings with, 379–380
- vehicle positioning guides with, 379
- Ramp control signal
 - defined, 19
- Ramp meter. *See* Ramp control signal
- Ramp metering sign (R10-28), 97, 97f
- Ramp narrows sign (W5-4)
 - temporary traffic control with, 588f, 592
- Ranger station sign, 338f
- Rattlesnakes sign, 337f
- Recreational and cultural interest area signs, 330–341
 - accommodations, 330, 331t, 338f
 - application of, 330
 - arrangement of, 335f
 - conventional road, 334f
 - dedication, 339–341
 - design requirements for, 330
 - directional assemblies, 333f
 - directional signs, 333f
 - educational plaques for, 332
 - examples of, 333f, 334f
 - freeway/expressway, 334f
 - general applications, 330, 331t, 337f
 - height of, 335f
 - land recreation, 330, 331t, 339f
 - lateral position of, 335f
 - memorial, 339–341
 - placement of, 332–333
 - prohibitive circle and diagonal slash for, 332, 333f
 - regulatory, 330
 - scope of, 330
 - services, 330, 331t, 338f
 - symbol and destination guide sign layout for, 336f
 - symbol sign sizes for, 332
 - symbols on, 332–333
 - warning, 330
 - water recreation, 330, 331t, 340f
 - winter recreation, 330, 331t, 341f
- Recreational vehicle site sign, 338f
- Recycling sign, 337f
- Red. *See also* Circular red signal
 - meaning for traffic control devices of, 10
- Red arrow
 - application of, 453–454
 - meaning of, 451
 - vertical position within signal face of, 458, 458f
- Red clearance interval
 - defined, 19
 - yellow change interval with, 485, 489
- Reduced school speed limit ahead sign (S4-5), 743
- Reduced speed limit ahead sign, 124, 124f
- RED X signal
 - lane-use control with, 525
- Red/yellow lens automated flagger assistance device, 571–573, 572f
 - change interval with, 573
 - circular red/circular yellow lens with, 571
 - example of use of, 572f
 - gate arms with, 571
 - Stop Hear On Red sign with, 571
- Reference location signs (D10-1 through D10-3), 294–296, 295f, 792t, 799f, 804
- Regulatory signs, 29, 45–102
 - advance intersection lane control, 64
 - application of, 45, 583
 - authority, 583
 - bicycle, 791t, 793f, 795
 - bridge out, 532t, 534f
 - defined, 19
 - design of, 45, 583
 - divided highway crossing, 82
 - do not drive on shoulder, 72f, 75
 - do not enter, 75–76, 75f, 76f, 532t, 534f
 - do not pass, 72, 72f, 532t, 534f
 - do not pass on shoulder, 72f, 75
 - emergency restriction, 90f, 92
 - feeder bender, 101, 101f
 - grade crossing, 532t
 - hazardous material, 99–100, 99f
 - headlight use, 100, 100f
 - intersection lane control, 61–62, 62f
 - jughandle, 67–71, 68f–71f
 - keep left, 72f, 73–74
 - keep off median, 97, 98f
 - keep right, 72f, 73–74, 532t, 534f
 - keep right except to pass, 72f, 73
 - low-volume road, 534–535, 534f–535f
 - mandatory movement lane control, 62–63
 - movement prohibition, 60–61, 60f
 - multi-way stop, 52
 - national network, 99f, 100
 - no hitchhiking, 92, 93f
 - no parking, 532t, 535f
 - no trucks, 532t, 534f
 - no turn on red, 95–97, 96f
 - one way, 77–82, 78f–83f, 532t, 534f
 - optional movement lane control, 63–64
 - parking, 88–92, 88f–90f
 - pass with care, 72f, 73, 532t, 534f
 - pedestrian crossing, 55–56, 55f, 92–94, 93f, 94f
 - photo enforced, 97
 - ramp metering, 97, 97f
 - recreational and cultural interest area, 330
 - retroreflectivity of, 29
 - reversible lane control, 65–67, 65f, 65t, 66f
 - right (left) lane must exit, 64
 - right-of-way, 49–51
 - road closed, 98, 98f, 532t, 534f
 - road closed to thru traffic, 532t, 534f
 - roundabout, 84–87, 84f–87f
 - runaway vehicles only, 72f, 74
 - seat belt symbol on, 101, 101f
 - selective exclusion, 75f, 76–77
 - size of, 45–49, 46t–49t
 - slow vehicle turn-out, 72f, 74
 - speed limit, 46t, 56–59, 57f, 532t, 534, 534f
 - standing/stopping, 88–92, 88f–90f
 - stay in lane, 72f, 74
 - stop, 46t, 51–54, 51f, 532t, 534, 534f, 542f, 543, 560
 - stop here for pedestrians, 54–55, 55f
 - temporary traffic control with, 583
 - traffic signal actuation, 94, 94f
 - truck route, 99, 99f
 - trucks use right lane, 72f, 73
 - two-way left turn only, 64

- walk on left facing traffic, 92, 93f
- weigh station, 99, 99f
- weight limit, 98–99, 98f, 532t, 534f
- wrong way, 75f, 76, 76f
- yield, 46t, 51f, 53–54, 532t, 534f, 542f, 543, 560
- yield here to pedestrians, 54–55, 55f
- Rest area signs, 307–308, 307f
- Restrooms sign, 338f
- Retroreflection
 - bicycle traffic control markings with, 806
 - channelizing devices with, 429
 - conventional road guide signs, 137
 - delineator with, 424
 - freeway/expressway guide signs, 182
 - maintaining minimum, 30–31, 31t
 - school area traffic control, 734
 - sign, 29–32, 29t, 31t
 - street name signs, 162
- Reverse curve sign (W1-4 series)
 - temporary traffic control with, 588f, 596
- Reversible lane control signs, 65–67, 65f, 65t, 66f
- Revision of manual legislation, A1–1
- Ridesharing signs, 310f, 311
- Ride with traffic plaque (R5-1b), 791t, 793f, 794–795
- Right (left) lane closed sign (W20-5)
 - temporary traffic control with, 590f, 591
- Right (left) lane exit only ahead sign, 125f, 126–127
- Right (left) lane must exit sign (R3-33), 64
- Right-of-way
 - defined, 19
 - sign, 49–51
- Right-of-way transfer time
 - defined, 19
- Right-turn indications, 474–484, 476f–482f
 - permissive only mode of, 475–478, 475f–478f
 - protected only mode of, 478–480, 479f, 480f
 - protected/permissive mode of, 478f, 480–484, 481f, 482f
 - signal faces for controlling, 475
 - variable, 475
- Right turn only lane
 - bicycle lane with, 811f, 812f
- Road closed sign (R11-2), 98, 98f
 - sizes for low-volume roads of, 532t, 534f
 - temporary traffic control with, 578t, 583–585, 585f
- Road closed to thru traffic sign (R11-4), 532t, 534f
 - temporary traffic control with, 578t, 585, 585f
- Road closure
 - safety with, 565
- Road machinery ahead sign (W21-3), 533t
 - temporary traffic control with, 592f, 593
 - temporary traffic control zones with, 545f
- Road may flood sign (W8-18), 532t
 - temporary traffic control zones with, 545f
- Road narrows sign (W5-1), 117, 118f
- Roadside area signs, 307–308, 307f
- Road (area) use permit required for thru traffic sign, 343f, 343t, 345
- Road user
 - defined, 19
- Roadway
 - defined, 19
 - delineator for edge of, 428f
 - obstruction, 135, 135f
 - pedestrian gate with, 782f
 - shared, 20
- Roadway network
 - defined, 19
 - highway traffic signal needs study with, 446
- Roadway obstruction object markers, 135, 135f
- Road work next XX miles sign (G20-1), 590f, 597
- Road work sign (W20-1), 533t
 - temporary traffic control with, 590f, 591
 - temporary traffic control zones with, 545f
- Rock collecting sign, 339f
- Rough road sign (W8-8), 532t
 - temporary traffic control zones with, 545f
- Roundabout
 - bicycle lane not provided on, 809
 - defined, 19
 - destination signs at, 157–158, 158f–160f
- Roundabout markings, 399–414
 - approach and circulatory, 399f
 - arrow, 413–414
 - central island extended, 402f
 - central island unextended, 401f
 - crosswalk, 413
 - diamond interchange with, 412f
 - edge line, 413
 - lane-use arrow, 400f
 - one-lane, 400f
 - other circular intersections, 414
 - symbol, 413–414
 - three-lane with three-lane approach, 409f
 - three-lane with two- and three-lane approach, 408f
 - three-lane with two-lane exits, 410f
 - two-lane with consecutive double left turn, 407f
 - two-lane with double left turn, 405f
 - two-lane with double right turn, 406f
 - two-lane with one- and two-lane approach, 401f–402f
 - two-lane with one-lane exit, 403f
 - two-lane with two-lane exit, 404f
 - two linked roundabouts, 411f
 - white line, 413
 - word, 413–414
 - yield line, 413
- Roundabout sign, 84–87, 84f–87f
- Route shield pavement markings, 390f
- Route signs, 142–144, 143f, 210–211, 210f
 - assemblies, 148, 149f–152f
 - auxiliaries, 144
 - bicycle, 792t, 800–801, 800f
 - design of, 143–144
- Rowboating sign, 340f
- Rumble strip
 - defined, 19
- Rumble strip markings, 432
 - color of edge line associated with, 432
 - longitudinal, 432
 - transverse, 432, 432f
- Rumble strips
 - temporary traffic control with, 618
- Runaway vehicles only sign (R4-10), 72f, 74
- Rural highway
 - defined, 19
- RV Access supplemental messages sign, 316, 316f
- RV sanitary station sign, 299t, 301f

S

S1-1 sign. *See* School signs

S3-1 sign. *See* School bus stop ahead sign

S3-2 sign. *See* School bus turn ahead sign

Safety

activity area for, 564

firefighter/emergency responder, 565

high-visibility apparel for, 565

law enforcement use with, 565

lighting for, 565

pedestrians, 549–550, 561–565

planning for worker, 564

road closure for, 565

shadow vehicle for, 565

special devices for, 565

temporary traffic barriers for, 564

training for worker, 564

worker, 561–565

Sailing sign, 340f

Sanitary station sign, 338f

School

defined, 19

School area traffic control, 731–746

color in signs of, 734

crossing supervision for, 745–746

crosswalk markings for, 744

established school crossings with, 731

height of signs for, 734

illumination for, 734

installation of signs for, 734

lettering for, 734

low-volume roads with, 546

markings for, 744, 744f

need for standards for, 731

pavement markings for, 744, 744f

position of signs for, 734

retroreflection for, 734

routes with, 731, 732f

school crossings criteria for, 731

scope, 732

signs for, 733–744, 733t, 735f, 741f

size of signs for, 733, 733t

School bus stop ahead sign (S3-1), 742

School bus turn ahead sign (S3-2), 742

School crossing assembly, 741–742, 741f

advance, 736, 741f

stop sign with, 741, 741f

yield sign with, 741, 741f

School crossing signal warrant, 442, 445

School plaque, 735f, 736

School signs (S1-1), 733–744, 733t, 735f, 741f

advance crossing assembly, 736, 741f

color in, 734

crossing assembly, 741–742, 741f

finer double plaque, 735f, 736

finer higher plaque, 735f, 736

four applications of, 734

height of, 734

higher fines zone, 735f, 736

illumination for, 734

installation of, 734

lettering for, 734

parking, 743

position of, 734

reduced school speed limit ahead, 743

retroreflection for, 734

school bus stop ahead, 742

school bus turn ahead, 742

school speed limit assembly, 742–743

size of, 733, 733t

stop, 741, 741f

stopping, 743

yield, 741, 741f

zone, 735f, 736

School speed limit assembly, 742–743

end higher fines zone sign for, 742–743

end school speed limit sign for, 742–743

end school zone sign for, 742–743

finer double plaque for, 742–743

finer higher plaque for, 742–743

School zone

defined, 19

School zone sign, 735f, 736

all year plaque with, 735f, 736

end school zone plaque with, 735f, 736

school plaque with, 735f, 736

Screens

temporary traffic control with, 618

Scuba diving sign, 340f

Seal viewing sign, 340f

Sea plane sign, 337f

Seat belt symbol on sign, 101, 101f

Selective exclusion signs, 75f, 76–77

Semi-actuated operation

defined, 19

Separate turn signal face

defined, 19

Separation time

defined, 19

Shadow vehicle, 565

Shared lane marking, 810

Shared left-turn/right-turn indications, 484–485,

486f–488f

Shared roadway

defined, 20

Shared turn signal face

defined, 20

Shared-use path

center line markings for, 808f

defined, 20

pattern/color markings for, 806

Shared-use path sign (R9-7), 791t, 793f, 795

Share the road plaque (W16-1P), 132f, 133–134, 791t, 796–798,

797f

Shelter directional signs, 343f, 343t, 346

chemical, 343f, 346

fallout, 343f, 346

hurricane, 343f, 346

size of, 343t

Shifting tapers, 557, 557t

Shoulder drop off plaque (W8-17P)

temporary traffic control with, 589f, 595

Shoulder sign, 121f, 122

Shoulder tapers, 557, 557t

- Shoulder work sign, 533t
 - temporary traffic control with, 590f, 594
 - temporary traffic control zones with, 545f
- Showers sign, 338f
- Side road warning sign (W2-2), 536f, 537
- Sidewalk
 - defined, 20
- Sidewalk closed sign
 - temporary traffic control with, 578t, 585f, 586
- Signal backplate
 - defined, 20
- Signal coordination
 - defined, 20
- Signal face
 - aiming of, 461–463
 - defined, 20
 - horizontal position of indicators within, 458f, 459
 - lateral offset (clearance) of, 465, 465f, 493
 - lateral positioning of, 463–464, 463f
 - left-turn indications controlled by, 466
 - longitudinal positioning of, 463f, 464
 - mounting height of, 465, 465f
 - number on approach of, 459–461, 460f, 461t
 - position of indicators within, 457, 458f
 - right-turn indications controlled by, 475
 - shielding of, 461–463
 - U-turn, 456, 456f
 - vertical position of indicators within, 457–459, 458f
 - visibility of, 461–463, 461t
- Signal heads
 - defined, 20
 - pedestrian, 495–497, 496f
 - pedestrian hybrid beacon with, 512
- Signal housing
 - defined, 20
- Signal indication
 - defined, 20
- Signal lens
 - defined, 20
- Signal louver
 - defined, 20
- Signal phase
 - defined, 20
- Signals. *See also* Flashing-light signals; Freeway entrance ramps control signals; Highway traffic signal; Lane-use control signals; Light rail transit signals; Pedestrian signal heads; Traffic control signal
 - accessible pedestrian, 504–508
 - bicycle traffic control, 816
 - hand-signaling devices, 566–567
 - movable bridge, 16
 - portable traffic control, 18, 492–493
 - UPRAISED HAND, 454, 496, 496f, 512
 - WALKING PERSON, 454, 496, 496f
- Signal section
 - defined, 20
- Signal system
 - defined, 20
- Signal timing
 - defined, 20
- Signal visor
 - defined, 20
- Sign assembly
 - defined, 20
- Sign illumination
 - defined, 20
- Signing
 - defined, 20
- Sign legend
 - defined, 20
- Sign panel
 - defined, 20
- Signs. *See also* Regulatory signs; Warning signs
 - bicycle traffic control, 790–805, 790f, 791t–792t, 793f, 797f, 799f–803f, 805f
 - borders with, 36
 - classification of, 28
 - colors of, 32, 33t
 - defined, 20
 - design of, 28–29
 - dimensions of, 32–34
 - enhanced conspicuity for, 36–37, 37f
 - excessive use of, 27
 - function of, 27
 - height of, 38f, 42
 - illumination of, 29–30, 29t
 - lateral offset of, 38f, 43
 - legislation on, A1–2
 - location at intersection of, 39f, 40f
 - location standardization for, 37–41, 38f–40f
 - maintenance of, 44
 - median opening treatments with, 44
 - mountings of, 44
 - orientation of, 43
 - overhead installation of, 41
 - pathway grade crossing, 786, 787f
 - pictographs on, 29
 - posts for, 44
 - purpose of, 27
 - rail grade crossing traffic control with, 751–768
 - retroreflectivity of, 29–31, 29t, 31t
 - school area traffic control, 733–744, 733t, 735f, 741f
 - shape of, 32
 - sizes for low-volume roads of, 532t
 - standardization of, 27
 - symbols used with, 34–35
 - temporary traffic control, 576–601, 578t–580t, 581f, 582f, 584f, 585f, 588f–590f
 - traffic control signal with, 493–494
 - word messages used with, 35–36
- Simultaneous preemption
 - defined, 20
- Single-exit interchange service signs, 317–318
- Skateboarding sign, 339f
- Skewed crossing sign (W10-12), 532t, 759f, 764
- Ski jumping sign, 341f
- Sledding sign, 341f
- Sleeping shelter sign, 338f
- Slow traffic ahead sign (W23-1)
 - temporary traffic control with, 590f, 592
- Slow vehicle turn-out sign (D17-7), 72f, 74, 178, 178f
- Smoking sign, 337f
- Snack bar sign, 337f
- Snowboarding sign, 341f
- Snowmobiling sign, 341f
- Snowshoeing sign, 341f
- Snow tubing sign, 341f
- Soft shoulder sign (W8-4), 589f, 595

- Special purpose road
 - defined, 20
- Specific service signs, 312–319
 - application, 313
 - double-exit interchange, 318
 - eligibility for, 312–313
 - examples of, 314f, 315f
 - interchange, 317–318
 - intersection, 319
 - letter and numeral sizes for, 316t, 317
 - locations for, 315f
 - logos/logo sign panels with, 313–318, 314f–316f
 - policy for, 319
 - recreational and cultural interest area signs for, 330, 331t, 338f
 - RV Access supplemental messages on, 316, 316f
 - single-exit interchange, 317–318
 - sizes of, 317
 - supplemental message, 316, 316f
 - trailblazer, 318–319, 319f
- Speed
 - defined, 21
- Speed hump markings, 395, 396f–398f
 - advance, 395, 398f
 - with crosswalks, 397f
 - without crosswalks, 396f
- Speed hump sign (W17-1), 120, 121f
- Speed limit
 - defined, 21
- Speed limit sign beacon, 524
 - defined, 21
- Speed limit signs (R2-1), 46t, 56–59, 57f
 - higher fines, 57f, 59
 - minimum, 57f, 59
 - night, 57f, 58–59
 - size of, 46t
 - sizes for low-volume roads of, 532t, 534, 534f
 - truck, 57f, 58
- Speed measurement markings
 - defined, 21
- Speed measurement pavement markings, 393
- Speed reduction pavement markings, 393, 394f
- Speed zone
 - defined, 21
- Spelunking/caves sign, 339f
- Splitter island
 - defined, 21
- Stable sign, 338f
- Standing/stopping signs, 88–92, 88f–90f
- Station crossing
 - defined, 21
- Statutory speed limit
 - defined, 21
- Stay in lane sign (R4-9), 72f, 74
 - temporary traffic control with, 578t, 585f, 586
- Stay on trail sign, 337f
- Steady mode
 - defined, 21
- Steel plate ahead sign (W8-24), 589f, 595
- Stop ahead pay toll warning sign, 242
- Stop ahead sign (W3-1)
 - sizes for low-volume roads of, 532t, 537, 538f
- Stop beacon, 524
 - defined, 21
- Stop here for pedestrians pavement markings, 381
- Stop here for pedestrians sign (R1-5 series), 54–55, 55f
- STOP HERE ON RED sign (R10-6), 519
- Stop here on red sign (R10-6), 753f, 761
- Stop here when flashing sign (R8-10), 753f, 761
- Stop lines
 - defined, 21
 - highway rail grade crossing with, 766–767
 - light rail grade crossing traffic control with, 766–767
 - pathway grade crossing, 786–787
 - railroad grade crossing traffic control with, 766–767
- Stop lines pavement markings, 381–382
- Stop or yield control method, 560
- Stopping at school sign (R8 series), 743
- Stopping sight distance
 - speed, function of, 555t, 575t
- Stop signs (R1-1), 46t, 51–54, 51f
 - applications, 52
 - bicycle traffic control with, 791t, 792–794, 793f
 - crossbuck assemblies with, 754–758, 754f–756f
 - multi-way, 52
 - placement, 53–54
 - size of, 46t
 - sizes for low-volume roads of, 532t, 534, 534f
 - temporary traffic control with, 560
- STOP/SLOW automated assistance device, 569–571, 570f
 - example of use of, 570f
 - gate arms with, 569
 - WAIT ON STOP sign with, 571
 - warning lights with, 569
- Stop/slow paddle, 566–567
- Storage space sign (W10-11), 759f, 764
- Street name signs (D3-1), 161–164, 162f, 163t
 - advance, 163–164
 - colors for, 163
 - illumination for, 162
 - letter heights of, 163t
 - lettering for, 161–162
 - pictographs for, 162
 - retroreflection for, 162
- Stripes
 - legislation on, A1–2
- Strollers sign, 337f
- Supplemental message signs, 316, 316f
- Supplemental signal face
 - defined, 21
- Supplemental warning plaques, 131–134, 132f
 - advance street name, 132f, 133
 - arrow, 132–133, 132f
 - cross traffic does not stop, 133
 - design of, 132
 - distance, 132, 132f
 - hill-related, 132f, 133
 - new, 132f, 134
 - photo enforced, 132f, 134
 - share the road, 132f, 133–134
- Supplementary distance plaque (W7-3aP), 589f, 597
- Surface condition signs, 121f, 122
- Surfing sign, 340f
- Survey crew sign (W21-6), 533t
 - temporary traffic control with, 590f, 594
 - temporary traffic control zones with, 545f
- Swimming sign, 340f
- Swing gates, 784f

Symbol pavement markings, 387–393, 388f, 390f–392f

Symbols

- destination guide sign layout with, 336f
- freeway/expressway guide signs with, 192
- pavement marking with, 387–393, 388f, 390f–392f
- preferential lane markings with, 415–416
- recreational and cultural interest area signs with, 332–333
- roundabout markings with, 413–414
- seat belt, 101, 101f
- sign, 34–35
- sizes for signs with, 332

T

Tapers

- buffer spaces with, 556f
- downstream, 557, 557t
- length criteria for, 557t
- length determining formulas for, 557t, 633t
- length for temporary traffic control zone of, 557t
- merging, 557, 557t
- one-lane, two-way, 557, 557t
- shifting, 557, 557t
- shoulder, 557, 557t
- temporary traffic control with, 555–558, 556f, 557t
- types of, 556f

Taxi only lane

- preferential lane markings for, 415

Technical rock climbing sign, 339f

Telecommunication Device for deaf sign, 300t, 301f

Telephone sign, 299t, 301f

Temporary auxiliary signs (M4-7), 145f, 147

Temporary detour auxiliary signs, 147

Temporary lane separators

- temporary traffic control with, 610

Temporary markings

- temporary traffic control with, 612–613

Temporary raised islands, 611

Temporary raised pavement marking, 613

Temporary traffic barriers, 564, 616–617

Temporary traffic control (TTC), 547–729

- accessibility considerations with, 563–564

activity area of, 554–555, 555t

advance warning area of, 552–554, 554t

bicyclists with, 549–550

detours and diversions for, 558

devices for, 576–618

devices for safety with, 563

elements of, 551–560

emergency-vehicle lighting for, 727

firefighter/emergency responder safety with, 565

flagger control with, 566–575, 570f, 572f, 574f, 575t

fundamental principles of, 549–550

guidelines for, 549

incident management areas for, 726–729, 730f

inspections for, 550

intermediate traffic in, 728

major traffic in, 727

minor traffic in, 728

motorists with, 549–550

nighttime hours in, 629–630

normal roadway function suspended then, 547

one-lane, two-way, 557–560, 557t, 559f

pedestrians safety with, 549–550, 561–565

plans for, 547, 551–552

public relations with, 550

roadside safety with, 550

road user movement not inhibited with, 549

stopping sight distance needed for, 555t

tapers for, 555–558, 556f, 557t

termination area of, 555

training for, 550

transition area of, 554

typical applications, 631–725

worker safety with, 561–565

Temporary traffic control devices, 576–618

ADAAG guidelines for placement of, 581

advance warning signs for, 586–591, 587f–590f

advisory speed plaque for, 589f, 596

arrow boards for, 601–603, 602f

barricades, 581–583, 582f

barricades for, 605f, 607–608

begin higher fines sign for, 578t, 584f, 586

blasting zone ahead sign for, 590f, 595

business/commercial area placement of, 581f

center lane closed sign for, 589f, 592

channelizing devices for, 604–606, 605f

cones for, 605f, 606

crash cushions for, 617–618

delineators for, 613

detectable edging for pedestrians for, 610–611

detour sign for, 590f, 591, 592f, 598

direction indicator barricade for, 605f, 608–610

double reverse curve sign for, 590f, 596

drums for, 605f, 607

end blasting zone sign for, 589f, 595

end detour sign for, 592f, 598

end higher fines sign for, 578t, 584f, 586

end road work miles sign for, 590f, 598

end work zone speed limit sign for, 578t, 584f, 586

exit closed sign for, 592, 592f

exit only sign for, 592f, 593

exit open sign for, 592, 592f

fines double plaque for, 578t, 584f, 586

fines higher plaque for, 578t, 584f, 586

flagger sign for, 592f, 593

floodlights for, 614

fresh oil sign for, 592f, 593

guide signs for, 597–598

high-level warning devices for, 603

lane ends sign for, 588f, 592

lighting devices for, 614

local traffic only sign for, 578t, 585, 585f

longitudinal channelizing device for, 609–610

low shoulder sign for, 589f, 595

motorcycle plaque for, 589f, 597

motorized traffic signs for, 589f, 594

new traffic pattern ahead sign for, 592f, 593

no center line sign for, 589f, 595

one lane sign for, 590f, 591

opposing traffic lane divider/sign for, 611–612

pavement marking for, 612

pedestrian/bicycle detour sign for, 592f, 598

- pedestrian crosswalk sign for, 578t, 584f, 586
- pilot car follow me sign for, 590f, 598
- portable changeable message signs for, 598–601
- ramp narrows sign for, 588f, 592
- on ramp plaque for, 589f, 592
- regulatory sign applications for, 583
- regulatory sign authority for, 583
- regulatory sign design for, 583
- residential area placement of, 581f
- reverse curve sign for, 588f, 596
- right (left) lane closed sign for, 590f, 591
- ROAD (STREET) CLOSED sign for, 578t, 583–585, 585f
- road closed to thru traffic sign for, 578t, 585, 585f
- road machinery ahead sign for, 592f, 593
- road work ahead sign for, 586, 590f
- road work next XX miles sign for, 590f, 597
- road work sign for, 590f, 591
- rumble strips for, 618
- rural area placement of, 581f
- safety with, 563
- screens for, 618
- shoulder drop off sign for, 589f, 595
- shoulder work sign for, 590f, 594
- sidewalk closed sign for, 578t, 585f, 586
- sign characteristics for, 576–577
- sign for, 576–601, 578t–580t, 581f, 582f, 584f, 585f, 588f–590f
- sign height for, 581f
- sign lateral location for, 581f
- sign maintenance for, 583
- sign mounting for, 582f
- sign placement for, 577–583, 578t–580t, 581f, 582f
- sign sizes for, 578t–580t
- slow traffic ahead sign for, 590f, 592
- soft shoulder sign for, 589f, 595
- special regulatory signs for, 586
- stay in lane sign for, 578t, 585f, 586
- steel plate ahead sign for, 589f, 595
- supplementary distance plaque for, 589f, 597
- survey crew sign for, 590f, 594
- temporary lane separators for, 610
- temporary markings for, 612–613
- temporary raised islands for, 611
- temporary raised pavement marking for, 613
- temporary traffic barriers for, 609, 616–617
- temporary traffic control signals for, 615–616
- tubular markers for, 605f, 606–607
- turn off 2 way radio sign for, 590f, 595
- two-way traffic sign for, 588f, 593
- types of, 576
- uneven lanes sign for, 589f, 595
- utility work sign for, 590f, 594
- vertical panels for, 605f, 607
- warning lights with, 569, 614–615
- warning signs for, 586–597, 587f–590f, 592f
- weight limit sign for, 578t, 585, 585f
- workers sign for, 592f, 593
- work zone sign for, 580t, 584f, 586
- Temporary traffic control signals, 615–616
 - defined, 21
- Temporary traffic control typical applications, 631–725
 - blasting zone, 632t, 636, 637f
 - closure at side of intersection, 632t, 686, 687f
 - closure in center of intersection, 632t, 684, 685f
 - crosswalk closures, 632t, 690, 691f
 - detour for closed street, 632t, 672, 673f
 - detour for one-travel direction, 632t, 670, 671f
 - detour with overlapping routes, 632t, 650, 651f
 - double lane closure on freeway, 632t, 706, 707f
 - half road closure on far side of intersection, 632t, 680, 681f
 - haul road crossing, 632t, 660, 661f
 - interior lane closure on freeway, 632t, 708, 709f
 - interior lane closure on multi-lane street, 632t, 692, 693f
 - lane closure on minor street, 632t, 668, 669f
 - lane closure on near side of intersection, 632t, 674, 675f
 - lane closure on temporary traffic barrier, 632t, 700, 701f
 - lane closure on two-lane road using flaggers, 632t, 652, 653f
 - lane closure on two-lane road using traffic devices, 632t, 656, 657f
 - lane closure on two-lane road with low volume, 632t, 654, 655f
 - lane closure on uneven directional volume street, 632t, 694, 695f
 - lane shift of freeway, 632t, 704, 705f
 - left lane closure on far side of intersection, 632t, 678, 679f
 - letter codes on diagrams of, 633t
 - median crossover on entrance ramp, 632t, 712, 713f
 - median crossover on exit ramp, 632t, 714, 715f
 - median crossover on freeway, 632t, 710, 711f
 - mobile operation on multi-lane road, 632t, 702, 703f
 - multi-lane closure at intersection, 632t, 682, 683f
 - multi-lane highway, half road closure, 632t, 696, 697f
 - partial closure of exit ramp, 632t, 718, 719f
 - pedestrian detours, 632t, 690, 691f
 - right lane closure on far side of intersection, 632t, 675, 677f
 - road closure with diversion, 632t, 646, 647f
 - road closure with off-site detour, 632t, 648, 649f
 - shoulder closure on freeway, 632t, 642, 643f
 - sidewalk detour or diversion, 632t, 688, 689f
 - stationary lane closure on divided highway, 632t, 698, 699f
 - surveying center line on low volume road, 632t, 664, 665f
 - symbols on diagrams of, 633f
 - taper length determining formulas for, 633t
 - temporary reversible lane using movable barriers, 632t, 722, 723f
 - temporary road closure, 632t, 658, 659f
 - two-land road, mobile operations, 632t, 666, 667f
 - work beyond shoulder, 632t, 634, 635f
 - work in low volume road center, 632t, 662, 663f
 - work in vicinity of entrance ramp, 632t, 720, 721f
 - work in vicinity of exit ramp, 632t, 716, 717f
 - work in vicinity of grade crossing, 632t, 724, 725f
 - work on shoulder, 632t, 638, 639f
 - work on shoulder, minor encroachment, 632t, 644, 645f
 - work on shoulder, short duration, 632t, 640, 641f
- Temporary traffic control zones, 552
 - activities, 619–630
 - applications, 544, 545f, 619
 - buffer spaces with, 553f
 - channelization devices for, 544
 - components of, 552, 553f
 - crossovers in, 628
 - defined, 21
 - interchanges in, 628–629
 - location of work in, 621
 - low-volume roads with, 544–545, 545f
 - markings for, 545
 - modifications to fulfill special needs in, 621–622
 - nighttime hours with, 629–630
 - regulatory signs/plaques for, 584f, 585f
 - signs/plaques for, 545f

- tapers length criteria for, 557t
- two-way traffic on normally divided highway in, 628
- work affecting pedestrian/bicycle facilities in, 622
- work duration with, 619–621
- work in vicinity of grade crossing in, 629
- work on shoulder with minor encroachment in, 624
- work on shoulder with no encroachment in, 623
- work outside of shoulder in, 622–623
- work within median in, 624
- work within traveled way of freeway/expressway in, 627–628
- work within traveled way of intersection in, 626–627
- work within traveled way of multi-lane highway in, 626
- work within traveled way of two-lane in, 624
- work within traveled way of urban street in, 625–626
- Tennis sign, 339f
- Termination area, 555
- Theater sign, 338f
- Theoretical gore
 - defined, 21
- Three-lane road
 - roundabout with three-lane approach on, 409f
 - roundabout with two- and three-lane approach on, 408f
 - roundabout with two-lane exits on, 410f
 - traffic direction transition in center lane of, 354, 355f
 - yellow center line markings, 352f
- Through lane-use arrow, 392f
- Timed exit gate operating mode
 - defined, 21
- Toll booth
 - defined, 21
- Toll island
 - defined, 21
- Toll lane
 - defined, 21
- Toll plaza
 - advance signs, 248–249, 248f
 - canopy signs, 248f, 250f, 252
 - defined, 21
 - ETC account-only lane markings for, 423
 - guide signs, 243–248, 245f–247f
 - lane-use control signals at, 522
 - markings for, 423
 - ORT lane markings for, 423
 - regulatory signs, 238–240, 240f
 - traffic control signal at, 522
 - warning beacons at, 522
- Toll road signs, 237–252
 - advance sign for diverging alignment, 249, 251f
 - ETC account-only auxiliary, 243, 243f
 - ETC account pictographs with, 238, 239f
 - ETC program information, 252
 - pay toll warning, 240–241, 241f
 - purple background color with, 238
 - scope of, 237
 - sizes of, 237, 237f
 - stop ahead pay toll warning, 242
 - toll auxiliary, 242
 - toll plazas, 238–240, 240f
 - toll plazas advance, 248–249, 248f
 - toll plazas canopy, 248f, 250f, 252
 - toll plazas guide, 243–248, 245f–247f
- Toll-ticket system
 - defined, 22
- Tour boat sign, 340f
- Tourist information signs, 299t, 301f, 308–309, 309f
- Tourist-oriented directional signs, 320–324
 - advance, 322f, 323
 - application, 320
 - design of, 320
 - examples of, 321f
 - intersection approach, 322f
 - lettering style with, 323
 - location of, 324
 - purpose of, 320
 - size of, 323
 - state policy with, 324
 - TOURIST ACTIVITIES message on, 320, 321f
- Tracks out of service sign (R8-9), 753f, 760–761
- Traffic
 - defined, 22
- Traffic control devices. *See also* School area traffic control
 - active, 770f
 - authority for, 3–4
 - color code for, 10
 - defined, 22
 - design of, 1–2, 4
 - experimentations for, 4–7, 5f
 - low-volume road, 531–546
 - maintenance of, 2
 - operation of, 2
 - pathway grade crossing, 787–788
 - placement of, 2
 - principles of, 1
 - purpose of, 1
 - responsibility for, 2–3
 - uniformity of, 2
- Traffic control point sign, 343f, 343t, 344
- Traffic control signal
 - aiming of signal face with, 461–463
 - application of signal indications for, 452–455
 - circular green with, 450–451, 453
 - circular red with, 451, 453
 - circular yellow with, 451, 453–454
 - color with, 456
 - defined, 22
 - design of, 456
 - emergency-vehicle access with, 513–515
 - features of, 449–493
 - flashing operation of, 491–492
 - flashing red with, 452
 - flashing yellow with, 452
 - freeway entrance ramps, 517–518
 - green arrow with, 451, 453–454
 - horizontal position of indicators within signal face of, 458f, 459
 - illumination with, 456
 - lane-use control signals, 522, 525–527, 526f
 - lateral offset (clearance) of signal face with, 465, 465f
 - lateral offset of supports/cabinets with, 493
 - lateral positioning of signal face with, 463–464, 463f
 - left-turn indications with, 465–474, 467f–473f
 - longitudinal positioning of signal face with, 463f, 464
 - maintenance responsibility for, 449–450
 - mounting height of signal face with, 465, 465f
 - movable bridges, 519–521
 - not in operation, 449
 - number of signal face on approach with, 459–461, 460f, 461t
 - operation of, 449–450
 - pavement markings used with, 494

- portable, 492–493
 - position of indicators within signal face of, 457, 458f
 - preemption/priority control of, 489–491
 - provisions for pedestrians, 450
 - red arrow with, 451, 453–454
 - right-turn indications with, 474–484, 476f–482f
 - shared left-turn/right-turn indications with, 484–485, 486f–488f
 - shielding of signal face with, 461–463
 - signal induction during flashing operation of, 491–492
 - signs used with, 493–494
 - size of indicators with, 456–457
 - temporary, 492–493
 - toll plaza, 522
 - transition out of flashing operation of, 492
 - upraised hand with, 454
 - U-turn signal face, 456, 456f
 - vehicular signal indications with, 450–452
 - vertical position of indicators within signal face of, 457–459, 458f
 - visibility of signal face with, 461–463, 461t
 - walking person with, 454
 - yellow arrow with, 451, 453–454
 - yellow change and red clearance intervals with, 485, 489
 - Traffic signal actuation sign, 94, 94f
 - Traffic signal signs, 127f, 128
 - Trailblazer assemblies, 210–211
 - Trailblazer service signs, 318–319, 319f
 - Trailer camping sign, 299t, 301f
 - Trailer site sign, 338f
 - Trail shelter sign, 338f
 - Train
 - defined, 22
 - Trains may exceed 80 mph sign (W10-8), 532t
 - Tramway sign, 338f
 - Transition area, 554
 - Transverse markings
 - defined, 22
 - Trash dumpster sign, 338f
 - Trauma center plaque, 300t, 301f
 - Traveled way
 - defined, 22
 - TRAVEL INFO CALL 511 sign, 310f, 311
 - Truck crossing (W8-6)
 - sizes for low-volume roads of, 532t
 - temporary traffic control with, 589f, 594
 - Truck escape ramp
 - delineator for, 427
 - Truck escape ramp sign (W7-4), 115–117, 117f
 - Truck lane sign (D17-1), 178, 178f
 - Truck parking sign, 300t, 301f
 - Truck rollover warning sign (W1-13), 109f, 114
 - Truck route sign (R-14-1), 99, 99f
 - Truck speed limit plaque (R2-2P), 57f, 58
 - Trucks use right lane sign, 72f, 73
 - T-symbol warning sign (W2-4), 536f, 537
 - TTC. *See* Temporary traffic control
 - Tubular markers
 - temporary traffic control with, 605f, 606–607
 - Tunnel sign, 337f
 - Turn and through lane-use arrow, 392f
 - Turn bay
 - defined, 22
 - Turn lane-use arrow, 392f
 - Turn off 2 way radio sign (W22-2), 590f, 595
 - Turn or curve warning sign (W1 series), 791t, 796, 797f
 - 24-hour plaque, 300t, 301f
 - Two-direction large arrow sign (W1-7), 127f, 128
 - sizes for low-volume roads of, 532t
 - Two-lane road
 - roundabout with consecutive double left turn on, 407f
 - roundabout with double left turn on, 405f
 - roundabout with double right turn on, 406f
 - roundabout with one-lane exit for, 403f
 - roundabout with two-lane exit on, 404f
 - TTC - lane closure on, 632t, 652, 653f
 - TTC zone - two-way traffic on normally divided, 628
 - work within traveled way of, 624
 - yellow center line markings on, 350f
 - Two-way left turn arrow
 - lane-use control with, 525, 526f
 - Two-way left turn only sign, 64
 - Two-way street
 - pavement markings for bicycle lane on, 813f
 - Two-way traffic sign (W6-3), 125f, 127
 - temporary traffic control with, 588f, 593
- ## U
- Uneven lanes sign (W8-11), 589f, 595
 - “The Uniform Vehicle Code and Model Traffic Ordinance,” 789
 - UPRAISED HAND signal, 496, 496f
 - pedestrian hybrid beacon with, 512
 - traffic control signal with, 454
 - Urban street
 - defined, 22
 - U.S. bicycle route sign (M1-9), 792t, 800f, 801
 - Utility work sign (W21-7), 533t
 - temporary traffic control with, 590f, 594
 - temporary traffic control zones with, 545f
 - U-turn signal face, 456, 456f
- ## V
- Van accessible plaque, 299t, 301f
 - Vehicle
 - defined, 22
 - Vehicular traffic warning signs (W11 series), 128–130, 129f, 537–539, 538f
 - Vertical panels
 - temporary traffic control with, 605f, 607
 - Vibrotactile pedestrian device
 - defined, 22
 - Viewing area sign, 337f
 - Visibility-limited signal face
 - defined, 22
- ## W
- W1-1 sign. *See* Horizontal Alignment signs
 - W1-4 series. *See* Reverse curve sign
 - W1-6 sign. *See* One-direction large arrow sign

- W1-7 sign. *See* Two-direction large arrow sign
 W1-8 sign. *See* Chevron Alignment signs
 W1-13 sign. *See* Truck rollover warning sign
 W1 series. *See* Turn or curve warning sign
 W2-1. *See* Crossroad warning sign
 W2-2. *See* Side road warning sign
 W2-4. *See* T-symbol warning sign
 W2-5. *See* Y-symbol warning sign
 W2 series. *See* Intersection warning sign
 W3-1 sign. *See* Advance traffic control sign; Stop ahead sign
 W3-2 sign. *See* Yield ahead sign
 W3-4 sign. *See* Be prepared to stop sign
 W3-6 sign. *See* DRAW BRIDGE sign
 W4-2 sign. *See* Lane ends sign
 W4-3 sign. *See* Added lane sign
 W5-1 sign. *See* Road narrows sign
 W5-2 sign. *See* Narrow bridge sign
 W5-3 sign. *See* One lane bridge sign
 W5-4a sign. *See* Path narrows sign
 W5-4 sign. *See* Ramp narrows sign
 W6-1 sign. *See* Divided highway sign
 W6-2 sign. *See* Divided highway ends sign
 W6-3 sign. *See* Two-way traffic sign
 W7-1 sign. *See* Hill sign
 W7-3aP plaque. *See* Supplementary distance plaque
 W7-4 sign. *See* Truck escape ramp sign
 W7-5 sign. *See* Hill sign
 W7-6 sign. *See* Hill blocks view sign
 W8-1 sign. *See* Bump sign
 W8-2 sign. *See* Dip sign
 W8-3 sign. *See* Pavement ends sign
 W8-4 sign. *See* Soft shoulder sign
 W8-6 sign. *See* Truck crossing
 W8-7 sign. *See* Loose gravel
 W8-8 sign. *See* Rough road sign
 W8-9 sign. *See* Low shoulder sign
 W8-10 sign. *See* Bicycle surface condition warning sign
 W8-11 sign. *See* Uneven lanes sign
 W8-12 sign. *See* No center line sign
 W8-15P plaque. *See* Motorcycle plaque
 W8-17P plaque. *See* Shoulder drop off plaque
 W8-18 sign. *See* Road may flood sign
 W8-24 sign. *See* Steel plate ahead sign
 W9-3 sign. *See* Center lane closed sign
 W9-6 sign. *See* Pay toll warning signs
 W10-1aP plaque. *See* Exempt plaque
 W10-1 sign. *See* Grade crossing advance warning signs
 W10-5 sign. *See* Low ground clearance grade crossing sign
 W10-7 sign. *See* Light rail transit approaching-activated blank out warning sign
 W10-8 sign. *See* Trains may exceed 80 mph sign
 W10-9 sign. *See* No train horn sign
 W10-11 sign. *See* Storage space sign
 W10-12 sign. *See* Skewed crossing sign
 W10-13P plaque. *See* No gates or lights plaque
 W10 series. *See* Grade crossing advance warning signs
 W11-1 sign. *See* Bicycle warning sign
 W11-15 sign. *See* Bicycle/pedestrian sign
 W11 series. *See* Vehicular traffic warning signs
 W12-1 sign. *See* Double arrow sign
 W12-2 sign. *See* Low clearance sign
 W14-1 sign. *See* Dead end sign
 W14-2 sign. *See* No outlet sign
 W14-3 sign. *See* No passing zone sign
 W16-1P plaque. *See* Share the road plaque
 W16-9P plaque. *See* Ahead plaque
 W17-1 sign. *See* Speed hump sign
 W20-2 sign. *See* Detour signs
 W20-5 sign. *See* Right (left) lane closed sign
 W20-7 sign. *See* Flagger sign
 W21-1 sign. *See* Workers sign
 W21-2 sign. *See* Fresh oil sign
 W21-3 sign. *See* Road machinery ahead sign
 W21-6 sign. *See* Survey crew sign
 W21-7 sign. *See* Utility work sign
 W22-1 sign. *See* Blasting zone ahead sign
 W22-2 sign. *See* Turn off 2 way radio sign
 W22-3 sign. *See* End blasting zone sign
 W23-1 sign. *See* Slow traffic ahead sign
 W23-2 sign. *See* New traffic pattern ahead sign
 W24-1 series. *See* Double reverse curve sign
 Wading sign, 340f
 Walk-in camp sign, 338f
 WALKING PERSON signal, 496, 496f
 pedestrian hybrid beacon with, 512
 traffic control signal with, 454
 Walk interval
 defined, 22
 Walk on boardwalk sign, 337f
 Walk on left facing traffic sign (R9-1), 92, 93f
 Warning beacon, 523–524
 defined, 22
 toll plaza with, 522
 Warning lights
 channelizing devices with, 604
 defined, 22
 temporary traffic control with, 569, 614–615
 Warning signs, 29, 103–136
 added lane, 125f, 126
 advance, 586–591, 587f–590f
 advance ramp control, 121f, 124
 advance traffic control, 121f, 123–124
 advisory exit/ramp speed, 109f, 114–115, 116f
 Advisory Speed, 109f, 110t, 111f, 112
 advisory speed, 589f, 596
 application of, 103
 be prepared to stop, 532t, 545f
 bicycle traffic control with, 791t, 796–798, 797f
 blasting zone ahead, 590f, 595
 bump, 120, 121f
 categories of, 104t
 center lane closed, 589f, 592
 Chevron Alignment, 109f, 110t, 111f, 112–113, 532t
 circular intersections, 536f, 537
 combination Horizontal Alignment/advisory exit/ramp speed, 109f, 114–115, 116f
 combination Horizontal Alignment/advisory speed, 113
 combination Horizontal Alignment/intersection, 113
 crossroad, 536f, 537
 dead end, 118f, 119–120, 532t, 538f, 539
 defined, 22
 design of, 103
 detour, 590f, 591
 dip, 120, 121f
 divided highway, 118f, 119
 divided highway ends, 118f, 119

- double arrow, 118f, 119
- double reverse curve, 590f, 596
- draw bridge, 125
- end blasting zone, 589f, 595
- flagger, 592f, 593
- freeway/expressway ends, 118f, 119
- fresh oil, 592f, 593
- function of, 103
- grade crossing advance, 532t, 542, 542f
- grade crossing advance warning, 532t
- hill, 115, 117f, 532t, 537, 538f
- hill blocks view, 117, 117f
- horizontal alignment, 109–111, 109f, 110t, 111f, 532t, 536, 536f
- intersection, 536f, 537, 791t, 796, 797f
- intersection warning, 127–128, 127f
- lane ends, 125f, 126, 588f, 592
- loose gravel, 532t, 545f
- low clearance, 118f, 120
- low shoulder, 589f, 595
- low-volume road, 536–539, 536f, 538f
- merge, 125–126, 125f
- motorcycle, 589f, 597
- motorcyclists', 121f, 123
- motorized traffic, 589f, 594
- narrow bridge, 118, 118f, 532t, 537, 538f
- new traffic pattern ahead, 131, 592f, 593
- no center line, 121f, 123, 589f, 595
- non-vehicular traffic warning, 130–131, 130f, 537–539, 538f
- no outlet, 118f, 119–120, 538f, 539
- no passing zone, 125f, 127
- no traffic, 533t, 538f, 539
- object marker, 134–136, 135f
- one-direction large arrow, 109f, 111f, 113–114, 532t
- one lane, 590f, 591
- one lane bridge, 118, 118f, 532t, 537, 538f
- one lane road, 533t, 545f
- pavement ends, 121f, 122, 532t, 537, 538f
- placement of, 108–109, 108t
- playground, 130f, 131
- on ramp, 589f, 592
- ramp narrows, 588f, 592
- recreational and cultural interest area, 330
- reduced speed limit ahead, 124, 124f
- retroreflectivity of, 29
- reverse curve, 588f, 596
- right (left) lane closed, 590f, 591
- right (left) lane exit only ahead, 125f, 126–127
- road machinery ahead, 592f, 593
- road may flood, 532t, 545f
- road narrows, 117, 118f
- road work, 533t, 545f, 590f, 591
- road work ahead, 586, 590f
- rough road, 532t, 545f
- shoulder, 121f, 122
- shoulder drop off, 589f, 595
- shoulder work, 590f, 594
- side road, 536f, 537
- size of, 103–108, 105t–107t
- skewed crossing, 532t
- slow traffic ahead, 590f, 592
- soft shoulder, 589f, 595
- speed hump, 120, 121f
- steel plate ahead, 589f, 595
- stop ahead, 532t, 537, 538f
- supplemental warning, 131–134, 132f
- supplementary distance, 589f, 597
- surface condition, 121f, 122
- survey crew, 590f, 594
- temporary traffic control with, 586–597, 587f–590f, 592f
- traffic signal, 127f, 128
- trains may exceed 80 mph, 532t
- truck crossing, 532t
- truck escape ramp, 115–117, 117f
- truck rollover, 109f, 114
- T-symbol, 536f, 537
- turn off 2 way radio, 590f, 595
- turn or curve, 791t, 796, 797f
- two-direction large arrow, 127f, 128, 532t
- two-way traffic, 125f, 127, 588f, 593
- uneven lanes, 589f, 595
- utility work, 590f, 594
- vehicular traffic warning, 128–130, 129f, 537–539, 538f
- weather condition, 121f, 123
- workers, 592f, 593
- yield ahead, 532t, 537, 538f
- Y-symbol, 536f, 537
- Warrant.** *See also* Highway traffic signal needs study
 - crash experience signal, 445–446
 - defined, 22
 - peak hour signal, 439, 441f
 - pedestrian volume signal, 442, 443f, 444f
 - school crossing signal, 442, 445
- Water recreation**
 - recreational and cultural interest area signs for, 330, 331t, 340f
- Waterskiing sign, 340f**
- Wayside equipment**
 - defined, 22
- Wayside horn systems**
 - defined, 22
 - rail grade crossing traffic control with, 775
- Weather condition signs, 121f, 123**
- Weigh station signs (R13 series), 99, 99f, 172, 173f, 236**
- Weight limit sign (R12-1), 98–99, 98f**
 - sizes for low-volume roads of, 532t, 534f
 - temporary traffic control with, 578t, 585, 585f
- Welcome area signs, 308–309, 309f**
- Whale viewing sign, 340f**
- White**
 - meaning for traffic control devices of, 10
 - pavement color, 428
- White line pavement markings, 356–370, 357f–370f, 372f–378**
 - broken, 356
 - chevron crosshatch, 371
 - dotted line, 358f–361f, 362, 372f–378
 - entrance ramps with, 356, 360f–361f
 - exit ramps with, 358f–359f
 - longitudinal, 370–371
 - roundabout, 413
 - same direction travel designated by, 356
 - solid line where crossing lane discouraged, 362, 370f
 - two-way left-turn land with, 357f
- Wildlife viewing sign, 339f**
- Wind surfing sign, 340f**
- Winter recreation**
 - recreational and cultural interest area signs for, 330, 331t, 341f

Winter recreational area sign, 341f
 Wireless internet sign, 300t, 301f
 Women's restroom sign, 338f
 Wood gathering sign, 337f
 Word messages
 MUTCD defined use of, 10–23
 pavement markings with, 387–393, 387f, 392f
 preferential lane markings with, 415–416
 roundabout markings with, 413–414
 sign, 35–36
 Work duration
 five categories of, 619
 temporary traffic control with, 619–621
 Worker
 defined, 23
 temporary traffic control safety provisions for, 561–565
 Workers sign (W21-1), 533t
 temporary traffic control with, 592f, 593
 Work zone plaque (G20-5aP), 580t, 584f, 586
 Work zones
 blasting zone, 632t, 636, 637f
 closure at side of intersection, 632t, 686, 687f
 closure in center of intersection, 632t, 684, 685f
 crosswalk closures, 632t, 690, 691f
 detour for closed street, 632t, 672, 673f
 detour for one-travel direction, 632t, 670, 671f
 detour with overlapping routes, 632t, 650, 651f
 double lane closure on freeway, 632t, 706, 707f
 half road closure on far side of intersection, 632t, 680, 681f
 haul road crossing, 632t, 660, 661f
 interior lane closure on freeway, 632t, 708, 709f
 interior lane closure on multi-lane street, 632t, 692, 693f
 lane closure on minor street, 632t, 668, 669f
 lane closure on near side of intersection, 632t, 674, 675f
 lane closure on temporary traffic barrier, 632t, 700, 701f
 lane closure on two-lane road using flaggers, 632t, 652, 653f
 lane closure on two-lane road using traffic devices, 632t, 656, 657f
 lane closure on two-lane road with low volume, 632t, 654, 655f
 lane closure on uneven directional volume street, 632t, 694, 695f
 lane shift of freeway, 632t, 704, 705f
 left lane closure on far side of intersection, 632t, 678, 679f
 median crossover on entrance ramp, 632t, 712, 713f
 median crossover on exit ramp, 632t, 714, 715f
 median crossover on freeway, 632t, 710, 711f
 mobile operation on multi-lane road, 632t, 702, 703f
 multi-lane closure at intersection, 632t, 682, 683f
 multi-lane highway, half road closure, 632t, 696, 697f
 partial closure of exit ramp, 632t, 718, 719f
 pedestrian detours, 632t, 690, 691f
 right lane closure on far side of intersection, 632t, 675, 677f
 road closure with diversion, 632t, 646, 647f
 road closure with off-site detour, 632t, 648, 649f
 shoulder closure on freeway, 632t, 642, 643f
 sidewalk detour or diversion, 632t, 688, 689f
 stationary lane closure on divided highway, 632t, 698, 699f
 surveying center line on low volume road, 632t, 664, 665f
 temporary reversible lane using movable barriers, 632t, 722, 723f
 temporary road closure, 632t, 658, 659f

two-lane road, mobile operations, 632t, 666, 667f
 work beyond shoulder, 632t, 634, 635f
 work in low volume road center, 632t, 662, 663f
 work in vicinity of entrance ramp, 632t, 720, 721f
 work in vicinity of exit ramp, 632t, 716, 717f
 work in vicinity of grade crossing, 632t, 724, 725f
 work on shoulder, 632t, 638, 639f
 work on shoulder, minor encroachment, 632t, 644, 645f
 work on shoulder, short duration, 632t, 640, 641f
 Wrong-way arrow, 392f
 defined, 23
 Wrong way sign, 75f, 76, 76f
 Wrong-way traffic control, 235–236

Y

Yellow. *See also* Circular yellow signal
 meaning for traffic control devices of, 10
 pavement color, 428
 Yellow arrow
 application of, 453–454
 meaning of, 451
 vertical position within signal face of, 458, 458f
 Yellow center line markings, 349–352, 350f–352f
 four-lane, two-way example of, 351f
 three-lane, two-way example of, 352f
 two-lane, two-way example of, 350f
 Yellow change interval
 defined, 23
 red clearance interval with, 485, 489
 Yellow-green
 meaning for traffic control devices of, 10
 Yellow longitudinal pavement markings, 354
 YELLOW X signal
 lane-use control with, 525
 Yield ahead pavement markings, 390–391, 391f
 Yield ahead sign (W3-2)
 sizes for low-volume roads of, 532t, 537, 538f
 Yield here to pedestrians pavement markings, 381, 383f
 Yield here to pedestrians sign (R1-5 series), 54–55, 55f
 school, 741, 741f
 Yield lines
 defined, 23
 highway rail grade crossing with, 766–767
 light rail grade crossing traffic control with, 766–767
 pavement markings, 381–382, 382f, 383f
 railroad grade crossing traffic control with, 766–767
 roundabout markings, 413
 Yield signs (R1-2), 46t, 51f, 53–54, 542f, 543
 applications, 53
 bicycle traffic control with, 791t, 792–794, 793f
 crossbuck assemblies with, 754–758, 754f–756f
 placement, 53–54
 size of, 46t
 sizes for low-volume roads of, 532t, 534f
 temporary traffic control with, 560
 Y-symbol warning sign (W2-5), 536f, 537