



November 16, 2007

Michael D. Weeks, P.E., P.S.  
TranSystems Corporation  
5747 Perimeter Drive, Suite 240  
Dublin, OH 43017

**Re: Pavement Design Information**  
**Phase 3 - Mainline and Side Road CBR Values**  
SCI-823-0.00 Portsmouth Bypass  
Phase 3 – Stage I  
DLZ Job No.: 0121-3070.03  
PID No. 77366

Dear Mr. Weeks:

This document presents the findings of subsurface explorations performed for proposed side roads, ramps and the mainline alignment for Phase 3 of the SCI-823 Portsmouth Bypass project. The Phase 3 area is defined as being from station 54+11.25 to station 352+00.

The side roads in the Phase 3 area have been independently evaluated for subgrade improvements and pavement design information. Please refer to these documents for more information.

Appendix A: Pavement Design Information  
-US 52

Appendix B: Pavement Design Information  
SR 140

Appendix C: Pavement Design Information  
Pershing Avenue


Appendix D: Pavement Design Information  
Phase 3 Mainline

Michael D. Weeks, P.E., P.S.  
November 16, 2007  
Page 2

We appreciate having the opportunity to be of service to you on this project. Please do not hesitate to call if you have any questions concerning our reports.

Respectfully submitted,

**DLZ OHIO, INC.**




Steven J. Riedy  
Geotechnical Engineer



Eric W. Tse, P.E.  
Senior Geotechnical Engineer



Andrew M. Jalbrzikowski  
Engineering Geologist



Pete Nix, P.E.  
Geotechnical Division Manager



cc: File





ENGINEERS • ARCHITECTS • SCIENTISTS  
PLANNERS • SURVEYORS

November 16, 2007

Michael D. Weeks, P.E., P.S.  
TranSystems Corporation  
5747 Perimeter Drive, Suite 240  
Dublin, OH 43017

Re: **Pavement Design Information**  
**US 52 Interchange**  
SCI-823-0.00 Portsmouth Bypass  
DLZ Job No.: 0121-3070.03  
PID #77366  
Document #0091

Dear Mr. Weeks:

This letter presents the findings of a subsurface investigation performed for the US 52 pavement project. This pavement project is part of the reconstruction project of existing US 52 and the construction of the proposed US 52 Ramp A and Ramp B Bridges over Ohio River Road and US 52 of the Portsmouth bypass project. The findings included in this letter pertain to the reconstruction portion of the existing northbound US 52, approximately between Station 5+00 and Station 26+50, and the reconstruction portion of the existing southbound US 52, approximately between Station 5+00 and Station 18+23.0. This letter also presents the findings for the proposed Ramp A, approximately between Station 26+50 (approximately Station 25+00 referenced to Ramp A baseline) and Station 35+00 (approximately Station 34+00 referenced to Ramp A baseline), and for the proposed Ramp B, approximately between Station 18+23.00 (approximately Station 16+50 referenced to Ramp B baseline) and Station 31+50 (approximately Station 29+50 referenced to Ramp B baseline). Note that the stationing used in this report is referenced to the centerline of US 52 unless noted otherwise. Subsurface explorations were performed for the other features of the project but the results are presented in separate reports.

According to the information provided, embankment fills or sidehill fills, approximately between 1 and 10 feet thick, will be required for the construction of the proposed Ramp A up to Station 34+00 (referenced to Ramp A baseline) while the fills required for the construction of the proposed Ramp B up to Station 29+50 (referenced to Ramp B baseline) will be approximately between 2 and 20 feet. The finished grades for the reconstruction portion of existing US 52 are not known at this time and were assumed to approximate the existing grades.

The recommendations presented in this report have been made on the basis of the foregoing information. If the proposed alignment or concept is changed or differs from that assumed, DLZ Ohio, Inc. (DLZ) must be informed of the changes so that recommendations and conclusions presented in this letter may be revised as necessary.

Michael D. Weeks, P.E., P.S.

November 16, 2007

Page 2

The results of the subgrade evaluations are based in part upon the findings of seventeen subgrade borings. Borings B-1510 through B-1516, and B-1521 were drilled between January 4 and 16, 2006. Boring B-1519 was drilled between December 28 and 30, 2005. Borings B-1533 and B-1534 were drilled on August 16, 2006. Borings B-1535 through B-1540 were drilled on October 11, 2006. These borings were drilled to depths between 10.0 and 80.4 feet. In addition to subgrade information, the deeper borings also provided subsurface data for previous site development plans and other features of the Portsmouth bypass project. For the purposes of subgrade evaluation, continuous sampling was performed in each of the borings, from approximately 1 foot to approximately 6.0 to 7.0 feet below the existing ground surface. Additional (non-subgrade) borings drilled within the proposed pavement area were also considered in developing the subgrade recommendations. These additional borings were B-1501 through B-1509, B-1517, B-1518, B-1520, and B-1522 through B-1532. The subgrade borings and the additional borings were drilled using a truck mounted rotary-type drill rig. Borings were planned and staked in the field by representatives of DLZ. The surveyed locations and ground surface elevations of the borings were determined by representatives from Lockwood, Lanier, Mathias & Noland, Inc. (2LMN). A boring plan showing the locations of borings and the logs of borings are attached.

At the ground surface, the subgrade borings encountered between 4 and 12 inches of asphalt concrete underlain by either 7 to 9 inches of Portland cement concrete or 1 to 8 inches of aggregate base except in Boring B-1514, where only 12 inches of asphalt concrete were encountered. Below the pavement materials, the subgrade borings encountered a variety of cohesive and granular soils in the upper 10 feet of the borings. Generally, the cohesive soils consisted of stiff to hard sandy silt (A-4a), silt (A-4b), silt and clay (A-6a), and silty clay (A-6b) while the granular soils consisted of loose to very dense gravel with sand (A-1-b), fine sand (A-3), coarse and fine sand (A-3a), and gravel with sand and silt (A-2-4). Note that the materials encountered in the upper 10 feet of Borings B-1533 and B-1534 appeared to be fills and possible fills.

Seepage was encountered in subgrade borings B-1510 through B-1519, B-1520, B-1521, B-1533 and B-1534. Seepage encountered in these borings was generally at depths greater than 10 feet below the ground surface except in Borings B-1510, B-1516, B-1533 and B-1534, where seepage was first encountered between depths of 1.0 and 6.3 feet. Prior to rock coring or adding water to wash out heaving sand, groundwater levels were observed at depths between 8.9 and 49.8 feet. Water levels at the completion of drilling, which included drilling water, were at depths between 15.0 and 68.0 feet.

Michael D. Weeks, P.E., P.S.

November 16, 2007

Page 3

Seepage was not encountered in subgrade borings B-1535 through B-1540. Groundwater was not observed in these borings during the field investigation.

Based upon the anticipated finished grades and the findings of the 17 subgrade borings, Table 1 presents the amount of cut or fill anticipated at each boring location and the uppermost layer of subgrade material encountered at the boring locations.

**Table 1: Summary of Uppermost layer of Subgrade Material at Boring Locations**

Boring No.	Station*	Existing Ground Surface Elev. (ft)	Proposed Grade (ft)	Fill / (Cut) (ft)	Uppermost Layer of Subgrade Material
B-1519	5+67.1	541.4	541.4	0	Sandy Silt (A-4a)
B-1535	9+66.6	542.5	542.5	0	Coarse and Fine Sand (A-3a)
B-1533	9+86.2	542.6	542.6	0	Silt and Clay (A-6a)
B-1516	10+14.5	542.5	542.5	0	Coarse and Fine Sand (A-3a)
B-1515	11+67.8	542.6	542.6	0	Coarse and Fine Sand (A-3a)
B-1514	13+03.6	543.1	543.1	0	Coarse and Fine Sand (A-3a)
B-1536	13+75.3	543.4	543.4	0	Sandy Silt (A-4a)
B-1534	13+90.5	543.4	543.4	0	Gravel with Sand (A-1b)
B-1513	14+62.9	543.2	543.2	0	Gravel with Sand (A-1b)
B-1512	16+15.9	543.2	543.2	0	Coarse and Fine Sand (A-3a)
B-1537	17+59.1	543.5	543.5	0	Silty Clay (A-6b)
B-1511	17+75.3	543.4	543.4	0	Coarse and Fine Sand (A-3a)
B-1510	19+13.0	543.7	543.7	0	Coarse and Fine Sand (A-3a)
B-1538	21+65.7	543.3	543.3	0	Gravel with Sand (A-1b)
B-1521	24+76.9	536.8	540.8	4.0	Silt and Clay (A-6a)
B-1539	25+57.1	544.2	544.2	0.0	Gravel with Sand (A-1b)
B-1540	29+54.5	546.0	548.7	2.7	Silt (A-4b)

Michael D. Weeks, P.E., P.S.

November 16, 2007

Page 4

\* Stations are referenced to the centerline of US 52 except Station 24+76.9 (Boring B-1521), which is referenced to the baseline of the proposed US 52 Ramp B.

### Pavement Design Information

Table 2 below lists the subgrade soils encountered by the borings and the group indices, CBR values, and number of samples tested for each soil type.

**Table 2: Subgrade Soils**

ODOT Classification	Group Index	CBR	No. Samples Tested
Gravel with Sand (A-1b)	0	13	5
Fine Sand (A-3)	0	13	1
Coarse and Fine Sand (A-3a)	0	13	3
Gravel w/ Sand and Silt (A-2-4)	0	13	1
Sandy Silt (A-4a)	3	9	5
Silt (A-4b)	8	7	2
Silt and Clay (A-6a)	9	6	5
Silty Clay (A-6b)	10	6	3

Based upon averaging the results of the laboratory testing, a CBR value of 9 is recommended for pavement design.

### Subgrade Condition and Preparation

The existing subgrade soils at the boring locations were evaluated for suitability according to the ODOT Geotechnical Bulletin GB-1 "Plan Subgrades." The optimum moisture content (MC) for each soil type was estimated using the following criteria:

- Optimum MC = plastic limit minus 3 (A-7-6 soils)
- = plastic limit minus 5 (A-4 and A-6 soils)
- = 6 to 10 (granular soils)
- = 11 (non-plastic silts)

Michael D. Weeks, P.E., P.S.  
November 16, 2007  
Page 5

It should be noted that only samples within 6.0 to 7.0 feet of the estimated finished grade were evaluated. The GB-1 Soil Investigation Summary Sheet is attached.

According to the GB-1, any soil with moisture content exceeding the optimum moisture content of the soil by three or more percentage points, or has low N-values (generally  $N < 10$ ), is considered problematic soil and will likely require some form of subgrade treatment. The stabilization options available include undercutting, cement stabilization, and lime stabilization. However, the cement or lime stabilization may not be effective in very weak soils (N-values less than 5 blows per foot).

Results of this surface investigation indicate that approximately 36 percent of the tested samples, located within 6 to 7 feet of the estimated finished grade, had moisture contents exceeding their corresponding optimum moisture contents by more than 3 percent and that approximately 16 percent of the samples located within 6 to 7 feet of the estimated finished grade had low N-values. The natural moisture contents of the tested soil samples ranged from 3% to 23%, with an average of 12.9%, and the N-values varied from 5 to 71, with an average of 23.2. The low N-value of each boring varied from 5 to 30, with an average of 14.8.

To determine the appropriate treatment option, the average standard penetration value (N-value) and the plasticity index (PI) of the subgrade soils were considered. The average N-value, PI, moisture content, and CBR are summarized in Table 3.

**Table 3**

<b>Percent of Tested Samples Over Optimum MC + 3 Percent</b>	<b>Average <math>N_L</math>*</b>	<b>Average PI</b>	<b>Average MC</b>	<b>CBR Average</b>
36	14.8	10.9	12.9	9

\* -  $N_L$  indicates lowest standard penetration value (N) in subgrade soil.

According to the GB-1 Soil Investigation Summary Sheet, cement stabilization of 12 to 14 inches of the subgrade or undercutting of 1 to 2 feet is recommended at Borings B-1537 (Station 17+59.1), B-1510 (Station 19+13.0), B-1538 (Station 21+65.7) and B-1539 (Station 25+57.1). However, cement stabilization of 14 inches of the subgrade or undercutting of 5 feet is recommended at Boring B-1540 (Station 29+54.5) and undercutting of 5 feet is recommended at Boring B-1520 (Station 27+68.3 referenced to Ramp B baseline). Generally, chemical stabilization is more economical when the area to be stabilized is greater than a mile. Given the fact that less than one-half mile of the subgrade would require treatment, undercutting of the



Michael D. Weeks, P.E., P.S.

November 16, 2007

Page 6

subgrade appears to be a more cost-effective soil stabilization method. The undercut area should be replaced with compacted Type B or Type C granular material (ODOT Item 703.16.C) and should extend 18 inches beyond the edge of the pavement, paved shoulders, or paved medians. Before placing the compacted granular material, proof-roll the entire undercut area. If any areas rut or deflect, overexcavate the soft or loose soils and replace with compacted Type B or Type C granular material. Please note that the ODOT Geotechnical Bulletin GB-1 requires that a geotextile fabric Type D (ODOT Item 712.09) be placed in the bottom of the undercut for separation purposes.

Based on the GB-1 Soil Investigation Summary Sheet, the subsurface conditions at the subgrade borings and the “non-subgrade” borings along the proposed Ramp A alignment, and the anticipated amounts of fill for the proposed Ramp A, the subgrade soils along the proposed Ramp A should be undercut in areas and to depths indicated in Table 4 below.

**Table 4: Undercut and Replace Option for Existing Northbound US 52 and Proposed Ramp A**

<b>Begin Station*</b>	<b>End Station*</b>	<b>Depth of Undercut of Existing Subgrade Soil, ft.</b>
17+00	17+70	2.0
18+60	19+60	2.0
21+15	22+00	1.0
25+10	26+00	1.0
29+25 (27+50)	29+90 (28+15)	2.5**

\*Stations are referenced to the centerline of US 52. Stations in parentheses are approximate stations referenced to the baseline of US 52 Ramp A.

\*\*The depth of undercut was recommended based on the anticipation that approximately 2.7 feet of sidehill fills will be required in the area.

Given the anticipated amounts of fill for the proposed Ramp B, and the subsurface conditions at the subgrade borings and the “non-subgrade” borings along the proposed Ramp B alignment, it appears that subgrade treatment would not be necessary for the reconstruction of existing southbound US 52 and the construction of the proposed Ramp B. However, since undercutting of unsuitable subgrade soils is required in a portion of the existing northbound US 52 and the proposed Ramp A, poor subgrade soil conditions may present in the existing southbound US 52 and the proposed Ramp B other than where the borings were drilled. It is recommended that the subgrade soil be proof-rolled with a heavy piece of construction equipment to determine if any soft yielding areas are present. If any yielding areas are revealed, they should be undercut to

Michael D. Weeks, P.E., P.S.  
November 16, 2007  
Page 7

firm non-yielding soils, and replaced with compacted Type B or Type C granular material (ODOT Item 703.16.C). The undercut should extend 18 inches beyond the edge of the pavement, paved shoulders, or paved medians.


Seepage was first encountered in subgrade borings B-1510, B-1516, B-1533 and B-1534 between depths of 1.0 and 6.3 feet. Seepage was also observed at shallow depths, between 1 and 4 feet, in "non-subgrade" borings B-1518, B-1517, B-1530. These borings and the subgrade borings are located in the existing US 52 alignment, approximately between Station 6+00 and Station 15+00.

Seepage is anticipated for the pavement excavations, particularly between Station 6+00 and 15+00. The Contractor should be prepared to perform dewatering, likely with sumping and pumping. In addition, the Contractor should be prepared to deal with unexpected seepage and precipitation entering any excavations.


We appreciate having the opportunity to be of service to you on this project. Please do not hesitate to call if you have any questions concerning our findings.

Respectfully submitted,

**DLZ OHIO, INC.**



Eric W. Tse, P.E.  
Senior Geotechnical Engineer



Bryan Wilson, P.E.  
Senior Geotechnical Engineer



Encl: As noted

cc: file





III.C. Subgrade Checklist

C-R-S: SCI-823-0.00 (US 52)	PID: 77366	Reviewer: E. Tse/B. Wilson	Date: 11-15-07
-----------------------------	------------	----------------------------	----------------

If you do not have any subgrade work on the project, you do not have to fill out this checklist.

<u>Y</u> N X 1	Has the subsurface investigation adequately characterized the soil or rock according to <u>Geotechnical Bulletin 1: Plan Subgrades (GB1)</u> ?	
<u>Y</u> N X 2	If soils classified as A-2-5, A-4b, A-5, or A-7-5 are present at the proposed subgrade (soil profile), do the plans specify that these materials need to be removed and replaced?	
<u>Y</u> N X	a If these materials are to be removed and replaced, have the station limits, depth, and lateral limits for the planned removal been provided?	
Y N <u>X</u> 3	If there is any rock, shale, or coal present at the proposed subgrade (CMS 204.05), do the plans specify the removal of the material?	No rock in the proposed subgrade.
Y N <u>X</u>	a If removal of any rock, shale, or coal is required, have the station limits, depth, and lateral limits for the planned removal of the material at proposed subgrade been provided?	
<u>Y</u> N X 4	In accordance with GB1, do the SPT values and existing moisture contents for the proposed subgrade soils indicate the need for subgrade stabilization?	
<u>Y</u> N X	a If removal and replacement is applicable, has the detail of subgrade removal been shown on the plans, including depth of removal, station limits, lateral extent, replacement material, and plan notes (Item 204 – Subgrade Compaction and Proof Rolling)?	Refer to roadway cross-sections.
Y N <u>X</u>	b If chemical stabilization is applicable, has the detail of this treatment been shown on the plans, including depth, percentage of chemical, station limits, lateral extent, and plan notes?	
	Indicate type of subgrade treatment specified:	GB-1 recommends cement treatment or undercutting. Undercutting was recommended for subgrade treatment.
	<input checked="" type="checkbox"/> cement treatment <input type="checkbox"/> lime treatment	
	<input type="checkbox"/> other                                      List Other items:	
<u>Y</u> N X 5	If drainage or groundwater is an issue with the proposed subgrade, has an appropriate drainage system (e.g., pipe, underdrains) been provided?	Refer to roadway cross-sections.
Y N <u>X</u> 6	Has an appropriate quantity of Proof Rolling been included in the plans (CMS 204.06)?	Refer to roadway cross-sections.
<u>Y</u> N X 7	Has a design CBR value been provided?	

### III.C. Subgrade Checklist

---

Notes:

Stage 1:

## **GENERAL INFORMATION DRILLING PROCEDURES AND LOGS OF BORINGS**

Drilling and sampling were conducted in accordance with procedures generally recognized and accepted as standardized methods of investigation of subsurface conditions concerning geotechnical engineering considerations. Borings were drilled with either a truck-mounted or ATV-mounted drill rig.

Drive split-barrel sampling was performed in 1.5 to 2 foot increments at intervals not exceeding 5 feet. In the event the sampler encountered resistance to penetration of 6 inches or less after 50 blows of the drop hammer, the sampling increment was discontinued. Standard penetration data were recorded and one or more representative samples were preserved from each sampling increment.

In borings where rock was cored, NXM or NQ size diamond coring tools were used.

In the laboratory all samples were visually classified by a geotechnical engineer. Moisture contents of representative fine-grained soil samples were determined. A limited number of samples, considered representative of foundation materials present, were selected for performance of grain-size analyses and plasticity characteristics tests. The results of these tests are shown on the boring logs.

The boring logs included in the Appendix have been prepared on the basis of the field record of drilling and sampling, and the results of the laboratory examination and testing of samples. Stratification lines on the boring logs indicating changes in soil stratigraphy represent depths of changes approximated by the driller, by sampling effort and recovery, and by laboratory test results. Actual depths to changes may differ somewhat from the estimated depths, or transitions may occur gradually and not be sharply defined. The boring logs presented in this report therefore contain both factual and interpretative information and are not an exact copy of the field log.

Although it is considered that the borings have disclosed information generally representative of site conditions, it should be expected that between borings conditions may occur which are not precisely represented by any one of the borings. Soil deposition processes and natural geologic forces are such that soil and rock types and conditions may change in short vertical intervals and horizontal distances.

Soil/rock samples will be stored at our laboratory for a period of six months. After this period of time, they will be discarded, unless notified to the contrary by the client.

## LEGEND – BORING LOG TERMINOLOGY

Explanation of each column, progressing from left to right

1. Depth (in feet) – refers to distance below the ground surface.
2. Elevation (in feet) – is referenced to mean sea level, unless otherwise noted.
3. Standard Penetration (N) – the number of blows required to drive a 2-inch O.D., 1-3/8 inch I.D., split-barrel sampler, using a 140-pound hammer with a 30-inch free fall. The blows are recorded in 6-inch drive increments. Standard penetration resistance is determined from the total number of blows required for one foot of penetration by summing the second and third 6-inch increments of an 18-inch drive.  
  
50/n – indicates number of blows (50) to drive a split-barrel sampler a certain number of inches (n) other than the normal 6-inch increment.
4. The length of the sampler drive is indicated graphically by horizontal lines across the “Standard Penetration” and “Recovery” columns.
5. Sample recovery from each drive is indicated numerically in the column headed “Recovery”.
6. The drive sample location is designated by the heavy vertical bar in the “Sample No., Drive” column.
7. The length of hydraulically pressed “Undisturbed” samples is indicated graphically by horizontal lines across the “Press” column.
8. Sample numbers are designated consecutively, increasing in depth.
9. Soil Description

- a. The following terms are used to describe the relative compactness and consistency of soils:

### Granular Soils – Compactness

<u>Term</u>	<u>Blows/Foot Standard Penetration</u>
Very Loose	0 – 4
Loose	4 – 10
Medium Dense	10 – 30
Dense	30 – 50
Very Dense	over 50

### Cohesive Soils – Consistency

<u>Term</u>	<u>Unconfined Compression tons/sq.ft.</u>	<u>Blows/Foot Standard Penetration</u>	<u>Hand Manipulation</u>
Very Soft	less than 0.25	below 2	Easily penetrated by fist
Soft	0.25 – 0.50	2 – 4	Easily penetrated by thumb
Medium Stiff	0.50 – 1.0	4 – 8	Penetrated by thumb with moderate pressure
Stiff	1.0 – 2.0	8 – 15	Readily indented by thumb but not penetrated
Very Stiff	2.0 – 4.0	15 – 30	Readily indented by thumb nail
Hard	over 4.0	over 30	Indented with difficulty by thumb nail

- b. Color – If a soil is a uniform color throughout, the term is single, modified by such adjective as light and dark. If the predominant color is shaded by a secondary color, the secondary color precedes the primary color. If two major and distinct colors are swirled throughout the soil, the colors are modified by the term “mottled”.
- c. Texture is based on the Ohio Department of Transportation Classification System. Soil particle size definitions are as follows:

<u>Description</u>	<u>Size</u>	<u>Description</u>	<u>Size</u>
Boulders	Larger than 8"	Sand – Coarse	2.0 mm to 0.42 mm
Cobbles	8" to 3"	– Fine	0.42 mm to 0.074 mm
Gravel – Coarse	3" to ¾"	Silt	0.074 mm to 0.005 mm
– Fine	¾" to 2.0 mm	Clay	smaller than 0.005 mm



- d. The main soil component is listed first. The minor components are listed in order of decreasing percentage of particle size.
- e. Modifiers to main soil descriptions are indicated as a percentage by weight of particle sizes.

trace	0 to 10%
little	10 to 20%
some	20 to 35%
"and"	35 to 50%

- f. Moisture content of **cohesionless soils** (sands and gravels) is described as follows:

<u>Term</u>	<u>Relative Moisture or Appearance</u>
Dry	No moisture present
Damp	Internal moisture, but none to little surface moisture
Moist	Free water on surface
Wet	Voids filled with free water

- g. The moisture content of **cohesive soils** (silts and clays) is expressed relative to plastic properties.

<u>Term</u>	<u>Relative Moisture or Appearance</u>
Dry	Powdery
Damp	Moisture content slightly below plastic limit
Moist	Moisture content above plastic limit but below liquid limit
Wet	Moisture content above liquid limit

#### 10. Rock Hardness and Rock Quality Designation

- a. The following terms are used to describe the relative hardness of the **bedrock**.

<u>Term</u>	<u>Description</u>
Very Soft	Permits denting by moderate pressure of the fingers. Resembles hard soil but has rock structure. (Crushes under pressure of fingers and/or thumb)
Soft	Resists denting by fingers, but can be abraded and pierced to shallow depth by a pencil point. (Crushes under pressure of pressed hammer)
Medium Hard	Resists pencil point, but can be scratched with a knife blade. (Breaks easily under single hammer blow, but with crumbly edges.)
Hard	Can be deformed or broken by light to moderate hammer blows. (Breaks under one or two strong hammer blow, but with resistant sharp edges.)
Very Hard	Can be broken only by heavy and in some rocks repeated hammer blows.

- b. Rock Quality Designation, RQD – This value is expressed in percent and is an indirect measure of rock soundness. It is obtained by summing the total length of all core pieces which are at least four inches long, and then dividing this sum by the total length of the core run.

11. Gradation – when tests are performed, the percentage of each particle size is listed in the appropriate column (defined in Item 9c).
12. When a test is performed to determine the natural moisture content, liquid limit moisture content, or plastic limit moisture content, the moisture content is indicated graphically.
13. The standard penetration (N) value in blows per foot is indicated graphically.

Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

**LOG OF: Boring B-1501**

Location: Sta. 32+00.5, 7.8 ft. LT of US 52 Ramp A BL

Date Drilled: 12/28/05 to 12/29/05

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / * Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: None Water level at completion: None (prior to coring) 17.8' (inside hollowstem augers)	GRADATION						STANDARD PENETRATION (N) Natural Moisture Content, % - ● PL ————— LL Blows per foot - ○ 10 20 30 40					
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay						
0	548.9																		
0.5	548.4						Topsoil - 6"												
		3				1.25	Stiff brown SILT AND CLAY (A-6a), trace fine to coarse sand, trace gravel; damp.												
		3	4	14															
3.5	545.4						Medium dense brown COARSE AND FINE SAND (A-3a), trace silty clay, trace gravel; damp.												
		7				2													
		13																	
5.0	543.9						Very stiff brown SILT AND CLAY (A-6a), trace fine to coarse sand, trace gravel; damp.												
		16		17															
		6				2.5													
		6	4	13															
8.5	540.4						Stiff to very stiff brown SILT (A-4b), little clay, trace fine sand; moist to wet.												
		2				1.0													
		2		18															
10																			
		2				2.5													
		9																	
		8		16															
13.5	535.4						Severely weathered brown SANDSTONE.												
14.0	534.9	50/3		2		6	Medium hard to hard brown SANDSTONE; very fine to fine grained, highly weathered, argillaceous, micaceous, thickly bedded to massive, highly fractured to broken. @ 16.1'-16.2', 20.8'-21.2', broken zones. @ 16.2'-17.7', lost recovery, possible broken zone. @ 17.7', gray. @ 21.5', slightly fractured.												
15																			
		Core 120"	Rec 102"			RQD 58%													
						R-1													
24.0	524.9						Bottom of Boring - 24.0'												
25																			
30																			

FILE: 0121-3070-03 [ 11/13/2007 6:11 PM ]

Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

**LOG OF: Boring B-1502**

Location: Sta. 29+49.3, 14.2 ft. LT of US 52 Ramp A BL

Date Drilled: 12/28/05

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 8.0'-10.5' Water level at completion: 7.8'	GRADATION						STANDARD PENETRATION (N) Natural Moisture Content, % - ● PL ————— LL Blows per foot - ○ 10 20 30 40						
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay							
0	544.0																			
0.6	543.4						Topsoil - 7"													
		5 6 6	14			3.75	Very stiff brown SILT AND CLAY (A-6a), trace fine to coarse sand, trace gravel; damp.													
3.5	540.5						Medium dense brown COARSE AND FINE SAND (A-3a), trace to little silty clay, trace gravel; damp.													
		4 8 11	16																	
6.0	538.0						Stiff brown SILT AND CLAY (A-6a), trace to little fine to coarse sand, trace gravel; damp to moist.													
		2 2 3	14			1.5														
7.5	536.5						Medium dense brown COARSE AND FINE SAND (A-3a), trace to little silty clay, trace gravel; moist.													
		3 9 20	10																	
10																				
11.4	532.6	50/5	2				@ 11.0'-11.4', very dense.													
							Bottom of Boring - 11.4'													

FILE: 0121-3070-03 ( 11/13/2007 6:11 PM )













Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

LOG OF: Boring B-1507

Location: Sta. 23+61.5, 36.8 ft. RT of US 52 CL

Date Drilled: 1/4/06

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: None Water level at completion: 12.0' (includes drilling water)	GRADATION						STANDARD PENETRATION (N) Natural Moisture Content, % - ● PL ————— LL Blows per foot - ○ 10 20 30 40		
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay			
0	543.6						DESCRIPTION Asphalt Concrete Pavement - 11" Aggregate Base - 5" Stiff to very stiff brown SILT AND CLAY (A-6a), some to "and" fine to coarse sand, little gravel; damp. @ 3.5'-5.0', hard. Severely weathered gray SILTSTONE, arenaceous. Loose brown GRAVEL WITH SAND, SILT, AND CLAY (A-2-6); contains coal fragments; damp. Severely weathered gray SILTSTONE, arenaceous. Medium dense brown FINE SAND (A-3), trace silty clay; damp. Hard gray SANDSTONE; very fine grained, moderately to highly weathered, argillaceous, micaceous, thickly bedded, highly fractured to broken. @ 22.0'-22.1', high angle fracture. @ 22.0'-24.6', brown. @ 25.9'-27.0', lost recovery, possible broken zone. @ 29.1', slightly fractured.									
1.2	542.4	5 4 7 6		1		1.0										
		4 15 29 16		2		4.25										
5	538.1	30 22 20	9	3												
8.5	535.1	4 3 3 7		4												
10	533.1	8 22 9 3		5												
13.0	530.6	7 6 8 0		6												
15		3 7 9 15		7												
20		7 13 15 15		8												
22.0	521.6	50/2	1	9												
25																
30																

FILE: 0121-3070-03 [ 11/13/2007 6:11 PM ]



Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

**LOG OF: Boring B-1508**

Location: Sta. 22+13.3, 38.5 ft. RT of US 52 CL

Date Drilled: 1/4/06 to 1/5/06

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 33.5' Water level at completion: 27.5' (with augers removed)	GRADATION						STANDARD PENETRATION (N) Natural Moisture Content, % - ● PL ————— LL Blows per foot - ○ 10 20 30 40			
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay				
0	543.2						Asphalt Concrete Pavement - 12"										
1.0	542.2	14			1	3.75	Very stiff reddish brown SILT AND CLAY (A-6a), trace fine to coarse sand, trace gravel; damp.										
		6	7	7													
		5	7	14	2	3.0											
5		7	6	7	3	4.25	Medium dense brown GRAVEL WITH SAND, SILT, AND CLAY (A-2-6); damp.										
	535.2	3	5	5	4												
		5	16														
10							Soft to medium hard gray SILTSTONE; moderately to highly weathered, argillaceous.										
10.5	532.7	21	29	10	5												
		12	26	10	6												
15		8	7	5	7		Dense brown GRAVEL WITH SAND (A-1-b), trace silty clay; damp to moist.										
		12	10	9	8												
		12	10	9	12												
20							Medium dense brown FINE SAND (A-3), trace to little coarse sand, trace gravel; wet.										
20.5	522.7	3	6	9	9												
		6	9	17													
23.0	520.2	2	4	25	10		Dense brown GRAVEL WITH SAND (A-1-b); moist to wet.										
		10	15	21	11												
		10	15	21	18												
25							Medium dense brown COARSE AND FINE SAND (A-3a), trace gravel; wet.										
25.5	517.7	6	11	10	12												
		6	11	10	18												
28.0	515.2																
30																	

FILE: 0121-3070-03 [ 11/13/2007 6:11 PM ]

Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

**LOG OF: Boring B-1508**

Location: Sta. 22+13.3, 38.5 ft. RT of US 52 CL

Date Drilled: 1/4/06

to 1/5/06

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 33.5' Water level at completion: 27.5' (with augers removed)	GRADATION						STANDARD PENETRATION (N) Natural Moisture Content, % - ● PL ————— LL Blows per foot - ○ 10 20 30 40
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay	
30	513.2						Medium dense brown COARSE AND FINE SAND (A-3a), trace gravel; wet.							
		5	13	13										
33.0	510.2					0.5	Very soft to soft gray SILT (A-4b), trace fine sand; wet.							
		2	11	14										
35														
		2	11	14										
40						0.25								
		WOH 4	19	15										
44.0	499.2					4.5+	Hard brown and gray SANDY SILT (A-4a), little gravel; contains siltstone fragments; damp.							
		9	15	16										
45														
		9	15	16										
50						4.5+								
		8	14	17										
54.5	488.7						Bottom of Boring - 54.5'							
		15	14	17										
55														
60														

FILE: 0121-3070-03 | 11/13/2007 6:11 PM |

Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

**LOG OF: Boring B-1509**

Location: Sta. 20+59.5, 36.8 ft. RT of US 52 CL

Date Drilled: 1/5/06

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 43.5', 48.5', 53.5', 58.5' Water level at completion: 54.0' (prior to coring) 52.9' (includes drilling water)	GRADATION						STANDARD PENETRATION (N)					
				Drive	Press / Core			DESCRIPTION	% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay	Natural Moisture Content, % - ● PL ————— LL Blows per foot - ○ 10 20 30 40				
0	543.5																		
0.9	542.6	4		1			Asphalt Concrete Pavement - 11"												
		6 9	5				Medium dense gray COARSE AND FINE SAND (A-3a), little gravel; contains rock fragments; dry.												
3.5	540.0	5		2		2.0	Stiff brown SILTY CLAY (A-6b), some fine to coarse sand; damp.												
		8 8	13																
6.0	537.5	3		3			Medium dense brown COARSE AND FINE SAND (A-3a), trace gravel, trace clay; damp to moist.												
		9 12	16																
8.5	535.0	4		4		4.0	Very stiff brown SILT AND CLAY (A-6a), some fine to coarse sand, trace gravel; damp to moist.	8	8	--	15	41	28						
		6 17	11																
11.0	532.5	5		5			Medium dense to dense brown COARSE AND FINE SAND (A-3a), little clay, trace gravel; damp to moist.												
		15 27	15				@ 13.5'-15.0', some gravel.	22	24	--	28	18	8						
		4 15	13																
		4 9	6	7															
		6 11	18																
		4 6	11	8															
		4 6	11																
		5 5	10	9															
		10 11	15	11															
		10 11	15																
23.5	520.0	3		10		2.0	Very stiff brown SANDY SILT (A-4a), some gravel, trace clay; contains rock fragments; damp.	28	14	--	9	42	7						
		7 31	16																
		10 11	15	11		3.0													
		10 11	15																
28.5	515.0	8		12			Medium dense brown COARSE AND FINE SAND (A-3a); moist.												
		12 13	15																
		8 12	15	12															

FILE: 0121-3070-03 | 11/13/2007 6:11 PM |

Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

LOG OF: Boring B-1509

Location: Sta. 20+59.5, 36.8 ft. RT of US 52 CL

Date Drilled: 1/5/06

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 43.5', 48.5', 53.5', 58.5' Water level at completion: 54.0' (prior to coring) 52.9' (includes drilling water).	GRADATION						STANDARD PENETRATION (N) Natural Moisture Content, % - ● PL ————— LL Blows per foot - ○ 10 20 30 40					
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay						
30.0	513.5						Dense to very dense brown GRAVEL WITH SAND (A-1-b), little silt, trace clay; moist.												
	513.5																		
35		31 25 7	14			13													
40		16 32 47	15			14		33	17	--	30	17	3	●				Non-Plastic	
45		18 19 16	14			15													
47.0	496.5						Medium dense brown GRAVEL WITH SAND AND SILT (A-2-4), trace clay; damp.												
50		9 14 8	12			16			46	17	--	11	23	3	●				Non-Plastic
55		7 13 14	15			17													
59.5	484.0	50/3	1			18													

FILE: 0121-3070-03 [ 11/13/2007 6:11 PM ]



Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

**LOG OF: Boring B-1510**

Location: Sta. 19+13.0, 37.0 ft. RT of US 52 CL

Date Drilled: 1/10/06

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 6.3', 29.6' Water level at completion: 30.5' (inside hollowstem augers)	GRADATION					STANDARD PENETRATION (N) Natural Moisture Content, % - ● PL ————— LL Blows per foot - ○ 10 20 30 40						
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt		% Clay					
0	543.7																		
1.0	542.7	3			1a		Asphalt Concrete Pavement - 9" Aggregate Base - 3"												
2.0	541.7	4 4	12		1b	3.75	Loose brown COARSE AND FINE SAND (A-3a), trace gravel; damp to moist.												
		6 10 16	14		2	4.5	Very stiff to hard brown SILT AND CLAY (A-6a), trace to little fine to coarse sand, trace gravel; damp.												
5		3 6 8	13		3	4.5													
6.5	537.2	3 8	13		4a 4b	3.0	Medium dense brown COARSE AND FINE SAND (A-3a), trace gravel; damp.												
		6 10			5														
10		7	12																
11.0	532.7	3 4	12		6	4.25	Very stiff to hard brown SILT AND CLAY (A-6a), trace gravel; damp to moist.												
		5 7 12	16		7	4.5+													
15		5 5 8	18		8	3.0													
		3 5	18		9	2.5													
20		3 4 4	18		10	1.25	@ 21.0'-22.5', stiff.												
		3 5 6	18		11	2.25													
25		1 2 2	18		12	0.75	@ 26.0'-30.0', medium stiff to stiff.												
		2 2	18		13a	1.25													
30		2 9	18																

FILE: 0121-3070-03 [ 11/13/2007 6:11 PM ]



Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

**LOG OF: Boring B-1510**

Location: Sta. 19+13.0, 37.0 ft. RT of US 52 CL

Date Drilled: 1/10/06

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 6.3', 29.6' Water level at completion: 30.5' (inside hollowstem augers)	GRADATION						STANDARD PENETRATION (N) Natural Moisture Content, % - ● PL ————— LL Blows per foot - ○ 10 20 30 40						
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay							
30	513.7					1.25	Stiff brown SILT AND CLAY (A- 6a), trace grave; damp to moist.  Severely weathered gray SHALE.  Bottom of Boring - 33.8'													
33.5	510.2																			
33.8	509.9	50/3	3			14														50
35																				
40																				
45																				
50																				
55																				
60																				

FILE: 0121-3070-03 [ 11/13/2007 6:11 PM ]

Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

**LOG OF: Boring B-1511**

Location: Sta. 17+75.3, 38.9 ft. RT of US 52 CL

Date Drilled: 1/10/06

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 20.5', 32.0' Water level at completion: 34.0' (prior to coring) 15.6' (includes drilling water)	GRADATION						STANDARD PENETRATION (N)			
				Drive	Press / Core			DESCRIPTION	% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay	Natural Moisture Content, % - ●	Blows per foot - ○	
0	543.4																
-1.0	542.4	19					Asphalt Concrete Pavement - 11" Aggregate Base - 1"										
-2.0	541.4	8	5	1			Loose to medium dense brown COARSE AND FINE SAND (A-3a), trace to little gravel; damp.										
		7		2		4.25	Very stiff to hard brown SILT AND CLAY (A-6a), trace fine to coarse sand; damp.										
		9	10														
		13		2													
		6															
5		6	13	3		4.5+											
		10															
		13	13														
		3		4		2.5											
		4	13														
		5															
		3															
-9.5	533.9	9	18	5a		4.5											
-10.0	533.4	36		5b			Loose to medium dense black and gray COARSE AND FINE SAND (A-3a), trace to little silty clay; damp.										
		4															
		5	18	6a		4.5	Very stiff to hard gray SILT AND CLAY (A-6a), trace fine to coarse sand, trace gravel; damp.										
		8		6b		4.5+	@ 12.0'-15.0', brown and gray.										
		3															
		5	18	7		2.0											
		6															
15																	
-15.5	527.9	12					Hard brown and gray SILT (A-4b), little clay, trace fine to coarse sand; damp.	0	1	--	3	78	18				
		16	18														
		16		8													
-18.5	524.9	2															
		4	18	9		2.5	Very stiff to hard brown and gray SILT AND CLAY (A-6a), trace fine to coarse sand; damp.										
		5															
20																	
-21.0	522.4	3					Soft brown SILT (A-4b), little fine to coarse sand, trace gravel; moist to wet.										
		2	18	10		0.5											
		3															
-23.5	519.9	2					@ 23.5'-24.0' contains decomposed rock fragments										
		1	18	11		0.5	Soft to medium stiff brown and gray CLAY (A-7-6), trace silt; damp to moist.										
		3															
25																	
-26.0	517.4	1					Soft to medium stiff brown and gray SILT AND CLAY (A-6a), trace fine to coarse sand; moist.	0	2	--	3	60	35				
		2	18	12		1.0											
		3															
		1															
		3	13	13		0.75											
30																	

FILE: 0121-3070-03 | 11/13/2007 5:11 PM |

Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

LOG OF: Boring B-1511

Location: Sta. 17+75.3, 38.9 ft. RT of US 52 CL

Date Drilled: 1/10/06

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 20.5', 32.0' Water level at completion: 34.0' (prior to coring) 15.6' (includes drilling water)	GRADATION						STANDARD PENETRATION (N)						
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay	Natural Moisture Content, % - ● PL ——— LL Blows per foot - ○ 10 20 30 40						
30	513.4						Soft to medium stiff brown and gray SILT AND CLAY (A-6a), trace fine to coarse sand; damp to moist.  Very dense gray GRAVEL WITH SAND AND SILT (A-2-4), trace clay; contains rock fragments; moist to wet.  Medium hard gray SANDSTONE; very fine to fine grained, slightly to moderately weathered, argillaceous, micaceous, thickly bedded, moderately fractured. @ 35.5'-38.0', highly fractured. @ 37.2'-37.5', 38.3'-38.6', high angle fractures. @ 38.0'-45.5', slightly fractured.  @ 43.3', decomposed, argillaceous seam. @ 44.0'-44.6', lost recovery, possible decomposed zone.													
33.5	509.9	15			14			35	16	--	22	22	5							
35		16 48	16																	
35.5	507.9																			
40		Core 120"	Rec 112"	RQD 93%	R1															
45																				
45.5	497.9						Bottom of Boring - 45.5'													
50																				
55																				
60																				

FILE: 0121-3070-03 [ 11/13/2007 6:11 PM ]

Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

LOG OF: Boring B-1512

Location: Sta. 16+15.9, 39.1 ft. RT of US 52 CL

Date Drilled: 1/11/06

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 42.0' Water level at completion: 47.3' (inside hollowstem augers)	GRADATION						STANDARD PENETRATION (N) Natural Moisture Content, % - ● PL ————— LL Blows per foot - ○ 10 20 30 40							
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay								
0	543.2																				
1.0	542.2	10	6	1			Asphalt Concrete Pavement - 11" Aggregate Base - 1"														
		4					Medium dense to dense brown COARSE AND FINE SAND (A-3a), trace gravel; damp to moist.														
		10		2a																	
		8	16	2b																	
		9																			
		14																			
5		6		3																	
		20																			
		27	22																		
		36																			
		5	13	4																	
		7	13																		
		5	14	5																	
10		18	9																		
11.0	532.2	4		6		4.5+	Very stiff to hard brown and gray SILT AND CLAY (A-6a), trace fine to coarse sand, trace gravel; damp to moist.														
		5	16																		
		6																			
		2	18	7		2.5															
15		5	18																		
		8																			
		5	18	8		1.75	@ 16.0'-17.5', stiff.														
		6																			
		9	18																		
		5																			
20		6	18	9		2.0															
		5																			
		6	18																		
		3																			
		4	18	10		3.0															
		6																			
		3																			
		4	18																		
		5																			
25		4	18	11		3.25															
		5																			
		8	18																		
		4																			
		5	18	12		2.25															
		8																			
		3																			
		3	18	13		2.0															
30		8																			

FILE: 0121-3070-03 [ 11/13/2007 6:11 PM ]

Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

**LOG OF: Boring B-1512**

Location: Sta. 16+15.9, 39.1 ft. RT of US 52 CL

Date Drilled: 1/11/06

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 42.0' Water level at completion: 47.3' (inside hollowstem augers)	GRADATION						STANDARD PENETRATION (N)					
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay	PL	LL				
30	513.2						.Stiff brown and gray SILT AND CLAY (A-6a), trace fine to coarse sand, trace gravel; damp to moist.												
34.0	509.2	2		10	21	18		Dense to very dense brown COARSE AND FINE SAND (A-3a), trace gravel; damp.											
35																			
40		26		19	30	18													
45		50/5				2													
48.5	494.7						Severely weathered gray SHALE. Bottom of Boring - 49.0'												
49.0	494.2	50/4				4													
50																			
55																			
60																			

Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

**LOG OF: Boring B-1513**

Location: Sta. 14+62.9, 39.4 ft. RT of US 52 CL

Date Drilled: 1/11/06 to 1/12/06

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 32.0' Water level at completion: 43.5' (prior to coring) 39.8' (includes drilling water)	GRADATION						STANDARD PENETRATION (N)				
				Drive	Press / Core			DESCRIPTION	% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay	Natural Moisture Content, %	Blows per foot		
0	543.2																	
1.0	542.2	9	3	1			Asphalt Concrete Pavement - 10" Aggregate Base - 2"											
		7						Medium dense to very dense brown GRAVEL WITH SAND (A-1-b), trace clay; damp to moist.										
		4		2														
		7	8															
		15																
		4		3				18	32	--	43	7						
		6	13															
		20		4														
		14	13															
		9		4				26	29	--	38	7						
		26	14															
		23																
		4		5														
		8	17															
		21																
10																		
10.5	532.7	7		6		3.75	Very stiff brown and gray SILTY CLAY (A-6b), trace gravel, trace fine to coarse sand; damp to moist.											
		13	12															
		3		7		2.5		9	1	--	2	35	53					
		4	18															
		10		8		4.5+												
		15	18															
		4																
		10	18															
18.0	525.2	6		9		2.5	Very stiff brown and gray SILT (A-4b), some clay, trace fine to coarse sand, trace gravel; moist.											
		9	18						9	2	--	2	64	23				
		13																
20																		
20.5	522.7	4		10		2.75	Very stiff brown and gray SILTY CLAY (A-6b), little to some gravel, trace fine to coarse sand; damp to moist.											
		5	18						20	0	--	1	29	50				
		8																
		4		11		4.5+												
		6	18															
		9																
25																		
		4		12		2.0												
		5	18															
		8																
		2		13		2.0												
		7	18															
30		10																

FILE: 0121-3070-03 [ 11/13/2007 6:11 PM ]

Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

**LOG OF: Boring B-1513**

Location: Sta. 14+62.9, 39.4 ft. RT of US 52 CL

Date Drilled: 1/11/06 to 1/12/06

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 32.0' Water level at completion: 43.5' (prior to coring) 39.8' (includes drilling water)	GRADATION						STANDARD PENETRATION (N) Natural Moisture Content, % - ● PL ——— LL Blows per foot - ○ 10 20 30 40					
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay						
30.0	513.2						Dense gray and brown SILT (A-4b), some clay, little fine to coarse sand, trace gravel; moist to wet.												
35	513.2	3 8 34	18			14			2	2	-	11	64	21					
36.5	506.7						Medium dense to dense brown and gray GRAVEL WITH SAND (A-1-b), trace clay; damp.												
40		10 23 26	18			15			46	25	-	25	4		●				
45		3 11 12	18			16													
50		6 12 14	17			17													
52.0	491.2						Severely weathered gray SANDSTONE, argillaceous, micaceous.												
55		50/5	2			18													
56.0	487.2						Medium hard gray SANDSTONE; very fine to fine grained, moderately weathered, argillaceous, micaceous, thickly bedded, slightly to moderately fractured. @ 56.6'-58.4', lost recovery, possible fracture zone.												
60																			





Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

LOG OF: Boring B-1514

Location: Sta. 13+03.6, 38.2 ft. RT of US 52 CL

Date Drilled: 1/12/06

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 52.0' Water level at completion: 56.1' (inside hollowstem augers)	GRADATION						STANDARD PENETRATION (N) Natural Moisture Content, % - ● PL ————— LL Blows per foot - ○ 10 20 30 40						
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay							
0	543.1																			
1.0	542.1	8			1		Asphalt Concrete Pavement - 12"													
2.0	541.1	5 6 14 16	7		2	4.5+	FILL: Medium dense brown and gray COARSE AND FINE SAND (A-3a), trace gravel; contains slag; damp. Very stiff to hard brown SILT AND CLAY (A-6a), trace fine to coarse sand, trace gravel; damp.													
5.0	538.1	8 16 21 34	14		3a 3b	2.75	Dense to very dense brown COARSE AND FINE SAND (A-3a), trace gravel; damp.													
		8 22 35	14		4															
		7 11 24	18		5															
10		12 12 16	2		6															
13.5	529.6	12 8 16	8		7	4.5+	Very stiff to hard brown and gray SILT AND CLAY (A-6a), trace fine to coarse sand, trace gravel; damp.													
15		6 9 12	18		8	3.75														
20		4 6 10	18		9	3.5														
21.0	522.1	3 5 7	18		10		Medium dense to dense brown FINE SAND (A-3); damp.													
		6 8 8	18		11															
25		6 8 15	18		12															
		10 15 16	18		13															
30																				

FILE: 0121-3070-03 [ 11/13/2007 6:11 PM ]

Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

**LOG OF: Boring B-1514**

Location: Sta. 13+03.6, 38.2 ft. RT of US 52 CL

Date Drilled: 1/12/06

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 52.0' Water level at completion: 56.1' (inside hollowstem augers)	GRADATION						STANDARD PENETRATION (N) Natural Moisture Content, % - ● PL ————— LL Blows per foot - ○ 10 20 30 40						
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay							
30	513.1																			
33.5	509.6	5																		
35		6 9	18		14															
40		11 16 16	18		15															
45		5 6 13	14		16															
50		9 12 14	16		17															
53.5	489.6	13 15 19	6		18															
55																				
58.5	484.6	50/2	2		19															
59.0	484.1																			
60																				

FILE: 0121-3070-03 | 11/13/2007 6:11 PM |

50+



Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

**LOG OF: Boring B-1515**

Location: Sta. 11+67.8, 39.3 ft. RT of US 52 CL

Date Drilled: 1/13/06

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 53.5' Water level at completion: 49.8' (prior to coring) 44.2' (includes drilling water)	GRADATION						STANDARD PENETRATION (N) Natural Moisture Content, % - ● PL ————— LL Blows per foot - ○ 10 20 30 40				
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay					
0	542.6						Asphalt Concrete Pavement - 12" Aggregate Base - 6"											
1.5	541.1	5	4	1			Dense to very dense brown COARSE AND FINE SAND (A-3a), trace to little silty clay, trace gravel; contains slag; damp to moist.											
		8		2														
		15	8															
		23		3														
		10																
5		19		3														
		25	19															
		32		4														
		9	18															
		14																
		18																
		9		5														
		16	18															
		23																
10																		
11.0	531.6	5		6		4.5+	Very stiff to hard brown SILT AND CLAY (A-6a), trace fine to coarse sand, trace gravel; damp.											
		7	17															
		6		7		3.5												
		3	10															
		9																
		9		8		4.5+												
		4	18															
		5																
		8																
		3		9		4.5												
		4	18															
		4																
		9	18			2.75												
		15																
		4		10														
		5	18															
		7																
		18		11		3.0												
		3	14															
		6																
		7		12		2.5												
		14																
		2																
		2	17			2.5												
		6		13														

FILE: 0121-3070-03 [ 11/13/2007 6:11 PM ]

Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

**LOG OF: Boring B-1515**

Location: Sta. 11+67.8, 39.3 ft. RT of US 52 CL

Date Drilled: 1/13/06

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetro- meter (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 53.5' Water level at completion: 49.8' (prior to coring) 44.2' (includes drilling water)	GRADATION						STANDARD PENETRATION (N) Natural Moisture Content, % - ● PL ————— LL Blows per foot - ○ 10 20 30 40					
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay						
30	512.6						Very stiff to hard brown SILT AND CLAY (A-6a), trace fine to coarse sand, trace gravel; damp.												
33.5	509.1	5			11	18		Medium dense brown FINE SAND (A-3), trace coarse sand; contains coal fragments; damp.											
35		11			16	18													
40		2			11	13	18	15											
45		5			6	11	18	16											
50		6			7	8	18	17											
53.5	489.1	2			3	4	5	18											
55																			
60		2			3	3	3	19											
									Loose brown COARSE AND FINE SAND (A-3a); wet.										

Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

LOG OF: Boring B-1515

Location: Sta. 11+67.8, 39.3 ft. RT of US 52 CL

Date Drilled: 1/13/06

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 53.5' Water level at completion: 49.8' (prior to coring) 44.2' (includes drilling water)	GRADATION						STANDARD PENETRATION (N) Natural Moisture Content, % - ● PL ————— LL Blows per foot - ○ 10 20 30 40	
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay		
60	482.6						DESCRIPTION  Loose brown COARSE AND FINE SAND (A-3a); wet.  @ 63.5', 9.0' sand heave; washed out.  Severely weathered gray SHALE.  Medium hard to hard gray SANDSTONE; very fine to fine grained, moderately weathered, argillaceous, micaceous, massive, moderately fractured. @ 64.2', 64.6', 65.6', 65.8', 65.9', 67.8', 70.0', low angle fractures. @ 65.8'-66.1', broken and decomposed. @ 66.5'-67.0', lost recovery. -								
63.5	479.1	50/5	2		20										
64.0	478.6														50+
65															
70		Core 120"	Rec 111"		RQD 83%	R-1									
74.0	468.6						Bottom of Boring - 74.0'								
75															
80															
85															
90															

Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

**LOG OF: Boring B-1516**

Location: Sta. 10+14.5, 36.8 ft. RT of US 52 CL

Date Drilled: 1/4/06

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 1.5'-2.0', 53.5'-70.0' Water level at completion: None (prior to washing out) 68.0' (inside hollowstem augers)	GRADATION						STANDARD PENETRATION (N)			
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay	PL	LL		
0	542.5																
-1.3	541.2	9			1		Asphalt Concrete Pavement - 9" Aggregate Base - 6"										
-2.0	540.5	6	3				Medium dense dark brown COARSE AND FINE SAND (A-3a), trace gravel; damp to moist.										
-3.0	539.5	5			2A	3.0	Very stiff gray and brown SILT AND CLAY (A-6a), some fine to coarse sand, trace gravel; damp to moist.	6	10	--	15	35	34				
		6	12		2B		Medium dense brown FINE SAND (A-3), trace gravel, some coarse sand, trace silty clay; damp to moist.										
		10	14		3												
		14	16														
		18	14		4												
		9	7														
		7	16														
		5															
		8			5A												
-9.5	533.0	8	18		5B		Medium dense brown COARSE AND FINE SAND (A-3a), little clay, trace gravel; moist.	3	20	--	44	17	16				
-10.5	532.0	8				4.5+	Hard brown CLAY (A-7-6), little fine to coarse sand; damp to moist.	0	7	--	10	33	50				
		4	7		6												
		7	9														
		13															
		3	4		7	4.5+											
		6	16														
15		3	4														
		6	16														
-16.0	526.5	5			8	4.25	Hard brown and gray SILTY CLAY (A-6b), trace to little fine to coarse sand; damp to moist. @ 16.0'-17.5', contains odor.										
		5	6														
		18															
		3	4		9	4.5											
		8	14														
		4															
		7	10		10	4.5+											
		10	18														
-23.0	519.5	3			11	2.5	Very stiff brown SILT AND CLAY (A-6a), trace fine to coarse sand; damp to moist.	0	4	--	5	59	32				
		5	6														
		15															
		3	4		12	2.5											
		6	18														
-28.0	514.5	3					Very stiff brown and gray SILT (A-4b), some clay, some fine sand, trace gravel; moist.	1	0	--	22	54	23				
		8			13	--											
		12	18														
30		18															

FILE: 0121-3070-03 [ 11/13/2007 6:11 PM ]







Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

**LOG OF: Boring B-1517**

Location: Sta. 8+62.5, 37.8 ft. RT of US 52 CL

Date Drilled: 12/28/05

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 1.0'-4.0', 49.5-70.0' Water level at completion: 46.5' (prior to coring) 44.1' (includes drilling water) 46.5' (after 93 hours)	GRADATION						STANDARD PENETRATION (N)					
				Drive	Press / Core			DESCRIPTION	% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay	Natural Moisture Content, % - ●		Blows per foot - ○		
0	542.0																		
1.3	540.7	9			1														
4.0	538.0	6			2A 2B	4.5+		9	27	--	51	8	5						
6.0	536.0	12			3			12	23	--	40	17	8						
8.5	533.5	3			4	4.25		1	2	--	14	41	42						
10		5			5	4.5+													
15		6			6	2.5													
16.0	526.0	4			7	4.5+													
20		4			8	2.5													
23.0	519.0	4			9	1.25													
25		3			10	1.25													
28.5	513.5	8			11	2.5													
30		10			12														

FILE: 0121-3070-03 | 11/13/2007 6:11 PM |

Non-Plastic

Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

LOG OF: Boring B-1517

Location: Sta. 8+62.5, 37.8 ft. RT of US 52 CL

Date Drilled: 12/28/05

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 1.0'-4.0', 49.5-70.0' Water level at completion: 46.5' (prior to coring) 44.1' (includes drilling water) 46.5' (after 93 hours)	GRADATION						STANDARD PENETRATION (N) Natural Moisture Content, % - ● PL ——— LL Blows per foot - ○ 10 20 30 40						
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay							
30	512.0						Loose to medium dense brown FINE SAND (A-3), some coarse sand, trace gravel; damp to wet.													
35		6 9 13	14	13																
40		3 3 6	18	14					3	22	--	72	3							Non-Plastic
45		6 8 8	14	15																
50		6 9 9	17	16																
55		7 10 14	18	17				@ 53.5', 4.0' sand heave, becomes wet.												
60		6 6 9	15	18																

FILE: 0121-3070-03 [ 11/13/2007 6:11 PM ]

Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

**LOG OF: Boring B-1517**

Location: Sta. 8+62.5, 37.8 ft. RT of US 52 CL

Date Drilled: 12/28/05

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 1.0'-4.0', 49.5-70.0' Water level at completion: 46.5' (prior to coring) 44.1' (includes drilling water) 46.5' (after 93 hours)	GRADATION						STANDARD PENETRATION (N) Natural Moisture Content, % - ● PL ——— LL Blows per foot - ○ 10 20 30 40					
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay						
60	482.0						Loose brown FINE SAND (A-3), some coarse sand, trace gravel; wet.												
65		2 3 5	8	19					7	27	--	63	3	Non-Plastic					
67.0	475.0							Medium dense brown GRAVEL WITH SAND (A-1-b), trace silt, trace clay; wet.											
70		3 6 12	8	20						38	43	--	8	9	2	Non-Plastic			
73.5	468.5	50/4	4	21			Severely weathered gray SILTSTONE, arenaceous, micaceous.												
76.0	466.0						Medium hard gray SANDSTONE; very fine to fine grained, slightly weathered, argillaceous, micaceous, massive, slightly fractured.  @ 77.8'-78.0', decomposed fracture.  @ 84.8', low angle fracture.												
80		Core 120"	Rec 120"	RQD 89%	R-1														
86.0	456.0							Bottom of Boring - 86.0'											
90																			

FILE: 0121-3070-03 [ 11/13/2007 6:11 PM ]

Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

**LOG OF: Boring B-1518**

Location: Sta. 7+14.9, 36.9 ft. RT of US 52 CL

Date Drilled: 12/22/05 to 12/28/05

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 1.0'-2.5', 49.5'-74.2' Water level at completion: 53.0' (includes drilling water)	GRADATION						STANDARD PENETRATION (N) Natural Moisture Content, % - ● PL ————— LL Blows per foot - ○ 10 20 30 40						
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay							
0	541.6						DESCRIPTION													
1.3	540.3	7 6 10	13	1			Asphalt Concrete Pavement - 10" Aggregate Base - 6"													
5		8 9 8	16	2			Medium dense to dense brown COARSE AND FINE SAND (A-3a), trace gravel; damp to moist.													
		22 16 16	18	3																
8.5	533.1	6 7 8	12	4		4.5+		Very stiff to hard brown and gray SILT AND CLAY (A-6a), trace fine to coarse sand, trace gravel; damp.												
10		8 9 11	18	5A 5B		4.5+ 4.0														
15		5 8 11	14	6		4.5+														
		6 8 10	18	7		4.5+														
20		3 3 5	18	8		2.5														
21.0	520.6	3 5 6	18	9		-	Medium stiff to stiff brown SANDY SILT (A-4a), trace clay; damp.													
25		3 4 4	18	10		-														
26.0	515.6	5 6 9	18	11			Medium dense brown FINE SAND (A-3), trace to little silty clay; damp to moist.													
30		9 11 13	13	12																

Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

LOG OF: Boring B-1518

Location: Sta. 7+14.9, 36.9 ft. RT of US 52 CL

Date Drilled: 12/22/05 to 12/28/05

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 1.0'-2.5', 49.5'-74.2' Water level at completion: 53.0' (includes drilling water)	GRADATION						STANDARD PENETRATION (N) Natural Moisture Content, % - ● PL ————— LL Blows per foot - ○ 10 20 30 40					
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay						
30	511.6						Medium dense brown FINE SAND (A-3), trace to little silty clay; damp to moist.												
33.5	508.1	5			13			Medium dense brown COARSE AND FINE SAND (A-3a), trace gravel; damp to moist.											
35		6	11	12															
40		4	4	8	14														
45		6	7	7	13														
48.5	493.1	5			16		Loose to medium dense brown FINE SAND (A-3), trace coarse sand, trace gravel; moist to wet.												
50		6	8	11															
55		1	3	6	14		@ 53.5', becomes wet. @ 53.5'-60.0', 1.0'-3.0' sand heave.												
60		12	8	7	18														

FILE: 0121-3070-03 ( 11/13/2007 6:11 PM )

Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

**LOG OF: Boring B-1518**

Location: Sta. 7+14.9, 36.9 ft. RT of US 52 CL

Date Drilled: 12/22/05 to 12/28/05

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS:	GRADATION						STANDARD PENETRATION (N) Natural Moisture Content, % - ● PL ——— LL Blows per foot - ○ 10 20 30 40					
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay						
60	481.6						WATER OBSERVATIONS: Water seepage at: 1.0'-2.5', 49.5'-74.2' Water level at completion: 53.0' (includes drilling water)												
		1 2 3	6	19				Loose to medium dense brown FINE SAND (A-3), trace coarse sand, trace gravel; wet.  @ 63.5', 68.5', 4.0' sand heave.											
65		4 12 10	18	20															
70		15 30 50/3	15	21A 21B															
74.5 75.0	467.1 466.6						Severely weathered gray SHALE.												
							Bottom of Boring - 75.0'												
80																			
85																			
90																			

FILE: 0121-3070-03 [ 11/13/2007 6:11 PM ]

Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

**LOG OF: Boring B-1519**

Location: Sta. 5+67.1, 28.7 ft. RT of US 52 CL

Date Drilled: 12/28/05 to 12/30/05

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 50.0' Water level at completion: 45.0' (prior to coring)	GRADATION						STANDARD PENETRATION (N)						
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay	Natural Moisture Content, % - ●		Blows per foot - ○				
													PL ————— LL							
													10 20 30 40							
0	541.4						Asphalt Concrete - 5" Portland Cement Concrete - 9"													
1.2	540.2	6 13	10	1		3.5	Very stiff to hard brown SANDY SILT (A-4a), little gravel, trace clay; damp.													
		20 28		2		4.5+			13	19	--	29	31	8	●					
4.0	537.4	8 21	22	3			Very dense brown COARSE AND FINE SAND (A-3a), little gravel, trace clay; damp.													
5		30 33		3					12	31	--	42	10	5	●					
7.5	533.9						Hard brown CLAY (A-7-6), "and" silt, trace fine to coarse sand; damp to moist.													
		4 11	13	4		4.5+														
10		5 11		5		4.5+			0	1	--	3	39	57	●					
15		7 14	18	6		4.5+														
		20 20		6																
16.0	525.4	2 5	18	7		1.5	Stiff brown SILT (A-4b), some fine to coarse sand, little clay; damp.													
		7 7		7																
20		2 5	18	8		1.5			0	1	--	30	50	19	●					
		8 8		8																
		5 5	18	9		1.5														
		9 9		9																
23.5	517.9	16 19	18	10			Dense brown GRAVEL WITH SAND (A-1-b), trace silty clay; dry to damp.													
		20 20		10																
25		13 19	15	11					2	49	--	46	2	1	●					
		19 19		11																
		6 18	16	12																
30		28 28		12																
				12																

FILE: 0121-3070-03 [ 11/13/2007 6:11 PM ]



Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

LOG OF: Boring B-1519

Location: Sta. 5+67.1, 28.7 ft. RT of US 52 CL

Date Drilled: 12/28/05 to 12/30/05

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS:	GRADATION						STANDARD PENETRATION (N)					
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay		Natural Moisture Content, % - PL	LL	Blows per foot		
30	511.4						Water seepage at: 50.0' Water level at completion: 45.0' (prior to coring)												
35		15 21 25	14			13		Dense brown GRAVEL WITH SAND (A-1-b), little silty clay; dry to damp.	31	35	--	15	19	●					Non-Plastic
37.0	504.4						Medium dense brown FINE SAND (A-3), trace coarse sand, trace silt; damp.												
40		7 11 14	16			14													
45		6 7 8	17			15			0	4	--	93	3	0	●				Non-Plastic
50		11 11 14	14			16													
52.0	489.4						Medium dense brown COARSE AND FINE SAND (A-3a), trace silty clay, trace gravel; wet.												
55		13 16 12	18			17			3	30	--	55	8	4	●				Non-Plastic
60		3 6 9	18			18													

FILE: 0121-3070-03 [ 11/13/2007 6:11 PM ]

Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

**LOG OF: Boring B-1519**

Location: Sta. 5+67.1, 28.7 ft. RT of US 52 CL

Date Drilled: 12/28/05 to 12/30/05

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 50.0' Water level at completion: 45.0' (prior to coring)	GRADATION						STANDARD PENETRATION (N) Natural Moisture Content, % - ● PL ————— LL Blows per foot - ○ 10 20 30 40					
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay						
60	481.4						Loose to medium dense brown COARSE AND FINE SAND (A-3a), trace silty clay, trace gravel; moist to wet.												
65		3 4	18	19															
70		8 10	18	20															
75.0	466.4	60 50/3	9	21				@ 73.5', very dense, little to some silty clay.											
80.4	461.0	Core 65"	Rec 65"	RQD 58%	R-1		Medium hard to hard gray SANDSTONE; very fine to fine grained, slightly weathered, argillaceous, massive, slightly fractured, contains few to moderate argillaceous laminations.  @ 79.4'-80.0', calcareous.												
							Bottom of Boring - 80.4'												

FILE: 0121-3070-03 [ 11/13/2007 6:11 PM ]

Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

**LOG OF: Boring B-1520**

Location: Sta. 27+68.3, 25.8 ft. LT of US 52 Ramp B BL

Date Drilled: 1/16/06

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 13.5' Water level at completion: None (Prior to coring) 10.7' (Includes drilling water)	GRADATION						STANDARD PENETRATION (N) Natural Moisture Content, % - ● PL ————— LL Blows per foot - ○ 10 20 30 40							
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay								
0	534.7																				
1.0	533.7	1				2.25	Asphalt Concrete Pavement - 5" Aggregate Base - 7"														
		2	14	1		4.5+	Very stiff to hard gray SILT AND CLAY (A-6a), trace fine to coarse sand, trace gravel; damp to moist.  @ 11.0'-12.5', stiff.														
		3		2		4.5+															
		4		3		4.0															
		4		4		2.0															
		4		5		1.5															
		2		6																	
10		3	18																		
		4		7																	
		4		8																	
		8	24																		
		8		9																	
		5		7																	
		5		7																	
		6		7																	
13.5	521.2	39	12	7			Very dense brown GRAVEL WITH SAND AND SILT (A-2-4); moist.														
15.0	519.7	50/3					Medium hard brown SANDSTONE; very fine to fine grained, highly weathered, argillaceous, micaceous, massive, highly fractured to broken.  @ 18.0'-18.4', high angle fracture.														
19.6	515.1	Core 120"	Rec 120"	RQD 56%	R-1		Medium hard to hard gray SANDSTONE; very fine to fine grained, slightly to moderately weathered, argillaceous, micaceous, massive, slightly fractured to unfractured.  @ 16.4'-17.5', 18.7'-18.8', broken.														
25.0	509.7						Bottom of Boring - 25.0'														

FILE: 0121-3070-03 [ 11/13/2007 6:11 PM ]





Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

**LOG OF: Boring B-1522**

Location: Sta. 22+02.7, 8.2 ft. RT of US 52 Ramp B BL

Date Drilled: 1/12/06

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 8.1', 11.0', 13.5' Water level at completion: 8.1' (prior to coring) 4.4' (includes drilling water)	GRADATION						STANDARD PENETRATION (N) Natural Moisture Content, % - ● PL ————— LL Blows per foot - ○ 10 20 30 40						
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay							
0	529.2																			
1.0	528.2	3			1	3.0	Topsoil - 6"													
		3	4	13			Very stiff brown SILT (A-4b), little clay; damp.													
3.5	525.7	4			2	3.5	Very stiff to hard brown SILT AND CLAY (A-6a), trace to little fine to coarse sand; damp to moist.													
		5	11	16																
		4			3A	4.5+														
		9		16	3B	4.5+		0	1	--	10	64	25							
		4			4A	2.5														
		6		18	4B	2.0														
10		4						0	2	--	8	60	30							
11.0	518.2	4			5		Dense gray GRAVEL WITH SAND (A-1-b), trace silt; wet.													
		5		13				41	29	--	25	5								
		6			6		Severely weathered gray SANDSTONE, argillaceous.													
13.5	515.7	50/5		4			Medium hard to hard gray SANDSTONE; fine grained, moderately to highly weathered, argillaceous, thickly bedded, moderately to highly fractured.													
14.0	515.2						@ 14.0'-16.6', 17.4'-17.9', iron stained.													
							@ 14.6', 17.0', 17.4', 17.6', 18.1', low angle fractures with iron staining.													
							@ 15.4', 15.6', 16.2', 17.0', 18.7', low angle fractures.													
							@ 18.7', slightly to moderately fractured.													
							@ 19.6'-19.9', 23.1'-23.5', high angle fractures.													
20																				
		Core 120"	Rec 120"		RQD 67%	R-1														
24.0	505.2						Bottom of Boring - 24.0'													
25																				
30																				

FILE: 0121-3070-03 [ 11/13/2007 6:11 PM ]

Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

**LOG OF: Boring B-1523**

Location: Sta. 18+98.8, 22.7 ft. RT of US 52 Ramp B BL

Date Drilled: 11/3/05

to 11/7/05

Depth (ft)	Elev. (ft)	SPT		Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 33.5' Water level at completion: 54.2' (prior to coring) 20.5' (includes drilling water)	GRADATION						STANDARD PENETRATION (N) Natural Moisture Content, % - ● PL ————— LL Blows per foot - ○ 10 20 30 40						
		Blows per 6"	Recovery (in)	Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay							
0	540.8						Asphalt Concrete Pavement - 8" Aggregate Base - 4" Medium dense brown COARSE AND FINE SAND (A-3a), trace gravel; moist. Very stiff brown SILTY CLAY (A-6b), little fine to coarse sand, trace gravel; moist.													
1.0	539.8	7			1A	4.0														
1.5	539.3	4	12		1B															
		7																		
		6				3.0														
		5	8		2															
5		5																		
		10	14																	
		14	17		3															
8.5	532.3	6						Medium dense to dense brown COARSE AND FINE SAND (A-3a), trace gravel; damp to moist.												
		10	12		4															
10		17	12																	
		15																		
		17	13		5															
		21																		
		10																		
		12	15		6															
15		11																		
		6																		
		8	18		7															
		13																		
		5																		
		11	16		8															
20		8																		
		9																		
		9	14		9															
		8																		
23.5	517.3	4					Loose to medium dense gray SANDY SILT (A-4a), trace clay, trace fine to coarse sand, trace gravel; moist.													
		3	9		10															
25		3																		
		5	10		11															
		5																		
		6																		
28.5	512.3	5					Medium dense brown COARSE AND FINE SAND (A-3a), trace gravel; moist to wet													
		5																		
		10	2		12															
30		10																		

FILE: 0121-3070-03 | 11/13/2007 6:11 PM |

Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

LOG OF: Boring B-1523

Location: Sta. 18+98.8, 22.7 ft. RT of US 52 Ramp B BL

Date Drilled: 11/3/05 to 11/7/05

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 33.5' Water level at completion: 54.2' (prior to coring) 20.5' (includes drilling water)	GRADATION						STANDARD PENETRATION (N) Natural Moisture Content, % - ● PL ————— LL Blows per foot - ○ 10 20 30 40					
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay						
30	510.8						Medium dense brown COARSE AND FINE SAND (A-3a), trace gravel; moist to wet.  @ 33.5'-35.0', very loose, wet.												
33		3																	
35		1	1	18															
38																			
40		8	10	11	16														
43.5	497.3	22	42	32	14		Very dense brown COARSE AND FINE SAND (A-3a), trace gravel; moist to wet.												
45																			
48.5	492.3	10	15	9	12		Severely weathered gray SHALE.												
50																			
53		16	43	24	15														
55																			
58		50/2		2															
60																			

FILE: 0121-3070-03 [ 11/13/2007 6:11 PM ]





Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

**LOG OF: Boring B-1524**

Location: Sta. 17+90.5, 35.9 ft. LT of US 52 CL

Date Drilled: 11/7/05 to 11/9/05

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 11.0', 28.5' Water level at completion: 29.8' (inside hollowstem augers)	GRADATION						STANDARD PENETRATION (N) Natural Moisture Content, % - ● PL ————— LL Blows per foot - ○ 10 20 30 40
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay	
0	542.2						<p><b>DESCRIPTION</b></p> <p>Asphalt Concrete Pavement - 9" Aggregate Base - 3"</p> <p>POSSIBLE FILL: Medium dense brown FINE SAND (A-3), trace gravel, trace silt; moist.</p> <p>Very stiff to hard brown SILT AND CLAY (A-6a), little fine to coarse sand, trace gravel; damp to moist.</p> <p>Loose brown FINE SAND (A-3), trace fine to coarse sand, trace gravel; moist.</p> <p>Hard brown SILTY CLAY (A-6b), trace fine to coarse sand, trace gravel; damp.</p> <p>@ 11.0'-11.3', wet sand seam.</p> <p>Stiff brown and gray SILT AND CLAY (A-6a), little fine to coarse sand; moist.</p> <p>Loose to medium dense gray SILT (A-4b), trace fine to coarse sand; damp.</p> <p>@ 18.5'-22.5', occasional rust stains.</p> <p>@ 21.0'-22.5', very loose.</p> <p>Stiff gray SILT AND CLAY (A-6a), little fine to coarse sand, trace gravel; contains rust stains; moist.</p> <p>Loose to medium dense brown COARSE AND FINE SAND (A-3a), little gravel, little silty clay; wet.</p>							
1.0	541.2	5												
1.5	540.7	4	7	12	1A	4.0								
					1B									
		3	5	8	2	4.5+								
5			4	14	3	3.0								
8.0	534.2													
9.0	533.2	3	4	12	4A	4.5+								
10			3		4B									
11.3	530.9	3	3	18	5A	1.0								
					5B									
13.5	528.7	3	5	11	6									
15			10	6	7									
			2	2	8									
20			1	1	9									
			2	2										
23.5	518.7	2	3	15	10	1.75								
25			1	3	11	1.5								
			3	4										
28.0	514.2													
		5	6	4	12									
30														

FILE: 0121-3070-03 | 11/13/2007 6:11 PM |

Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

LOG OF: Boring B-1524

Location: Sta. 17+90.5, 35.9 ft. LT of US 52 CL

Date Drilled: 11/7/05

to 11/9/05

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS:	GRADATION						STANDARD PENETRATION (N) Natural Moisture Content, % - ● PL ——— LL Blows per foot - ○					
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay						
30.0	512.2						Water seepage at: 11.0', 28.5' Water level at completion: 29.8' (inside hollowstem augers)												
34.2	508.0	2		14	23	16	0.5	Medium stiff gray SILT AND CLAY (A-6a), little fine to coarse sand; contains interbedded sand seams; moist.											
35									Medium dense to dense rusty brown COARSE AND FINE SAND (A-3a), little silt, trace to little gravel; damp.										
40		16		16	17	14													
45		5		6	9	16													
48.5	493.7							Severely weathered gray SILTSTONE fragments, arenaceous. Bottom of Boring - 48.9'											
48.9	493.3	50/5		5		16													
50																			
55																			
60																			

FILE: 0121-3070-03 [ 11/13/2007 6:11 PM ]

Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

**LOG OF: Boring B-1525**

Location: Sta. 16+39.4, 37.2 ft. LT of US 52 CL

Date Drilled: 11/9/05

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 28.5' Water level at completion: 47.2' (prior to coring) 18.8' (includes drilling water)	GRADATION						STANDARD PENETRATION (N) Natural Moisture Content, % - ● PL ————— LL Blows per foot - ○ 10 20 30 40
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay	
0	543.1						<p><b>DESCRIPTION</b></p> <p>Asphalt Concrete Pavement - 7" Aggregate Base - 5"</p> <p>Stiff brown SANDY SILT (A-4a), little clay, trace gravel; moist.</p> <p>Hard brown and gray SILT AND CLAY (A-6a), little fine to coarse sand, trace gravel; damp.</p> <p>Medium dense to dense brown FINE SAND (A-3), little coarse sand, trace gravel; damp.</p> <p>Very stiff brown and gray SILT AND CLAY (A-6a), little fine to coarse sand; contains occasional rust stains; moist.</p> <p>Medium dense brown SILT (A-4b), little fine to coarse sand; damp.</p> <p>Stiff to very stiff brown and gray SILT AND CLAY (A-6a), little fine to coarse sand; moist.</p> <p>Loose gray SANDY SILT (A-4a), trace clay; contains interbedded sand seams; moist.</p> <p>Medium dense brown FINE SAND (A-3); wet.</p>							
1.0	542.1	5 7 7	0	1										
3.5	539.6	7 6	15	2A	4.5									
4.7	538.4	13 16 22 26	13	2B										
		12 10 10	16	4										
11.0	532.1	8 6 5	11	5	2.75									
		3 5 8	15	6	3.25									
16.0	527.1	11 11 10	18	7										
18.5	524.6	2 3 4	15	8	2.25									
20		1 2 3	14	9	1.5									
23.5	519.6	2 4 4	18	10										
25		4 4 6	18	11										
28.5	514.6	7 10 20	16	12										
30														

FILE: 0121-3070-03 [ 11/13/2007 6:11 PM ]

Client: TranSystems, Inc. Project: SCI-823-0.00 Job No. 0121-3070.03  
 LOG OF: Boring B-1525 Location: Sta. 16+39.4, 37.2 ft. LT of US 52 CL Date Drilled: 11/9/05

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 28.5' Water level at completion: 47.2' (prior to coring) 18.8' (includes drilling water)	GRADATION						STANDARD PENETRATION (N) Natural Moisture Content, % - ● PL ————— LL Blows per foot - ○ 10 20 30 40						
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay							
30	513.1						Medium dense brown FINE SAND (A-3), little coarse sand, little gravel; wet.													
35		15 14 14	13			13														
40		7 13 16	18			14														
42.0	501.1							Medium dense brown COARSE AND FINE SAND (A-3a), trace silt, trace gravel; wet.												
45		5 6 7	12			15														
50		8 7 9	16			16														
53.5	489.6	50/5	4			17	Severely weathered gray SILTSTONE fragments, arenaceous.													
55.0	488.1						Medium hard to hard gray SANDSTONE; very fine to fine grained, slightly weathered, argillaceous, micaceous, massive, slightly to moderately fractured. @ 55.7', 56.9', 58.9', 59.4', low angle fractures. @ 57.5'-57.8', high angle fracture.													
60		Core 120"	Rec 120"	RQD 89%	R1															

FILE: 0121-3070-03 [ 11/13/2007 6:11 PM ]

Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

LOG OF: Boring B-1525

Location: Sta. 16+39.4, 37.2 ft. LT of US 52 CL

Date Drilled: 11/9/05

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 28.5' Water level at completion: 47.2' (prior to coring) 18.8' (includes drilling water)	GRADATION						STANDARD PENETRATION (N)						
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay	Natural Moisture Content, % - ●		Blows per foot - ○				
							DESCRIPTION						PL ————— LL							
													10 20 30 40							
60	483.1						Medium hard to hard gray SANDSTONE; very fine to fine grained, slightly weathered, argillaceous, micaceous, massive, slightly to moderately fractured. @ 60.3'-60.6', high angle fracture.													
65.0	478.1							Bottom of Boring - 65.0'												
70																				
75																				
80																				
85																				
90																				

FILE: 0121-3070-03 | 11/13/2007 6:11 PM |



Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

LOG OF: Boring B-1526

Location: Sta. 14+86.7, 36.9 ft. LT of US 52 CL

Date Drilled: 11/10/05

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 53.5' Water level at completion: 53.9' (inside hollowstem augers)	GRADATION						STANDARD PENETRATION (N) Natural Moisture Content, % - ● PL ————— LL Blows per foot - ○ 10 20 30 40							
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay								
30	513.3						Medium dense brown FINE SAND (A-3), trace silt, trace gravel; damp.														
35		4		4	8	12		13													
40		14		13	12	16		14													
45		6		7	8	15		15													
50		7		7	7	18		16													
52.0	491.3							Medium dense brown GRAVEL WITH SAND (A-1-b), "and" fine to coarse sand, trace silt; wet.													
55		6		6	8	16			17												
58.5	484.8	50/2		2				Severely weathered gray SILTSTONE fragments, arenaceous.													
58.7	484.6						18														
60																					50+

FILE: 0121-3070-03 [ 11/13/2007 6:11 PM ]





Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

LOG OF: Boring B-1527

Location: Sta. 13+26.9, 36.5 ft. LT of US 52 CL

Date Drilled: 11/10/05 to 11/15/05

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 8.5', 53.5' Water level at completion: 22.0' (11/14/06) 53.5' (inside hollowstem augers)	GRADATION						STANDARD PENETRATION (N) Natural Moisture Content, % - ● PL ————— LL Blows per foot - ○ 10 20 30 40
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay	
0	543.1						Asphalt Concrete Pavement - 8" Aggregate Base - 6"							
1.2	541.9	9			1A		Medium dense brown COARSE AND FINE SAND (A-3a), trace gravel; moist.							
1.5	541.6	5	14		1B	4.5								
3.5	539.6	3	13	14	2		Hard brown SILTY CLAY (A-6b), trace fine sand; moist.							
5		8	18	22	3		Medium dense to dense brown FINE SAND (A-3), trace to little gravel, trace coarse sand ; moist.  @ 8.5'-15.0', wet spoons.							
		9	13	13	4									
		5	8	7	5									
		3	10	14	6									
15														
16.0	527.1	3	5	7	7	4.5+	Hard brown SILT AND CLAY (A-6a), trace fine to coarse sand; moist.							
18.5	524.6	3	3	6	8	3.0	Very stiff to hard brown and gray SILTY CLAY (A-6b), trace fine to coarse sand; moist.							
20		3	4	5	9	4.25								
		2	4	5	10	3.25								
25														
		3	3	4	11	2.25	@ 26.0'-27.5', contains rust stains.							
28.5	514.6	3	4											
30		4	6	18	12	3.75	Very stiff brown SILT AND CLAY (A-6a), trace fine to coarse sand; contains rust stains; moist							

FILE: 0121-3070-03 | 11/13/2007 6:11 PM |

Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

**LOG OF: Boring B-1527**

Location: Sta. 13+26.9, 36.5 ft. LT of US 52 CL

Date Drilled: 11/10/05 to 11/15/05

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 8.5', 53.5' Water level at completion: 22.0' (11/14/06) 53.5' (inside hollowstem augers)	GRADATION						STANDARD PENETRATION (N) Natural Moisture Content, % - ● PL ——— LL Blows per foot - ○ 10 20 30 40				
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay					
30.0	513.1 513.1-						Medium dense brown COARSE AND FINE SAND (A-3a), little silt, trace gravel; moist.        Medium dense to dense brown FINE SAND (A-3), little silt, trace gravel; moist.       @ 53.5', 58.5', 2.0' sand heave.    @ 58.5', very dense.											
35		6 11 16	9		13													
38.5	504.6	5																
40		9 10	12		14													
45		4 5 7	18		15													
50		6 9 9	14		16													
55		16 34 15	18		17													
60		7 26 50/4	15		18													

FILE: 0121-3070-03 | 11/13/2007 6:11 PM

Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

LOG OF: Boring B-1527

Location: Sta. 13+26.9, 36.5 ft. LT of US 52 CL

Date Drilled: 11/10/05 to 11/15/05

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 8.5', 53.5' Water level at completion: 22.0' (11/14/06) 53.5' (inside hollowstem augers)	GRADATION						STANDARD PENETRATION (N) Natural Moisture Content, % - ● PL ——— LL Blows per foot - ○ 10 20 30 40
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay	
60	483.1						Loose brown FINE SAND (A-3), little silt, trace gravel; moist.  @ 63.5', 15.0' sand heave.  @ 68.5'-68.6', severely weathered gray SILTSTONE, arenaceous.  Medium hard to hard gray SANDSTONE; very fine to fine grained, slightly weathered, argillaceous, micaceous, medium bedded, slightly fractured. @ 68.7'-69.2', 69.5'-70.3', 70.6'-70.7', 75.5'-75.7', few argillaceous laminations. @ 70.0', 76.3', low angle fractures.							
65		4 2 1	12	19										
68.5	474.6	50/1	1	20										
70														
75		Core 120"	Rec 120"	RQD 93%	R1									
78.5	464.6													
80														
85														
90														





Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

LOG OF: Boring B-1528

Location: Sta. 11+77.5, 35.5 ft. LT of US 52 CL

Date Drilled: 11/16/05 to 11/17/05

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / * Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 53.5' Water level at completion: 58.5' (inside hollowstem augers)	GRADATION						STANDARD PENETRATION (N) Natural Moisture Content, % - ● PL ——— LL Blows per foot - ○					
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay						
60	482.6						Medium dense to dense brown FINE SAND (A-3), trace gravel; wet.												
65		8 9 13	16	19															
69.0 70	473.6	32 43 50/5	12	20A 20B				Very dense brown COARSE AND FINE SAND (A-3a), little silt, trace gravel; wet.											
73.5 73.7	469.1 468.9	50/2	2	21			Severely weathered gray SILTSTONE, arenaceous. Bottom of Boring - 73.7'												
75																			
80																			
85																			
90																			

FILE: 0121-3070-03 | 11/13/2007 6:11 PM |

Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

**LOG OF: Boring B-1529**

Location: Sta. 10+35.5, 35.3 ft. LT of US 52 CL

Date Drilled: 11/17/05 to 11/22/05

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 53.5' Water level at completion: 53.4'	GRADATION						STANDARD PENETRATION (N) Natural Moisture Content, % - ● PL ————— LL Blows per foot - ○ 10 20 30 40						
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay							
0	542.5																			
1.0	541.5	7			1A		Asphalt Concrete Pavement - 10" Aggregate Base - 2"													
2.0	540.5	5 8	12		1B	4.5+	POSSIBLE FILL: Medium dense brown FINE SAND (A-3), trace coarse sand; contains occasional silty clay pieces; damp.													
3.5	539.0	5			2		Hard brown and gray SILT AND CLAY (A-6a), some fine to coarse sand, trace gravel; damp.													
5		10 12	9				Medium dense brown COARSE AND FINE SAND (A-3a), little silt, trace gravel; moist.													
7.0	535.5	8 10	18		3A 3B	4.5+	Hard brown SILT AND CLAY (A-6a), some fine to coarse sand, trace gravel; damp.													
8.5	534.0	6 7	16		4		Medium dense brown COARSE AND FINE SAND (A-3a), little silt, trace gravel; moist.													
10		10																		
11.5	531.0	5 6	18		5A 5B	4.0	Hard brown SILTY CLAY (A-6b), little fine to coarse sand, trace gravel; damp.													
15		3 5	14		6	4.25														
15.5	527.0						Stiff brown SANDY SILT (A-4a), some fine to coarse sand, trace gravel; moist.													
16.5	526.0	4 6	18		7A 7B	4.5	Hard brown CLAY (A-7-6), little fine to coarse sand; moist.													
20		3 4	14		8	4.5+	@ 18.5'-20.0', gray, contains rust stains.													
21.0	521.5	3 5	18		9	4.5	Hard brown SILT AND CLAY (A-6a), little to some fine to coarse sand, trace gravel; contains rust stains; moist.													
25		2 3	18		10	0.75	@ 23.5'-27.5', medium stiff to stiff.													
28.5	514.0	3 4 5	18		11	1.25														
30		6 8 10	15		12		Medium dense brown FINE SAND (A-3); damp.													

FILE: 0121-3070-03 [ 11/13/2007 6:11 PM ]





Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

**LOG OF: Boring B-1529**

Location: Sta. 10+35.5, 35.3 ft. LT of US 52 CL

Date Drilled: 11/17/05 to 11/22/05

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 53.5' Water level at completion: 53.4'	GRADATION						STANDARD PENETRATION (N) Natural Moisture Content, % - ● PL ————— LL Blows per foot - ○ 10 20 30 40						
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay							
60	482.5						Loose brown FINE SAND (A-3); wet.													
65		WOH 2 5	18	19																
67.0	475.5							Loose brown COARSE AND FINE SAND (A-3a), trace silt, trace gravel; wet.												
70		WOH 3 4	18	20																
73.5	469.0	26 50/5	8	21			Hard gray SILT AND CLAY (A-6a), little fine to coarse sand, little gravel; damp. (DECOMPOSED SILTSTONE) Hard gray SANDSTONE; very fine to fine grained, slightly to moderately weathered, argillaceous, micaceous, massive, slightly fractured. @ 75.3', 77.3', 77.8', low angle fractures.													
75.0	467.5																			
80		Core 120"	Rec 120"	RQD 76%	R1															
85.0	457.5						Bottom of Boring - 85.0'													
90																				

FILE: 0121-3070-03 [ 11/13/2007 6:11 PM ]

Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

**LOG OF: Boring B-1530**

Location: Sta. 8+95.4, 33.9 ft. LT of US 52 CL

Date Drilled: 12/07/05 to 12/08/05

Depth (ft)	Elev. (ft)	Blows per 6"		Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 1.5'-4.0', 53.5'-75.0' Water level at completion: 65.5' (inside hollowstem augers)	GRADATION						STANDARD PENETRATION (N)		
		Recovery (in)	Drive	Press / Core	DESCRIPTION			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay	Natural Moisture Content, % - ●	PL ——— LL	
0	542.1															
1.2	540.9	7	8	16	14	1	Asphalt Concrete Pavement - 8" Aggregate Base - 6"									
4.0	538.1	3	9	10	12	2A 2B	Medium dense brown COARSE AND FINE SAND (A-3a), little gravel, trace clay; moist.									
5							4.5+ Hard brown SILT AND CLAY (A-6a), little fine to coarse sand, little gravel; damp.									
6.0	536.1	16	15	13	15	3	Medium dense brown COARSE AND FINE SAND (A-3a), little gravel, trace silt; moist.	16	26	--	45	13	●			
8.5	533.6	5	5	8	16	4	4.5+ Hard brown SILTY CLAY (A-6b), trace fine to coarse sand; damp.									
10																
11.0	531.1	5	6	10	18	5	3.25 Very stiff brown SANDY SILT (A-4a), little clay, trace gravel; damp.	6	7	--	32	32	23	●		
13.5	528.6	4	6	10	16	6	4.5+ Hard brown SILTY CLAY (A-6b), trace fine sand, trace gravel; dry to damp.									
15																
18.5	523.6	3	3	4	16	8	3.5 Very stiff brown SILT AND CLAY (A-6a), trace fine to coarse sand; damp.									
20																
21.0	521.1	3	4	5	18	9	1.0 Stiff brown SANDY SILT (A-4a), trace to little clay; damp.									
23.5	518.6	4	4	4	15	10	Loose brown SANDY SILT (A-4a), little clay, trace gravel; damp.	5	5	--	46	29	15	●		
25																
27.0	515.1	4	6	9	18	11A 11B	1.5 Loose to medium dense brown COARSE AND FINE SAND (A-3a), trace clay, trace silt; damp.									
30		4	4	8	13	12										

FILE: 0121-3070-03 [ 11/13/2007 6:11 PM ]

Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

**LOG OF: Boring B-1530**

Location: Sta. 8+95.4, 33.9 ft. LT of US 52 CL

Date Drilled: 12/07/05 to 12/08/05

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 1.5'-4.0', 53.5'-75.0' Water level at completion: 65.5' (inside hollowstem augers)	GRADATION						STANDARD PENETRATION (N)			
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay	PL	LL		
30.0	512.1						Medium dense brown GRAVEL WITH SAND (A-1-b), trace silt; damp.  @ 33.5' some gravel.										
	512.1	6						25	55	-	16	4					
35		10	10														
		12															
40		4															
		6	13														
45		4															
		6	12														
47.0	495.1						Loose to medium dense brown COARSE AND FINE SAND (A-3a), trace silty clay, trace gravel; damp.  @ 53.5', wet, contains rock fragments.										
		4						2	45	-	50	3					
50		5	15														
		7															
55		6															
		9	18														
		13															
60		WOH															
		2	18														
		5															

FILE: 0121-3070-03 [ 11/13/2007 6:11 PM ]

Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

LOG OF: Boring B-1530

Location: Sta. 8+95.4, 33.9 ft. LT of US 52 CL

Date Drilled: 12/07/05 to 12/08/05

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 1.5'-4.0', 53.5'-75.0' Water level at completion: 65.5' (inside hollowstem augers)	GRADATION						STANDARD PENETRATION (N) Natural Moisture Content, % - ● PL ——— LL Blows per foot - ○ 10 20 30 40				
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay					
60	482.1						Loose to medium dense brown COARSE AND FINE SAND (A-3a), trace silty clay, trace gravel; damp.											
65		12 8 11	16	19														
70		2 3 5	18	20														
75		5 15 50/5	13	21		@ 73.5', little gravel.			14	16	--	57	13					Non-Plastic 50+
77.0	465.1						Severely weathered gray SILTSTONE.											
78.7	463.4	50/2	2	22			Bottom of Boring - 78.7'											50+
80																		
85																		
90																		

FILE: 0121-3070-03 [ 11/13/2007 6:11 PM ]



Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

LOG OF: Boring B-1531

Location: Sta. 7+30.5, 32.2 ft. LT of US 52 CL

Date Drilled: 12/09/05 to 12/14/05

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 23.5'-25.8', 33.5'-35.0', 48.5'-75.0' Water level at completion: 50.1' (prior to coring) 48.0' (includes drilling water)	GRADATION						STANDARD PENETRATION (N) Natural Moisture Content, % - ● PL ————— LL Blows per foot - ○ 10 20 30 40					
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay						
30	511.8						Loose to medium dense brown FINE SAND (A-3), trace to little silt, trace coarse sand; damp.												
35		8 10 13	11		13														
38.5	503.3						Medium dense brown COARSE AND FINE SAND (A-3a), trace gravel; damp.												
40.0	501.8	2 4	7 15		14														
45		4 4 5	14		15		Loose to medium dense brown FINE SAND (A-3), trace coarse sand, trace gravel; damp to wet.												
50		5 8 11	14		16														
55		3 10 15	15		17														
60		3 7 17	1813		18														

Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

LOG OF: Boring B-1531

Location: Sta. 7+30.5, 32.2 ft. LT of US 52 CL

Date Drilled: 12/09/05 to 12/14/05

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetro- meter (tsf) / * Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 23.5'-25.8', 33.5'-35.0', 48.5'-75.0' Water level at completion: 50.1' (prior to coring) 48.0' (includes drilling water)	GRADATION						STANDARD PENETRATION (N) Natural Moisture Content, % - ● PL ————— LL Blows per foot - ○ 10 20 30 40					
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay						
60	481.8						Loose to medium dense brown FINE SAND (A-3), trace coarse sand, trace gravel; damp to wet.												
65		3	12	1	19														
70		6	8	3	20														
75		13	18	16	21														
78.5	463.3	50/2	2		22		Severely weathered gray SHALE.												
81.0	460.8						Hard gray SANDSTONE; very fine to fine grained, slightly to moderately weathered, argillaceous, micaceous, massive, slightly fractured. @ 81.3'-81.4', 83.0'-83.2', ferric bands.												
85		Core 120"	Rec 120"		RQD 96%	R-1	@ 85.7'-86.1', calcareous.  @ 87.2'-87.3', argillaceous zone. @ 87.3', low angle fracture.												
90																			

FILE: 0121-3070-03 | 11/13/2007 6:11 PM |





Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

**LOG OF: Boring B-1532**

Location: Sta. 5+85.5, 26.3 ft. LT of US 52 CL

Date Drilled: 12/20/05 to 12/21/05

Depth (ft)	Elev. (ft)	Blows per 6"		Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 6.0'-7.5', 33.5'-35.0', 48.5'-75.0' Water level at completion: 43.0' (prior to coring)	GRADATION						STANDARD PENETRATION (N) Natural Moisture Content, % - ● PL ——— LL Blows per foot - ○ 10 20 30 40					
		Drive	Press / Core	Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay						
0	541.5						Asphalt - 6", Portland Cement Concrete - 3", Asphalt - 5"												
1.2	540.3	3		1			Medium dense to dense brown COARSE AND FINE SAND (A-3a), trace silt and clay, trace gravel; damp.												
		6	25	6															
		9	17	8	12	2													
5																			
		13	21	17	15	3													
8.5	533.0	6	4	7	14	4	4.25	Very stiff to hard brown SILT AND CLAY (A-6a), trace fine to coarse sand, trace gravel; damp.											
10		5	6	7	13	5	3.0												
		1	5	7	16	6	4.5+												
15		4	6	8	11	7	4.5+												
		3	3	5	14	8	4.5+												
		5	5	8	10	9	4.5+												
20		2	4	4	13	10	2.5												
		3	3	4	9	11	1.75												
26.0	515.5	2	3	4	9	12	2.0		Stiff brown SILT AND CLAY (A-6a), trace fine to coarse sand, trace gravel; damp.										
		1	2	4	13	12	2.0												
30																			

FILE: 0121-3070-03 [ 11/13/2007 6:11 PM ]



Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

**LOG OF: Boring B-1532**

Location: Sta. 5+85.5, 26.3 ft. LT of US 52 CL

Date Drilled: 12/20/05 to 12/21/05

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: 6.0'-7.5', 33.5'-35.0', 48.5'-75.0' Water level at completion: 43.0' (prior to coring)	GRADATION						STANDARD PENETRATION (N) Natural Moisture Content, % - ● PL ——— LL Blows per foot - ○ 10 20 30 40				
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay					
60	481.5						Loose to medium dense brown COARSE AND FINE SAND (A-3a), trace gravel; moist to wet.  @ 63.5'-70.0', 2.0'-3.0' sand heave.          @ 73.5'-74.5', very dense, wet.											
65		4	1	5	12	19												
70		1	3	2	5	20												
74.5	467.0	8	13	50/5	16	21A 21B		Severely weathered gray SHALE.										
76.0	465.5						Medium hard to hard gray SANDSTONE; very fine to fine grained, slightly to moderately weathered, argillaceous, micaceous, thickly bedded to massive, slightly to moderately fractured. @ 76.5'-76.8', high angle fracture. @ 80.0'-80.1', decomposed zone. @ 80.1', low angle fracture. @ 82.3'-82.4', ferric band.											
80		Core 120"	Rec 120"			RQD 84% R-1												
86.0	455.5							Bottom of Boring - 86.0'										

FILE: 0121-3070-03 [ 11/13/2007 6:11 PM ]

Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

LOG OF: Boring B-1533

Location: Sta. 9+86.2, 28.4 ft. LT of US 52 CL

Date Drilled: 8/16/06

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / * Point-Load Strength (psi)	WATER OBSERVATIONS:	GRADATION						STANDARD PENETRATION (N)		
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay	PL	LL	
0	542.6						Water seepage at: 3.0'-9.5' Water level at completion: 8.9'									
1.3	541.3						Asphalt Concrete - 7" Portland Cement Concrete - 9"									
3.0	539.6	8 16 27 30 32 39	18	1A 1B		--	FILL: Medium stiff brown SILT AND CLAY (A-6a), some fine to coarse sand, trace gravel; damp. @ 2.8'-3.0', sand seam.	8 13	14 28	-- --	22 53	28 6	28	●	●	Non-Plastic
4.5	538.1	20 24 29	14	2			FILL: Very dense brown GRAVEL WITH SAND (A-1-b), trace silty clay; damp.	27	30	--	34	6 3	3	●	●	Non-Plastic
6.0	536.6	21 28 14	18	3 4			FILL: Very dense brown GRAVEL WITH SAND AND SILT (A-2-4), little silty clay; damp. FILL: Dense brown GRAVEL WITH SAND (A-1-b), trace silty clay; damp.	25 36	23 31	-- --	35 26	11 7	6	● ●	● ●	Non-Plastic Non-Plastic
8.5	534.1	12					POSSIBLE FILL: Medium dense brown COARSE AND FINE SAND (A-3a); damp.									
9.5	533.1	4	18	5A		2.0	POSSIBLE FILL: Stiff to very stiff brown SILT AND CLAY (A-6a), trace fine sand; damp.									
10.0	532.6	6		5B			Bottom of Boring - 10.0'									

FILE: 0121-3070-03 | 11/13/2007 6:11 PM |





Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

**LOG OF: Boring B-1536**

Location: Sta. 13+75.3, 29.3 ft. RT of US 52 CL

Date Drilled: 10/11/06

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: None Water level at completion: None	GRADATION						STANDARD PENETRATION (N) Natural Moisture Content, % - ● PL ————— LL Blows per foot - ○ 10 20 30 40						
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay							
0	543.4																			
							Asphalt Concrete Pavement - 8" Aggregate Base - 8"													
1.3	542.1	5			1	2.5	Very stiff dark brown SANDY SILT (A-4a), some gravel, little clay; damp.	21	20	--	21	20	18							
3.0	540.4	3	11	18	2	3.75	Very stiff brown SILT AND CLAY (A-6a), little fine to coarse sand, trace gravel; damp to moist.	3	6	--	9	43	39							
5.0	538.4	3	7	24	3		Medium dense brown FINE SAND (A-3), some coarse sand, little gravel, trace silt, trace clay; dry to damp.	12	27	--	51	4	6							
7.5	535.9	5	8	24			Stiff brown SILTY CLAY (A-6b), "and" fine to coarse sand; moist.													
10.0	533.4	19	18	2	4	1.25														
							Bottom of Boring - 10.0'													

FILE: 0121-3070-03 [ 11/13/2007 6:11 PM ]



Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

LOG OF: Boring B-1537

Location: Sta. 17+59.1, 29.5 ft. RT of US 52 CL

Date Drilled: 10/11/06

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: None Water level at completion: None	GRADATION						STANDARD PENETRATION (N) Natural Moisture Content, % - ● PL ——— LL Blows per foot - ○ 10 20 30 40					
				Drive	Press / Core			DESCRIPTION	% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt		% Clay				
0	543.5																		
-1.1	542.4	2				4.5+	Asphalt Concrete Pavement - 6" Aggregate Base - 7"												
		3					Hard brown SILTY CLAY (A-6b), little fine to coarse sand, trace gravel; damp.	1	8	--	7	40	44						
		5																	
-3.0	540.5	9	24				Medium dense brown COARSE AND FINE SAND (A-3a), little gravel, little silt, trace to little clay; damp.	18	26	--	32	14	10						
		9					Stiff brown and gray SILT AND CLAY (A-6a), little fine to coarse sand, trace gravel; moist.												
		8																	
-5.0	538.5	9	24			1.75		3	9	--	10	38	40						
		3					Medium dense brown GRAVEL WITH SAND AND SILT (A-2-4), trace clay; damp to moist.												
		4																	
-7.5	536.0																		
		4																	
		6																	
		14																	
-10.0	533.5	22	24				Bottom of Boring - 10.0'												

FILE: 0121-3070-03 [ 11/13/2007 6:11 PM ]

Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

**LOG OF: Boring B-1538**

Location: Sta. 21+65.7, 29.8 ft. RT of US 52 CL

Date Drilled: 10/11/06

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: None Water level at completion: None	GRADATION						STANDARD PENETRATION (N) Natural Moisture Content, % - ● PL ——— LL Blows per foot - ○					
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay						
0	543.3																		
1.1	542.2	3			1		Asphalt Concrete Pavement - 8" Aggregate Base - 5"												
		3 6 9	24		2		Loose to medium dense brown GRAVEL WITH SAND (A-1-b), trace silt; dry to damp.	40	27	--	31	2							
		4 11 11	24		3	4.5+		Hard brown SILTY CLAY (A-6b), little fine to coarse sand; damp.	0	2	--	13	48	37					
5.0	538.3	3			3		Medium dense brown GRAVEL WITH SAND, SILT, AND CLAY (A-2-6); damp to moist.												
		5 6 11	24		4			Bottom of Boring - 10.0'											
7.5	535.8																		
		6 14 13 9	24																
10.0	533.3																		
15																			
20																			
25																			
30																			


FILE: 0121-3070-03 [ 11/13/2007 6:11 PM ]















SCI-823-0.00

SOIL PROFILE - US 52 RAMP A  
 STA. 41+00.00 TO STA. 54+11.247

DRAWN  
 RLS  
 CHECKED  
 AEN






SCI-823-0.00

SOIL PROFILE - US 52 RAMP B  
 STA. 16+44.851 TO STA. 41+00.000

CAD/ANALYST  
 RLS  
 CHECKED  
 AEN



SCI-823-0.00

SOIL PROFILE U.S. 52 RAMP B  
 STA. 41+00.00 TO STA. 54+11.247

DRAWN  
 RLS  
 CHECKED  
 AEN





ENGINEERS • ARCHITECTS • SCIENTISTS  
PLANNERS • SURVEYORS

August 22, 2006

Michael D. Weeks, P.E., P.S.  
TranSystems Corporation  
5747 Perimeter Drive, Suite 240  
Dublin, OH 43017

Re: **Pavement Design Information**  
**SR 140 Improvements and Widening**  
SCI-823-0.00 Portsmouth Bypass  
DLZ Job No.: 0121-3070.03  
Document # 0028

Dear Mr. Weeks:

This letter includes the findings of a subsurface exploration performed for the SR 140 improvement and widening near the intersection of proposed SR 823. The findings included in this letter pertain to SR 140 only. The findings of other subsurface explorations for pavement design will be submitted in separate documents.

The improvements will essentially consist of regrading and widening approximately 1125 feet of existing SR 140 from station 4+45 to 15+70. Plan and profile drawings indicate that the proposed grade will be essentially at existing grade. Additionally, a turn lane will be added to the north side of SR 140. See attached plan drawing for more information.

The recommendations presented in this report have been made on the basis of the foregoing information. If the proposed improvements or concept is changed or differs from that assumed, DLZ Ohio, Inc. (DLZ) should be informed of the changes so that recommendations and conclusions presented in this letter may be revised as necessary.

The results of these evaluations are based upon the findings of five subgrade borings. Borings B-1401, B-1402, and B-1404 were drilled on January 25 and January 26, 2006. Borings B-1403A and B-1405A were drilled on July 26, 2006. All borings were drilled using a truck mounted rotary-type drill rig. Borings were planned and staked in the field by representatives of DLZ. The surveyed locations and ground surface elevations of the borings were determined by representatives from Lockwood, Lanier, Mathias & Noland, Inc. (2LMN). Borings were advanced to depths between 6.0 and 11.0 feet. Continuous sampling was performed from below the pavement layers to approximately 6.0 feet below the ground surface to evaluate the subgrade soil properties. See attached Boring Plan and Boring Logs.

All borings were drilled within the travel lanes of SR 140. Borings B-1401 and B-1402 encountered 3.5 to 4 inches of asphalt concrete pavement over 9 inches of portland cement concrete. Below the pavement layers, boring B-1401 first encountered sandy silt (A-4a) over

Michael D. Weeks, P.E., P.S.  
August 22, 2006  
Page 2

gravel with sand and silt (A-2-4). Also below the pavement layers, boring B-1402 first encountered sandy silt (A-4a) over silt (A-4b). Additionally, borings B-1403A and B-1405A encountered 12 to 14 inches of asphalt concrete pavement, over 6 inches of red brick pavers, over 4 inches of aggregate base. Below the pavement layers, boring B-1403A first encountered gravel with sand and silt (A-2-4) over silt (A-4b). Also, below the pavement layers, boring B-1405A first encountered silt (A-4b) over sandy silt (A-4a). Boring B-1404 encountered 11 inches of asphalt concrete pavement. No well-defined aggregate base layer was observed in borings B-1401, B-1402, and B-1404. Below the pavement layer, boring B-1404 first encountered sandy silt (A-4a) to a depth of 10.0 feet.

Seepage was encountered in borings B-1401, B-1403A, and B-1405A. Observed seepage was first encountered in borings from 4.0 to 7.0 feet below ground surface. No groundwater was observed in the borings upon completion of drilling.

### **Pavement Design Information**

It is anticipated that the majority of the project will be at grade with the widening portion requiring small fill sections within five feet of existing grade. Table 1 below lists the subgrade soils encountered by the borings and the group indices, CBR values, and number of samples tested for each soil type.

**Table 1: Subgrade Soils**

ODOT Classification	Group Index	CBR	No. Samples Tested
Gravel with Sand and Silt (A-2-4)	0	13	2
Sandy Silt (A-4a)	3	9	9
Silt (A-4b)	7	7	4

Based upon averaging the results of the laboratory testing, a CBR value of 9 is recommended for pavement design.

Silt (A-4b) was encountered in four out of five borings drilled for this project. Of the four borings, two of them encountered silt (A-4b) within the upper three feet of existing grade. As per GB-1 "Plan Subgrades", when silt (A-4b) soil is encountered in natural ground or an existing embankment within 3 feet of top of subgrade, regardless of its consistency or moisture content, it shall be removed or chemically stabilized because of its susceptibility to frost heaving.

Michael D. Weeks, P.E., P.S.  
August 22, 2006  
Page 3

**Subgrade Condition and Preparation**

The existing subgrade soils along the project were evaluated for suitability according to the ODOT Geotechnical Bulletin GB-1 “Plan Subgrade.” The optimum moisture content (MC) for each soil tested was estimated using the following criteria:

- Optimum MC = plastic limit minus 3 (A-7-6 soils)
- = plastic limit minus 5 (A-4 and A-6 soils)
- = 6 to 10 (granular soils)
- = 11 (non-plastic silts)

The results of this evaluation are presented in the attached spreadsheet. Note only samples within six feet of the proposed grade were evaluated. According to the referenced guidelines, any soils with moisture contents that exceed the optimum moisture content by three or more percentage points will likely require some form of subgrade treatment. In addition, any soils with standard penetration values (N-Values) of 10 or less will also likely require some form of subgrade treatment.

To determine the appropriate option, the average standard penetration value (N-value) and the plasticity index (PI) of the subgrade soils were considered. The average N-value, PI, moisture content, and CBR are presented in Table 2 below.

**Table 2**

Percent of Samples Over Optimum MC + 3 Percent	Average N <sub>L</sub> *	Average PI	Average MC	CBR Average
33	7.6	6.8	14.9	9

\* - N<sub>L</sub> indicates lowest standard penetration value (N) in subgrade soil.

Based on GB-1 guidelines, cement treatment is the preferred stabilization option for soils with average N-values less than 10 and an average PI less than 20, as encountered on SR 140. In lieu of complete removal using undercutting and replacement with granular material, all silt (A-4b) encountered within 3.0 feet of top of subgrade will require cement stabilization. In addition, cement stabilization is also an option for stabilizing weak or soft soils encountered across the project. Consequently, it is recommended that the entire project area be treated with cement to a depth of 16 inches.

Another subgrade stabilization option that could be considered is to undercut the weak, soft or unsuitable soils and replace the subgrade with compacted Type B or C granular material (ODOT

Michael D. Weeks, P.E., P.S.  
August 22, 2006  
Page 4

Item 703.16.C). If cement stabilization is not selected as an option on this project, the silt (A-4b) will have to be completely removed from the top 3 feet of proposed subgrade. As an alternative to cement stabilization, it is recommended that subgrade soils be undercut in areas and to depths indicated in Table 3 below.

**Table 3: Undercut and Replace Option**

Begin Station	End Station	Depth of Undercut
4+45	9+00	2.0'
9+00	15+70	3.0'


For both options recommended for this site, the subgrade treatment should be extended to 18 inches beyond the edge of pavement, paved shoulders, or paved medians.

Seepage was first encountered in the borings from 4.0 to 7.0 feet. No groundwater was noted in any of the borings. Although no groundwater was encountered in the borings, the contractor should be prepared to maintain reasonable dry excavations if water from seepage or precipitation enters any excavations.


We appreciate having the opportunity to be of service to you on this project. Please do not hesitate to call if you have any questions concerning our findings.

Respectfully submitted,


**DLZ OHIO, INC.**



Steven J. Riedy  
Geotechnical Engineer




Dorothy A. Adams, MSCE, P.E.  
Senior Geotechnical Engineer



Encl: As noted


cc: file



S.R. 140 - STA. 3+00 TO STA. 17+1+74

END RAMP A  
 STA. 78+21.61


END RAMP B  
 STA. 82+92.08




SCI-823-0.00

**BORING PLAN**  
**S.R. 140 INTERCHANGE**

CAD/AMVED  
 RLS  
 CHECKED  
 AEN













Client: TranSystems, Inc.

Project: SCI-823-0.00


Job No. 01273070.03

**LOG OF: Boring B-1404**

Location: Sta. 13+01.1, 27.2 ft. RT of SR 140 CL

Date Drilled: 01/26/06

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: None Water level at completion: None	GRADATION						STANDARD PENETRATION (N)		
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay	Natural Moisture Content, % - ●	Blows per foot - ○	
0	561.1															
0.9	560.2	3				0.5	Asphalt Concrete Pavement - 11"									
		4	6	1		0.5	POSSIBLE FILL: Soft to medium stiff brown SANDY SILT (A-4a), little to some gravel, trace to little clay; damp to moist.	20	18	--	19	35	9	●		
		2		2		0.5		18	12	--	12	40	18	○		
		3		3		0.5	@ 4.0'-5.0', "and" gravel.	44	10	--	10	26	11	●		
5		3	2	3		0.5	Very stiff mottled brown and gray SANDY SILT (A-4a), little gravel; damp to moist.	11	16	--	17	39	17	●		
6.0	555.1	4	16	4		2.5		11	16	--	17	39	17	○		
		5		5		2.5	Loose to medium dense brown SANDY SILT (A-4a), trace clay; damp to moist.							○		
		3	12	5		2.5								○		
9.0	552.1	8		6			Bottom of Boring - 10.0'							○		
10.0	551.1	9	7	6										○		



Non-Plastic

L:\001\_VARS\0610-03\_1\_17121001\_3105 EN 1



**Soil Investigation Summary**

Do NOT Rubblize & Roll  
Global CS may be an option  
Global LS is NOT an option

Design CBR is 9

Number of Borings = 5

Classification Counts by Sample															
R	1a	1b	3	3a	2-4	2-5	2-6	2-7	4a	4b	5	6a	6b	7-5	7-6
0	0	0	0	0	2	0	0	0	9	4	0	0	0	0	0
13%									60% 27%						
0.0%									86.7%						

Class @ Surface	
2-5	0
4b	1 20%
5	0
7-5	0
7-6	0
R	0

% Borings	
N <sub>1</sub> < 10	40%
N <sub>1</sub> < 10	80%
N <sub>1</sub> < 20	0%
M+	60%

% @ Surface	
60%	
20%	40%
% Borings	
100%	

	N		N <sub>L</sub>		PI		M		M <sub>OPT</sub>		GI
Average	14.1	7.6	6.8	12.7	14.9	12.5	3.53				
Maximum	60	14	31	21	10	71	31	95	28	16	8
Minimum	5	5	22	15	2	22	6	28	6	10	0

80%	80%	0%	60%	80%	80%
-----	-----	----	-----	-----	-----

SCI-823-0.00		SR 140 (Webster Street)				Standard Penetration										Physical Characteristics				Moisture		Classification		Comments
#	B #	Boring Location	Depth	To	Cut Fill	n <sub>2</sub>	n <sub>3</sub>	N	N <sub>L</sub>	LL	PL	PI	% Silt	% Clay	P 200	M	M <sub>OPT</sub>	Class	GI					
1	1401	4+43, 7'Lt.	1.0	3.0		8	8	16		28	18	10	32	10	42	8	13	4a	1					
			3.0	5.0		4	3	7		28	18	10	26	9	35	11	10	2-4	0					
			5.0	7.0		5	10	15		23	17	6	53	12	65	12	12	4b	6					
									7															
2	1402	6+87, 7'Rt.	1.0	2.0		3	4	7		25	16	9	37	15	52	10	11	4a	3					
			2.0	4.0		5	12	17		23	21	2	33	8	41	12	16	4a	1					
			4.0	6.0		4	5	9		31	21	10	64	31	95	25	16	4b	8					
									7															
3	1403A	10+76, 6'Rt.	1.5	3.0		14	10	24		NP	NP	NP	22	6	28	6	10	2-4	0					
			3.0	4.5		3	2	5		NP	NP	NP	71	11	82	28	11	4b	8					
			4.5	6.0		5	7	12		24	20	4	41	10	51	15	15	4a	3					
									5															
4	1404	12+99, 15'Rt.	1.0	2.0		3	4	7		NP	NP	NP	35	9	44	15	11	4a	5					
			2.0	4.0		3	2	5		24	15	9	40	18	58	19	10	4a	5					
			4.0	5.0		3	3	6		24	17	7	26	11	37	15	12	4a	0					
			5.0	7.0		3	4	7	5	26	18	8	39	17	56	18	13	4a	4					
									5															
5	1405A	13+88, 7'Lt.	2.0	4.0		9	5	14		22	19	3	52	12	64	16	14	4b	6					
			4.0	5.0		30	30	60		22	19	3	40	11	51	14	14	4a	3					
									14															

Problem	
w/ Class	w/ MN

Treatments			
LS	CS	UC Class	UC MN

4b	N		16	3	2
4b	MN		16	3	2
4b	MN		--	3	5
	MN		16		3
	MN		--		5
	N		16		3
	MN		16		3
4b				3	

### III.C. Subgrade Checklist

C-R-S: SC-823-0.00 SR 140

PID: 77366

Reviewer: AMJ

Date: 11-16-2007

If you do not have any subgrade work on the project, you do not have to fill out this checklist.

<u>Y</u> N X	1	Has the subsurface investigation adequately characterized the soil or rock according to <u>Geotechnical Bulletin 1: Plan Subgrades (GB1)</u> ?	
<u>Y</u> N X	2	If soils classified as A-2-5, A-4b, A-5, or A-7-5 are present at the proposed subgrade (soil profile), do the plans specify that these materials need to be removed and replaced?	
<u>Y</u> N X	a	If these materials are to be removed and replaced, have the station limits, depth, and lateral limits for the planned removal been provided?	
Y <u>N</u> X	3	If there is any rock, shale, or coal present at the proposed subgrade (CMS 204.05), do the plans specify the removal of the material?	
Y N <u>X</u>	a	If removal of any rock, shale, or coal is required, have the station limits, depth, and lateral limits for the planned removal of the material at proposed subgrade been provided?	
<u>Y</u> N X	4	In accordance with GB1, do the SPT values and existing moisture contents for the proposed subgrade soils indicate the need for subgrade stabilization?	
Y <u>N</u> X	a	If removal and replacement is applicable, has the detail of subgrade removal been shown on the plans, including depth of removal, station limits, lateral extent, replacement material, and plan notes (Item 204 - Subgrade Compaction and Proof Rolling)?	Refer to roadway cross-sections.
Y N <u>X</u>	b	If chemical stabilization is applicable, has the detail of this treatment been shown on the plans, including depth, percentage of chemical, station limits, lateral extent, and plan notes?	
		Indicate type of subgrade treatment specified:	GB-1 recommends cement treatment or undercutting. Undercutting was recommended for subgrade treatment.
		9 <u>cement treatment</u> 9 lime treatment	
		9 other List Other items:	
<u>Y</u> N X	5	If drainage or groundwater is an issue with the proposed subgrade, has an appropriate drainage system (e.g., pipe, underdrains) been provided?	Refer to roadway cross-sections.
Y N <u>X</u>	6	Has an appropriate quantity of Proof Rolling been included in the plans (CMS 204.06)?	Refer to roadway cross-sections.
<u>Y</u> N X	7	Has a design CBR value been provided?	







November 16, 2007

Michael D. Weeks, P.E., P.S.  
TranSystems Corporation  
5747 Perimeter Drive, Suite 240  
Dublin, OH 43017

**Re: Pavement Design Information  
Pershing Avenue  
SCI-823-0.00 Portsmouth Bypass  
DLZ Job No.: 0121-3070.03  
Document # 0099**

Dear Mr. Weeks:

This letter includes the findings of a subsurface exploration performed for the subgrade of Pershing Avenue. The findings in this letter pertain to the realignment and resurfacing of Pershing Avenue to accommodate the proposed embankment and bridge structure associated with the construction of SCI-823. Note that the stationing used in the report is referenced to the centerline of Pershing Avenue unless noted otherwise. Subsurface explorations were performed for the other features of the project but the results are presented in separate reports.

According to the information provided, approximately 1260 feet of Pershing Avenue will be realigned. The intersection of North Pershing Avenue will be realigned to intersect with Slocum Avenue approximate 90 feet southeast of the current intersection, while the intersection of South Pershing Avenue will be relocated 280 feet northwest. See the attached boring plan for more information. The recommendations presented in this report have been made on the basis of the foregoing information. If the proposed improvements or concept is changed or differs from that assumed, DLZ Ohio, Inc. (DLZ) should be informed of the changes so that recommendations and conclusions presented in this letter may be revised as necessary.

The results of these evaluations are based upon the findings of five borings. Borings B-1601, B-1604, B-1605 and B-1606 were drilled on January 10, 2006, while boring B-1602 was drilled on January 17, 2007. All borings were drilled using an ATV mounted, rotary-type drill rig. Borings were planned and staked in the field by representatives of DLZ. The surveyed locations and ground surface elevations of the borings were determined by representatives from Lockwood, Lanier, Mathias & Noland, Inc. (2LMN). Borings were advanced to depths between 6.0 and 10.0 feet. The borings were continuously sampled below the pavement layers to approximately 6.0 feet below the ground surface to evaluate the subgrade soil properties. See the attached boring logs for more information

The station and offsets for all the borings are listed on the attached GB-1 spreadsheet and boring logs. Four of the borings were drilled on the asphalt pavement of Pershing Avenue or Slocum

Michael D. Weeks, P.E., P.S.

November 16, 2007

Page 2

Avenue, while B-1602 was drilled off the road at station 17+7.5. Borings drilled in the road surface encountered 5 to 10 inches of asphalt concrete pavement over 3 to 9 inches of aggregate base. Boring B-1602 encountered 4 inches of topsoil.

Below the pavement layers, boring B-1601 encountered very stiff brown silt (A-4b), clay (A-7-6), and silt and clay (A-6a). Below the topsoil, boring B-1602 encountered stiff to very stiff brown silt (A-4b), sandy silt (A-4a), and clay (A-7-6). B-1604 encountered stiff brown clay (A-7-6) and elastic clay (A-7-5) beneath the asphalt layer. Below the asphalt layers, B-1605 encountered stiff silt and clay (A-6a), while boring B-1606 encountered sandy silt (A-4a) over stiff silty clay (A-6b).

### **Pavement Design Information**

It is anticipated that the majority of the project will be at grade with a portion of South Pershing Avenue requiring a small fill section along the proposed realignment. See the attached profile sheets for more information. The table below lists the subgrade soils encountered by the borings and the group indices, CBR values, and number of samples tested for each soil type.

<b>ODOT Classification</b>	<b>Group Index</b>	<b>CBR</b>	<b>No. Samples Tested</b>
Sandy Silt (A-4a)	8	7	1
Silt (A-4b)	8	7	1
Silt and Clay (A-6a)	10	6	3
Silty Clay (A-6b)	11	6	2
Elastic Clay (A-7-5)	12	5	1
Clay (A-7-6)	12	5	5

Based upon the average results of the laboratory testing, a CBR value of 6 is recommended for pavement design.

### **Subgrade Condition and Preparation**

The existing subgrade soils along the project were evaluated for suitability according to the ODOT Geotechnical Bulletin GB-1 "Plan Subgrade." The optimum moisture content (MC) for each soil tested was estimated using the following criteria:

- Optimum MC = plastic limit minus 3 (A-7-6 soils)
- = plastic limit minus 5 (A-4 and A-6 soils)
- = 6 to 10 (granular soils)

Michael D. Weeks, P.E., P.S.

November 16, 2007

Page 3

= 11 (non-plastic silts)

The results of this evaluation are presented in the attached spreadsheet. Note only samples within six feet of the proposed grade were evaluated. According to the referenced guidelines, any soils with moisture contents that exceed the optimum moisture content by three or more percentage points will likely require some form of subgrade treatment. In addition, any soils with standard penetration values (N-Values) of 10 or less will also likely require some form of subgrade treatment.

To determine the appropriate option, the average standard penetration value (N-value) and the plasticity index (PI) of the subgrade soils were considered. The average N-value, PI, moisture content, and CBR are presented in the table below.

Percent of Samples Over Optimum MC + 3 Percent	Average $N_L$ *	Average PI	Average MC	CBR Average
100	12.2	15	23.7	6

\* -  $N_L$  indicates lowest standard penetration value (N) in subgrade soil.

According to the GB-1, any soil with moisture content exceeding the optimum moisture content of the soil by three or more percentage points, or has low N-values (generally  $N < 10$ ), is considered problematic soil and will likely require some form of subgrade treatment. The stabilization options available include undercutting, cement stabilization, and lime stabilization. However, the cement or lime stabilization may not be effective in very weak soils (N-values less than 5 blows per foot).

Based on GB-1 guidelines, cement treatment is the preferred stabilization option for soils with average N-values less than 10 and an average PI less than 20. However, cement stabilization is generally not effective in stabilizing subgrade soils with N-values less than 5 because the soils do not gain sufficient strength. Two of the five borings were determined to be suitable for cement treatment. Generally, chemical stabilization is more economical when the area to be stabilized is greater than a mile. Given the fact that less than one-half mile of the subgrade would require treatment, undercutting of the subgrade appears to be a more cost-effective soil stabilization method.

It should be noted that the existing pavement is failing. Excessive cracking, settlements, and rutting were observed in the project area. In addition, boring B-1601 encountered silt (A-4b) to a depth of two feet. Silt is listed as an unsuitable material in GB-1 and must be completely removed. Based on the GB-1 guidelines, and given the poor condition of the current asphalt

Michael D. Weeks, P.E., P.S.

November 16, 2007

Page 4

pavement, all of the subgrade soils along the proposed South Pershing Avenue realignment should be undercut to a depth of three feet.

Boring B-1604 encountered elastic clay (A-7-5) to a depth of four feet. GB-1 guidelines list elastic clay as an unsuitable subgrade material that should be completely removed. Accordingly, it is recommended the subgrade soil for the proposed North Pershing Avenue realignment be undercut to a depth of four feet.


The undercut areas should be replaced with compacted Type B or Type C granular material (ODOT Item 703.16.C) and should extend 18 inches beyond the edge of the pavement, paved shoulders, or paved medians. In addition to undercutting, it is recommended that the entire subgrade be proof-rolled to identify any soft or weak areas that require subgrade stabilization. If any soft or weak areas are encountered, it is recommended that the area be overexcavated and replaced with compacted Type B or C granular material (ODOT Item 703.16.C).

Seepage and groundwater were not encountered in any of the borings. Although no groundwater was encountered within the proposed subgrade elevations, the contractor should be prepared to maintain reasonably dry excavations if water from seepage or precipitation enters any excavations.

We appreciate having the opportunity to be of service to you on this project. Please do not hesitate to call if you have any questions concerning our findings.

Respectfully submitted,


DLZ OHIO, INC.




Andrew Jalbrzikowski  
Engineering Geologist



Pete Nix, P.E.  
Geotechnical Division Manager






PERSHING AVE. NORTH-STA. 30+00 TO STA. 32+79.57  
PERSHING AVE. SOUTH-STA. 13+82.19 TO STA. 20+00





SCI-823-0.00

**BORING PLAN**  
**PERSHING AVE. NORTH & SOUTH**

DRAWN  
RLS  
CHECKED  
AEN













Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

**LOG OF: Boring B-1604**

Location: Sta. 33+30.3, 5.2 ft. LT of Pershing Ave. North CL

Date Drilled: 1/10/06

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetrometer (tsf) / * Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: None Water level at completion: None	GRADATION						STANDARD PENETRATION (N) Natural Moisture Content, % - ● PL ——— LL Blows per foot - ○ 10 20 30 40						
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay							
0	554.6																			
1.0	553.6	2 12	4 12	1		3.5	Asphalt Concrete Pavement - 5" Aggregate Base - 7"	0	1	--	4	38	57							
3.0	551.6	3 4	6 19	2		2.75	Very stiff brown CLAY (A-7-6), "and" silt, trace fine to coarse sand; damp to moist.	0	1	--	3	38	58							
5.0	549.6	5 7	9 24	3		2.5	Very stiff brown ELASTIC CLAY (A-7-5), "and" silt, trace fine to coarse sand; damp to moist.	0	0	--	2	44	54							
		3 4	6 20	4		2.25	Stiff to very stiff brown SILTY CLAY (A-6b), trace fine sand; damp to moist. @ 7.0', moist.													
		3	6	5		1.75														
10.0	544.6						Bottom of Boring - 10.0'													

FILE: 0121-3070-03 [ 11/15/2007 11:06 AM ]

Client: TranSystems, Inc.

Project: SCI-823-0.00

Job No. 0121-3070.03

**LOG OF: Boring B-1605**

Location: Sta. 20+05.8, 88.5 ft. RT of Pershing Ave. South BL

Date Drilled: 1/10/06

Depth (ft)	Elev. (ft)	Blows per 6"	Recovery (in)	Sample No.		Hand Penetro- meter (tsf) / * Point-Load Strength (psi)	WATER OBSERVATIONS: Water seepage at: None Water level at completion: None	GRADATION						STANDARD PENETRATION (N) Natural Moisture Content, % - ● PL ————— LL Blows per foot - ○ 10 20 30 40						
				Drive	Press / Core			% Aggregate	% C. Sand	% M. Sand	% F. Sand	% Silt	% Clay							
0	555.4																			
1.0	554.4	3 4 6 14		1		3.25	Asphalt Concrete Pavement - 9" Aggregate Base - 3"	0	1	--	5	48	46							
		4 6 7 10 22		2		3.0	Very stiff mottled brown and gray SILT AND CLAY (A-6a), trace fine to coarse sand; damp to moist. @ 3.0', trace organic clay, moist.	0	0	--	3	40	57							
5.0	550.4	6 9 11 20		3		2.5	Very stiff mottled brown and gray CLAY (A-7-6), "and" silt, trace fine to coarse sand; damp to moist.	0	0	--	7	46	47							
		3 4 6 18		4		2.5														
		2 4 8 16		5		2.75														
10.0	545.4						Bottom of Boring - 10.0'													
15																				
20																				
25																				
30																				

FILE: 0121-3070-03 [ 11/15/2007 11:06 AM ]



**Subgrade Analysis**  
V. 9.09 08/10/07

Design CBR **6**  
Item 320 No  
Global CS Option  
Global LS No

Classification Counts by Sample																	
R	1a	1b	3	3a	2-4	2-5	2-6	2-7	4a	4b	5	6a	6b	7-5	7-6	8a	8b
0	0	0	0	0	0	0	0	0	1	1	0	3	2	1	5	0	0
0.0%	0.0%						100.0%										

Class @ Surface	
2-5	0
4b	1 20%
5	0
7-5	0
7-6	2 40%
8a	0
8b	0
R	0

% Borings	
N <sub>i</sub> ≤ 5	0%
N <sub>i</sub> ≤ 10	40%
N <sub>i</sub> ≥ 20	0%
M+	100%
R	0%

% Surface	
80%	
20%	80%
% Borings	
100%	

5 Total Borings

Average	N <sub>60</sub>	N <sub>L</sub>	PI	Clay	M	M <sub>OPT</sub>	GI				
16.3	12.2	15.0	50.9	23.7	17.8	10.69					
Maximum	25	14	58	47	21	55	61	98	25	21	14
Minimum	10	10	30	20	10	37	42	90	22	15	8

SCI-823-0.00 Pershing Ave.																	Problem		Treatments									
#	B #	Boring Location	Depth To	Cut Fill	Standard Penetration				Physical Characteristics					Moisture		Classification		Comments	w/ Class	w/ MN	LS	CS	UC Class	UC MN				
					n <sub>2</sub>	n <sub>3</sub>	N <sub>m</sub>	Rig	N <sub>60</sub>	N <sub>L</sub>	LL	PL	PI	% Silt	% Clay	P 200	M								M <sub>OPT</sub>	Class	GI	
1	1601	STA. 12+53.2 4.9 ft. LT	0.5 2.0 2.0 4.0 4.0 6.0		13	7	20	A	20		31	21	10	51	42	93	25	16	4b	8		4b	M			3	1	
									14		44	23	21	37	61	98	23	20	7-6	13			M				1	
									10		33	21	12	55	42	97	24	18	7-6	9								
2	1602	STA. 17+07.5 14.8 ft. LT	4.5 6.0	5.0	4	6	10	A	10								25	18	7-6	14			MN				1	
									10																			
3	1604	STA 33+30.3 5.2' LT	0.5 2.0 2.0 4.0 4.0 6.0		12	4	16	A	16		45	24	21	38	57	95	24	21	7-6	13								
									13		58	47	11	38	58	96	24		7-5	12			Un			All	1	
									18		40	23	17	44	54	98	24	18	6b	11								
4	1605	STA 20+5.8 88.5' RT	0.5 2.0 2.0 4.0 4.0 6.0		4	6	10	A	10		39	23	16	48	46	94	23	18	6a	10				MN			12	1
									10		34	20	14	40	57	97	25	15	6a	10				M				1
									10		43	24	19	46	47	93	23	21	7-6	12								1
5	1606	STA 30+6 55.1' RT	0.5 2.0 2.0 4.0 4.0 6.0		12	5	17	A	17		30	20	10	46	44	90	22	15	4a	8				M				1
									14		38	22	16	44	52	96	23	17	6b	10				MN				1
									14		34	21	13	43	51	94	25	16	6a	9				M		12		1

### III.C. Subgrade Checklist

C-R-S: SC-823-0.00 Pershing Ave.

PID: 77366

Reviewer: AMJ

Date: 11-16-2007

If you do not have any subgrade work on the project, you do not have to fill out this checklist.

<u>Y</u> N X	1	Has the subsurface investigation adequately characterized the soil or rock according to <u>Geotechnical Bulletin 1: Plan Subgrades (GB1)</u> ?	
<u>Y</u> N X	2	If soils classified as A-2-5, A-4b, A-5, or A-7-5 are present at the proposed subgrade (soil profile), do the plans specify that these materials need to be removed and replaced?	
<u>Y</u> N X	a	If these materials are to be removed and replaced, have the station limits, depth, and lateral limits for the planned removal been provided?	
Y <u>N</u> X	3	If there is any rock, shale, or coal present at the proposed subgrade (CMS 204.05), do the plans specify the removal of the material?	
Y N <u>X</u>	a	If removal of any rock, shale, or coal is required, have the station limits, depth, and lateral limits for the planned removal of the material at proposed subgrade been provided?	
<u>Y</u> N X	4	In accordance with GB1, do the SPT values and existing moisture contents for the proposed subgrade soils indicate the need for subgrade stabilization?	
Y <u>N</u> X	a	If removal and replacement is applicable, has the detail of subgrade removal been shown on the plans, including depth of removal, station limits, lateral extent, replacement material, and plan notes (Item 204 - Subgrade Compaction and Proof Rolling)?	Refer to roadway cross-sections.
Y N <u>X</u>	b	If chemical stabilization is applicable, has the detail of this treatment been shown on the plans, including depth, percentage of chemical, station limits, lateral extent, and plan notes?	
		Indicate type of subgrade treatment specified:	GB-1 recommends cement treatment or undercutting. Undercutting was recommended for subgrade treatment.
		9 <u>cement treatment</u> 9 lime treatment	
		9 other List Other items:	
<u>Y</u> N X	5	If drainage or groundwater is an issue with the proposed subgrade, has an appropriate drainage system (e.g., pipe, underdrains) been provided?	Refer to roadway cross-sections.
Y N <u>X</u>	6	Has an appropriate quantity of Proof Rolling been included in the plans (CMS 204.06)?	Refer to roadway cross-sections.
<u>Y</u> N X	7	Has a design CBR value been provided?	







November 16, 2007

Michael D. Weeks, P.E., P.S.  
TranSystems Corporation  
5747 Perimeter Drive, Suite 240  
Dublin, OH 43017

**Re: Pavement Design Information**  
**Phase 3 Mainline**  
SCI-823-0.00 Portsmouth Bypass  
DLZ Job No.: 0121-3070.03  
Document No. 0100

Dear Mr. Weeks:

We have evaluated the existing laboratory test results performed as of June 6, 2006, to estimate a recommended CBR value for the above-mentioned project. A minor amount of testing was performed subsequent to this date, but including the subsequent data should not substantially change the overall conclusions and recommendations. Because the vast majority of the project's alignment will be in rock cuts or on embankments, all of the laboratory test results for the Phase 3 area were considered. Accordingly, the results of Phase 3 only are presented in this letter.

The method used was essentially the same as the one used by the Office of Geotechnical Engineering to determine the design CBR for the Nelsonville Bypass project. The alignment for that project was similar to the Portsmouth Bypass alignment in that most of it will also be in rock cuts or on embankments.

It is understood that the Phase 3 area is inclusive of station 54+11 to 353+00. The results of the other phases will be presented in separate documents.

A total of 252 samples have been tested for particle size and plasticity where necessary. A summary of the soil samples tested is presented on the following page.

Based upon the results of the laboratory testing, an average CBR value of 6.4 was calculated for Phase 3. Consequently, a CBR value of 7 is recommended for the pavement design on the mainline alignment and ramps of the new alignment in Phase 3.

Michael D. Weeks, P.E., P.S.  
November 16, 2007


**Summary of Soil Samples Tested**

ODOT Classification	Number of Samples Tested
Gravel with sand (A-1-b)	4
Fine sand (A-3)	1
Gravel, sand and silt (A-2-4)	10
Sandy silt (A-4a)	38
Silt (A-4b)	81
Silt and clay (A-6a)	50
Silty clay (A-6b)	24
Elastic clay (A-7-5)	1
Clay (A-7-6)	43


We appreciate having the opportunity to be of service to you on this project. Please do not hesitate to call if you have any questions concerning our report.

Respectfully submitted,


**DLZ OHIO, INC.**




Steven J. Riedy  
Geotechnical Engineer



Andrew M. Jalbrzikowski  
Engineering Geologist



Pete Nix, P.E.  
Geotechnical Division Manager



cc: File