



PAVEMENT DATA

ROUTE	FROM	TO	DISTANCE	PAVT WIDTH	TREATMENT WIDTH ***	TYPICAL SECTION	PAVT AREA	407	421	
								TACK-LESSS TACK COAT **	MICRO-SURFACING, SURFACE COURSE	
								TOTAL WIDTH OF PAVEMENT		
			MILES	FEET	FEET		SQ YD	GAL	SQ YD	
ALL 75	1.00	1.40	0.40	2112	44 x (2)	24 x (2)	1	11264	1014	11264
ALL 75	2.94	3.40	0.46	2429	44 x (2)	24 x (2)	1	12954	1166	12954
ALL 75	4.60	5.25	0.65	3432	44 x (2)	24 x (2)	1	18304	1647	18304
Totals								3827	42522	

** Not carried to General Summary, Item is incidental to Microsurfacing per CMS 421.13. The quantity is provided for informational purposes only.

*** Microsurfacing will only be applied to the driving lanes. Shoulders will not be included.

ROUTE	FROM	TO	DISTANCE	621		642				
				RPM WHITE/RED	RPM REMOVED	EDGE LINE WHITE 6" (TYPE 1)	EDGE LINE YELLOW 6" (TYPE 1)	LANE LINE 6" (TYPE 1)	REMOVAL OF PAVEMENT MARKING	
				EACH	EACH	MILE	MILE	MILE	MILE	
ALL 75	1.00	1.40	0.40	2112	53	53	0.80	0.80	0.80	2.40
ALL 75	2.94	3.40	0.46	2429	61	61	0.92	0.92	0.92	2.76
ALL 75	4.60	5.25	0.65	3432	86	86	1.30	1.30	1.30	3.90
SUB-TOTALS					199	199	3.02	3.02	3.02	9.06

1,200 FT. of Item 642, Dotted Line, 6", Type 1 has been provided in the General Summary for delineating the entrance ramp from SR 65 to NB IR 75.

I:\Project\data\I4300\Design\Roadway\Sheets\I4300_006.dgn_Sheet 3/12/2021 8:59:37 AM mbrunet

MICROSURFACING AND PAVEMENT MARKING SUB-SUMMARY

ALL-75-1.00/
2.94 / 4.60