

ITEM 514 – FIELD PAINTING

THE CONTRACTOR SHALL NOT OVERSPRAY ONTO THE CONCRETE DECK OR CONCRETE SUBSTRUCTURE COMPONENTS (BACK WALLS, ABUTMENTS, AND PIERS). PAINTING SHALL BE CONFINED TO THE STRUCTURAL STEEL COMPONENTS, UTILITY SUPPORTS, AND THE DRAINAGE SCUPPERS INCLUDING DOWNSPOUTS.

UTILITY CONDUITS AND GUIDE SIGN SUPPORTS SHALL NOT BE PAINTED AND SHALL BE PROTECTED FROM SANDBLASTING. STEEL UTILITY SUPPORTS AND DRAINAGE SCUPPERS SHALL BE PAINTED.

THE FINISH COAT COLOR AT LOCATIONS 1-7 SHALL BE FEDERAL COLOR NUMBER FC595B-16440 (LIGHT GREY, GLOSS). THE CONTRACTOR SHALL PROVIDE SAMPLE COLOR CHIPS TO THE ENGINEER FOR APPROVAL PRIOR TO COMMENCING WORK.

THE FINISH COAT COLOR AT LOCATION 8 SHALL BE FEDERAL COLOR NUMBER FC#24148 (GREEN). THE CONTRACTOR SHALL PROVIDE SAMPLE COLOR CHIPS TO THE ENGINEER FOR APPROVAL PRIOR TO COMMENCING WORK.

ITEM 519 - PATCHING CONCRETE STRUCTURE, AS PER PLAN

PRIOR TO THE SURFACE CLEANING SPECIFIED IN 519.04 AND WITHIN 24 HOURS OF PLACING PATCHING MATERIAL, BLAST CLEAN ALL SURFACES TO BE PATCHED INCLUDING THE EXPOSED REINFORCING STEEL. ACCEPTABLE METHODS INCLUDE HIGH PRESSURE WATER BLASTING WITH OR WITHOUT ABRASIVES IN THE WATER, ABRASIVE BLASTING WITH CONTAINMENT, OR VACUUM ABRASIVE BLASTING. AREAS REQUIRING PATCHING WILL BE DETERMINED IN THE FIELD BY THE PROJECT ENGINEER AND REPAIRED AS PER THE REQUIREMENTS OF ITEM 519 - PATCHING CONCRETE STRUCTURE.

COORDINATE PATCHING WORK WITH MAINTENANCE OF TRAFFIC ZONES UTILIZED FOR PAINTING WORK.

AT LOCATION 1 (CUY-480-15.849) AN ALLOWANCE OF **505 SQ. FT.** IS INCLUDED IN THE CONTRACT DOCUMENTS TO PATCH DEFICIENT AREAS OF THE CONCRETE BRIDGE RAILING UNLESS NOTED OTHERWISE. THE OEPA NOTIFICATION FORM IS REQUIRED FOR THIS LOCATION.

AT LOCATION 5 (CUY-480-15.956) AN ALLOWANCE OF **10 SQ. FT.** IS INCLUDED IN THE CONTRACT DOCUMENTS TO PATCH DEFICIENT AREAS OF THE CONCRETE SUBSTRUCTURE UNLESS NOTED OTHERWISE.

ASBESTOS NOTIFICATION

AT LOCATION 1 (CUY-480-15.849) A CERTIFIED ASBESTOS HAZARD EVALUATION SPECIALIST SURVEYED THE BRIDGE STRUCTURE SCHEDULED FOR REHABILITATION; THE SURVEY DETERMINED THAT NO ASBESTOS IS PRESENT ON THE BRIDGE STRUCTURE.

ODOT SHALL PROVIDE A COPY OF THE OHIO ENVIRONMENTAL PROTECTION AGENCY (OEPA) NOTIFICATION OF DEMOLITION AND RENOVATION FORM, PARTIALLY COMPLETED AND SIGNED BY THE BRIDGE OWNER, TO THE SUCCESSFUL BIDDER. THE CONTRACTOR SHALL COMPLETE THE FORM AND SUBMIT IT TO ONE OF THE ADDRESSES BELOW AT LEAST TEN (10) WORKING DAYS PRIOR TO THE START OF ANY DEMOLITION AND/OR RENOVATION.

ASBESTOS PROGRAM OHIO EPA, DAPC
P.O. BOX 1049
COLUMBUS, OH 43216-1049

OR

ASBESTOS PROGRAM OHIO EPA, DAPC
50 W. TOWN ST., SUITE 700
COLUMBUS, OH 43215

THE CONTRACTOR SHALL PROVIDE A COPY OF THE COMPLETED FORM TO THE ENGINEER AT LEAST TEN (10) WORKING DAYS PRIOR TO THE START OF ANY DEMOLITION AND/OR RENOVATION. THE FORM SHALL INCLUDE: 1) THE CONTRACTORS NAME AND ADDRESS, 2) THE SCHEDULED DATES FOR THE START AND COMPLETION OF THE BRIDGE REMOVAL AND 3) A DESCRIPTION OF THE PLANNED DEMOLITION WORK AND THE METHOD(S) TO BE USED. COPIES OF THE OEPA FORM AND BRIDGE INSPECTION REPORT ARE AVAILABLE FOR REVIEW AT THE ODOT DISTRICT 12 OFFICE, 5500 TRANSPORTATION BLVD, GARFIELD HEIGHTS, OHIO 44125.

BASIS FOR PAYMENT: THE CONTRACTOR SHALL FURNISH ALL FEES, LABOR, AND MATERIAL NECESSARY TO COMPLETE AND SUBMIT THE OEPA NOTIFICATION FORM. PAYMENT FOR THIS WORK SHALL BE INCIDENTAL TO ITEM 519- PATCHING CONCRETE STRUCTURE, AS PER PLAN.

