

PID: 112998	SFN: 1802437	PROJECT: CUY-17-13.50	STATION / OFFSET: 113+33, 10' RT.				START: 3/24/22		END: 3/30/22		PG 2 OF 3		B-004-0-22							
MATERIAL DESCRIPTION AND NOTES		ELEV.	DEPTHS		SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	HOLE SEALED
		666.4								GR	CS	FS	SI	CL	LL	PL	PI			
STIFF TO VERY STIFF, GRAY, SILT, "AND" CLAY, MOIST (continued)		+++++		61																
		+++++		62																
		+++++		63																
		+++++		64	5 6	16	100	SS-16	3.00	-	-	-	-	-	-	-	24	A-4b (V)		
		+++++		65																
		+++++		66																
		+++++		67																
		+++++		68																
		+++++		69	3 3	8	100	SS-17	2.50	2	3	5	29	61	36	21	15	30	A-6a (10)	
		+++++		70																
STIFF TO VERY STIFF, GRAY, SILT AND CLAY, TRACE SAND, TRACE GRAVEL, MOIST				71																
				72																
				73																
				74	3 4	9	100	SS-18	1.50	-	-	-	-	-	-	-	34	A-6a (V)		
				75																
				76																
				77																
				78																
				79	2 3	7	100	SS-19	1.50	-	-	-	-	-	-	-	32	A-6a (V)		
				80																
				81																
				82																
				83																
				84	6 8	20	100	SS-20	3.50	-	-	-	-	-	-	-	23	A-6a (V)		
				85																
				86																
				87			100	ST-21	3.00	-	-	-	-	-	-	-	26	A-6a (V)		
				88																
				89	6 7	19	100	SS-22	3.00	-	-	-	-	-	-	-	26	A-6a (V)		
				90																
				91																
				92																
				93																
				94	4 7	20	100	SS-23	1.00	-	-	-	-	-	-	-	26	A-6a (V)		
				95																
				96																
				97																
				98																
				99	4 5	12	100	SS-24	2.50	1	1	2	31	65	35	21	14	25	A-6a (10)	
				100																
				101																
				102																
				103																
				104	3 4	11	100	SS-25	1.50	-	-	-	-	-	-	-	27	A-6a (V)		
				105																
				106																
				107			96	ST-26	4.50	-	-	-	-	-	-	-	22	A-6a (V)		
				108																
				109	7 7	16	100	SS-27	2.00	-	-	-	-	-	-	-	25	A-6a (V)		
				110																
				111																
				112																
				113																
				114	5 7	20	33	SS-28	2.00	-	-	-	-	-	-	-	21	A-6a (V)		
				115																
				116																
				117																
				118																
				119	9 15	44	100	SS-29	4.00	5	4	8	39	44	26	17	9	16	A-4a (8)	
				120																
HARD, GRAY, SANDY SILT, "AND" CLAY, TRACE GRAVEL, DAMP				121																