



PID: 112998	SFN: 1802437	PROJECT: CUY-17-13.50	STATION / OFFSET: 113+33, 10' RT.			START: 3/24/22		END: 3/30/22		PG 3 OF 3		B-004-0-22							
MATERIAL DESCRIPTION AND NOTES		ELEV.	DEPTHS	SPT/ RQD	N <sub>60</sub>	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	HOLE SEALED
		604.5							GR	CS	FS	SI	CL	LL	PL	PI			
HARD, GRAY, <b>SANDY SILT</b> , "AND" CLAY, TRACE GRAVEL, DAMP (continued)			587.9	TR	123														
					124	23 35 50/6"	-	100	SS-30	4.50	-	-	-	-	-	-	-	15	A-4a (V)
					125														
					126														
					127														
					128														
					129	23 50/6"	-	100	SS-31	4.50	-	-	-	-	-	-	-	12	A-4a (V)
					130														
					131														
					132														
					133														
					134	24 50/4"	-	100	SS-32	4.50	-	-	-	-	-	-	-	12	A-4a (V)
<b>SHALE</b> , SLIGHTLY WEATHERED, MODERATELY STRONG, VERY FINE GRAINED, MEDIUM TO THICK BEDDED, SLIGHTLY FRACTURED; RQD 92%, REC 100%.		582.4	EOB	138															
				139	60/2"	-	100	SS-33	-	-	-	-	-	-	-	9	Rock (V)		
				140															
				141	92		100	RC-34											
				142															
				143															
				144															

NOTES: NONE

ABANDONMENT METHODS, MATERIALS, QUANTITIES: PLACED 1 BAG ASPHALT PATCH; POURED BENTONITE GROUT; PLACED 1 HOLE PLUG