

PID: 112998	SFN: 1802437	PROJECT: CUY-17-13.50	STATION / OFFSET: 118+21, 9' LT.				START: 3/31/22		END: 4/6/22		PG 2 OF 3		B-001-0-22										
MATERIAL DESCRIPTION AND NOTES			ELEV.	DEPTHS		SPT/ RQD	N ₆₀	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG				ODOT CLASS (GI)	HOLE SEALED		
			658.7								GR	CS	FS	SI	CL	LL	PL	PI	WC				
STIFF, GRAY, SANDY SILT , "AND" CLAY, WET			657.7																				
				61																			
				62																			
				63																			
				64	2	2	6	67	SS-17	1.50	-	-	-	-	-	-	-	-	-	-	30	A-4a (V)	
				65		3																	
				66																			
				67																			
				68																			
				69	2	2	6	100	SS-18	1.50	-	-	-	-	-	-	-	-	-	-	33	A-4a (V)	
				70		3																	
				71																			
				72																			
				73																			
				74	2	3	8	100	SS-19	1.00	0	1	0	49	50	29	20	9	27	A-4a (8)			
				75		4																	
				76																			
			MEDIUM STIFF TO STIFF, GRAY, CLAY , SOME SILT, TRACE SAND, MOIST			641.7																	
							77																
	78																						
	79	3				3	8	100	SS-20	1.50	-	-	-	-	-	-	-	-	-	-	26	A-7-6 (V)	
	80					4																	
	81																						
	82																						
	83																						
	84	3				4	11	100	SS-21	1.50	-	-	-	-	-	-	-	-	-	-	27	A-7-6 (V)	
	85					5																	
	86																						
	87																						
	88																						
	89	3				5	13	67	SS-22	1.50	-	-	-	-	-	-	-	-	-	-	25	A-7-6 (V)	
	90					6																	
	91																						
	92																						
	93																						
	94	3				3	8	100	SS-23	1.00	0	1	2	30	67	41	24	17	29	A-7-6 (11)			
	95					4																	
	96																						
	97																						
	98																						
	99	3				4	11	100	SS-24	1.50	-	-	-	-	-	-	-	-	-	-	31	A-7-6 (V)	
	100					5																	
VERY STIFF TO HARD, GRAY, SANDY SILT , "AND" CLAY, TRACE SHALE FRAGMENTS, DAMP TO MOIST						615.2																	
							101																
				102																			
				103																			
				104	4	6	16	0	SS-25	-	-	-	-	-	-	-	-	-	-	-	-	A-4a (V)	
				105		8																	
				106																			
				107																			
				108																			
				109	5	8	20	100	SS-26	2.50	-	-	-	-	-	-	-	-	-	-	16	A-4a (V)	
				110		9																	
				111																			
				112																			
				113																			
				114	6	8	21	100	SS-27	2.00	10	6	6	36	42	27	19	8	20	A-4a (8)			
				115		10																	
				116																			
				117																			
				118																			
				119	10	16	43	67	SS-28	4.00	-	-	-	-	-	-	-	-	-	-	18	A-4a (V)	
				120		21																	
	121																						