GENERAL NOTES

PLAN NO.

CONVERSION OF STANDARD CONSTRUCTION DRAWINGS

The Metric Standard Drawings referenced in this plan shall be converted to English units using the SI (Metric) to English conversion factors provided in Section 109.02 of the 2005 Construction and Material Specifications. Conversions shall be appropriately precise and shall reflect standard industry English values where suitable.

NOTIFICATION

The Contractor shall notify the Ohio Department of Transportation District Seven Construction Engineer two (2) weeks prior to beginning any work. Phone: (937) 497-6848.

ITEM 512 - TREATING OF CONCRETE BRIDGE DECK WITH SRS.

Bridge Decks shall be sealed with SRS Sealer as per Item 512 - Treating of Concrete Bridge Deck with SRS, except as noted below.

Note: Deck must be flooded with SRS Sealer. The use of sprayers is prohibited.

Allow one (1.0) hour minimum cure time after completion of the SRS Treatment and ensure that the material does not track, per 512.05 F before opening the roadway to traffic.

ITEM 519 - SPECIAL, PATCHING CONCRETE BRIDGE DECK, TYPE B

It is not the intent to sound the entire deck surface. Only patch visible areas in need of repair.

CALCULATED BY

DØ7-BRIDGE-PM-FYØ7

AS