

ITEM 614, LAW ENFORCEMENT OFFICER (WITH PATROL CAR) FOR ASSISTANCE DURING CONSTRUCTION OPERATIONS

USE OF LAW ENFORCEMENT OFFICERS (LEOS) BY CONTRACTORS OTHER THAN THE USES SPECIFIED BELOW WILL NOT BE PERMITTED AT PROJECT COST. LEOS SHOULD NOT BE USED WHERE THE OMTCD INTENDS THAT FLAGGERS BE USED.

IN ADDITION TO THE REQUIREMENTS OF C&MS 614 AND THE OMTCD, A UNIFORMED LEO WITH AN OFFICIAL PATROL CAR (CAR WITH TOP-MOUNTED EMERGENCY FLASHING LIGHTS AND COMPLETE MARKINGS OF THE APPROPRIATE LAW ENFORCEMENT AGENCY) SHALL BE PROVIDED FOR THE FOLLOWING TRAFFIC CONTROL TASKS:

DURING THE ENTIRE ADVANCE PREPARATION AND CLOSURE SEQUENCE WHERE COMPLETE BLOCKAGE OF TRAFFIC IS REQUIRED.

DURING A TRAFFIC SIGNAL INSTALLATION WHEN IMPACTING THE NORMAL FUNCTION OF THE SIGNAL OR THE FLOW OF TRAFFIC, OR WHEN TRAFFIC NEEDS TO BE DIRECTED THROUGH AN ENERGIZED TRAFFIC SIGNAL CONTRARY TO THE SIGNAL DISPLAY (E.G., DIRECTING MOTORISTS THROUGH A RED LIGHT).

IN ADDITION TO THE REQUIREMENT OF C&MS 614 AND THE OMTCD, A UNIFORMED LEO WITH AN OFFICIAL PATROL CAR (CAR WITH TOP-MOUNTED EMERGENCY FLASHING LIGHTS AND COMPLETE MARKINGS OF THE APPROPRIATE LAW ENFORCEMENT AGENCY) SHOULD BE PROVIDED FOR THE FOLLOWING TRAFFIC CONTROL TASKS AS APPROVED BY THE ENGINEER:

FOR LANE CLOSURES: DURING INITIAL SET-UP PERIODS, TEAR DOWN PERIODS, SUBSTANTIAL SHIFTS OF A CLOSURE POINT OR WHEN NEW LANE CLOSURE ARRANGEMENTS ARE INITIATED FOR LONG-TERM LANE CLOSURES/SHIFTS (FOR THE FIRST AND LAST DAY OF MAJOR CHANGES IN TRAFFIC CONTROL SETUP).

IN GENERAL, LEOS SHOULD BE POSITIONED IN ADVANCE OF AND ON THE SAME SIDE AS THE LANE RESTRICTION OR AT THE POINT OF ROAD CLOSURE, AND TO MANUALLY CONTROL TRAFFIC MOVEMENTS THROUGH SIGNALIZED INTERSECTIONS IN WORK ZONES.

LEOS SHOULD NOT FORGO THEIR TRAFFIC CONTROL RESPONSIBILITIES TO APPREHEND MOTORISTS FOR ROUTINE TRAFFIC VIOLATIONS. HOWEVER, IF A MOTORIST'S ACTIONS ARE CONSIDERED TO BE RECKLESS, THEN PURSUIT OF THE MOTORIST IS APPROPRIATE.

THE LEOS WORK AT THE DIRECTION OF THE CONTRACTOR. THE CONTRACTOR IS RESPONSIBLE FOR SECURING THE SERVICES OF THE LEOS WITH THE APPROPRIATE AGENCIES AND COMMUNICATING THE INTENTIONS OF THE PLANS WITH RESPECT TO DUTIES OF THE LEOS. THE ENGINEER SHALL HAVE FINAL CONTROL OVER THE LEOS' DUTIES AND PLACEMENT, AND WILL RESOLVE ANY ISSUES THAT MAY ARISE BETWEEN THE TWO PARTIES.

ENSURE PROVIDED LEOS HAVE BEEN TRAINED APPROPRIATE TO THE JOB DECISIONS THEY ARE REQUIRED TO MAKE WHILE ON THE PROJECT, IN ACCORDANCE WITH C&MS 614.03.

THE LEO SHALL REPORT IN TO THE CONTRACTOR PRIOR TO THE START OF THE SHIFT, IN ORDER TO RECEIVE INSTRUCTIONS REGARDING SPECIFIC WORK ASSIGNMENTS DURING HIS/HER SHIFT. THE LEO IS EXPECTED TO STAY AT THE PROJECT SITE FOR THE ENTIRE DURATION OF HIS/HER SHIFT. THE LEO SHALL REPORT TO THE CONTRACTOR AT THE END OF HIS/HER SHIFT. SHOULD IT BE NECESSARY TO LEAVE THE PROJECT SITE, THE LEO SHALL NOTIFY THE ENGINEER. THE CONTRACTOR SHALL PROVIDE THE LEO WITH A TWO-WAY COMMUNICATION DEVICE WHICH SHALL BE RETURNED TO THE CONTRACTOR AT THE END OF HIS/HER SHIFT.

LEOS (WITH PATROL CAR) REQUIRED BY THE TRAFFIC MAINTENANCE TASKS ABOVE SHALL BE PAID FOR ON A UNIT PRICE (HOURLY) BASIS UNDER ITEM 614, LAW ENFORCEMENT OFFICER (WITH PATROL CAR) FOR ASSISTANCE. THE FOLLOWING ESTIMATED QUANTITIES HAVE BEEN CARRIED TO THE GENERAL SUMMARY.

ITEM 614, LAW ENFORCEMENT OFFICER WITH PATROL CAR FOR ASSISTANCE 88 HOURS

THE HOURS PAID SHALL INCLUDE ANY MINIMUM SHOW-UP TIME REQUIRED BY THE LAW ENFORCEMENT AGENCY INVOLVED.

ANY ADDITIONAL COSTS (ADMINISTRATIVE OR OTHERWISE) INCURRED BY THE CONTRACTOR TO OBTAIN THE SERVICES OF A LEO ARE INCLUDED WITH THE BID UNIT PRICE FOR ITEM 614, LAW ENFORCEMENT OFFICER WITH PATROL CAR FOR ASSISTANCE.

ITEM 614, PORTABLE CHANGEABLE MESSAGE SIGNS, AS PER PLAN

THE CONTRACTOR SHALL FURNISH, INSTALL, MAINTAIN AND REMOVE, WHEN NO LONGER NEEDED, A CHANGEABLE MESSAGE SIGN. THE SIGN SHALL BE OF A TYPE SHOWN ON A LIST OF APPROVED PCMS UNITS AVAILABLE ON THE OFFICE OF MATERIALS MANAGEMENT WEB PAGE. THE LIST CONTAINS CLASS A AND B UNITS WITH MINIMUM LEGIBILITY DISTANCES OF 800 FEET AND 650 FEET, RESPECTIVELY.

EACH SIGN SHALL BE TRAILER-MOUNTED AND EQUIPPED WITH A FUNCTIONAL DIMMING MECHANISM, TO DIM THE SIGN DURING DARKNESS, AND A TAMPER AND VANDAL PROOF ENCLOSURE. EACH SIGN SHALL BE PROVIDED WITH APPROPRIATE TRAINING AND OPERATION INSTRUCTIONS TO ENABLE ON-SITE PERSONNEL TO OPERATE AND TROUBLESHOOT THE UNIT. THE SIGN SHALL ALSO BE CAPABLE OF BEING POWERED BY AN ELECTRICAL SERVICE DROP FROM A LOCAL UTILITY COMPANY. THE PCMS SHALL BE DELINEATED IN ACCORDANCE WITH C&MS 614.03.

PLACEMENT, OPERATION, MAINTENANCE AND ALL ACTIVATION OF THE SIGNS BY THE CONTRACTOR SHALL BE AS DIRECTED BY THE ENGINEER. THE PCMS SHALL BE LOCATED IN A HIGHLY VISIBLE POSITION YET PROTECTED FROM TRAFFIC. THE CONTRACTOR SHALL, AT THE DIRECTION OF THE ENGINEER, RELOCATE THE PCMS TO IMPROVE VISIBILITY OR ACCOMMODATE CHANGED CONDITIONS. WHEN NOT IN USE, THE PCMS SHALL BE TURNED OFF. ADDITIONALLY, WHEN NOT IN USE FOR EXTENDED PERIODS OF TIME, THE PCMS SHALL BE TURNED AWAY FROM ALL TRAFFIC.

THE ENGINEER SHALL BE PROVIDED ACCESS TO EACH SIGN UNIT AND SHALL BE PROVIDED WITH APPROPRIATE TRAINING AND OPERATION INSTRUCTIONS TO ENABLE ODOT PERSONNEL TO OPERATE AND TROUBLESHOOT THE UNIT, AND TO REVISE SIGN MESSAGES, IF NECESSARY.

ALL MESSAGES TO BE DISPLAYED ON THE SIGN WILL BE PROVIDED BY THE ENGINEER. A LIST OF ALL REQUIRED PRE-PROGRAMMED MESSAGES WILL BE GIVEN TO THE CONTRACTOR AT THE PROJECT PRECONSTRUCTION CONFERENCE. THE SIGN SHALL HAVE THE CAPABILITY TO STORE UP TO 99 MESSAGES. MESSAGE MEMORY OR PRE-PROGRAMMED DISPLAYS SHALL NOT BE LOST AS A RESULT OF POWER FAILURES TO THE ON-BOARD COMPUTER. THE SIGN LEGEND SHALL BE CAPABLE OF BEING CHANGED IN THE FIELD. THREE-LINE PRESENTATION FORMATS WITH UP TO SIX MESSAGE PHASES SHALL BE SUPPORTED. PCMS FORMAT SHALL PERMIT THE COMPLETE MESSAGE FOR EACH PHASE TO BE READ AT LEAST TWICE.

THE PCMS SHALL CONTAIN AN ACCURATE CLOCK AND PROGRAMMING LOGIC WHICH WILL ALLOW THE SIGN TO BE ACTIVATED, DEACTIVATED OR MESSAGES CHANGED AUTOMATICALLY AT DIFFERENT TIMES OF THE DAY FOR DIFFERENT DAYS OF THE WEEK.

THE CONTRACTOR SHALL BE RESPONSIBLE FOR 24-HOUR-PER-DAY OPERATION AND MAINTENANCE OF THESE SIGNS ON THE PROJECT FOR THE DURATION OF THE PHASES WHEN THE PLAN REQUIRES THEIR USE.

PAYMENT FOR THE ABOVE DESCRIBED ITEM SHALL BE AT THE CONTRACT UNIT PRICE. PAYMENT SHALL INCLUDE ALL LABOR, MATERIALS, EQUIPMENT, FUELS, LUBRICATING OILS, SOFTWARE, HARDWARE AND INCIDENTALS TO PERFORM THE ABOVE DESCRIBED WORK.

ITEM 614, PORTABLE CHANGEABLE MESSAGE SIGN, AS PER PLAN 2 SIGN MONTH ASSUMING 2 PCMS SIGNS FOR 1 MONTH

850 GROOVING FOR RECESSED PAVEMENT MARKING (BY WIDTH AND BY TYPE), AS PER PLAN
IN ADDITION TO THE REQUIREMENTS OF SS 850, THE FOLLOWING SHALL APPLY: GROOVES SHALL BEGIN OR END NO MORE THAN 12 INCHES FROM A RAISED PAVEMENT MARKER CASTING. WHERE THE GROOVING HAS BEEN SUSPENDED AROUND A CASTING, THE CONTRACTOR SHALL CONTINUE WITH THE PLACEMENT OF THE WET REFLECTIVE PAVEMENT MARKING DESPITE THE LACK OF A GROOVE.



SHEET NUM.											PART.		ITEM	ITEM EXT	GRAND TOTAL	UNIT	DESCRIPTION	SEE SHEET NO.
3	5										01/SAF/OT	02/SAF/OT						
TRAFFIC CONTROL																		
	0.36										0.36		644	00104	0.36	MILE	EDGE LINE, 6"	
	0.18										0.18		644	00204	0.18	MILE	LANE LINE, 6"	
	5.58										5.58		646	10010	5.58	MILE	EDGE LINE, 6"	
	5.25										5.25		646	10110	5.25	MILE	LANE LINE, 6"	
	800										800		646	10310	800	FT	CHANNELIZING LINE, 12"	
	0.64										0.64		807	12010	0.64	MILE	WET REFLECTIVE EPOXY PAVEMENT MARKING, EDGE LINE, 6"	
	0.56										0.56		807	12110	0.56	MILE	WET REFLECTIVE EPOXY PAVEMENT MARKING, LANE LINE, 6"	
	2,154										2,154		807	12310	2,154	FT	WET REFLECTIVE EPOXY PAVEMENT MARKING, CHANNELIZING LINE, 12"	
	768										768		807	12410	768	FT	WET REFLECTIVE EPOXY PAVEMENT MARKING, DOTTED LINE, 6"	
	16.73										7.29	9.44	807	14010	16.73	MILE	WET REFLECTIVE THERMOPLASTIC PAVEMENT MARKING, EDGE LINE, 6"	
	12.68										5.83	6.85	807	14110	12.68	MILE	WET REFLECTIVE THERMOPLASTIC PAVEMENT MARKING, LANE LINE, 6"	
	6.14											6.14	807	14200	6.14	MILE	WET REFLECTIVE THERMOPLASTIC PAVEMENT MARKING, CENTER LINE	
	9,220										4,850	4,370	807	14310	9,220	FT	WET REFLECTIVE THERMOPLASTIC PAVEMENT MARKING, CHANNELIZING LINE, 12"	
	11,141										2,328	8,813	807	14410	11,141	FT	WET REFLECTIVE THERMOPLASTIC PAVEMENT MARKING, DOTTED LINE, 6"	
	12.28											12.28	850	10001	12.28	MILE	GROOVING FOR 4" RECESSED PAVEMENT MARKING, (ASPHALT), AS PER PLAN	3
	29.41										13.12	16.29	850	10011	29.41	MILE	GROOVING FOR 6" RECESSED PAVEMENT MARKING, (ASPHALT), AS PER PLAN	3
	11,141										2,328	8,813	850	10111	11,141	FT	GROOVING FOR 6" RECESSED PAVEMENT MARKING, (ASPHALT), AS PER PLAN	3
	9,220										4,850	4,370	850	10131	9,220	FT	GROOVING FOR 12" RECESSED PAVEMENT MARKING, (ASPHALT), AS PER PLAN	3
	1.2										1.2		850	20011	1.2	MILE	GROOVING FOR 6" RECESSED PAVEMENT MARKING, (CONCRETE), AS PER PLAN	3
	768										768		850	20111	768	FT	GROOVING FOR 6" RECESSED PAVEMENT MARKING, (CONCRETE), AS PER PLAN	3
	2,154										2,154		850	20131	2,154	FT	GROOVING FOR 12" RECESSED PAVEMENT MARKING, (CONCRETE), AS PER PLAN	3
MAINTENANCE OF TRAFFIC																		
88											32	56	614	11110	88	HOUR	LAW ENFORCEMENT OFFICER WITH PATROL CAR FOR ASSISTANCE	
2											2		614	18601	2	SNMT	PORTABLE CHANGEABLE MESSAGE SIGN, AS PER PLAN	3
INCIDENTALS																		
											LS	LS	614	11000	LS		MAINTAINING TRAFFIC	
											LS	LS	624	10000	LS		MOBILIZATION	

GENERAL SUMMARY

DESIGN AGENCY



DESIGNER
PMM

REVIEWER
MAG 09/25/20

PROJECT ID
113754

SHEET TOTAL
P.4 | 5

D08-R-WR PAVEMENT MARKING FY21

MODEL: Sheet PAPER: 17x11 (in.) DATE: 1/7/2021 TIME: 1:07:52 PM USER: pmonnier
 pwo\ohodol-pw.bentley.com\shhdol-pw-02\Documents\01 Active Projects\Distict 08_D08\113754\400-Engineering\Traffic\Sheets\113754_TC001.dgn

COUNTY	PLAN SPLIT	ROUTE	BEGIN SLM	DESCRIPTION	END SLM	DESCRIPTION	807		807		807		807		807		807		807		850		850		850		850		850		646		646		646		644		644		REMARKS								
							WET REFLECTIVE THERMOPLASTIC PAVEMENT MARKING, CENTER LINE		WET REFLECTIVE THERMOPLASTIC PAVEMENT MARKING, EDGE LINE, 6 INCH		WET REFLECTIVE THERMOPLASTIC PAVEMENT MARKING, LANE LINE, 6 INCH		WET REFLECTIVE THERMOPLASTIC PAVEMENT MARKING, CHANNELIZING LINE, 12 INCH		WET REFLECTIVE THERMOPLASTIC PAVEMENT MARKING, DOTTED LINE, 6 INCH		WET REFLECTIVE EPOXY PAVEMENT MARKING, EDGE LINE, 6 INCH		WET REFLECTIVE EPOXY PAVEMENT MARKING, LANE LINE, 6 INCH		WET REFLECTIVE EPOXY PAVEMENT MARKING, CHANNELIZING LINE, 12 INCH		WET REFLECTIVE EPOXY PAVEMENT MARKING, DOTTED LINE, 6 INCH		GROOVING FOR 4 INCH RECESSED PAVEMENT MARKING, ASPHALT, AS PER PLAN		GROOVING FOR 6 INCH RECESSED PAVEMENT MARKING, ASPHALT, AS PER PLAN		GROOVING FOR 12 INCH RECESSED PAVEMENT MARKING, ASPHALT, AS PER PLAN		GROOVING FOR 6 INCH RECESSED PAVEMENT MARKING, ASPHALT, AS PER PLAN		GROOVING FOR 8 INCH RECESSED PAVEMENT MARKING, CONCRETE, AS PER PLAN		GROOVING FOR 12 INCH RECESSED PAVEMENT MARKING, CONCRETE, AS PER PLAN		GROOVING FOR 6 INCH RECESSED PAVEMENT MARKING, CONCRETE, AS PER PLAN		EDGE LINE, 6 INCH			LANE LINE, 6 INCH		CHANNELIZING LINE, 12 INCH		EDGE LINE, 6 INCH		LANE LINE, 6 INCH	
							WHITE	YELLOW	WHITE	YELLOW	WHITE	YELLOW	WHITE	YELLOW	WHITE	YELLOW	WHITE	YELLOW	WHITE	YELLOW	WHITE	YELLOW	WHITE	YELLOW	WHITE	YELLOW	WHITE	YELLOW	WHITE	YELLOW	WHITE	YELLOW	WHITE	YELLOW	WHITE	YELLOW	WHITE	YELLOW	WHITE	YELLOW		WHITE	YELLOW						
HAM	01/SAF/OT	IR-275	39.4	US 52 BRIDGE	39.9	FOUR MILE BRIDGE																																				EXISTING CONCRETE PAVEMENT							
	01/SAF/OT		39.9	FOUR MILE BRIDGE	41.37	COMBS HIEL BRIDGE APPROACH SLAB	2.81	2.10	5.61	4095.00	2328.00	0.34	0.30	0.56	2154.00	768.00			10.52	4095.00	2328.00	1.20	2154.00	768.00			1.00	1.00	1.50	800.00											NEW ASPHALT AND CONCRETE PAVEMENTS								
	01/SAF/OT		41.37(72.85)	COMBS HIEL BRIDGE	73.5	KENTUCKY SIDE																																				COMBS HIEL BRIDGE.							
	01/SAF/OT	IR-275		US 52 RAMP F																																													
	01/SAF/OT	IR-275		KELLOGG AVE RAMP N			0.21	0.21											0.42																														
	01/SAF/OT	IR-275		KELLOGG AVE RAMP O			0.19	0.16	0.18	517.00									0.53	517.00																													
	01/SAF/OT	IR-275		KELLOGG AVE RAMP P			0.22	0.21		48.00									0.43	48.00																													
	01/SAF/OT	IR-275		KELLOGG AVE RAMP Q			0.38	0.37	0.04	190.00									0.79	190.00																													
	01/SAF/OT	IR-275		KELLOGG AVE RAMP R			0.21	0.22											0.43																														
HAM	02/SAF/OT	SR 125	4.07	CITY OF CINCINNATI CORP LIMIT	7.52	COUNTY LINE	6.14	9.44	6.85	4370.00	8813.00								12.28	16.29	4370.00	8813.00																							REFER TO PID 102548 FOR PAVEMENT MARKING PLANS				
																																												IGNORE COMMENTS TO SUSPEND PAVEMENT MARKINGS					
SUBTOTAL												0.34	0.30															2.77	2.81																				
CARRIED TO GENERAL SUMMARY							6.14	16.73	12.68	9220.00	11141.00		0.64	0.56	2154.00	768.00			12.28	29.41	9220.00	11141.00	1.20	2154.00	768.00		5.58	5.25	800.00								0.36	0.18											

PAVEMENT MARKING SUBSUMMARY

DESIGN AGENCY



DESIGNER
PMM

REVIEWER
MAG 09/25/20

PROJECT ID
113754

SHEET TOTAL
P.5 | 5