

GENERAL:
THE CONTRACTOR SHALL SUBMIT IN WRITING A SCHEDULE OF OPERATIONS TO THE ENGINEER AND RECEIVE APPROVAL IN WRITING BEFORE WORK IS STARTED ON THIS PROJECT. ALL TRAFFIC CONTROL DEVICES SHALL BE FURNISHED, ERECTED, MAINTAINED, AND REMOVED BY THE CONTRACTOR IN ACCORDANCE WITH THE OHIO MANUAL OF UNIFORM TRAFFIC CONTROL DEVICES.

THE CONTRACTOR SHALL NOTIFY THE EXPO CENTER AND OHIO HISTORY CENTER FACILITIES PROJECT SUPERINTENDENTS THREE (3) WORKING DAYS PRIOR TO THE BEGINNING OF WORK AT ANY OF THE LOCATIONS.

ALIGNMENT AND PROFILE:
THE MAJORITY OF THE WORK INVOLVED IN THIS PROJECT IS TO MAINTAIN THE EXISTING CROSS-SLOPE (CROWN). THE CONTRACTOR SHALL TAKE SPECIAL CARE AS TO MAINTAIN PROPER GRADE DURING THE MILLING PROCESS SO THAT WATER WILL NOT POND.

CONTINGENCY QUANTITIES:
THE CONTRACTOR SHALL NOT ORDER MATERIALS OR PERFORM WORK FOR ITEMS DESIGNATED BY PLAN NOTE TO BE USED "AS DIRECTED BY THE ENGINEER" UNLESS AUTHORIZED BY THE ENGINEER. THE ACTUAL WORK LOCATIONS AND QUANTITIES USED FOR SUCH ITEMS SHALL BE INCORPORATED INTO THE FINAL CHANGE ORDER GOVERNING COMPLETION OF THIS PROJECT.

WORK LIMITS:
THE WORK AREAS SHOWN ON THESE PLANS ARE FOR PHYSICAL CONSTRUCTION ONLY AND ARE TO BE CONSIDERED A GENERAL DESCRIPTION OF THE ACTUAL WORK LIMITS. EXACT LIMITS ARE TO BE COORDINATED WITH AND MARKED BY THE ENGINEER AND THE FACILITIES PROJECT SUPERINTENDENTS.

EXPO CENTER
FERRIS ELLIS
717 EAST 17TH AVE
COLUMBUS, OHIO 43211
614-817-8949
F.ELLIS@EXPO.OHIO.GOV

OHIO HISTORY CENTER
CARLOS LUGO
800 E. 17TH AVE
COLUMBUS, OHIO 43211-2474
614.297.2460
CLUGO@OHIOHISTORY.ORG

REMOVAL ITEMS:
UNLESS OTHERWISE INSTRUCTED, GRINDINGS AS A RESULT OF THE PLANING SHALL BECOME PROPERTY OF THE CONTRACTOR AND SHALL BE DISPOSED OF. PAYMENT FOR THE ABOVE SHALL BE INCLUDED IN THE UNIT PRICE BID FOR THE REMOVED ITEM.

UNDERGROUND UTILITIES:
THE CONTRACTOR SHALL GIVE NOTICE OF INTENT TO CONSTRUCT TO THE OHIO UTILITIES PROTECTION SERVICE, PRODUCERS UNDERGROUND PROTECTION SERVICE, AND OWNERS OF UNDERGROUND FACILITIES THAT ARE NOT MEMBERS OF A REGISTERED PROTECTION SERVICE IN ACCORDANCE WITH SECTION 153.64 OF THE OHIO REVISED CODE. THE ABOVE MENTIONED NOTICE SHALL BE GIVEN AT LEAST TWO WORKING DAYS PRIOR TO THE START OF CONSTRUCTION.

OHIO UTILITY PROTECTION SERVICE 1-800-362-2764
PRODUCERS UNDERGROUND PROTECTIVE SERVICE 1-614-587-0486
NON-MEMBERS MUST BE CALLED DIRECTLY.

THERE IS NO UTILITY IMPACTS ANTICIPATED; HOWEVER, DUE TO ANY UNFORESEEN CIRCUMSTANCES IT WOULD BE THE RESPONSIBILITY OF THE EXPO CENTER (LOCATIONS 1 AND 2) AND/OR THE OHIO HISTORY CENTER (LOCATIONS 3, 4 AND 5) TO PAY FOR AND COORDINATE ANY RELOCATION NECESSARY.

REVIEW OF DRAINAGE FACILITIES:
BEFORE ANY WORK IS STARTED ON THE PROJECT AND AGAIN BEFORE FINAL ACCEPTANCE OF THE PROJECT BY THE STATE, REPRESENTATIVES OF THE STATE AND THE CONTRACTOR SHALL INSPECT ALL EXISTING SEWERS WHICH ARE TO REMAIN IN SERVICE AND WHICH MAY BE AFFECTED BY THE WORK. THE CONDITION OF EXISTING CONDUITS AND THEIR APPURTENANCE SHALL BE DETERMINED FROM FIELD OBSERVATIONS. RECORDS OF THE INSPECTION SHALL BE KEPT IN WRITING BY THE STATE.

ALL EXISTING SEWERS INSPECTED INITIALLY BY THE ABOVE MENTIONED PARTIES SHALL BE MAINTAINED AND LEFT IN A CONDITION REASONABLY COMPARABLE TO THAT DETERMINED BY THE ORIGINAL INSPECTION. THE CONTRACTOR, TO THE SATISFACTION OF THE ENGINEER, SHALL CORRECT ANY CHANGE IN THE CONDITION RESULTING FROM THE CONTRACTOR'S OPERATIONS.

ITEM 202 - PAVEMENT REMOVED, AS PER PLAN
THE AVERAGE DEPTH OF REMOVAL SHALL BE 4.5" TO REMOVE THE ENTIRE ASPHALT CONCRETE LAYER. THE SUBGRADE SHALL BE EXPOSED IN ORDER TO COMPLETE COMPACTION.

ITEM 202 - CURB REMOVED, AS PER PLAN
THE EXISTING CURB MATERIAL IS ASPHALT. REMOVE CURB ADJACENT TO PAVING AREAS TO AN EXTENT TO ALLOW FOR NEW CONCRETE CURB INSTALLATION.

ITEM 659 - SEEDING AND MULCHING:
THE FOLLOWING QUANTITIES ARE PROVIDED TO PROMOTE GROWTH AND CARE OF PERMANENT SEEDING AREAS IN AREAS OF CURB REPLACEMENT:

ITEM 659 - TOPSOIL	= 51 CY
ITEM 659 - SEEDING AND MULCHING	= 493 SY
ITEM 659 - REPAIR SEEDING AND MULCHING	= 24 SY
ITEM 659 - INTER-SEEDING	= 24 SY
ITEM 659 - COMMERICAL FERTILIZER	= 0.07 TON
ITEM 659 - LIME	= 0.10 ACRE
ITEM 659 - WATER	= 2 MGAL

ITEM 253 - PAVEMENT REPAIR, AS PER PLAN, 4.5", 301
ALL REPAIR AREAS SHALL BE IDENTIFIED AND MARKED OUT BY THE PROJECT ENGINEER. THE REPAIR AREAS SHALL BE OF VARYING LENGTH AND WIDTH. THE AVERAGE DEPTH OF EACH REPAIR SHALL BE 4.5". ALL AREAS SHALL BE REFILLED 4.5" OF ITEM 301 - ASPHALT CONCRETE BASE, PG64-22, (449) . PAVEMENT REPAIR AREAS SHALL BE INCLUDED IN THE GENERAL RESURFACING. SEE DETAIL ON SHEET P.02.

ITEM 253 - PAVEMENT REPAIR, AS PER PLAN, 4.5", 441
ALL REPAIR AREAS SHALL BE IDENTIFIED AND MARKED OUT BY THE PROJECT ENGINEER. THE REPAIR AREAS SHALL BE OF VARYING LENGTH AND WIDTH. THE AVERAGE DEPTH OF EACH REPAIR SHALL BE 4.5". ALL AREAS SHALL BE REFILLED 3.0" OF ITEM 301 - ASPHALT CONCRETE BASE, PG64-22, (449) AND 1.5" OF ITEM 441 - ASPHALT CONCRETE SURFACE COURSE, TYPE 1, (449), PG64-22. SEE DETAIL ON SHEET P.02.

ITEM 644 - THERMOPLASTIC PAVEMENT MARKINGS:
THE LOCATIONS, SIZES, AND SHAPES OF PROPOSED PAVEMENT MARKINGS WILL BE APPROXIMATELY THE SAME AS EXISTING. IT IS THE CONTRACTOR'S RESPONSIBILITY TO VERIFY THE LOCATION, SIZE, AND SHAPE OF THESE EXISTING PAVEMENT MARKINGS BEFORE THE PAVEMENT REPAIRS, PAVEMENT PLANING, AND RESURFACING OBLITERATES THEM. HANDICAP SYMBOL MARKINGS SHALL BE AS DIRECTED BY THE EXPO CENTER AND OHIO HISTORY CENTER FACILITIES PROJECT SUPERINTENDENT. PAVEMENT MARKINGS WHICH ARE PLACED AT THE WRONG LOCATIONS SHALL BE REMOVED AND REPLACED AT THE CONTRACTOR'S EXPENSE.

ITEM 623 - CONSTRUCTION LAYOUT STAKES AND SURVEYING, AS PER PLAN:
THIS ITEM IS PROVIDED TO COMPENSATE THE CONTRACTOR FOR ANY SURVEYING AND STAKING NECESSARY TO PERFORM THE WORK. THE CONTRACTOR SHALL USE ANY METHOD, AS APPROVED BY THE ENGINEER, TO ESTABLISH AND VERIFY THAT THE WORK IS BEING PERFORMED AS DETAILED IN THIS PLAN.



GENERAL SUMMARY

DESIGNER AGENCY



DESIGNER
KLM

REVIEWER
DKR 07/14/25

PROJECT ID
122854

SHEET
P.08

TOTAL
21