

LEGEND

	DESCRIPTION	ODOT CLASS	CLASSIFIED MECH./VISUAL	
	SANDY SILT	A-4a	2	4
	SILT AND CLAY	A-6a	9	7
	SITLY CLAY	A-6b	3	29
		TOTAL	14	40
	PAVEMENT OR BASE = X = APPROXIMATE THICKNESS	VISUAL		

-  BORING LOCATION - PLAN VIEW.
-  DRIVE SAMPLE AND/OR ROCK CORE BORING PLOTTED TO VERTICAL SCALE ONLY. HORIZONTAL BAR INDICATES A CHANGE IN STRATIGRAPHY.
-  AUGER BORING PLOTTED TO VERTICAL SCALE ONLY. HORIZONTAL BAR INDICATES A CHANGE IN STRATIGRAPHY.

WC INDICATES WATER CONTENT IN PERCENT.

w— INDICATES FREE WATER ELEVATION.

▼ INDICATES STATIC WATER ELEVATION.

N<sub>60</sub> INDICATES STANDARD PENETRATION RESISTANCE NORMALIZED TO 60% DRILL ROD ENERGY RATIO.  
 ● INDICATES A PLASTIC MATERIAL WITH A MOISTURE CONTENT EQUAL TO OR GREATER THAN THE LIQUID LIMIT MINUS 3.

SS INDICATES A SPLIT SPOON SAMPLE.

ST INDICATES A SHELBY TUBE.

NI INDICATES A NOT INTACT SAMPLE.

TR INDICATES TOP OF ROCK.

\* INDICATES UNCONFINED COMPRESSIVE STRENGTH TEST BY ASTM D 2166

ORGANIC CONTENT INDICATES ORGANIC CONTENT BY LOSS ON IGNITION.















