



LEGEND & NOTES

- 1) "*" MINIMUM "NO PARKING ZONE" DISTANCE FROM CROSS STREET, DRIVEWAY, ALLEY, OR FIRE HYDRANT.
- 2) "++" ONE PARKING STALL AT EACH END OF PARALLEL PARKING STALLS SHALL BE 20' IN LENGTH.
- 3) "**" INTERIOR PARKING STALLS, BETWEEN END STALLS, SHALL BE EQUAL IN LENGTH (22' TO 26').
- 4) MAXIMIZE THE NUMBER OF PARKING STALLS DURING INSTALLATION.
- 5) PARALLEL PARKING STALLS SHALL BE 8' WIDE UNLESS OTHERWISE SHOWN.
- 6) WHEEL CHAIR SYMBOL (40" WIDE x 40" HEIGHT), AS SHOWN TO THE RIGHT, SHALL BE MARKED IN ALL DISABILITY PARKING STALLS.
- 7) CURB ALONG "NO PARKING ZONES" SHALL BE PAINTED YELLOW BY CITY OR VILLAGE.

LOCATION	ITEM	DESCRIPTION	UNIT	QUANTITY		TOTAL
				LEFT	RIGHT	
	630	GROUND MOUNTED SUPPORT, NO. 3 POST	FT	15	15	30
	630	SIGN, FLAT SHEET	SF	9	9	18
BS	630	REMOVAL OF GROUND MOUNTED SIGN AND DISPOSAL	EACH	1	1	2
	630	REMOVAL OF GROUND MOUNTED POST AND DISPOSAL	EACH	1	1	2
SL	644	STOP LINE	FT		27	27
	644	CROSS WALK LINE	FT		44	44
PS	644	PARKING LOT STALL MARKING	FT		167	167
	644	WORD ON PAVEMENT, 96" ("XING")	EACH		2	2
	644	BIKE CORSSING SYMBOL	EACH		2	2

ITEMS 644 CARRIED TO RPM AND PAVEMENT MARKINGS SHEET WHILE ITEMS 630 ARE CARRIED TO GENERAL SUMMARY.

\projects\88767\roadway\sheet\88767\001.dgn