

Coor 5/24/22 JAC 327 1358 Jost, Thomas  
 60

STA	+	H/I	-	ECC	DESC.
CP01	2.021	102.021		100.000	See Below
BM1				5.995	96.026
	5.617	101.643			
TP1				9.954	91.689
	3.708	95.397			
CP02				2.997	92.400
	6.779	99.179			
BM2				0.317	98.862
	0.875	99.737			
CP03				1.863	97.874
	1.544	99.418			
TP2				7.597	91.821
	4.169	95.990			Reinforce
TP3				2.663	93.327
	8.624	101.951			
CP01				1.943	100.008 (10.008)
CP01 →	Set 5/8" rebar in "open trench" 10' cap near road				
CP02 →	embankment by a concrete monument				
	Set 5/8" rebar in "open trench" 10' cap near				
CP03 →	pullout by conduit				
	Set 5/8" rebar in "open trench" 10' cap near				
BM1 →	power pole				
	Set RD spike in				Power Pole
BM2 →	Set RL spike in				Power Pole near 003,

Coor 5/24/22 JAC 327 1358 Jost, Thomas  
 60

Angles & Distances

1 @ CP02  
 BS @ CP01  
 AS @ CP03

Direct

191-59-00  
 168-00-59  
 359-59-59

CP01

① 635.725  
 ② 633.724  
 ③ 633.728  
 ④ 633.729  
 \* 633.725

Indirect

11-58-59  
 348-00-58  
 359-59-57

CP03

① 300.656  
 ② 300.659  
 ③ 300.662  
 ④ 300.662  
 \* 300.660