

STATION TO STATION		SIDE	LENGTH L	AVERAGE WIDTH W	SURFACE AREA A A = L x W	CADD AREAS	204	204	301	304	407	441	441	609
							SUBGRADE COMPACTION SY	PROOF ROLLING HR	ASPHALT CONCRETE BASE, PG64-22, (449) CY	AGGREGATE BASE CY	TACK COAT (0.055 GAL/SY) GAL	ASPHALT CONCRETE SURFACE COURSE, TYPE 1, (448), PG64-22 CY	ASPHALT CONCRETE INTERMEDIATE COURSE, TYPE 1, (448) CY	CURB, TYPE 4C FT
STA. 27+60.22	STA. 28+31.53	LT/RT	71	26.17		1860.54	207	0.10	46	34	23	9	9	
STA. 31+65.68	STA. 32+38.11	LT/RT	72	26.08		1807.55	201	0.10	45	34	22	8	8	
STA. 28+31.53	STA. 28+55.94	LT/RT	24	33.00	806		90			15				
STA. 31+44.06	STA. 31+68.47	LT/RT	24	33.00	806		90			15				
STA. 28+18.34	STA. 28+38.34	RT												20
STA. 28+36.65	STA. 28+56.65	LT												20
STA. 31+63.48	STA. 31+43.48	LT												20
STA. 31+81.80	STA. 31+61.80	RT												20
TOTALS CARRIED TO GENERAL SUMMARY							588	0.20	91	98	45	17	17	80

PAVEMENT CALCULATIONS / SUBSUMMARY

DESIGN AGENCY



DESIGNER
CJK

REVIEWER
JMZ 09/24/21

PROJECT ID
105777

SHEET TOTAL
P.11 50