ALIGNMENT AND PROFILE

THE WORK PROPOSED BY THIS PROJECT CONSISTS OF MICROSURFACING OF THE EXISTING PAVEMENT. THE ALIGNMENT OF THE EXISTING PAVEMENT WILL NOT BE CHANGED AND THE PROFILE OF THE PROPOSED SURFACE WILL BE SIMILAR TO THAT OF THE EXISTING PAVEMENT.

COORDINATION OF WORK:

LOG-33-15.67 (PID 101175) LOG-CS-FY2021 (PID 113075) D07-CHIP-FY21B (PID 109708)

THE CONTRACTOR IS ADVISED THAT ADJACENT CONSTRUCTION PROJECTS WITHIN OR NEAR THE WORK LIMITS OF THIS PLAN MAY IMPACT THE PROJECT SCHEDULE, SEQUENCE OF CONSTRUCTION AND/OR TRAFFIC CONTROL BETWEEN ADJACENT ZONES. THE CONTRACTOR IS REQUIRED TO COORDINATE ALL MAINTENANCE OF TRAFFIC OPERATIONS WITH ADJACENT CONSTRUCTION PROJECTS. COOPERATION WITH THE ENGINEER, INSPECTORS AND ALL OTHER CONTRACTORS ON OR ADJACENT TO THE PROJECT IS REQUIRED PER CMS 105.08.

ITEM 253 - PAVEMENT REPAIR, AS PER PLAN (A) ITEM 253 - PAVEMENT REPAIR, AS PER PLAN (B)

PAVEMENT REPAIR SHALL BE IN ACCORDANCE WITH ITEM 253 -PAVEMENT REPAIR, WITH THE FOLLOWING ADDITIONS:

THE ENGINEER SHALL DESIGNATE THE LOCATIONS AND LIMITS OF THE AREAS TO BE REPAIRED. THE AREAS SHALL BE ROUGHLY RECTANGULAR IN SHAPE AND SAWED OR MILLED TO A NEAT LINE. THE DEPTH OF REMOVAL, AS DIRECTED BY THE ENGINEER, SHALL BE SUFFICIENT TO REMOVE ALL DETERIORATED PAVEMENT. THE ENTIRE AREA INCLUDING VERTICAL FACES SHALL BE COATED PRIOR TO PLACING THE REPLACEMENT MATERIAL PER 253.03.

PAVEMENT REPAIR (A) AREAS SHALL BE A MINIMUM OF OF 12.5 FEET IN WIDTH, 25 FEET IN LENGTH AND 4 INCHES IN DEPTH OR AS DIRECTED BY THE ENGINEER. THE REPLACEMENT MATERIAL SHALL BE ITEM 442, ASPHALT CONCRETE INTERMEDIATE COURSE, 9.5 MM, TYPE A, (448) AND FINISHED TO MATCH THE EXSTING PAVEMENT SURFACE. SEALING THE PERIMETER OF THE REPAIR AREA PER 253.03 IS INCLUDED IN THE PAYMENT OF ITEM 253.

PAVEMENT REPAIR (B) AREAS ALONG THE LANE AND EDGE LINES SHALL BE A MINIMUM OF 2 FEET IN WIDTH AND 4 INCHES IN DEPTH OR AS DIRECTED BY THE ENGINEER. THE REPLACEMENT MATERIAL SHALL BE ITEM 442, ASPHALT CONCRETE INTERMEDIATE COURSE, 9.5 MM TYPE A, (448), AND FINISHED TO MATCH THE EXSTING PAVEMENT SURFACE. SEALING THE PERIMETER OF THE REPAIR AREA PER 253.03 IS INCLUDED IN THE PAYMENT OF ITEM 253.

THE FOLLOWING ESTIMATED QUANTITIES HAVE BEEN CARRIED TO THE GENERAL SUMMARY TO BE USED AS DIRECTED BY THE ENGINEER.

ITEM 253 - PAVEMENT REPAIR, AS PER PLAN (A) = 1500 SQ YD , ITEM 253 - PAVEMENT REPAIR, AS PER PLAN (B) = 5500 SQ YD

PAVEMENT MARKINGS

IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO DOCUMENT THE LAYOUT OF THE EXISTING PAVEMENT MARKINGS INCLUDING EXISTING LANE AND SHOULDER WIDTHS IN A LOG AND SUBMIT TO THE DEPARTMENT FOR ACCEPTANCE. THE DEPARTMENT WILL NOT ALLOW THE CONTRACTOR TO PERFORM ANY PAVEMENT WORK FUNCTIONS (MILLING, OVERLAY, ETC.) UNTIL ACCEPTANCE OF THE SUBMITTED EXISTING MARKING LOG.

MARKINGS SHALL REPLACED IN KIND EXCEPT WHERE EXISTING MARKINGS DO NOT MEET THE CURRENT STANDARD CONSTRUCTION DRAWINGS. THE CONTRACTOR SHALL COORDINATE AND CORRABORATE THE PROPOSED LAYOUT OF ALL PAVEMENT MARKINGS PER APPLICABLE STANDARD CONSTRUCTION DRAWINGS WITH ODOT.

NO PERMANENT PAVEMENT MARKINGS, RAISED PAVEMENT MARKERS, NOR RUMBLE STRIPS SHALL BE PLACED UNTIL THE ODOT PROJECT ENGINEER HAS APPROVED THE LOCATION AND/OR LAYOUT OF THE WORK ZONE PAVEMENT MARKINGS.

PAVEMENT MARKINGS ON INTERSECTING ROADWAYS

THE EDGE LINE SHALL BE CONTINUED AROUND ALL RADII TO MATCH THE EXISTING EDGE LINE OF THE INTERSECTING ROUTE. IF THE INTERSECTING ROUTE HAS A CENTER LINE MARKING, THE CENTER LINE SHALL BE RE-STRIPED OVER THE AREA OF RESURFACING.

THERMOPLASTIC PAVEMENT MARKINGS

THE CONTRACTOR SHALL WAIT A MINIMUM OF 14 DAYS BEFORE PLACING THE PERMANENT THERMOPLASTIC PAVEMENT MARKINGS.

 \bigcirc

 \bigcirc

 \bigcirc

 \bigcirc

PROTECTION OF THE MAD RIVER WATER TRAIL

THE CONTRACTOR MUST ENSURE THAT THE MAD RIVER CHANNEL IN THE VICINITY OF SLM 21.10 REMAINS OPEN TO BOAT TRAFFIC. IF NECESSARY TO PROTECT BOATERS DURING OVERHEAD WORK, THE CONTRACTOR MAY DIRECT BOATERS THROUGH SIGNAGE OR A LOOKOUT TO STEER TO A SPECIFIC SIDE OF THE CHANNEL.

PROJECT SCHEDULE

NO WORK SHALL BEGIN ON THE PROJECT UNTIL JUNE 1, 2021.

GENERAL NOTES

ဖ
9
ມີ
<u> </u>
ŝ
ဗ
Ġ
Ō

					SHEE	T NUM.						PA	RT.		ITEM	GRAND		
						3	4	5	7	8	9	01/NHS/PV	02/SAF/O T	ITEM	EXT	TOTAL	UNIT	
						\sim	\sim	\sim	\sim	\sim	\sim		\sim	\sim	\sim	\sim		mmm
						1,500						1,500		253	01001	1,500	SY	PAVEMENT REPAIR, AS PER PLAN (A)
					<u> </u>	5,500			100 700			5,500 190,729		253 121	01001	5,500 190.79	SY	PAVEMENT REPAIR, AS PER PLAN (B)
						$\mu \tau$	$\overline{\gamma}$	\sim	198.728 177,004	\mathcal{P}	$\overline{\gamma}$	177,004	$\gamma \gamma \gamma$	421	10020	177,004	SY SY	MIAROSURFACING, SURFACE SOURSE
										35.07		,	35.07	850	10010	35.07	MILE	GROOVING FOR 6" RECESSED PAVEMENT MARI
~																		
\bigcirc		-								7,428 7,201			7,428	850 850	10110 10130	7,428 7,201	FT FT	GROOVING FOR 6" RECESSED PAVEMENT MARI GROOVING FOR 12" RECESSED PAVEMENT MAR
										0.87			7,201 0.87	850 850	20010	0.87	MILE	GROOVING FOR 12" RECESSED PAVEMENT MAR
										240			240	850	20110	240	FT	GROOVING FOR 6" RECESSED PAVEMENT MARI
										163			163	850	20130	163	FT	GROOVING FOR 12" RECESSED PAVEMENT MAR
											655	655		621	00100	655	EACH	RPM
											655	655		621	54000	655	EACH	RAISED PAVEMENT MARKER REMOVED
\sim										0.58			0.58	807	12010	0.58	MILE	WET REFLECTIVE EPOXY PAVEMENT MARKING,
\bigcirc										0.29			0.29	807	12110	0.29	MILE	WET REFLECTIVE EPOXY PAVEMENT MARKING,
										163			163	807	12310	163	FT	WET REFLECTIVE EPOXY PAVEMENT MARKING,
										240			240	807	12410	240	FT	WET REFLECTIVE EPOXY PAVEMENT MARKING
										23.38			23.38	807	14010	23.38	MILE	WET REFLECTIVE THERMOPLASTIC PAVEMENT
										11.69			11.69	807	14110	11.69	MILE	WET REFLECTIVE THERMOPLASTIC PAVEMENT
	-			-						7,201 7,428			7,201 7,428	807 807	14310 14410	7,201 7,428	FT FT	WET REFLECTIVE THERMOPLASTIC PAVEMENT WET REFLECTIVE THERMOPLASTIC PAVEMENT
										1,420			1,420	007	14410	7,420	<i>F1</i>	WEI REFLECTIVE THERMOFLASTIC FAVEMENT
	w																	M
	e si						200					200		614	11110	200	HOUR	LAW ENFORCEMENT OFFICER WITH PATROL C
	≥ ∪			 				4		47.92		4 47.92		614 614	18601 98000	4 47.92	SNMT MILE	PORTABLE CHANGEABLE MESSAGE SIGN, AS F WORK ZONE PAVEMENT MARKING, MISC.: WOR
	-									35.94		35.94		614	98000	35.94	MILE	WORK ZONE PAVEMENT MARKING, MISC.: WOR WORK ZONE PAVEMENT MARKING, MISC.: WOR
:	^<									22,092		22,092		614	98100	22,092	FT	WORK ZONE PAVEMENT MARKING, MISC.:WORK
	2:54																	
	8:03							6		23,004		23,004 6		614 808	98100 18700	23,004 6	FT SNMT	WORK ZONE PAVEMENT MARKING, MISC.:WORK DIGITAL SPEED LIMIT (DSL) SIGN ASSEMBLY
	20							0				0		000	18700	0	SININT	DIGITAL SPEED LIMIT (DSL) SIGN ASSEMBLT
	/20																	
	61/1											LS		614	11000	LS		MAINTAINING TRAFFIC
	+											LS		624	10000	LS		MOBILIZATION
	9																	
	Jộp.																	
	loog																	
0	ts/																	
	9																	
	Ô×																	
	00																	
	sig																	
0	1567																	
	- m m																	
	50 ⁻ 0																	
	1/10																	
				+	+							+						
	to																	
1																		
	o 			 														
I				+														
	<u></u>	1	1	1	1				1		1	1		I		1		1

		<u> </u>
DESCRIPTION	SEE SHEET NO.	CALCULATED TMK CHECKED CWW
PAVEMENT		
	3	
	3	
ARKING, (ASPHALT)		
ARKING, (ASPHALT) ARKING, (ASPHALT)		
ARKING, (ASPHALT) ARKING, (CONCRETE)		
ARKING, (CONCRETE)		
ARKING, (CONCRETE)		
TRAFFIC CONTROL		
IG, EDGE LINE, 6"		
IG, LANE LINE, 6"		🛴
IG, CHANNELIZING LINE, 12"		SUMMARY
		5
IG, DOTTED LINE, 6"		
NT MARKING, EDGE LINE, 6″		
NT MARKING, LANE LINE, 0 NT MARKING, CHANNELIZING LINE, 12"		
NT MARKING, DOTTED LINE, 6"		
MAINTENANCE OF TRAFFIC		GENERAL
CAR FOR ASSISTANCE		<u> </u>
PER PLAN	5	<u> </u>
ORK EDGE LINE, CLASS 1, 6", 807 PAINT	8	
ORK ZONE LANE LINE, CLASS 1, 6", 807 PAINT RK ZONE CHANNELIZING LINE, CLASS 1, 12", 807 PAINT	8	
TA ZOWE CHANNELIZING LINE, CLASS 1, 12, 601 FAINT	0	
RK ZONE DOTTED LINE, CLASS 1, 6", 807 PAINT	8	
Y		
INCIDENTALS		
INCIDENTALS		
		ဖ
		မိ
		15
		ິ ເຕັ
		⁽¹⁾
		G
		0G-33-15.6
		\vdash
		6
		9
	1	\sim