

BRIDGE / MEMBER DATA

Structure I. D. HAM500

Material of Construction SS
 Year of Construction 1959
 Roadway Width 32.000
 Center to Center Truss 38.833
 Number of Spans 1
 Live Load Distribution Factor 1.5840

Comments:

Truss I. D. 1 Truss Type: THROUGH

Span Length: Span 1
191.333

Number of Panels: 8 Symmetry:

Panel No.	Panel Code	Panel Length	Sub-Divided Panel Length	Vertical Height	Sub-Divided Vertical
1	7	23.917	0.000	28.000	0.000
2	2	23.917	0.000	33.250	0.000
3	2	23.917	0.000	35.000	0.000
4	4	23.917	0.000	35.000	0.000
5	3	23.917	0.000	35.000	0.000
6	1	23.917	0.000	33.250	0.000
7	1	23.917	0.000	28.000	0.000
8	5	23.917	0.000	0.000	0.000

Superimposed Dead Load:

Uniform Dead Load
 (kips/ft)
 Loaded Chord Unloaded Chord

 0.355 0.000

Superimposed Dead Load:

Loaded Chord Dist.	Loaded Chord Load	Unloaded Chord Dist.	Unloaded Chord Load
0.000	28.160	0.000	0.000
23.917	62.790	0.000	0.000
47.833	52.440	0.000	0.000
71.750	54.970	0.000	0.000
95.667	53.790	0.000	0.000

119.583	54.970	0.000	0.000
143.500	52.440	0.000	0.000
167.417	62.790	0.000	0.000

Truss Members Selected:

L 0L 1
L 0U 1
U 1L 1
U 1U 2
L 1L 2
U 1L 2
U 2L 2
U 2U 3
L 2L 3
U 2L 3
U 3L 3
L 3L 4
U 3U 4
U 3L 4
L 3U 4
U 4L 4
L 4L 5
U 4U 5
L 4U 5
U 4L 5
U 5L 5
L 5L 6
U 5U 6
L 5U 6
U 6L 6
L 6L 7
U 6U 7
L 6U 7
U 7L 7
L 7L 8
U 7L 8

NOTE: All distances are shown in decimal feet, moments are shown in foot-kips, and shears are shown in kips. Section and section properties are shown as: in., in.**2, in.**3, and in.**4. Axial loads are shown in kips.

SECTION DATA (ASD/LFD)

Structure I. D. HAM500

Truss I. D. 1
 Truss Member I. D. L 0L 1

RATIO/Inv.	Allowable stress (fs) (psi)			
	Inventory	Operating	Posting	Special
Fy (tension)	18150.	24750.	0.	0.
Fy (compression)	14057.	17530.	0.	0.
Fy (ultimate)	33000.			

Member Properties:

Effective Length X (ft)	Effective Length Y (ft)	Eccentricity Y (in)	End Cond.	Batton
23.917	23.917	0.00	P	1.0

Gross Section Properties:

Height	Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy	Rx	Ry
15.00	22.50	421.86	743.54	7.50	4.33	5.75

Net Section Properties:

Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy
21.38	507.10	595.25	8.68

Truss influence line - loaded chord:

X ordinates:	0.000	23.917	191.333	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	0.747	0.000	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

Truss influence line - unloaded chord:

X ordinates:	0.000	23.917	191.333	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	0.747	0.000	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

RATING REPORT

Rating Types and Vehicles

Structure I. D. HAM500

INV.	OPER	POST	SPEC
HS20	5C1T		

Truss I. D.	1
Truss Member I. D.	L 0L 1

Axial Dead Load	
Tension	Compression

210.6	0.0
-------	-----

Veh.	Axial Tension	Load Capacity Compression	Available Tension	Capacity for LL+I Compression
INV.	325.6	263.0	199.2	389.4
OPER	542.6	438.4	332.0	649.1

Live Load Effect

Impact Factors: ten - .158 comp - .000

Rat. Typ.	Rat. Veh.	Truck w/imp.	Live Load w/o imp.	Force	Loc. of Front Wheel	Lane w/imp.	Live Load w/o imp.	Force	Loc. of Conc. Load
INV.	HS20	46.60 R	40.24		51.92	54.31	46.90		23.92
		0.00 R	0.00		0.00	0.00	0.00		0.00
OPER	5C1T	66.79 L	57.67		11.92	0.00	0.00		0.00
		0.00 R	0.00		0.00	0.00	0.00		0.00

Veh.	Rating Factor	Axial Rating Value	Load Capacity (tons)
HS20	3.67	HS 73.35	132.0
5C1T	4.97	0.00	397.6

SECTION DATA (ASD/LFD)

Structure I. D. HAM500

Truss I. D. 1
 Truss Member I. D. L 0U 1

RATIO/Inv.	Allowable stress (fs) (psi)			
	Inventory	Operating	Posting	Special
Fy (tension)	18150.	24750.	0.	0.
Fy (compression)	14277.	17804.	0.	0.
Fy (ultimate)	33000.			

Member Properties:

Effective Length X (ft)	Effective Length Y (ft)	Eccentricity Y (in)	End Cond.	Batton
36.823	36.823	0.00	P	1.0

Gross Section Properties:

Height	Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy	Rx	Ry
25.78	41.21	2775.48	2144.43	21.40	8.21	7.21

Net Section Properties:

Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy
41.21	2775.48	2144.43	21.40

Truss influence line - loaded chord:

X ordinates:	0.000	23.917	191.333	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	-1.151	0.000	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

Truss influence line - unloaded chord:

X ordinates:	0.000	23.917	191.333	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	-1.151	0.000	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

RATING REPORT

Structure I. D. HAM500 Rating Types and Vehicles

	INV.	OPER	POST	SPEC
	HS20	5C1T		
Truss I. D.				
Truss Member I. D.				

Axial Dead Load	
Tension	Compression
0.0	324.3

Veh.	Axial Tension	Load Capacity Compression	Available Tension	Capacity for LL+I Compression
INV.	627.7	489.3	822.3	294.7
OPER	1046.1	815.6	1370.4	491.2

Live Load Effect

Impact Factors: ten - .000 comp - .158

Rat. Typ.	Rat. Veh.	Truck w/imp.	Live Load w/o imp.	Force w/o imp.	Loc. of Front Wheel	Lane w/imp.	Live Load w/o imp.	Force w/o imp.	Loc. of Conc. Load
INV.	HS20	0.00 R	0.00	0.00	0.00	0.00	0.00	0.00	0.00
		-71.76 R	-61.96	51.92		-92.06	-79.50	23.92	
OPER	5C1T	0.00 R	0.00	0.00	0.00	0.00	0.00	0.00	0.00
		-102.83 L	-88.79	11.92		0.00	0.00	0.00	

Veh.	Rating Factor	Axial Rating Value	Load Capacity (tons)
HS20	3.20	HS 64.03	115.3
5C1T	4.78	0.00	382.2

SECTION DATA (ASD/LFD)

Structure I. D. HAM500

Truss I. D. 1
 Truss Member I. D. U 1L 1

RATIO/Inv.	Allowable stress (fs) (psi)			
	Inventory	Operating	Posting	Special
Fy (tension)	18150.	24750.	0.	0.
Fy (compression)	5837.	7280.	0.	0.
Fy (ultimate)	33000.			

Member Properties:

Effective Length X (ft)	Effective Length Y (ft)	Eccentricity Y (in)	End Cond.	Batton
28.000	28.000	0.00	P	1.0

Gross Section Properties:

Height	Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy	Rx	Ry
11.94	11.80	310.00	44.10	0.00	5.13	1.93

Net Section Properties:

Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy
11.51	415.42	31.40	0.77

Truss influence line - loaded chord:

X ordinates:	0.000	0.000	23.917	47.833	191.333	0.000	0.000	0
.000	0.000	0.000						
Y ordinates:	0.000	0.000	1.000	0.000	0.000	0.000	0.000	0
.000	0.000	0.000						

Truss influence line - unloaded chord:

X ordinates:	0.000	191.333	0.000	0.000	0.000	0.000	0.000	0
.000	0.000	0.000						
Y ordinates:	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0
.000	0.000	0.000						

RATING REPORT

Structure I. D. HAM500 Rating Types and Vehicles

	INV.	OPER	POST	SPEC
	HS20	5C1T		
Truss I. D.				
Truss Member I. D.	U 1L	1		

Axial Dead Load
Tension Compression

71.3 0.0

Veh.	Axial Tension	Load Capacity Compression	Available Tension	Capacity for LL+I Compression
INV.	175.3	57.3	132.5	100.1
OPER	292.2	95.5	220.9	166.8

Live Load Effect

Impact Factors: ten - .289 comp - .000

Rat. Typ.	Rat. Veh.	Truck w/imp.	Live Load w/o imp.	Force	Loc. of Front Wheel	Lane w/imp.	Live Load w/o imp.	Force	Loc. of Conc. Load
INV.	HS20	49.61 R	38.48	37.92	42.18	32.71	23.92		
		0.00 R	0.00	0.00	0.00	0.00	0.00		
OPER	5C1T	38.24 L	29.41	11.92	0.00	0.00	0.00		
		0.00 R	0.00	0.00	0.00	0.00	0.00		

Veh.	Rating Factor	Axial Rating Value	Load Capacity (tons)
HS20	2.67	HS 53.43	96.2
5C1T	5.78	0.00	462.2

SECTION DATA (ASD/LFD)

Structure I. D. HAM500

Truss I. D. 1
 Truss Member I. D. U 1U 2

RATIO/Inv.	Allowable stress (fs) (psi)			
	Inventory	Operating	Posting	Special
Fy (tension)	18150.	24750.	0.	0.
Fy (compression)	15011.	18720.	0.	0.
Fy (ultimate)	33000.			

Member Properties:

Effective Length X (ft)	Effective Length Y (ft)	Eccentricity Y (in)	End Cond.	Batton
24.486	24.486	0.00	P	1.0

Gross Section Properties:

Height	Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy	Rx	Ry
25.75	34.10	2388.22	1822.35	21.05	8.37	7.31

Net Section Properties:

Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy
34.10	2388.22	1822.35	21.05

Truss influence line - loaded chord:

X ordinates:	0.000	47.833	191.333	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	-1.105	0.000	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

Truss influence line - unloaded chord:

X ordinates:	0.000	47.833	191.333	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	-1.105	0.000	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

RATING REPORT

Structure I. D. HAM500 Rating Types and Vehicles

	INV.	OPER	POST	SPEC
	HS20	5C1T		
Truss I. D.				
Truss Member I. D.	U 1	U 2		

Axial Dead Load
Tension Compression

0.0 306.6

Veh.	Axial Tension	Load Capacity Compression	Available Tension	Capacity for LL+I Compression
INV.	519.4	425.7	703.3	241.8
OPER	865.6	709.5	1172.2	403.0

Live Load Effect

Impact Factors: ten - .000 comp - .158

Rat. Typ.	Rat. Veh.	Truck w/imp.	Live Load w/o imp.	Force w/o imp.	Loc. of Front Wheel	Lane w/imp.	Live Load w/o imp.	Force w/o imp.	Loc. of Conc. Load
INV.	HS20	0.00 R	0.00	0.00	0.00	0.00	0.00	0.00	0.00
		-68.20 R	-58.89	75.83	-80.27	-69.31	47.83		
OPER	5C1T	0.00 R	0.00	0.00	0.00	0.00	0.00	0.00	0.00
		-93.45 R	-80.70	150.83	0.00	0.00	0.00		

Veh.	Rating Factor	Axial Rating Value	Load Capacity (tons)
HS20	3.01	HS 60.25	108.4
5C1T	4.31	0.00	345.0

SECTION DATA (ASD/LFD)

Structure I. D. HAM500

Truss I. D. 1
 Truss Member I. D. L 1L 2

RATIO/Inv.	Allowable stress (fs) (psi)			
	Inventory	Operating	Posting	Special
Fy (tension)	18150.	24750.	0.	0.
Fy (compression)	14057.	17530.	0.	0.
Fy (ultimate)	33000.			

Member Properties:

Effective Length X (ft)	Effective Length Y (ft)	Eccentricity Y (in)	End Cond.	Batton
23.917	23.917	0.00	P	1.0

Gross Section Properties:

Height	Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy	Rx	Ry
15.00	22.50	421.86	743.54	7.50	4.33	5.75

Net Section Properties:

Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy
21.38	507.10	595.25	8.68

Truss influence line - loaded chord:

X ordinates:	0.000	23.917	191.333	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	0.747	0.000	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

Truss influence line - unloaded chord:

X ordinates:	0.000	23.917	191.333	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	0.747	0.000	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

RATING REPORT

Structure I. D. HAM500 Rating Types and Vehicles

	INV.	OPER	POST	SPEC
	HS20	5C1T		
Truss I. D.				
Truss Member I. D.				

Axial Dead Load	
Tension	Compression
210.6	0.0

Veh.	Axial Tension	Load Capacity Compression	Available Tension	Capacity for LL+I Compression
INV.	325.6	263.0	199.2	389.4
OPER	542.6	438.4	332.0	649.1

Live Load Effect

Impact Factors: ten - .158 comp - .000

Rat. Typ.	Rat. Veh.	Truck w/imp.	Live Load w/o imp.	Force	Loc. of Front Wheel	Lane w/imp.	Live Load w/o imp.	Force	Loc. of Conc. Load
INV.	HS20	46.60 R	40.24		51.92	54.31	46.90		23.92
		0.00 R	0.00		0.00	0.00	0.00		0.00
OPER	5C1T	66.79 L	57.67		11.92	0.00	0.00		0.00
		0.00 R	0.00		0.00	0.00	0.00		0.00

Veh.	Rating Factor	Axial Rating Value	Load Capacity (tons)
HS20	3.67	HS 73.35	132.0
5C1T	4.97	0.00	397.6

SECTION DATA (ASD/LFD)

Structure I. D. HAM500

Truss I. D. 1
 Truss Member I. D. U 1L 2

RATIO/Inv.	Allowable stress (fs) (psi)			
	Inventory	Operating	Posting	Special
Fy (tension)	18150.	24750.	0.	0.
Fy (compression)	5684.	7088.	0.	0.
Fy (ultimate)	33000.			

Member Properties:

Effective Length X (ft)	Effective Length Y (ft)	Eccentricity Y (in)	End Cond.	Batton
36.824	36.824	0.00	P	1.0

Gross Section Properties:

Height	Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy	Rx	Ry
12.19	17.00	475.00	107.00	0.00	5.29	2.51

Net Section Properties:

Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy
16.99	659.28	75.85	0.91

Truss influence line - loaded chord:

X ordinates:	0.000	23.917	47.833	191.333	0.000	0.000	0.000	0
.000	0.000	0.000						
Y ordinates:	0.000	-0.320	0.675	0.000	0.000	0.000	0.000	0
.000	0.000	0.000						

Truss influence line - unloaded chord:

X ordinates:	0.000	23.917	47.833	191.333	0.000	0.000	0.000	0
.000	0.000	0.000						
Y ordinates:	0.000	-0.320	0.675	0.000	0.000	0.000	0.000	0
.000	0.000	0.000						

RATING REPORT

Rating Types and Vehicles

Structure I. D. HAM500

INV.	OPER	POST	SPEC
HS20	5C1T		

Truss I. D.	1
Truss Member I. D.	U 1L 2

Axial Dead Load	
Tension	Compression

136.7	0.0
-------	-----

Veh.	Axial Tension	Load Capacity Compression	Available Tension	Capacity for LL+I Compression
INV.	258.8	80.4	176.8	162.4
OPER	431.3	133.9	294.6	270.6

Live Load Effect

Impact Factors: ten - .176 comp - .300

Rat. Typ.	Rat. Veh.	Truck w/imp.	Live Load w/o imp.	Force	Loc. of Front Wheel	Lane w/imp.	Live Load w/o imp.	Force	Loc. of Conc. Load
INV.	HS20	42.30	R	35.98	75.83	48.45	41.22	47.83	
		-14.92	L	-11.48	-4.08	-11.90	-9.16	23.92	
OPER	5C1T	53.50	L	45.51	35.83	0.00	0.00	0.00	
		-10.27	L	-7.90	-114.08	0.00	0.00	0.00	

Veh.	Rating Factor	Axial Rating Value	Load Capacity (tons)
HS20	3.65	HS 72.96	131.3
5C1T	5.51	0.00	440.5

SECTION DATA (ASD/LFD)

Structure I. D. HAM500

Truss I. D. 1
 Truss Member I. D. U 2L 2

RATIO/Inv.	Allowable stress (fs) (psi)			
	Inventory	Operating	Posting	Special
Fy (tension)	18150.	24750.	0.	0.
Fy (compression)	9543.	11901.	0.	0.
Fy (ultimate)	33000.			

Member Properties:

Effective Length X (ft)	Effective Length Y (ft)	Eccentricity Y (in)	End Cond.	Batton
33.250	33.250	0.00	P	1.0

Gross Section Properties:

Height	Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy	Rx	Ry
12.12	17.98	423.91	163.22	-0.50	4.86	3.01

Net Section Properties:

Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy
17.98	613.32	124.70	0.32

Truss influence line - loaded chord:

X ordinates:	0.000	47.833	71.750	191.333	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	0.487	-0.428	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

Truss influence line - unloaded chord:

X ordinates:	0.000	23.917	47.833	191.333	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	0.243	-0.513	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

RATING REPORT

Rating Types and Vehicles

Structure I. D. HAM500

INV.	OPER	POST	SPEC
HS20	5C1T		

Truss I. D.	1
Truss Member I. D.	U 2L 2

Axial Dead Load	
Tension	Compression
0.0	43.0

Veh.	Axial Tension	Load Capacity Compression	Available Tension	Capacity for LL+I Compression
INV.	273.8	142.7	299.6	116.9
OPER	456.3	237.8	499.3	194.8

Live Load Effect

Impact Factors: ten - .269 comp - .195

Rat. Typ.	Rat. Veh.	Truck w/imp.	Live Load w/o imp.	Force	Loc. of Front Wheel	Lane w/imp.	Live Load w/o imp.	Force	Loc. of Conc. Load
INV.	HS20	28.37 L	22.34	19.83	22.21	17.50	47.83		
		-26.88 R	-22.48	99.75	-27.47	-22.98	71.75		
OPER	5C1T	20.54 R	15.80	59.83	0.00	0.00	0.00		
		-29.35 R	-24.55	209.75	0.00	0.00	0.00		

Veh.	Rating Factor	Axial Rating Value	Load Capacity (tons)
HS20	4.25	HS 85.08	153.1
5C1T	6.64	0.00	530.9

SECTION DATA (ASD/LFD)

Structure I. D. HAM500

Truss I. D. 1
 Truss Member I. D. U 2U 3

RATIO/Inv.	Allowable stress (fs) (psi)			
	Inventory	Operating	Posting	Special
Fy (tension)	18150.	24750.	0.	0.
Fy (compression)	15016.	18726.	0.	0.
Fy (ultimate)	33000.			

Member Properties:

Effective Length X (ft)	Effective Length Y (ft)	Eccentricity Y (in)	End Cond.	Batton
23.981	23.981	0.00	P	1.0

Gross Section Properties:

Height	Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy	Rx	Ry
25.84	38.03	2805.75	1967.05	20.02	8.59	7.19

Net Section Properties:

Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy
38.03	2805.75	1967.05	20.02

Truss influence line - loaded chord:

X ordinates:	0.000	71.750	191.333	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	-1.285	0.000	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

Truss influence line - unloaded chord:

X ordinates:	0.000	71.750	191.333	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	-1.285	0.000	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

RATING REPORT

Rating Types and Vehicles

Structure I. D. HAM500

INV.	OPER	POST	SPEC
HS20	5C1T		

Truss I. D.	1
Truss Member I. D.	U 2U 3

Axial Dead Load	
Tension	Compression
0.0	355.8

Veh.	Axial Tension	Load Capacity Compression	Available Tension	Capacity for LL+I Compression
INV.	579.2	474.9	792.7	261.4
OPER	965.4	791.6	1321.2	435.7

Live Load Effect

Impact Factors: ten - .000 comp - .158

Rat. Typ.	Rat. Veh.	Truck w/imp.	Live Load w/o imp.	Force w/o imp.	Loc. of Front Wheel	Lane w/imp.	Live Load w/o imp.	Force w/o imp.	Loc. of Conc. Load
INV.	HS20	0.00 R	0.00	0.00	0.00	0.00	0.00	0.00	0.00
		-78.58 L	-67.86	57.75	-93.35	-80.61	71.75		
OPER	5C1T	0.00 R	0.00	0.00	0.00	0.00	0.00	0.00	0.00
		-108.40 R	-93.60	170.75	0.00	0.00	0.00		

Veh.	Rating Factor	Axial Rating Value	Load Capacity (tons)
HS20	2.80	HS 56.01	100.8
5C1T	4.02	0.00	321.6

SECTION DATA (ASD/LFD)

Structure I. D. HAM500

Truss I. D. 1
 Truss Member I. D. L 2L 3

RATIO/Inv.	Allowable stress (fs) (psi)			
	Inventory	Operating	Posting	Special
Fy (tension)	18150.	24750.	0.	0.
Fy (compression)	14058.	17531.	0.	0.
Fy (ultimate)	33000.			

Member Properties:

Effective Length X (ft)	Effective Length Y (ft)	Eccentricity Y (in)	End Cond.	Batton
23.917	23.917	0.00	P	1.0

Gross Section Properties:

Height	Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy	Rx	Ry
15.00	31.86	597.64	999.10	7.50	4.33	5.60

Net Section Properties:

Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy
30.27	718.34	800.48	8.68

Truss influence line - loaded chord:

X ordinates:	0.000	47.833	191.333	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	1.079	0.000	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

Truss influence line - unloaded chord:

X ordinates:	0.000	47.833	191.333	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	1.079	0.000	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

RATING REPORT

Structure I. D. HAM500 Rating Types and Vehicles

	INV.	OPER	POST	SPEC
	HS20	5C1T		
Truss I. D.				
Truss Member I. D.				

Axial Dead Load	
Tension	Compression
299.4	0.0

Veh.	Axial Tension	Load Capacity Compression	Available Tension	Capacity for LL+I Compression
INV.	461.0	372.5	281.3	552.2
OPER	768.3	620.8	468.9	920.3

Live Load Effect

Impact Factors: ten - .158 comp - .000

Rat. Typ.	Rat. Veh.	Truck w/imp.	Live Load w/o imp.	Force	Loc. of Front Wheel	Lane w/imp.	Live Load w/o imp.	Force	Loc. of Conc. Load
INV.	HS20	66.62 R	57.52	75.83	78.40	67.70	47.83		
		0.00 R	0.00	0.00	0.00	0.00	0.00		
OPER	5C1T	91.28 R	78.82	150.83	0.00	0.00	0.00		
		0.00 R	0.00	0.00	0.00	0.00	0.00		

Veh.	Rating Factor	Axial Rating Value	Load Capacity (tons)
HS20	3.59	HS 71.77	129.2
5C1T	5.14	0.00	411.0

SECTION DATA (ASD/LFD)

Structure I. D. HAM500

Truss I. D. 1
 Truss Member I. D. U 2L 3

RATIO/Inv.	Allowable stress (fs) (psi)			
	Inventory	Operating	Posting	Special
Fy (tension)	18150.	24750.	0.	0.
Fy (compression)	4483.	5590.	0.	0.
Fy (ultimate)	33000.			

Member Properties:

Effective Length X (ft)	Effective Length Y (ft)	Eccentricity Y (in)	End Cond.	Batton
40.958	40.958	0.00	P	1.0

Gross Section Properties:

Height	Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy	Rx	Ry
12.06	15.60	425.00	95.80	0.00	5.22	2.48

Net Section Properties:

Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy
15.60	587.24	67.82	0.89

Truss influence line - loaded chord:

X ordinates:	0.000	47.833	71.750	191.333	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	-0.385	0.654	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

Truss influence line - unloaded chord:

X ordinates:	0.000	47.833	71.750	191.333	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	-0.385	0.654	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

RATING REPORT

Structure I. D. HAM500 Rating Types and Vehicles

		INV.	OPER	POST	SPEC
		HS20	5C1T		
Truss I. D.	1				
Truss Member I. D.	U 2L 3				

Axial Dead Load
Tension Compression

95.0 0.0

Veh.	Axial Tension	Load Capacity Compression	Available Tension	Capacity for LL+I Compression
INV.	237.6	58.2	180.6	115.2
OPER	396.0	96.9	301.0	191.9

Live Load Effect

Impact Factors: ten - .193 comp - .275

Rat. Typ.	Rat. Veh.	Truck w/imp.	Live Load w/o imp.	Force	Loc. of Front Wheel	Lane w/imp.	Live Load w/o imp.	Force	Loc. of Conc. Load
INV.	HS20	41.03 R	34.40		99.75	42.70	35.81		71.75
		-22.53 L	-17.67		19.83	-17.16	-13.46		47.83
OPER	5C1T	44.82 L	37.59		59.75	0.00	0.00		0.00
		-15.96 L	-12.28		-90.17	0.00	0.00		0.00

Veh.	Rating Factor	Axial Rating Value	Load Capacity (tons)
HS20	4.23	HS 84.59	152.3
5C1T	6.72	0.00	537.2

SECTION DATA (ASD/LFD)

Structure I. D. HAM500

Truss I. D. 1
 Truss Member I. D. U 3L 3

RATIO/Inv.	Allowable stress (fs) (psi)			
	Inventory	Operating	Posting	Special
Fy (tension)	18150.	24750.	0.	0.
Fy (compression)	9066.	11306.	0.	0.
Fy (ultimate)	33000.			

Member Properties:

Effective Length X (ft)	Effective Length Y (ft)	Eccentricity Y (in)	End Cond.	Batton
35.000	17.500	0.00	P	1.0

Gross Section Properties:

Height	Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy	Rx	Ry
12.24	9.67	245.58	22.54	6.63	5.04	1.53

Net Section Properties:

Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy
8.96	207.22	14.08	7.66

Truss influence line - loaded chord:

X ordinates:	0.000	71.750	95.667	191.333	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	0.469	-0.425	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

Truss influence line - unloaded chord:

X ordinates:	0.000	47.833	71.750	191.333	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	0.312	-0.531	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

RATING REPORT

Structure I. D. HAM500 Rating Types and Vehicles

		INV.	OPER	POST	SPEC
		HS20	5C1T		
Truss I. D.	1				
Truss Member I. D.	U 3L 3				

Axial Dead Load
Tension Compression

0.0 13.7

Veh.	Axial Tension	Load Capacity Compression	Available Tension	Capacity for LL+I Compression
INV.	136.5	72.9	144.7	64.7
OPER	227.5	121.5	241.2	107.9

Live Load Effect

Impact Factors: ten - .239 comp - .215

Rat. Typ.	Rat. Veh.	Truck w/imp.	Live Load w/o imp.	Force	Loc. of Front Wheel	Lane w/imp.	Live Load w/o imp.	Force	Loc. of Conc. Load
INV.	HS20	28.81 L	23.25	43.75	24.36	19.67	71.75		
		-26.58 R	-21.87	123.67	-24.65	-20.28	95.67		
OPER	5C1T	24.37 L	19.67	-66.25	0.00	0.00	0.00		
		-25.41 R	-20.91	233.67	0.00	0.00	0.00		

Veh.	Rating Factor	Axial Rating Value	Load Capacity (tons)
HS20	2.43	HS 48.70	87.7
5C1T	4.25	0.00	339.6

SECTION DATA (ASD/LFD)

Structure I. D. HAM500

Truss I. D. 1
 Truss Member I. D. L 3L 4

RATIO/Inv.	Allowable stress (fs) (psi)			
	Inventory	Operating	Posting	Special
Fy (tension)	18150.	24750.	0.	0.
Fy (compression)	14057.	17530.	0.	0.
Fy (ultimate)	33000.			

Member Properties:

Effective Length X (ft)	Effective Length Y (ft)	Eccentricity Y (in)	End Cond.	Batton
23.917	23.917	0.00	P	1.0

Gross Section Properties:

Height	Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy	Rx	Ry
15.00	37.50	703.12	1139.26	7.50	4.33	5.51

Net Section Properties:

Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy
35.62	845.19	913.36	8.68

Truss influence line - loaded chord:

X ordinates:	0.000	71.750	191.333	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	1.281	0.000	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

Truss influence line - unloaded chord:

X ordinates:	0.000	71.750	191.333	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	1.281	0.000	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

RATING REPORT

Rating Types and Vehicles

Structure I. D. HAM500

INV.	OPER	POST	SPEC
HS20	5C1T		

Truss I. D.	1
Truss Member I. D.	L 3L 4

Axial Dead Load	
Tension	Compression

354.9	0.0
-------	-----

Veh.	Axial Tension	Load Capacity Compression	Available Tension	Capacity for LL+I Compression
INV.	542.6	438.4	329.7	651.4
OPER	904.3	730.7	549.4	1085.6

Live Load Effect

Impact Factors: ten - .158 comp - .000

Rat. Typ.	Rat. Veh.	Truck w/imp.	Live Load w/o imp.	Force	Loc. of Front Wheel	Lane w/imp.	Live Load w/o imp.	Force	Loc. of Conc. Load
INV.	HS20	78.37 L	67.68	57.75	93.10	80.39	71.75		
		0.00 R	0.00	0.00	0.00	0.00	0.00		
OPER	5C1T	108.11 R	93.35	170.75	0.00	0.00	0.00		
		0.00 R	0.00	0.00	0.00	0.00	0.00		

Veh.	Rating Factor	Axial Rating Value	Load Capacity (tons)
HS20	3.54	HS 70.82	127.5
5C1T	5.08	0.00	406.6

SECTION DATA (ASD/LFD)

Structure I. D. HAM500

Truss I. D. 1
 Truss Member I. D. U 3U 4

RATIO/Inv.	Allowable stress (fs) (psi)			
	Inventory	Operating	Posting	Special
Fy (tension)	18150.	24750.	0.	0.
Fy (compression)	15022.	18734.	0.	0.
Fy (ultimate)	33000.			

Member Properties:

Effective Length X (ft)	Effective Length Y (ft)	Eccentricity Y (in)	End Cond.	Batton
23.917	23.917	0.00	P	1.0

Gross Section Properties:

Height	Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy	Rx	Ry
25.78	41.21	2775.48	2144.43	21.40	8.21	7.21

Net Section Properties:

Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy
41.21	2775.48	2144.43	21.40

Truss influence line - loaded chord:

X ordinates:	0.000	95.667	191.333	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	-1.367	0.000	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

Truss influence line - unloaded chord:

X ordinates:	0.000	95.667	191.333	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	-1.367	0.000	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

RATING REPORT

Rating Types and Vehicles

Structure I. D. HAM500

INV.	OPER	POST	SPEC
HS20	5C1T		

Truss I. D.	1
Truss Member I. D.	U 3U 4

Axial Dead Load	
Tension	Compression
0.0	378.1

Veh.	Axial Tension	Load Capacity Compression	Available Tension	Capacity for LL+I Compression
INV.	627.7	514.9	854.5	288.0
OPER	1046.1	858.1	1424.2	480.0

Live Load Effect

Impact Factors: ten - .000 comp - .158

Rat. Typ.	Rat. Veh.	Truck w/imp.	Live Load w/o imp.	Force	Loc. of Front Wheel	Lane w/imp.	Live Load w/o imp.	Force	Loc. of Conc. Load
INV.	HS20	0.00 R	0.00		0.00	0.00	0.00		0.00
		-82.91 R	-71.60		109.67	-99.31	-85.75		95.67
OPER	5C1T	0.00 R	0.00		0.00	0.00	0.00		0.00
		-109.36 R	-94.44		146.67	0.00	0.00		0.00

Veh.	Rating Factor	Axial Rating Value	Load Capacity (tons)
HS20	2.90	HS 58.00	104.4
5C1T	4.39	0.00	351.1

SECTION DATA (ASD/LFD)

Structure I. D. HAM500

Truss I. D. 1
 Truss Member I. D. U 3L 4

RATIO/Inv.	Allowable stress (fs) (psi)			
	Inventory	Operating	Posting	Special
Fy (tension)	18150.	24750.	0.	0.
Fy (compression)	6622.	8258.	0.	0.
Fy (ultimate)	33000.			

Member Properties:

Effective Length X (ft)	Effective Length Y (ft)	Eccentricity Y (in)	End Cond.	Batton
42.391	21.196	0.00	P	1.0

Gross Section Properties:

Height	Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy	Rx	Ry
12.24	10.49	278.14	25.49	6.12	5.15	1.56

Net Section Properties:

Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy
9.91	253.85	17.03	7.09

Truss influence line - loaded chord:

X ordinates:	0.000	71.750	95.667	191.333	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	-0.454	0.606	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

Truss influence line - unloaded chord:

X ordinates:	0.000	71.750	95.667	191.333	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	-0.454	0.606	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

RATING REPORT

Rating Types and Vehicles

Structure I. D. HAM500

INV.	OPER	POST	SPEC
HS20	5C1T		

Truss I. D.	1
Truss Member I. D.	U 3L 4

Axial Dead Load	
Tension	Compression

41.1	0.0
------	-----

Veh.	Axial Tension	Load Capacity Compression	Available Tension	Capacity for LL+I Compression
INV.	150.9	0.0	126.2	0.0
OPER	251.5	0.0	210.3	0.0

Live Load Effect

Impact Factors: ten - .213 comp - .000

Rat. Typ.	Rat. Veh.	Truck w/imp.	Live Load w/o imp.	Force w/o imp.	Loc. of Front Wheel	Lane w/imp.	Live Load w/o imp.	Force w/o imp.	Loc. of Conc. Load
INV.	HS20	37.81 R	31.16	123.67	35.49	29.25	95.67		
		0.00 R	0.00	0.00	0.00	0.00	0.00		
OPER	5C1T	36.15 R	29.79	233.67	0.00	0.00	0.00		
		0.00 R	0.00	0.00	0.00	0.00	0.00		

Veh.	Rating Factor	Axial Rating Value	Load Capacity (tons)
HS20	3.34	HS 66.74	120.1
5C1T	5.82	0.00	465.5

SECTION DATA (ASD/LFD)

Structure I. D. HAM500

Truss I. D. 1
 Truss Member I. D. L 3U 4

RATIO/Inv.	Inventory	Allowable stress (fs) (psi)		
		0.00 Operating	0.00 Posting	0.00 Special
Fy (tension)	18150.	24750.	0.	0.
Fy (compression)	6622.	8258.	0.	0.
Fy (ultimate)	33000.			

Member Properties:

Effective Length X (ft)	Effective Length Y (ft)	Eccentricity Y (in)	End Cond.	Batton
42.391	21.196	0.00	P	1.0

Gross Section Properties:

Height	Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy	Rx	Ry
12.24	10.49	278.14	25.49	6.12	5.15	1.56

Net Section Properties:

Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy
9.91	253.85	17.03	7.09

Truss influence line - loaded chord:

X ordinates:	0.000	71.750	95.667	191.333	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	0.454	-0.606	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

Truss influence line - unloaded chord:

X ordinates:	0.000	71.750	95.667	191.333	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	0.454	-0.606	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

RATING REPORT

Structure I. D. HAM500 Rating Types and Vehicles

	INV.	OPER	POST	SPEC
	HS20	5C1T		
Truss I. D.				
Truss Member I. D.				

Axial Dead Load	
Tension	Compression
0.0	0.0

Veh.	Axial Tension	Load Capacity Compression	Available Tension	Capacity for LL+I Compression
INV.	150.9	0.0	150.9	0.0
OPER	251.5	0.0	251.5	0.0

Live Load Effect

Impact Factors: ten - .242 comp - .000

Rat. Typ.	Rat. Veh.	Truck w/imp.	Live Load w/o imp.	Force	Loc. of Front Wheel	Lane w/imp.	Live Load w/o imp.	Force	Loc. of Conc. Load
INV.	HS20	27.97 L	22.53		43.75	23.33	18.79		71.75
		0.00 R	0.00		0.00	0.00	0.00		0.00
OPER	5C1T	23.67 L	19.06		-66.25	0.00	0.00		0.00
		0.00 R	0.00		0.00	0.00	0.00		0.00

Veh.	Rating Factor	Axial Rating Value	Load Capacity (tons)
HS20	5.39	HS107.87	194.2
5C1T	10.62	0.00	850.0

SECTION DATA (ASD/LFD)

Structure I. D. HAM500

Truss I. D. 1
 Truss Member I. D. U 4L 4

RATIO/Inv.	Allowable stress (fs) (psi)			
	Inventory	Operating	Posting	Special
Fy (tension)	18150.	24750.	0.	0.
Fy (compression)	8906.	11106.	0.	0.
Fy (ultimate)	33000.			

Member Properties:

Effective Length X (ft)	Effective Length Y (ft)	Eccentricity Y (in)	End Cond.	Batton
35.000	17.500	0.00	P	1.0

Gross Section Properties:

Height	Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy	Rx	Ry
12.24	9.26	232.26	21.07	6.39	5.01	1.51

Net Section Properties:

Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy
8.49	196.92	12.61	7.41

Truss influence line - loaded chord:

X ordinates:	0.000	191.333	0.000	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

Truss influence line - unloaded chord:

X ordinates:	0.000	71.750	1148.002	1435.002	2296.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	0.000	-1.000	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

RATING REPORT

Structure I. D. HAM500 Rating Types and Vehicles

		INV.	OPER	POST	SPEC
		HS20	5C1T		
Truss I. D.	1				
Truss Member I. D.	U 4L 4				

Axial Dead Load
Tension Compression

-5.7 5.7

Veh.	Axial Tension	Load Capacity Compression	Available Tension	Capacity for LL+I Compression
INV.	129.3	68.6	132.7	65.2
OPER	215.5	114.3	221.2	108.7

Live Load Effect

Impact Factors: ten - .289 comp - .000

Rat. Typ.	Rat. Veh.	Truck w/imp.	Live Load w/o imp.	Force	Loc. of Front Wheel	Lane w/imp.	Live Load w/o imp.	Force	Loc. of Conc. Load
INV.	HS20	49.61 R	38.48		109.67	42.18	32.71		95.67
		0.00 R	0.00		0.00	0.00	0.00		0.00
OPER	5C1T	38.24 L	29.41		83.67	0.00	0.00		0.00
		0.00 R	0.00		0.00	0.00	0.00		0.00

Veh.	Rating Factor	Axial Rating Value	Load Capacity (tons)
HS20	999.00	HS999.00	999.0
5C1T	999.00	999.00	999.0

SECTION DATA (ASD/LFD)

Structure I. D. HAM500

Truss I. D. 1
 Truss Member I. D. L 4L 5

RATIO/Inv.	Allowable stress (fs) (psi)			
	Inventory	Operating	Posting	Special
Fy (tension)	18150.	24750.	0.	0.
Fy (compression)	14057.	17530.	0.	0.
Fy (ultimate)	33000.			

Member Properties:

Effective Length X (ft)	Effective Length Y (ft)	Eccentricity Y (in)	End Cond.	Batton
23.917	23.917	0.00	P	1.0

Gross Section Properties:

Height	Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy	Rx	Ry
15.00	37.50	703.12	1139.26	7.50	4.33	5.51

Net Section Properties:

Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy
35.62	845.19	913.36	8.68

Truss influence line - loaded chord:

X ordinates:	0.000	119.583	191.333	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	1.281	0.000	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

Truss influence line - unloaded chord:

X ordinates:	0.000	119.583	191.333	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	1.281	0.000	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

RATING REPORT

Structure I. D. HAM500 Rating Types and Vehicles

		INV.	OPER	POST	SPEC
		HS20	5C1T		
Truss I. D.	1				
Truss Member I. D.	L 4L 5				

Axial Dead Load
Tension Compression

354.9 0.0

Veh.	Axial Tension	Load Capacity Compression	Available Tension	Capacity for LL+I Compression
INV.	542.6	438.4	329.7	651.4
OPER	904.3	730.7	549.4	1085.6

Live Load Effect

Impact Factors: ten - .158 comp - .000

Rat. Typ.	Rat. Veh.	Truck w/imp.	Live Load w/o imp.	Force	Loc. of Front Wheel	Lane w/imp.	Live Load w/o imp.	Force	Loc. of Conc. Load
INV.	HS20	78.37 R	67.68	133.58	93.10	80.39	119.58		
		0.00 R	0.00	0.00	0.00	0.00	0.00		
OPER	5C1T	108.11 L	93.35	20.58	0.00	0.00	0.00		
		0.00 R	0.00	0.00	0.00	0.00	0.00		

Veh.	Rating Factor	Axial Rating Value	Load Capacity (tons)
HS20	3.54	HS 70.82	127.5
5C1T	5.08	0.00	406.6

SECTION DATA (ASD/LFD)

Structure I. D. HAM500

Truss I. D. 1
 Truss Member I. D. U 4U 5

RATIO/Inv.	Allowable stress (fs) (psi)			
	Inventory	Operating	Posting	Special
Fy (tension)	18150.	24750.	0.	0.
Fy (compression)	15022.	18734.	0.	0.
Fy (ultimate)	33000.			

Member Properties:

Effective Length X (ft)	Effective Length Y (ft)	Eccentricity Y (in)	End Cond.	Batton
23.917	23.917	0.00	P	1.0

Gross Section Properties:

Height	Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy	Rx	Ry
25.78	41.21	2775.48	2144.43	21.40	8.21	7.21

Net Section Properties:

Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy
41.21	2775.48	2144.43	21.40

Truss influence line - loaded chord:

X ordinates:	0.000	95.667	191.333	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	-1.367	0.000	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

Truss influence line - unloaded chord:

X ordinates:	0.000	95.667	191.333	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	-1.367	0.000	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

RATING REPORT

Structure I. D. HAM500 Rating Types and Vehicles

	INV.	OPER	POST	SPEC
	HS20	5C1T		
Truss I. D.				
Truss Member I. D.	U	4U	5	

Axial Dead Load	
Tension	Compression
0.0	378.1

Veh.	Axial Tension	Load Capacity Compression	Available Tension	Capacity for LL+I Compression
INV.	627.7	514.9	854.5	288.0
OPER	1046.1	858.1	1424.2	480.0

Live Load Effect

Impact Factors: ten - .000 comp - .158

Rat. Typ.	Rat. Veh.	Truck w/imp.	Live Load w/o imp.	Force w/o imp.	Loc. of Front Wheel	Lane w/imp.	Live Load w/o imp.	Force w/o imp.	Loc. of Conc. Load
INV.	HS20	0.00 R	0.00	0.00	0.00	0.00	0.00	0.00	0.00
		-82.91 R	-71.60	109.67		-99.31	-85.75	95.67	
OPER	5C1T	0.00 R	0.00	0.00	0.00	0.00	0.00	0.00	0.00
		-109.36 R	-94.44	146.67		0.00	0.00	0.00	

Veh.	Rating Factor	Axial Rating Value	Load Capacity (tons)
HS20	2.90	HS 58.00	104.4
5C1T	4.39	0.00	351.1

SECTION DATA (ASD/LFD)

Structure I. D. HAM500

Truss I. D. 1
 Truss Member I. D. L 4U 5

RATIO/Inv.	Allowable stress (fs) (psi)			
	Inventory	Operating	Posting	Special
Fy (tension)	18150.	24750.	0.	0.
Fy (compression)	6622.	8258.	0.	0.
Fy (ultimate)	33000.			

Member Properties:

Effective Length X (ft)	Effective Length Y (ft)	Eccentricity Y (in)	End Cond.	Batton
42.391	21.196	0.00	P	1.0

Gross Section Properties:

Height	Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy	Rx	Ry
12.24	10.49	278.14	25.49	6.12	5.15	1.56

Net Section Properties:

Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy
9.91	253.85	17.03	7.09

Truss influence line - loaded chord:

X ordinates:	0.000	95.667	119.583	191.333	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	0.606	-0.454	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

Truss influence line - unloaded chord:

X ordinates:	0.000	95.667	119.583	191.333	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	0.606	-0.454	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

RATING REPORT

Structure I. D. HAM500 Rating Types and Vehicles

		INV.	OPER	POST	SPEC
		HS20	5C1T		
Truss I. D.	1				
Truss Member I. D.	L 4U 5				

Axial Dead Load
Tension Compression

41.1 0.0

Veh.	Axial Tension	Load Capacity Compression	Available Tension	Capacity for LL+I Compression
INV.	150.9	0.0	126.2	0.0
OPER	251.5	0.0	210.3	0.0

Live Load Effect

Impact Factors: ten - .213 comp - .000

Rat. Typ.	Rat. Veh.	Truck w/imp.	Live Load w/o imp.	Force	Loc. of Front Wheel	Lane w/imp.	Live Load w/o imp.	Force	Loc. of Conc. Load
INV.	HS20	37.81 L	31.16		67.67	35.49	29.25		95.67
		0.00 R	0.00		0.00	0.00	0.00		0.00
OPER	5C1T	36.15 L	29.79		-42.33	0.00	0.00		0.00
		0.00 R	0.00		0.00	0.00	0.00		0.00

Veh.	Rating Factor	Axial Rating Value	Load Capacity (tons)
HS20	3.34	HS 66.74	120.1
5C1T	5.82	0.00	465.5

SECTION DATA (ASD/LFD)

Structure I. D. HAM500

Truss I. D. 1
 Truss Member I. D. U 4L 5

RATIO/Inv.	Allowable stress (fs) (psi)			
	Inventory	Operating	Posting	Special
Fy (tension)	18150.	24750.	0.	0.
Fy (compression)	6622.	8258.	0.	0.
Fy (ultimate)	33000.			

Member Properties:

Effective Length X (ft)	Effective Length Y (ft)	Eccentricity Y (in)	End Cond.	Batton
42.391	21.196	0.00	P	1.0

Gross Section Properties:

Height	Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy	Rx	Ry
12.24	10.49	278.14	25.49	6.12	5.15	1.56

Net Section Properties:

Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy
9.91	253.85	17.03	7.09

Truss influence line - loaded chord:

X ordinates:	0.000	95.667	119.583	191.333	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	-0.606	0.454	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

Truss influence line - unloaded chord:

X ordinates:	0.000	95.667	119.583	191.333	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	-0.606	0.454	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

RATING REPORT

Structure I. D. HAM500 Rating Types and Vehicles

		INV.	OPER	POST	SPEC
		HS20	5C1T		
Truss I. D.	1				
Truss Member I. D.	U 4L 5				

Axial Dead Load
Tension Compression

0.0 0.0

Veh.	Axial Tension	Load Capacity Compression	Available Tension	Capacity for LL+I Compression
INV.	150.9	0.0	150.9	0.0
OPER	251.5	0.0	251.5	0.0

Live Load Effect

Impact Factors: ten - .242 comp - .000

Rat. Typ.	Rat. Veh.	Truck w/imp.	Live Load w/o imp.	Force	Loc. of Front Wheel	Lane w/imp.	Live Load w/o imp.	Force	Loc. of Conc. Load
INV.	HS20	27.97 R	22.53	147.58		23.33	18.79	119.58	
		0.00 R	0.00	0.00		0.00	0.00	0.00	
OPER	5C1T	23.67 R	19.06	257.58		0.00	0.00	0.00	
		0.00 R	0.00	0.00		0.00	0.00	0.00	

Veh.	Rating Factor	Axial Rating Value	Load Capacity (tons)
HS20	5.39	HS107.87	194.2
5C1T	10.62	0.00	850.0

SECTION DATA (ASD/LFD)

Structure I. D. HAM500

Truss I. D. 1
 Truss Member I. D. U 5L 5

RATIO/Inv.	Allowable stress (fs) (psi)			
	Inventory	Operating	Posting	Special
Fy (tension)	18150.	24750.	0.	0.
Fy (compression)	9066.	11306.	0.	0.
Fy (ultimate)	33000.			

Member Properties:

Effective Length X (ft)	Effective Length Y (ft)	Eccentricity Y (in)	End Cond.	Batton
35.000	17.500	0.00	P	1.0

Gross Section Properties:

Height	Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy	Rx	Ry
12.24	9.67	245.58	22.54	6.63	5.04	1.53

Net Section Properties:

Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy
8.96	207.22	14.08	7.66

Truss influence line - loaded chord:

X ordinates:	0.000	95.667	119.583	191.333	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	-0.425	0.469	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

Truss influence line - unloaded chord:

X ordinates:	0.000	119.583	143.500	191.333	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	-0.531	0.312	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

RATING REPORT

Structure I. D. HAM500 Rating Types and Vehicles

		INV.	OPER	POST	SPEC
		HS20	5C1T		
Truss I. D.	1				
Truss Member I. D.	U 5L 5				

Axial Dead Load
Tension Compression

0.0 13.7

Veh.	Axial Tension	Load Capacity Compression	Available Tension	Capacity for LL+I Compression
INV.	136.5	72.9	144.7	64.7
OPER	227.5	121.5	241.2	107.9

Live Load Effect

Impact Factors: ten - .239 comp - .215

Rat. Typ.	Rat. Veh.	Truck w/imp.	Live Load w/o imp.	Force	Loc. of Front Wheel	Lane w/imp.	Live Load w/o imp.	Force	Loc. of Conc. Load
INV.	HS20	28.81 R	23.25		147.58	24.36	19.67		119.58
		-26.58 L	-21.87		67.67	-24.65	-20.28		95.67
OPER	5C1T	24.37 R	19.67		257.58	0.00	0.00		0.00
		-25.41 L	-20.91		-42.33	0.00	0.00		0.00

Veh.	Rating Factor	Axial Rating Value	Load Capacity (tons)
HS20	2.43	HS 48.70	87.7
5C1T	4.25	0.00	339.6

SECTION DATA (ASD/LFD)

Structure I. D. HAM500

Truss I. D. 1
 Truss Member I. D. L 5L 6

RATIO/Inv.	Allowable stress (fs) (psi)			
	Inventory	Operating	Posting	Special
Fy (tension)	18150.	24750.	0.	0.
Fy (compression)	14058.	17531.	0.	0.
Fy (ultimate)	33000.			

Member Properties:

Effective Length X (ft)	Effective Length Y (ft)	Eccentricity Y (in)	End Cond.	Batton
23.917	23.917	0.00	P	1.0

Gross Section Properties:

Height	Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy	Rx	Ry
15.00	31.86	597.64	999.10	7.50	4.33	5.60

Net Section Properties:

Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy
30.27	718.34	800.48	8.68

Truss influence line - loaded chord:

X ordinates:	0.000	143.500	191.333	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	1.079	0.000	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

Truss influence line - unloaded chord:

X ordinates:	0.000	143.500	191.333	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	1.079	0.000	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

RATING REPORT

Rating Types and Vehicles

Structure I. D. HAM500

INV.	OPER	POST	SPEC
HS20	5C1T		

Truss I. D.	1
Truss Member I. D.	L 5L 6

Axial Dead Load	
Tension	Compression

299.4	0.0
-------	-----

Veh.	Axial Tension	Load Capacity Compression	Available Tension	Capacity for LL+I Compression
INV.	461.0	372.5	281.3	552.2
OPER	768.3	620.8	468.9	920.3

Live Load Effect

Impact Factors: ten - .158 comp - .000

Rat. Typ.	Rat. Veh.	Truck w/imp.	Live Load w/o imp.	Force	Loc. of Front Wheel	Lane w/imp.	Live Load w/o imp.	Force	Loc. of Conc. Load
INV.	HS20	66.62 L	57.52	115.50	78.40	67.70	143.50		
		0.00 R	0.00	0.00	0.00	0.00	0.00		
OPER	5C1T	91.28 R	78.82	159.50	0.00	0.00	0.00		
		0.00 R	0.00	0.00	0.00	0.00	0.00		

Veh.	Rating Factor	Axial Rating Value	Load Capacity (tons)
HS20	3.59	HS 71.77	129.2
5C1T	5.14	0.00	411.0

SECTION DATA (ASD/LFD)

Structure I. D. HAM500

Truss I. D. 1
 Truss Member I. D. U 5U 6

RATIO/Inv.	Allowable stress (fs) (psi)			
	Inventory	Operating	Posting	Special
Fy (tension)	18150.	24750.	0.	0.
Fy (compression)	15016.	18726.	0.	0.
Fy (ultimate)	33000.			

Member Properties:

Effective Length X (ft)	Effective Length Y (ft)	Eccentricity Y (in)	End Cond.	Batton
23.981	23.981	0.00	P	1.0

Gross Section Properties:

Height	Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy	Rx	Ry
25.84	38.03	2805.75	1967.05	20.02	8.59	7.19

Net Section Properties:

Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy
38.03	2805.75	1967.05	20.02

Truss influence line - loaded chord:

X ordinates:	0.000	119.583	191.333	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	-1.285	0.000	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

Truss influence line - unloaded chord:

X ordinates:	0.000	119.583	191.333	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	-1.285	0.000	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

RATING REPORT

Structure I. D. HAM500 Rating Types and Vehicles

		INV.	OPER	POST	SPEC
		HS20	5C1T		
Truss I. D.	1				
Truss Member I. D.	U 5U 6				

Axial Dead Load	
Tension	Compression
0.0	355.8

Veh.	Axial Tension	Load Capacity Compression	Available Tension	Capacity for LL+I Compression
INV.	579.2	474.9	792.7	261.4
OPER	965.4	791.6	1321.2	435.7

Live Load Effect

Impact Factors: ten - .000 comp - .158

Rat. Typ.	Rat. Veh.	Truck w/imp.	Live Load w/o imp.	Force w/o imp.	Loc. of Front Wheel	Lane w/imp.	Live Load w/o imp.	Force w/o imp.	Loc. of Conc. Load
INV.	HS20	0.00 R	0.00	0.00	0.00	0.00	0.00	0.00	0.00
		-78.58 R	-67.86	133.58	-93.35	-80.61	119.58		
OPER	5C1T	0.00 R	0.00	0.00	0.00	0.00	0.00	0.00	0.00
		-108.40 L	-93.60	20.58	0.00	0.00	0.00		

Veh.	Rating Factor	Axial Rating Value	Load Capacity (tons)
HS20	2.80	HS 56.01	100.8
5C1T	4.02	0.00	321.6

SECTION DATA (ASD/LFD)

Structure I. D. HAM500

Truss I. D. 1
 Truss Member I. D. L 5U 6

RATIO/Inv.	Allowable stress (fs) (psi)			
	Inventory	Operating	Posting	Special
Fy (tension)	18150.	24750.	0.	0.
Fy (compression)	4806.	5994.	0.	0.
Fy (ultimate)	33000.			

Member Properties:

Effective Length X (ft)	Effective Length Y (ft)	Eccentricity Y (in)	End Cond.	Batton
40.958	40.958	0.00	P	1.0

Gross Section Properties:

Height	Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy	Rx	Ry
15.01	13.19	286.62	86.84	2.02	4.66	2.57

Net Section Properties:

Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy
12.87	425.41	58.86	2.77

Truss influence line - loaded chord:

X ordinates:	0.000	119.583	143.500	191.333	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	0.654	-0.385	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

Truss influence line - unloaded chord:

X ordinates:	0.000	119.583	143.500	191.333	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	0.654	-0.385	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

RATING REPORT

Rating Types and Vehicles

Structure I. D. HAM500

INV.	OPER	POST	SPEC
HS20	5C1T		

Truss I. D.	1
Truss Member I. D.	L 5U 6

Axial Dead Load	
Tension	Compression

95.0	0.0
------	-----

Veh.	Axial Tension	Load Capacity Compression	Available Tension	Capacity for LL+I Compression
INV.	196.0	52.7	139.0	109.7
OPER	326.6	87.9	231.6	182.9

Live Load Effect

Impact Factors: ten - .193 comp - .275

Rat. Typ.	Rat. Veh.	Truck w/imp.	Live Load w/o imp.	Force	Loc. of Front Wheel	Lane w/imp.	Live Load w/o imp.	Force	Loc. of Conc. Load
INV.	HS20	41.03 L	34.40		91.58	42.70	35.81		119.58
		-22.53 R	-17.67		171.50	-17.16	-13.46		143.50
OPER	5C1T	44.82 R	37.59		131.58	0.00	0.00		0.00
		-15.96 R	-12.28		281.50	0.00	0.00		0.00

Veh.	Rating Factor	Axial Rating Value	Load Capacity (tons)
HS20	3.26	HS 65.09	117.2
5C1T	5.17	0.00	413.4

SECTION DATA (ASD/LFD)

Structure I. D. HAM500

Truss I. D. 1
 Truss Member I. D. U 6L 6

RATIO/Inv.	Allowable stress (fs) (psi)			
	Inventory	Operating	Posting	Special
Fy (tension)	18150.	24750.	0.	0.
Fy (compression)	9563.	11925.	0.	0.
Fy (ultimate)	33000.			

Member Properties:

Effective Length X (ft)	Effective Length Y (ft)	Eccentricity Y (in)	End Cond.	Batton
33.250	33.250	0.00	P	1.0

Gross Section Properties:

Height	Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy	Rx	Ry
12.12	19.10	533.00	174.00	0.00	5.28	3.02

Net Section Properties:

Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy
19.10	708.48	135.48	0.77

Truss influence line - loaded chord:

X ordinates:	0.000	119.583	143.500	191.333	0.000	0.000	0.000	0
.000	0.000	0.000						
Y ordinates:	0.000	-0.428	0.487	0.000	0.000	0.000	0.000	0
.000	0.000	0.000						

Truss influence line - unloaded chord:

X ordinates:	0.000	143.500	167.417	191.333	0.000	0.000	0.000	0
.000	0.000	0.000						
Y ordinates:	0.000	-0.513	0.243	0.000	0.000	0.000	0.000	0
.000	0.000	0.000						

RATING REPORT

Structure I. D. HAM500 Rating Types and Vehicles

	INV.	OPER	POST	SPEC
	HS20	5C1T		
Truss I. D.				
Truss Member I. D.				

	Axial Dead Load
	Tension Compression
	0.0 43.0

Veh.	Axial Load Capacity Tension Compression	Available Capacity for LL+I Tension Compression
INV.	290.9 151.9	316.7 126.1
OPER	484.8 253.2	527.9 210.2

Live Load Effect

Impact Factors: ten - .269 comp - .195

Rat. Typ.	Rat. Veh.	Truck Live Load Force w/imp.	Load Force w/o imp.	Loc. of Front Wheel	Lane Live Load Force w/imp.	Load Force w/o imp.	Loc. of Conc. Load
INV.	HS20	28.37 R	22.34	171.50	18.30	14.41	143.50
		-26.88 L	-22.48	91.58	-24.23	-20.27	119.58
OPER	5C1T	20.54 L	15.80	131.50	0.00	0.00	0.00
		-29.35 L	-24.55	-18.42	0.00	0.00	0.00

Veh.	Rating Factor	Axial Rating Value	Load Capacity (tons)
HS20	4.69	HS 93.83	168.9
5C1T	7.16	0.00	572.8

SECTION DATA (ASD/LFD)

Structure I. D. HAM500

Truss I. D. 1
 Truss Member I. D. L 6L 7

RATIO/Inv.	Allowable stress (fs) (psi)			
	Inventory	Operating	Posting	Special
Fy (tension)	18150.	24750.	0.	0.
Fy (compression)	14057.	17530.	0.	0.
Fy (ultimate)	33000.			

Member Properties:

Effective Length X (ft)	Effective Length Y (ft)	Eccentricity Y (in)	End Cond.	Batton
23.917	23.917	0.00	P	1.0

Gross Section Properties:

Height	Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy	Rx	Ry
15.00	22.50	421.86	743.54	7.50	4.33	5.75

Net Section Properties:

Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy
21.38	507.10	595.25	8.68

Truss influence line - loaded chord:

X ordinates:	0.000	167.417	191.333	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	0.747	0.000	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

Truss influence line - unloaded chord:

X ordinates:	0.000	167.417	191.333	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	0.747	0.000	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

RATING REPORT

Structure I. D. HAM500 Rating Types and Vehicles

	INV.	OPER	POST	SPEC
	HS20	5C1T		
Truss I. D.				
Truss Member I. D.				

	Axial Dead Load
	Tension Compression
	210.6 0.0

Veh.	Axial Tension	Load Capacity Compression	Available Tension	Capacity for LL+I Compression
INV.	325.6	263.0	199.2	389.4
OPER	542.6	438.4	332.0	649.1

Live Load Effect

Impact Factors: ten - .158 comp - .000

Rat. Typ.	Rat. Veh.	Truck w/imp.	Live Load w/o imp.	Force	Loc. of Front Wheel	Lane w/imp.	Live Load w/o imp.	Force	Loc. of Conc. Load
INV.	HS20	46.60 L	40.24	139.42	54.31	46.90	167.42		
		0.00 R	0.00	0.00	0.00	0.00	0.00		
OPER	5C1T	66.78 R	57.67	179.42	0.00	0.00	0.00		
		0.00 R	0.00	0.00	0.00	0.00	0.00		

Veh.	Rating Factor	Axial Rating Value	Load Capacity (tons)
HS20	3.67	HS 73.35	132.0
5C1T	4.97	0.00	397.6

SECTION DATA (ASD/LFD)

Structure I. D. HAM500

Truss I. D. 1
 Truss Member I. D. U 6U 7

RATIO/Inv.	Allowable stress (fs) (psi)			
	Inventory	Operating	Posting	Special
Fy (tension)	18150.	24750.	0.	0.
Fy (compression)	15011.	18720.	0.	0.
Fy (ultimate)	33000.			

Member Properties:

Effective Length X (ft)	Effective Length Y (ft)	Eccentricity Y (in)	End Cond.	Batton
24.486	24.486	0.00	P	1.0

Gross Section Properties:

Height	Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy	Rx	Ry
25.75	34.10	2388.22	1822.35	21.05	8.37	7.31

Net Section Properties:

Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy
34.10	2388.22	1822.35	21.05

Truss influence line - loaded chord:

X ordinates:	0.000	143.500	191.333	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	-1.105	0.000	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

Truss influence line - unloaded chord:

X ordinates:	0.000	143.500	191.333	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	-1.105	0.000	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

RATING REPORT

Structure I. D. HAM500 Rating Types and Vehicles

	INV.	OPER	POST	SPEC
	HS20	5C1T		
Truss I. D.				
Truss Member I. D.	U 6U 7			

Axial Dead Load	
Tension	Compression
0.0	306.6

Veh.	Axial Tension	Load Capacity Compression	Available Tension	Capacity for LL+I Compression
INV.	519.4	425.7	703.3	241.8
OPER	865.6	709.5	1172.2	403.0

Live Load Effect

Impact Factors: ten - .000 comp - .158

Rat. Typ.	Rat. Veh.	Truck w/imp.	Live Load w/o imp.	Force	Loc. of Front Wheel	Lane w/imp.	Live Load w/o imp.	Force	Loc. of Conc. Load
INV.	HS20	0.00 R	0.00	0.00	0.00	0.00	0.00	0.00	0.00
		-68.20 L	-58.89	115.50		-80.27	-69.31	143.50	
OPER	5C1T	0.00 R	0.00	0.00	0.00	0.00	0.00	0.00	0.00
		-93.45 R	-80.70	159.50		0.00	0.00	0.00	

Veh.	Rating Factor	Axial Rating Value	Load Capacity (tons)
HS20	3.01	HS 60.25	108.4
5C1T	4.31	0.00	345.0

SECTION DATA (ASD/LFD)

Structure I. D. HAM500

Truss I. D. 1
 Truss Member I. D. L 6U 7

RATIO/Inv.	Allowable stress (fs) (psi)			
	Inventory	Operating	Posting	Special
Fy (tension)	18150.	24750.	0.	0.
Fy (compression)	5824.	7263.	0.	0.
Fy (ultimate)	33000.			

Member Properties:

Effective Length X (ft)	Effective Length Y (ft)	Eccentricity Y (in)	End Cond.	Batton
36.824	36.824	0.00	P	1.0

Gross Section Properties:

Height	Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy	Rx	Ry
12.19	15.59	312.46	100.52	-0.91	4.48	2.54

Net Section Properties:

Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy
15.36	492.22	69.38	-0.09

Truss influence line - loaded chord:

X ordinates:	0.000	143.500	167.417	191.333	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	0.675	-0.320	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

Truss influence line - unloaded chord:

X ordinates:	0.000	143.500	167.417	191.333	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	0.675	-0.320	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

RATING REPORT

Structure I. D. HAM500 Rating Types and Vehicles

	INV.	OPER	POST	SPEC
	HS20	5C1T		
Truss I. D.				
Truss Member I. D.				

	Axial Dead Load
	Tension Compression
	136.7 0.0

Veh.	Axial Load Capacity Tension Compression	Available Capacity for LL+I Tension Compression
INV.	234.0 75.5	152.0 157.5
OPER	390.0 125.8	253.3 262.5

Live Load Effect

Impact Factors: ten - .176 comp - .300

Rat. Typ.	Rat. Veh.	Truck Live Load Force w/imp.	Loc. of Front Wheel	Lane Live Load Force w/imp.	Loc. of Conc. Load
INV.	HS20	42.30 L	115.50	48.45	143.50
		-14.92 R	195.42	-11.90	167.42
OPER	5C1T	53.50 R	155.50	0.00	0.00
		-10.27 R	305.42	0.00	0.00

Veh.	Rating Factor	Axial Rating Value	Load Capacity (tons)
HS20	3.14	HS 62.73	112.9
5C1T	4.74	0.00	378.8

SECTION DATA (ASD/LFD)

Structure I. D. HAM500

Truss I. D. 1
 Truss Member I. D. U 7L 7

RATIO/Inv.	Allowable stress (fs) (psi)			
	Inventory	Operating	Posting	Special
Fy (tension)	18150.	24750.	0.	0.
Fy (compression)	5837.	7280.	0.	0.
Fy (ultimate)	33000.			

Member Properties:

Effective Length X (ft)	Effective Length Y (ft)	Eccentricity Y (in)	End Cond.	Batton
28.000	28.000	0.00	P	1.0

Gross Section Properties:

Height	Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy	Rx	Ry
11.94	11.80	310.00	44.10	0.00	5.13	1.93

Net Section Properties:

Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy
11.51	415.42	31.40	0.77

Truss influence line - loaded chord:

X ordinates:	0.000	143.500	167.417	191.334	191.333	0.000	0.000	0
.000	0.000	0.000						
Y ordinates:	0.000	0.000	1.000	0.000	0.000	0.000	0.000	0
.000	0.000	0.000						

Truss influence line - unloaded chord:

X ordinates:	0.000	191.333	0.000	0.000	0.000	0.000	0.000	0
.000	0.000	0.000						
Y ordinates:	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0
.000	0.000	0.000						

RATING REPORT

Structure I. D. HAM500 Rating Types and Vehicles

		INV.	OPER	POST	SPEC
		HS20	5C1T		
Truss I. D.	1				
Truss Member I. D.	U 7L 7				

Axial Dead Load
Tension Compression

71.3 0.0

Veh.	Axial Tension	Load Capacity Compression	Available Tension	Capacity for LL+I Compression
INV.	175.3	57.3	132.5	100.1
OPER	292.2	95.5	220.9	166.8

Live Load Effect

Impact Factors: ten - .289 comp - .000

Rat. Typ.	Rat. Veh.	Truck w/imp.	Live Load w/o imp.	Force	Loc. of Front Wheel	Lane w/imp.	Live Load w/o imp.	Force	Loc. of Conc. Load
INV.	HS20	49.61 R	38.48	181.42	34.01	26.38	167.42		
		0.00 R	0.00	0.00	0.00	0.00	0.00		
OPER	5C1T	38.24 R	29.41	266.42	0.00	0.00	0.00		
		0.00 R	0.00	0.00	0.00	0.00	0.00		

Veh.	Rating Factor	Axial Rating Value	Load Capacity (tons)
HS20	2.67	HS 53.43	96.2
5C1T	5.78	0.00	462.2

SECTION DATA (ASD/LFD)

Structure I. D. HAM500

Truss I. D. 1
 Truss Member I. D. L 7L 8

RATIO/Inv.	Allowable stress (fs) (psi)			
	Inventory	Operating	Posting	Special
Fy (tension)	18150.	24750.	0.	0.
Fy (compression)	14057.	17530.	0.	0.
Fy (ultimate)	33000.			

Member Properties:

Effective Length X (ft)	Effective Length Y (ft)	Eccentricity Y (in)	End Cond.	Batton
23.917	23.917	0.00	P	1.0

Gross Section Properties:

Height	Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy	Rx	Ry
15.00	22.50	421.86	743.54	7.50	4.33	5.75

Net Section Properties:

Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy
21.38	507.10	595.25	8.68

Truss influence line - loaded chord:

X ordinates:	0.000	167.417	191.333	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	0.747	0.000	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

Truss influence line - unloaded chord:

X ordinates:	0.000	167.417	191.333	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	0.747	0.000	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

RATING REPORT

Structure I. D. HAM500 Rating Types and Vehicles

	INV.	OPER	POST	SPEC
	HS20	5C1T		
Truss I. D.				
Truss Member I. D.				

	Axial Dead Load
	Tension Compression
210.6	0.0

Veh.	Axial Tension	Load Capacity Compression	Available Tension	Capacity for LL+I Compression
INV.	325.6	263.0	199.2	389.4
OPER	542.6	438.4	332.0	649.1

Live Load Effect

Impact Factors: ten - .158 comp - .000

Rat. Typ.	Rat. Veh.	Truck w/imp.	Live Load w/o imp.	Force	Loc. of Front Wheel	Lane w/imp.	Live Load w/o imp.	Force	Loc. of Conc. Load
INV.	HS20	46.60 L	40.24	139.42	54.31	46.90	167.42		
		0.00 R	0.00	0.00	0.00	0.00	0.00		
OPER	5C1T	66.78 R	57.67	179.42	0.00	0.00	0.00		
		0.00 R	0.00	0.00	0.00	0.00	0.00		

Veh.	Rating Factor	Axial Rating Value	Load Capacity (tons)
HS20	3.67	HS 73.35	132.0
5C1T	4.97	0.00	397.6

SECTION DATA (ASD/LFD)

Structure I. D. HAM500

Truss I. D. 1
 Truss Member I. D. U 7L 8

RATIO/Inv.	Allowable stress (fs) (psi)			
	Inventory	Operating	Posting	Special
Fy (tension)	18150.	24750.	0.	0.
Fy (compression)	14277.	17804.	0.	0.
Fy (ultimate)	33000.			

Member Properties:

Effective Length X (ft)	Effective Length Y (ft)	Eccentricity Y (in)	End Cond.	Batton
36.823	36.823	0.00	P	1.0

Gross Section Properties:

Height	Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy	Rx	Ry
25.78	41.21	2775.48	2144.43	21.40	8.21	7.21

Net Section Properties:

Area	Moment of Inertia Ix	Moment of Inertia Iy	Dy
41.21	2775.48	2144.43	21.40

Truss influence line - loaded chord:

X ordinates:	0.000	167.417	191.333	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	-1.151	0.000	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

Truss influence line - unloaded chord:

X ordinates:	0.000	167.417	191.333	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							
Y ordinates:	0.000	-1.151	0.000	0.000	0.000	0.000	0.000	0
.000 0.000	0.000							

RATING REPORT

Structure I. D. HAM500 Rating Types and Vehicles

		INV.	OPER	POST	SPEC
		HS20	5C1T		
Truss I. D.	1				
Truss Member I. D.	U 7L 8				

Axial Dead Load
Tension Compression

0.0 324.3

Veh.	Axial Tension	Load Capacity Compression	Available Tension	Capacity for LL+I Compression
INV.	627.7	489.3	822.3	294.7
OPER	1046.1	815.6	1370.4	491.2

Live Load Effect

Impact Factors: ten - .000 comp - .158

Rat. Typ.	Rat. Veh.	Truck w/imp.	Live Load w/o imp.	Force	Loc. of Front Wheel	Lane w/imp.	Live Load w/o imp.	Force	Loc. of Conc. Load
INV.	HS20	0.00 R	0.00		0.00	0.00	0.00		0.00
		-71.76 L	-61.96		139.42	-92.06	-79.50		167.42
OPER	5C1T	0.00 R	0.00		0.00	0.00	0.00		0.00
		-102.83 R	-88.79		179.42	0.00	0.00		0.00

Veh.	Rating Factor	Axial Rating Value	Load Capacity (tons)
HS20	3.20	HS 64.03	115.3
5C1T	4.78	0.00	382.2